

# Wind-Optimal Lateral Trajectories for a Multirotor Aircraft in Urban Air Mobility

Priyank Pradeep \*

*Universities Space Research Association, Moffett Field, CA, 94035, USA.*

Gano B. Chatterji †

*Crown Consulting Inc, Arlington, VA, 22209, USA.*

Todd A. Lauderdale ‡, Kapil Sheth §, Chok Fung Lai ¶, Heinz Erzberger ¶, and Banavar Sridhar \*\*  
*NASA Ames Research Center, Moffett Field, CA, 94035, USA.*

**The primary motivation for this paper is to quantify the operational benefits (energy consumption and flight duration) of flying wind-optimal lateral trajectories for short flights (less than 60 miles) anticipated in the urban environment. The optimal control model presented includes a wind model for quantifying the effect of wind on the lateral trajectory. The optimal control problem is numerically solved using the direct collocation method. Energy consumption and flight duration flying wind-optimal lateral trajectories are compared with corresponding values obtained flying great-circle paths between the same origin and destination pairs to determine the operational benefits of wind-optimal routing for short flights. The flight duration results for different scenarios are validated using a simulation tool designed and developed at NASA for exploring advanced air traffic management concepts. This research study suggests that for short flights in an urban environment, operational benefits of the wind-optimal lateral trajectories over the corresponding great-circle trajectories in terms of energy consumption and flight duration per flight are dependent on: i) wind field's spatial variability, ii) wind magnitude, iii) the direction of route relative to the wind field, and iv) cruise segment length. The operational benefits observed in realistic flyable wind scenarios are less than 2.5 %; these could be translated to an equivalent of a maximum of 2 minutes of cruise flight duration savings in the urban air mobility environment. As expected, headwinds and tailwinds along the flight route most significantly impact energy consumption and flight duration.**

---

\* Aerospace Engineer, Universities Space Research Association, NASA Ames Research Center, AIAA Senior Member.

† Senior Scientist and Lead, Crown Consulting Inc., AIAA Associate Fellow.

‡ Aerospace Engineer, Aviation Systems Division, NASA Ames Research Center.

§ Aerospace Research Engineer, Aviation Systems Division, NASA Ames Research Center, AIAA Associate Fellow.

¶ Aerospace Engineer, Aviation Systems Division, NASA Ames Research Center.

¶ Ames Associate, Aviation Systems Division, NASA Ames Research Center, AIAA Fellow.

\*\* Ames Associate, Aviation Systems Division, NASA Ames Research Center, AIAA Fellow.

## I. Nomenclature

$\lambda$	=	Latitude
$\tau$	=	Longitude
$h$	=	Altitude above mean sea level
$D$	=	Parasite drag
$V$	=	True airspeed
$V_{GS}$	=	Ground speed
$LRC$	=	Long range cruise airspeed
$m$	=	Mass
$q$	=	Dynamic pressure
$T$	=	Net thrust
$\psi$	=	Heading angle
$\chi$	=	Course angle
$T_{\text{rotor}}$	=	Thrust produced by an isolated rotor
$v_h$	=	Rotor-induced velocity in hover
$v_i$	=	Rotor-induced velocity during forward flight
$\alpha$	=	Angle-of-attack of air-stream relative to rotor tip-path-plane
$\theta$	=	Rotor tip-path-plane pitch angle
$\phi$	=	Rotor tip-path-plane roll angle
$\kappa$	=	Induced power factor
$P_{\text{max}}$	=	Total deliverable power
$A_{\text{rotor}}$	=	Rotor disk area
$R$	=	Radius of the rotor
$\Omega$	=	Rotational velocity of the rotor blades
$\sigma$	=	Thrust-weighted solidity ratio
$\sigma_{\text{wind}}$	=	Standard deviation (spatial variability) of the wind at any given epoch
$\sigma_{W_N}$	=	Standard deviation (spatial variability) of the north component of the wind at any given epoch
$\sigma_{W_E}$	=	Standard deviation (spatial variability) of the east component of the wind at any given epoch
$C_{d \text{ mean}}$	=	Mean blade drag coefficient
$\rho$	=	Density of air
$R_{\text{Earth}}$	=	Radius of the Earth assuming spherical model
$W_N$	=	North component of the wind speed

$W_E$  = East component of the wind speed

## II. Introduction


Urban Air Mobility (UAM) can alleviate transportation congestion on the ground by utilizing three-dimensional (3D) airspace efficiently, just as skyscrapers allowed cities to use limited land more efficiently [1]. The envisioned concept of UAM involves a network of small electric aircraft that can enable rapid and reliable transportation between suburbs and cities and, ultimately, within cities [1–4].

Recently, technological advances have made it possible to build and flight test eVTOL aircraft [2, 4, 5]. Several companies, for example, Airbus A<sup>3</sup>, Aurora Flight Sciences, EHang, Joby Aviation, Kitty Hawk, Leonardo, Lilium, Terrafugia, and Volocopter, are pursuing different design approaches to make eVTOLs a reality [4]. Despite various designs, they all have distributed electric propulsion (DEP) systems in common [2]. However, the low specific energy and nonlinear discharge behavior of current lithium-ion polymer (Li-Po) battery technology used in DEP impose constraints on the flight endurance of such aircraft [6]. In general, multirotor eVTOLs are a relatively low cruise speed aircraft compared to winged eVTOL aircraft; therefore, atmospheric winds play a significant role in their trajectories. The operational benefits of wind-optimal lateral trajectories have been extensively studied for commercial aircraft [7–9] but not for eVTOLs in the UAM environment. Therefore, in the current research, the operational benefits of wind-optimal lateral trajectories are studied in the UAM context.

The focus of the current research is on the trajectories of a multirotor eVTOL aircraft on short UAM missions (less than 60 miles) [1, 10]. Therefore, an optimal control model for a multirotor eVTOL is formulated that includes a wind effect model to quantify the effect of wind on the trajectory. The optimal control problem formulated using a lateral dynamics model and operational constraints, is numerically solved using the direct collocation method. The primary motivation of the paper is to quantify the operational benefits using wind-optimal lateral trajectories for short flights (less than 60 miles) anticipated in the urban environment. Energy consumption and flight duration flying wind-optimal lateral trajectories in the Dallas-Fort Worth and New York metropolitan areas are compared with the corresponding values obtained flying great-circle paths between the same origin and destination pairs to determine operational benefits of wind-optimal routing for short flights.

In this research, the concept of operations (CONOPs) of the multirotor eVTOL aircraft is assumed to be as follows: i) vertical climb; ii) cruise at a constant altitude along a path between UAM vertiports in metropolitan areas like Dallas-Fort Worth (DFW) and New York (NY); and iii) vertical descent. The scope of this research is focused on the low-altitude (1600 ft above mean sea level (MSL)) cruise phase [11]; therefore, climb and descent phases have been ignored in the problem formulation.

The rest of the paper is organized as follows. In Section III, the optimal control problem with energy consumption



**Fig. 1 Multirotor eVTOL aircraft in forward flight**

as the performance index is formulated to generate four-dimensional (4D) trajectories for a multirotor eVTOL aircraft. The optimal control model presented includes a wind model for quantifying the effect of wind on a lateral trajectory. In Section IV, wind-optimal and great-circle lateral trajectories generated under different wind conditions are described. Next, the flight duration results for different scenarios are validated using the simulation tool designed and developed at NASA. Finally, the main findings for this study are summarized in Section V.

### III. Optimal Control Model

#### A. eVTOL Aircraft Model

In this research, a quadrotor eVTOL aircraft concept proposed by Silva et al. [12], as shown in Figure 1a, is used to study the effect of wind on a multirotor eVTOL aircraft trajectory. This eVTOL has six-seater (up to 545 kg payload) capacity with a long range cruise airspeed (LRC) of 50.4 m/s (98 kts).

Table 1 lists the aircraft performance data for the lateral trajectory optimization in cruise phase.

**Table 1 Performance data of the eVTOL aircraft [12]**

Parameter (Unit)	Value
$V_{\text{cruise}}$ (m/s)	50.41
R (m)	4.0
$A_{\text{rotor}}$ (m <sup>2</sup> )	50.26
mass (kg)	2940
$\sigma$	0.055
$C_{d \text{ mean}}$	0.0089
$F_P$	0.97
$\kappa$	1.75
$\Omega$ (rad/sec)	30.12
$P_{\text{max}}$ (kW)	494.25

### B. Flight Dynamics and Kinematics Model

To study the effect of wind on the cruise phase of the multirotor eVTOL aircraft, a lateral flight dynamics model (two dimensional in space and one dimensional in time) is considered. The four lateral states of the model are:  $\lambda$ ,  $\tau$ ,  $V$ ,  $\psi$ ; where  $\lambda$  is the latitude,  $\tau$  is the longitude,  $V$  is the true airspeed (assumed to have only horizontal component during the cruise) and  $\psi$  is the heading angle w.r.t north [14, 15]. The three control variables of the model are: the net thrust ( $T$ ), the rotor tip-path-plane pitch angle ( $\theta$ ) and the rotor tip-path-plane roll (bank) angle ( $\phi$ ). Therefore, the quasi-steady cruise flight dynamics and kinematics of the multirotor eVTOL aircraft considering wind in a vehicle-carried frame of reference are as follows [2, 3, 9, 14–17]:

$$\frac{dV}{dt} = \frac{T \cos \phi \sin \theta - D}{m} - \frac{dW_N}{dt} \cos \psi - \frac{dW_E}{dt} \sin \psi \quad (1)$$

$$V \frac{d\psi}{dt} = \frac{T \sin \phi}{m} + \frac{dW_N}{dt} \sin \psi - \frac{dW_E}{dt} \cos \psi \quad (2)$$

$$(R_{\text{Earth}} + h) \frac{d\lambda}{dt} = V \cos \psi + W_N = V_{GS} \cos \chi \quad (3)$$

$$(R_{\text{Earth}} + h) \cos \lambda \frac{d\tau}{dt} = V \sin \psi + W_E = V_{GS} \sin \chi \quad (4)$$

where  $D$  is the parasite drag,  $V_{GS}$  is the ground speed,  $\chi$  is the course,  $h$  is the altitude above mean sea level and  $R_{\text{Earth}}$  is the mean radius of the Earth, and  $W_N$  and  $W_E$  are the components of the wind in north and east directions, respectively. The time derivative of wind components is assumed to be zero given the short duration flights in the UAM environment [1, 4].

For the quadrotor eVTOL aircraft, assuming that the rotors have negligible interference with each other, the net

thrust (T) produced by the four rotors is given by:

$$T = \sum_{n=1}^4 (T_{\text{rotor}})_n \quad (5)$$

where  $(T_{\text{rotor}})_n$  is the thrust produced by the  $n^{\text{th}}$  rotor. Also, assuming all the rotors produce the same amount of thrust  $(T_{\text{rotor}})$  in cruise phase, the net thrust (T) produced by the rotors is given by:

$$T = 4T_{\text{rotor}} \quad (6)$$

### C. Drag Model

The parasite drag (D) on the multirotor eVTOL is calculated as follows [12]:

$$D = 1.1984 \frac{\rho V^2}{2} \quad (7)$$

where  $\rho$  is the density of air, which is a function of altitude and 1.1984 is a product of drag coefficient and reference area [12].

### D. Induced Velocity and Induced Power

Using momentum theory [18–20], the hover induced velocity ( $v_h$ ) is given by:

$$v_h = \sqrt{\frac{T_{\text{rotor}}}{2\rho A_{\text{rotor}}}} \quad (8)$$

where  $A_{\text{rotor}}$  is the rotor disk area ( $\pi R^2$ ) and R is the radius of the rotor.

Consider an isolated rotor in forward motion at true airspeed ( $V$ ), with angle of attack ( $\alpha$ ) between the air-stream and the rotor disk (tip-path-plane). Using momentum theory in forward flight, the solution for induced velocity ( $v_i$ ) is given by [18–20]:

$$v_i = \frac{v_h^2}{\sqrt{(V \cos \alpha)^2 + (V \sin \alpha + v_i)^2}} \quad (9)$$

where the hover induced velocity ( $v_h$ ) on the right-hand side of the equation (9) is computed using the equation (8).

The equation (9) is a quartic polynomial that can be analytically solved for induced velocity ( $v_i$ ). Out of the four roots of the quartic equation (9), the one with real-positive and value lower than  $v_h$  is the correct solution for cruise phase. The equation (9) can also be numerically solved using an iterative technique with initial guess for  $v_i$  as  $v_h$ .

Once  $v_i$  is computed, the induced power loss of an isolated rotor ( $P_{\text{induced rotor}}$ ) in forward flight is computed as

follows [20, 21]:

$$P_{\text{induced rotor}} = \kappa T_{\text{rotor}} v_i \quad (10)$$

where the induced power factor ( $\kappa$ ) is assumed to be 1.75 [12].

### E. Power Required by the eVTOL Aircraft

Based on the quasi-steady flight assumption, the instantaneous power required in forward cruise flight at a constant altitude is equal to the sum of the induced power, parasite power, and profile power as follows [2, 3, 19, 20, 22]:

$$P_{\text{required}} = P_{\text{induced}} + P_{\text{parasite}} + P_{\text{profile}} \quad (11)$$

The total induced power loss of the eVTOL aircraft ( $P_{\text{induced}}$ ) is equal to the summation of the induced power loss of each rotor ( $P_{\text{induced rotor}}$ ). Therefore, the induced power loss of the aircraft is given by [12, 20]:

$$P_{\text{induced}} = \sum_{n=1}^4 (P_{\text{induced rotor}})_n = \kappa \sum_{n=1}^4 (T_{\text{rotor}})_n (v_i)_n \quad (12)$$

The power required to propel the aircraft forward (the parasite power loss) at a constant altitude is given by [20]:

$$P_{\text{parasite}} = TV \sin \alpha \quad (13)$$

The profile power loss is calculated from a mean blade drag coefficient ( $C_{d \text{ mean}}$ ) as follows [12, 20, 22]:

$$P_{\text{profile}} = \frac{\rho A_{\text{rotor}} (\Omega R)^3 \sigma C_{d \text{ mean}} F_P}{8} \quad (14)$$

where  $\Omega$  is the rotational velocity of the rotor blades,  $\sigma$  is the thrust weighted solidity ratio,  $C_{d \text{ mean}}$  is the mean blade drag coefficient and  $F_P$  is the function that accounts for the increase of the blade section velocity with rotor edgewise and axial speed [12, 20, 23]. However,  $F_P$  is assumed to be a constant (see Table 1) in this study because of cruise at constant altitude and nominal cruise speed.

Therefore, using the equations from (11) to (14), the instantaneous power required ( $P_{\text{required}}$ ) in forward flight is given by:

$$P_{\text{required}} = \kappa \sum_{n=1}^4 (T_{\text{rotor}})_n (v_i)_n + TV \sin \alpha + \frac{\rho A_{\text{rotor}} (\Omega R)^3 \sigma C_{d \text{ mean}} F_P}{8} \quad (15)$$

## F. Performance Index of Optimal Control Problem

The performance index for the wind-optimal lateral trajectory optimization problem is constructed as follows:

$$J = \int_{t_0}^{t_f} (P_{\text{required}}) dt = \int_{t_0}^{t_f} \left( \kappa \sum_{n=1}^4 (T_{\text{rotor}})_n (v_i)_n + TV \sin \alpha + \frac{\rho A_{\text{rotor}} (\Omega R)^3 \sigma C_{d \text{ mean}} F_P}{8} \right) dt \quad (16)$$

where  $t_0$  is the initial flight time at the top of climb (TOC) placed directly above the origin vertiport at the cruise altitude and  $t_f$  is the final flight time to reach the top of descent (TOD) placed directly above the destination vertiport at the cruise altitude.

## G. Path Constraints of Optimal Control Problem

For a level flight (cruise) in the absence of vertical component of wind, the net vertical force on the multirotor eVTOL aircraft is zero; therefore, the following path constraint is imposed on the problem:

$$T \cos \phi \cos \theta = mg \quad (17)$$

where  $m$  is the mass of the aircraft and  $g$  is the acceleration due to gravity.

The instantaneous power required ( $P_{\text{required}}$  in kw) is bounded by the total deliverable power ( $P_{\text{max}}$ ) of the quadrotor eVTOL aircraft[12, 21]:

$$P_{\text{required}} \leq 494.25 \quad (18)$$

where  $P_{\text{required}}$  is defined in equation 15.

## H. Great-Circle Path Constraint

The course angle ( $\chi$ ) for the great-circle trajectory between the two waypoints is calculated as follows [24]:

$$\tan \chi = \frac{\sin(\tau_2 - \tau_1) \cos \lambda_2}{\sin \lambda_2 \cos \lambda_1 - \sin \lambda_1 \cos \lambda_2 \cos(\tau_2 - \tau_1)} \quad (19)$$

where the origin latitude-longitude is  $(\lambda_1, \tau_1)$  and the destination latitude-longitude is  $(\lambda_2, \tau_2)$ . However, to generate a great-circle trajectory between the two waypoints using the optimal control framework developed in this research, a path constraint as a function of the wind components ( $W_N$  and  $W_E$ ), latitude-longitude coordinates of the two waypoints and heading angle ( $\psi$ ) is required. Therefore, the course angle ( $\chi$ ) needs to be eliminated from the equation (19).

Using the equations (3) and (4), the heading angle ( $\psi$ ) required to fly the course angle ( $\chi$ ) in the presence of the wind is computed as follows:

$$\tan \chi = \frac{V \sin \psi + W_E}{V \cos \psi + W_N} \quad (20)$$



where  $W_N$  and  $W_E$  are the components of the wind in north and east directions, respectively.

Equations (19) and (20) result in the following relation:

$$\frac{V \sin \psi + W_E}{V \cos \psi + W_N} = \frac{\sin(\tau_2 - \tau_1) \cos \lambda_2}{\sin \lambda_2 \cos \lambda_1 - \sin \lambda_1 \cos \lambda_2 \cos(\tau_2 - \tau_1)} \quad (21)$$

Hence, the path constraint for the great-circle trajectory between the two waypoints is given by:

$$(V \sin \psi + W_E)(\sin \lambda_2 \cos \lambda_1 - \sin \lambda_1 \cos \lambda_2 \cos(\tau_2 - \tau_1)) - (V \cos \psi + W_N)(\sin(\tau_2 - \tau_1) \cos \lambda_2) = 0 \quad (22)$$

## IV. Numerical Study and Results

### A. Optimal Control Solver

The trajectory optimization problems can be numerically solved, either using the direct or indirect methods [25]. Direct methods typically discretize the trajectory optimization problem, and convert the original trajectory optimization problem into a nonlinear program. On the other hand, indirect methods are characterized by explicitly solving the optimality conditions stated in terms of the adjoint differential equations, the maximum principle, and associated boundary (transversality) conditions [26]. Using the calculus of variations, the optimal control necessary conditions can be derived by setting the first variation of the Hamiltonian function to zero. A common way to distinguish these two methods is that a direct method discretizes and then optimizes, while an indirect method optimizes and then discretizes [25, 27].

In this research, PSOPT has been used to solve the optimal control problem to generate wind-optimal lateral trajectories for the multirotor eVTOL aircraft. PSOPT is an open-source optimal control software package written in C++ that uses direct collocation methods such as pseudospectral methods [28]. Pseudospectral methods directly discretize the original optimal control problem to formulate a nonlinear programming problem, which is then solved numerically using a sparse nonlinear programming solver to find approximate local optimal solutions. IPOPT is an open-source C++ package for large-scale nonlinear optimization, which uses an interior point method [28, 29]. IPOPT is the default nonlinear programming algorithm used by PSOPT. Approximation theory and practice show that pseudospectral methods are well suited for approximating smooth functions, integration, and differentiation, i.e., all of which are relevant to optimal control problems [28]. Nearly all trajectory optimization techniques require a good initial guess to begin the optimization. In the best case, a good initialization ensures that the solver rapidly arrives at the optimal solution [27].

## B. Wind Data

The Rapid Refresh (RR) operational weather prediction system, available on an hourly basis at 13 km spatial resolution from the National Center for Environmental Prediction [30], has been used to extract the wind data for analysis. The wind data are extracted for the entire month of January 2019 (i.e., 31 days) during peak traffic hours in the morning and evening, i.e., i) 7 AM to 11 AM (local time), and ii) 3 PM to 7 PM (local time) at cruise altitude (1600 ft above MSL) in 1-minute intervals at grid points equispaced 10 km apart. The grid points cover  $10^4$  km<sup>2</sup> area at the Dallas-Fort Worth and New York metropolitan areas of the United States.

### 1. Strongest Wind

To find the date and local time when the strongest wind (highest wind speed) occurred: First, the spatial average of wind speed is computed in 1-minute intervals (epochs). Finally, the spatially averaged wind speeds at each epoch are compared to find the epoch at which the highest wind speed magnitude occurred.

### 2. Highest Spatial Variability of the Wind

To find the date and local time when the highest spatial variability of wind speed occurred: First, the spatial average of wind speed is computed in 1-minute intervals (epochs). Next, the standard deviation of the wind is computed in 1-minute intervals as follows:

$$\sigma_{wind} = \sqrt{\sigma_{WN}^2 + \sigma_{WE}^2} \quad (23)$$

where  $\sigma_{wind}$  is the standard deviation of the wind at any given epoch,  $\sigma_{WN}$  is the standard deviation of the north component of the wind at any given epoch, and  $\sigma_{WE}$  is the standard deviation of the east component of the wind at any given epoch. Finally, the standard deviation of the wind at each epoch is compared to find the epoch at which the highest spatial variability occurred.

### 3. Wind Data Analysis Results

Table 2 and Table 3 show the following wind data analysis results:

- Date and time results in epoch, UTC, and local time format for the occurrence of the strongest wind and highest spatial variability of the wind in the Dallas-Fort Worth (DFW) and New York (NY) metropolitan areas.
- Statistics of wind fields chosen for the study in the Dallas-Fort Worth and New York metropolitan areas respectively.

### 4. Analytical Wind Models for Case Studies

Because PSOPT requires the equations in an analytical form, the MATLAB curve-fitting toolbox [31] is used to obtain equations for north and east components of the wind, needed in equations (3) and (4) for each case study. These

**Table 2 Occurrence of the strongest wind and highest spatial variability of the wind in the Dallas-Fort Worth (DFW) and the New York (NY) metropolitan areas**

Occurrence	DFW	NY
<b>Strongest Wind</b>		
Epoch (seconds)	1547906400	1548342000
UTC	January 19, 2019 14:00 Zulu	January 24, 2019 15:00 Zulu
Local Time	January 19, 2019 8:00 AM (CST)	January 24, 2019 10:00 AM (EST)
<b>Highest Spatial Variability of the Wind</b>		
Epoch (seconds)	1548198000	1548000000
UTC	January 22, 2019 23:00 Zulu	January 20, 2019 16:00 Zulu
Local Time	January 22, 2019 5:00 PM (CST)	January 20, 2019 11:00 AM (EST)

**Table 3 Wind statistics and model of the strongest wind and highest spatial variability of the wind in the Dallas-Fort Worth (DFW) and the New York (NY) metropolitan areas**

	North Wind ( $W_N$ m/s)	East Wind ( $W_E$ m/s)	Wind Speed ( $V_W$ m/s)
<b>DFW Wind Statistics and Model</b>			
<b>Strongest Wind</b>			
Spatial Average	-16.92	10.83	20.08
Standard Deviation	0.27	0.25	0.26
Wind Model	-16.92	10.83	N/A
<b>Highest Spatial Variability of the Wind</b>			
Spatial Average	-1.93	7.37	10.23
Standard Deviation	7.13	0.84	2.25
Wind Model	$2160.6 - 395.6\lambda + 1142.7\tau$	$-172.5 + 49.2\lambda - 89.5\tau$	N/A
<b>NY Wind Statistics and Model</b>			
<b>Strongest Wind</b>			
Spatial Average	28.35	0.54	28.40
Standard Deviation	5.01	1.67	5.02
Wind Model	$1218 - 691.3\lambda + 539.4\tau$	$380 - 253.5\lambda + 153.9\tau$	N/A
<b>Highest Spatial Variability of the Wind</b>			
Spatial Average	7.43	4.19	11.64
Standard Deviation	9.35	3.57	6.13
Wind Model	$2247.6 - 873.7\lambda + 1250.9\tau$	$-102.6 - 501.3\lambda - 357.6\tau$	N/A

equations are approximation of real wind data as a linear function of latitude ( $\lambda$ ) and longitude ( $\tau$ ), defined in radians.

Table 3 shows wind models obtained using MATLAB Toolbox [31] for different wind scenarios in the DFW and NY metropolitan areas. In general, R-square is a goodness-of-fit measure for linear regression models. R-square measures the strength of the relationship between the linear regression model and the dependent variable on a convenient 0 to 1 scale [31]. For the four wind models shown in Table 3, R-square values are observed between 0.91 to 0.95.

### C. Test Apparatus

NASA's Future Air Traffic Management (ATM) Concepts Evaluation Tool (FACET), designed and developed over the last 20 years, provides a flexible simulation environment for the exploration, development and evaluation of advanced ATM concepts [32]. FACET models four-dimensional (4D) aircraft trajectories in the presence of winds using round-earth kinematic equations. Aircraft can be flown along flight plan routes or great-circle routes as they climb, cruise and descend per their aircraft-type performance models. Performance parameters of the aircraft are obtained from a data look-up table. Therefore, a look-up table is created for the multirotor eVTOL aircraft based on the performance data of the conceptual multirotor eVTOL proposed by Silva, et al. [12]. The flight duration results of the optimal control framework using PSOPT solver are validated using the neighboring-optimal wind routing algorithm [33] implemented in FACET. FACET implementation performs a bi-linear interpolation in spatial and temporal dimensions on the available gridded wind data.

### D. Metrics to Measure Operational Benefits

The following two metrics are used to compute operational benefits of flying wind-optimal lateral trajectory compared to great-circle trajectory for a given origin and destination.

#### 1. Energy Savings

The energy savings (%) associated with flying the wind-optimal lateral trajectory compared to the great-circle trajectory is computed as follows:

$$\text{Energy Savings (\%)} = \frac{\text{Energy}_{\text{Great-Circle}} - \text{Energy}_{\text{Wind-Optimal}}}{\text{Energy}_{\text{Great-Circle}}} 100 \quad (24)$$

where  $\text{Energy}_{\text{Wind-Optimal}}$  and  $\text{Energy}_{\text{Great-Circle}}$  are energy consumed flying the wind-optimal lateral trajectory and great-circle trajectory under similar wind conditions, respectively.

## 2. Flight Duration Savings

The flight duration savings (%) associated with flying the wind-optimal lateral trajectory compared to the great-circle trajectory is computed as follows:


$$\text{Flight Duration Savings (\%)} = \frac{\text{Flight Duration}_{\text{Great-Circle}} - \text{Flight Duration}_{\text{Wind-Optimal}}}{\text{Flight Duration}_{\text{Great-Circle}}} 100 \quad (25)$$

where  $\text{Flight Duration}_{\text{Wind-Optimal}}$  and  $\text{Flight Duration}_{\text{Great-Circle}}$  are flight duration flying the wind-optimal lateral trajectory and great-circle trajectory under same wind conditions, respectively.

## E. Dallas-Fort Worth Metropolitan Area

Two types of wind scenarios are considered: i) strongest wind (as shown in Figure 2) and ii) highest spatial variability of the wind (Figure 4) in the Dallas-Fort metropolitan area. The location of vertiports and the direct route lengths are based on the Air Traffic Management - eXploration (ATM-X), Urban Air Mobility (UAM) Experiment 2 scenarios conducted at NASA Ames [11]. Therefore, the great-circle distance between different origin and destination pairs is 30 to 50 nautical miles.


### 1. Case Study - Strongest Wind in the Dallas-Fort Worth Metropolitan Area



**Fig. 2** Depiction of wind field and routes used to study operational benefits of flying wind-optimal lateral trajectories in the DFW metropolitan area for the strongest wind case study

To study wind-optimal lateral trajectories, three routes originating from the origin location (32.901767, -97.193954) are considered [11]. The destinations are chosen at a great-circle distance of 30 nautical miles from the origin. Figure 2 shows a depiction of wind fields and routes used to study the operational benefits of flying wind-optimal lateral trajectories in the Dallas-Fort Worth metropolitan area for the strongest-wind (Table 3) case study.

From Figure 3, it can be seen that in the uniform wind field, the energy consumption and flight duration for the wind-optimal lateral trajectories are the same as the corresponding great-circle trajectories. However, because of the slow nominal cruise speed (50.41 m/s), the energy consumption and flight duration while flying in the headwind is 2-3 times higher than flying the same distance (30 nm) in the tailwind. As shown in Figure 3, the flight duration (cruise) results of PSOPT are validated using the overall flight duration (climb, cruise, and descent) results of FACET. The flight duration results obtained using FACET are generally slightly different (1 - 2 mins) because of: i) climb and descent phases modeled in FACET, which are not considered in PSOPT; and ii) slight difference in the wind field modeling between FACET and PSOPT. FACET directly uses rapid refresh wind data at grid points for trajectory prediction, whereas PSOPT uses a wind model created using Matlab curve-fitting toolbox.




**Fig. 3 Comparison of wind-optimal and great-circle trajectories under different wind conditions in the Dallas-Fort Worth metropolitan area for the strongest wind case study**


## 2. Case Study - Highest Spatial Variability of Wind in the Dallas-Fort Worth Metropolitan Area

To study the impact of spatial variability of the wind field on the wind-optimal lateral trajectory, two routes (50 nm great-circle distance) as shown in Figure 4 are considered. The wind model used to generate wind-optimal and great-circle trajectories is listed in Table 3.

In this case study, the operational benefits (energy consumption and flight duration) with the wind-optimal lateral trajectory when compared to the corresponding great-circle trajectory are observed to be slightly less than 1 % for both the routes as shown in Figure 5. From Figure 5, it can be concluded that the spatial variability of the wind field has an impact on the amount of operational benefits.



**Fig. 4** Depiction of wind field, routes and computed wind-optimal lateral trajectories used to study operational benefits of flying wind-optimal lateral trajectories in the DFW metropolitan area for the highest spatial variability of the wind case study



**Fig. 5** Comparison of wind-optimal lateral trajectory with great-circle trajectory in the DFW metropolitan area for the highest spatial variability of the wind case study


## F. New York Metropolitan Area

Similar to the Dallas-Fort Worth case studies, two types of wind scenarios are considered: i) strongest wind (as shown in Figure 6) and ii) highest spatial variability of the wind (as shown in Figure 8) in the New York metropolitan area. The vertiports and direct route lengths of 30 and 50 nautical miles are based on the Air Traffic Management - eXploration (ATM-X), Urban Air Mobility (UAM) Experiment 2 conducted at NASA Ames [11].

### 1. Case Study - Strongest Wind in the New York Metropolitan Area

To study wind-optimal lateral trajectories, three routes originating from the location (40.703869, -74.176071) as shown in Figure 6 are considered.


From Figure 7, it can be seen that in the non-uniform wind field, the energy consumption and flight duration for the



**Fig. 6** Depiction of wind field and routes used to study operational benefits of flying wind-optimal lateral trajectories in the New York metropolitan area for the strongest wind case study

wind-optimal lateral trajectory are 1.2 % lower than the corresponding great-circle trajectory. However, because of the slow nominal cruise speed (50.41 m/s) and high magnitude of the headwind (approx. 28 m/s), the energy consumption and flight duration while flying in the headwind is 4-5 times higher than flying the same distance (30 nm) in the tailwind. As shown in Figure 7, the flight duration (cruise) results of PSOPT are validated using overall flight duration (climb, cruise, and descent) results obtained using FACET. The flight duration results of FACET are generally slightly different (1 - 2 mins) because of: i) climb and descent phases modeled in FACET, which are not considered in PSOPT; and ii) slight difference in the wind field modeling between FACET and PSOPT. FACET directly uses rapid refresh wind data at grid points for trajectory prediction, whereas PSOPT uses a wind model created using Matlab curve-fitting toolbox. Therefore, the slightly lower flight duration (around 1.5 %) result obtained using FACET under headwind conditions in Figure 7 can be attributed to a higher contribution from wind modeling error in this scenario.





**Fig. 7 Comparison of wind-optimal and great-circle trajectories under different wind conditions in the New York metropolitan area for the strongest wind case study**

To perform the sensitivity analysis on wind-optimal lateral trajectory, the headwind route is further extended to 50 nm (57.54 miles). The headwind route is picked among the three routes because it showed the greatest operational benefits (energy consumption and flight duration) of 1.2 % for wind-optimal lateral trajectory when compared to the corresponding great-circle trajectory. For the headwind route (origin: 41.3661, -74.176071 and destination: 40.2, -74.176071), the operational benefits with the wind-optimal lateral trajectory when compared to the great-circle trajectory are approximately 2.5 % as listed in Table 4. From Table 4 and Figure 7, it can be concluded that the length of the direct route, spatial variability of the wind field, wind magnitude, and direction of the direct route relative to the wind field impact the percentage of operational benefits.


**Table 4 Comparison of wind-optimal lateral trajectory with great-circle trajectory on headwind route (50 nm)**

Trajectory type	Energy consumption (MJ)	Flight duration (seconds)
Wind-Optimal	629.88	4037.71
Great-Circle	646.45	4143.9

## 2. Case Study - Highest Spatial Variability of the Wind in the New York Metropolitan Area


To study the impact of spatial variability of the wind field on the wind-optimal lateral trajectory, two routes (50 nm great-circle distance) as shown in Figure 8.

In this case study, the operational benefits of flying a wind-optimal route compared to the great-circle route for North-East bound flight are approximately 1.1 %. However, the operational benefits of flying a wind-optimal route compared to the great-circle route for South-West bound flight are about 2.3 % as shown in Figure 9. The results of this



(a) Wind field at epoch = 1548000000 (seconds)      (b) Computed great-circle and wind-optimal lateral trajectories

**Fig. 8** Depiction of wind field, routes and computed wind-optimal lateral trajectories used to study operational benefits of flying wind-optimal lateral trajectories in the New York metropolitan for the highest spatial variability of the wind case study




**Fig. 9** Comparison of wind-optimal lateral trajectory with great-circle trajectory in the New York metropolitan area for the highest spatial variability of the wind case study

case study reiterate the earlier conclusion that the length of the direct route, spatial variability of the wind field, wind magnitude, and direction of the direct route relative to the wind field impact the percentage of operational benefits.

### G. Case Study - Simulated Wind in the Dallas-Fort Worth Metropolitan Area

Since 50 nm great-circle distance corresponds to 6-7 wind extraction grid points with 13 km resolution for wind data, therefore, wind field is simulated to perform sensitivity analysis and substantiate the results of the impact of wind field with varying direction (higher magnitude of a spatial gradient than previous case studies) on a wind-optimal lateral trajectory. The north component of the wind ( $W_N$ ) is linearly varied from its maximum magnitude with the direction towards the north at the origin vertiport (32.901767, -97.193954) to its maximum magnitude with the direction towards the south at the destination vertiport (32.897850, -96.204208) as shown in Subfigure 10a. In the simulated wind-field scenario, the north component of the wind ( $W_N$ ) is linearly varied from + 15 m/s at the origin vertiport to - 15 m/s at the destination vertiport as shown in Subfigure 10a, whereas the east component of the wind ( $W_E$ ) is kept constant.

The linear curve-fit of the north component of the wind ( $W_N$  m/s) obtained using the MATLAB curve-fitting tool



(a) Simulated wind field (varying direction)

(b) Eastbound wind-optimal and great-circle trajectories

**Fig. 10** Wind-optimal lateral trajectory and great-circle trajectory in simulated wind with varying direction

[31] is as follows:

$$W_N = -1736.68\tau - 2931.03 \quad (26)$$

$$W_E = 15 \quad (27)$$

From Table 5, it can be seen that in the wind field with varying direction as shown in Figure 10, for the multirotor eVTOL aircraft on a short UAM mission (50 nm), the energy consumption and flight duration for the wind-optimal

lateral trajectory are approximately 1.4 % lower than the corresponding great-circle trajectory.

**Table 5 Comparison of wind-optimal lateral trajectory with great-circle trajectory in simulated wind with varying direction**

Lateral trajectory type	Energy consumption (MJ)	Flight duration (seconds)
Wind-Optimal	220.54	1413
Great-Circle	223.12	1430

## V. Conclusions

The optimal control problem with energy consumption as the performance index was formulated to generate trajectories for a multirotor electric vertical takeoff and landing aircraft on a short urban air mobility mission (less than 60 miles). The optimal control model presented includes a wind model for quantifying the effect of wind on the lateral trajectory. The wind models were formulated by analyzing the real wind data from the Rapid Refresh (RR) operational weather prediction system in the Dallas-Fort Worth and New York metropolitan areas for the following scenarios: i) strongest wind and ii) highest spatial variability of the wind.

Further, this paper presents a framework for comparing energy consumption and flight duration flying wind-optimal lateral trajectories and great-circle trajectories to evaluate the operational benefits (energy consumption and flight duration) of wind-optimal routing for short flights. The lateral trajectory optimization problem was numerically solved using the pseudospectral method for a NASA-proposed conceptual multirotor electric vertical takeoff and landing aircraft.

The numerical results in the Dallas-Fort Worth metropolitan area for the strongest wind case study showed that in uniform wind conditions, the wind-optimal lateral trajectories were identical to the corresponding great-circle trajectories for short flights (30 nm). However, the highest spatial variability of the wind case study showed operational benefits of slightly less than 1 % for both of the 50 nm direct routes, i.e., Eastbound and Westbound.

The numerical results in the New York metropolitan area for the strongest wind case study showed operational benefits flying the wind-optimal lateral trajectories compared to the corresponding great-circle trajectories for short flights (30 nm) with maximum benefit (1.2 %) in the headwind condition. Upon performing a sensitivity analysis by extending the headwind route to 50 nm, the operational benefits increased to 2.5 %. The operational benefits can be attributed to non-uniform wind conditions. However, the highest spatial variability of the wind case study showed operational benefits of 2.3 % for the South-West bound 50 nm direct route, and 1.1 % for the North-East bound 50 nm direct route.

In conclusion, this research study suggests that for short flights in an urban environment, operational benefits of the wind-optimal lateral trajectories over the corresponding great-circle trajectories in terms of energy consumption

and flight duration per flight are dependent on multiple factors. These factors are: i) wind field's spatial variability, ii) wind magnitude, iii) the direction of route relative to the wind field, and iv) cruise segment length. The operational benefits observed in realistic flyable wind scenarios are less than 2.5 %; these could be translated to an equivalent of a maximum of 2 minutes of cruise flight duration savings in the urban air mobility environment. As expected, headwinds and tailwinds along the flight route significantly impact energy consumption and flight duration.

## Acknowledgments

The authors thank Dr. Wayne Johnson, Christopher Silva, Carlos A. Malpica, and Dr. Gloria K. Yamauchi from the Aeromechanics branch at NASA Ames Research Center for constructive discussions and their valuable time. Also, special thanks to Christopher Silva for reviewing the drag and power equations. The material is based upon work supported by NASA under award number NNA16BD14C for NASA Academic Mission Services (NAMS). Part of this material was presented as a conference paper at the 2020 AIAA Aviation Forum [13].

## References

- [1] Uber-Elevate, "Fast-forwarding to the future of on-demand, urban air transportation," <https://www.uber.com/>, 2019. [Online; accessed 19-June-2019].
- [2] Pradeep, P., and Wei, P., "Energy-Efficient Arrival with RTA Constraint for Multirotor eVTOL in Urban Air Mobility," *Journal of Aerospace Information Systems*, Vol. 16, No. 7, 2019, pp. 263–277. doi:10.2514/1.I010710.
- [3] Pradeep, P., "Arrival management for eVTOL aircraft in on-demand urban air mobility," Ph.D. thesis, Iowa State University, Ames, 2019.
- [4] Thippavong, D. P., Apaza, R., Barmore, B., Battiste, V., Burian, B., Dao, Q., Feary, M., Go, S., Goodrich, H. J., Kenneth H, Idris, H. R., Kopardekar, P. H., Lachter, J. B., Neogi, N. A., Ng, H. K., Oseguera-Lohr, R. M., Patterson, M. D., and Verma, S. A., "Urban air mobility airspace integration concepts and considerations," *2018 Aviation Technology, Integration, and Operations Conference*, 2018, p. 3676. doi:10.2514/6.2018-3676.
- [5] Bosson, C., and Lauderdale, T. A., "Simulation evaluations of an autonomous urban air mobility network management and separation service," *2018 Aviation Technology, Integration, and Operations Conference*, 2018, p. 3365. doi:10.2514/6.2018-3365.
- [6] Bole, B., Daigle, M., and Gorospe, G., "Online prediction of battery discharge and estimation of parasitic loads for an electric aircraft," *ESC*, Vol. 2, 2014, p. 5S2P.
- [7] Sridhar, B., Ng, H. K., Linke, F., and Chen, N. Y., "Benefits analysis of wind-optimal operations for trans-atlantic flights," *14th AIAA Aviation Technology, Integration, and Operations Conference*, 2014, p. 2583.
- [8] Ng, H. K., Sridhar, B., and Grabbe, S., "A practical approach for optimizing aircraft trajectories in winds," *2012 IEEE/AIAA 31st Digital Avionics Systems Conference (DASC)*, IEEE, 2012, pp. 3D6–1.

- [9] Sridhar, B., Chen, N. Y., Hok, K. N., Rodionova, O., Delahaye, D., and Linke, F., “Strategic planning of efficient oceanic flights,” *11th USA/Europe Air Traffic Management Research and Development Seminar June 23-26, 2015 Lisbon, Portugal*, 2015.
- [10] “Uber Air Vehicle Requirements and Missions,” , 2020. URL <https://s3.amazonaws.com/uber-static/elevate/SummaryMissionandRequirements.pdf>, [Online; accessed 16-April-2020].
- [11] Verma, S. A., Monheim, S. C., Moolchandani, K. A., Pradeep, P., Cheng, A. W., Thippavong, D. P., Dulchinos, V. L., Arneson, H., Lauderdale, T. A., Bosson, C. S., Mueller, E. R., and Wei, B., “Lessons Learned: Using UTM Paradigm for Urban Air Mobility Operations,” *2020 AIAA/IEEE 39th Digital Avionics Systems Conference (DASC)*, 2020, pp. 1–10. doi:10.1109/DASC50938.2020.9256650.
- [12] Silva, C., Johnson, W. R., Solis, E., Patterson, M. D., and Antcliff, K. R., “VTOL Urban Air Mobility Concept Vehicles for Technology Development,” *2018 Aviation Technology, Integration, and Operations Conference*, 2018, p. 3847.
- [13] Pradeep, P., Lauderdale, T. A., Chatterji, G. B., Sheth, K., Lai, C. F., Sridhar, B., Edholm, K.-M., and Erzberger, H., “Wind-Optimal Trajectories for Multicopter eVTOL Aircraft on UAM Missions,” *AIAA AVIATION 2020 FORUM*, 2020, p. 3271.
- [14] Yomchinda, T., Horn, J., and Langelaan, J., “Flight path planning for descent-phase helicopter autorotation,” *AIAA Guidance, Navigation, and Control Conference*, 2011, p. 6601.
- [15] Tsuchiya, T., Ishii, H., Uchida, J., Ikaida, H., Gomi, H., Matayoshi, N., and Okuno, Y., “Flight trajectory optimization to minimize ground noise in helicopter landing approach,” *Journal of guidance, control, and dynamics*, Vol. 32, No. 2, 2009, pp. 605–615.
- [16] Weitz, L. A., “Derivation of a point-mass aircraft model used for fast-time simulation,” *MITRE Corporation*, 2015.
- [17] Erzberger, H., and Lee, H., “Constrained optimum trajectories with specified range,” *Journal of Guidance and Control*, Vol. 3, No. 1, 1980, pp. 78–85.
- [18] Hoffmann, G., Huang, H., Waslander, S., and Tomlin, C., “Quadrotor helicopter flight dynamics and control: Theory and experiment,” *AIAA Guidance, Navigation and Control Conference and Exhibit*, 2007, p. 6461.
- [19] Heyson, H. H., “A momentum analysis of helicopters and autogyros in inclined descent, with comments on operational restrictions,” 1975.
- [20] Johnson, W., *Helicopter theory*, Courier Corporation, 2012.
- [21] Johnson, W., “NDARC-NASA Design and Analysis of Rotorcraft,” 2015.
- [22] Leishman, J., *Principles of helicopter aerodynamics*, Cambridge Aerospace Series, Cambridge University Press, 2002. URL <https://books.google.com/books?id=-PnV2JuLZi4C>.
- [23] Johnson, W., Silva, C., and Solis, E., “Concept Vehicles for VTOL Air Taxi Operations,” *Conference on Aeromechanics Design for Transformative Vertical Flight, San Francisco, CA*, 2018.

- [24] Chatterji, G., Sridhar, B., and Bilimoria, K., "En-route flight trajectory prediction for conflict avoidance and traffic management," *Guidance, Navigation, and Control Conference*, 1996, p. 3766.
- [25] Betts, J. T., and Huffman, W. P., "Mesh refinement in direct transcription methods for optimal control," *Optimal Control Applications and Methods*, Vol. 19, No. 1, 1998, pp. 1–21.
- [26] Bryson, A. E., *Applied optimal control: optimization, estimation and control*, CRC Press, 1975.
- [27] Kelly, M., "An introduction to trajectory optimization: How to do your own direct collocation," *SIAM Review*, Vol. 59, No. 4, 2017, pp. 849–904.
- [28] Becerra, V. M., "Solving complex optimal control problems at no cost with PSOPT," *2010 IEEE International Symposium on Computer-Aided Control System Design*, 2010, pp. 1391–1396. doi:10.1109/CACSD.2010.5612676.
- [29] Wächter, A., and Biegler, L. T., "On the implementation of an interior-point filter line-search algorithm for large-scale nonlinear programming," *Mathematical programming*, Vol. 106, No. 1, 2006, pp. 25–57. doi:10.1007/s10107-004-0559-y.
- [30] Benjamin, S. G., Brown, J. M., Brundage, K. J., Schwartz, B. E., Smirnova, T. G., Smith, T. L., and Morone, L. L., "NWS Technical Procedures Bulletin 448 RUC-2-The Rapid Update Cycle Version 2," 1998.
- [31] Toolbox, C. F., "For Use with MATLAB;[user's Guide]," *Natick, MA: MathWorks*, 2001.
- [32] Bilimoria, K. D., Sridhar, B., Grabbe, S. R., Chatterji, G. B., and Sheth, K. S., "FACET: Future ATM concepts evaluation tool," *Air Traffic Control Quarterly*, Vol. 9, No. 1, 2001, pp. 1–20.
- [33] Jardin, M. R., and Bryson Jr, A. E., "Neighboring optimal aircraft guidance in winds," *Journal of Guidance, Control, and Dynamics*, Vol. 24, No. 4, 2001, pp. 710–715.