




Innovation Through the Lens of Regolith Polymer Composites for Lunar Construction

2024 ASCE Earth and Space Conference



Nathan Gelino
NASA, Kennedy Space Center, Swamp Works
4/18/24

Introduction

- Motivation:
 - To showcase insights, lessons learned, and innovations from Regolith-Polymer Composite (RPC) development work
 - To share a story about the sometimes-chaotic development path of technology maturation
- Context:
 - NASA is developing construction technologies to build infrastructure on the Moon
 - Examples include launch/landing pads, blast mitigation, power/comm towers, roads, protective shelters, dust free zones
 - An objective is to use resources available on the Moon as construction feedstock
 - Many previous and ongoing efforts show promise



What is Regolith Polymer Composite (RPC)?

- Regolith and polymers are mixed and extruded typically using a compounding process
- Raw regolith is used as a filler (not melted)
- Polymers are used as a binder
 - Thermoplastics
 - Thermosets
 - Geopolymers
- Mixture rate is controlled to minimize polymer content while maintaining good strength characteristics
- Additives can be used to enhance performance
- RPC can be used in typical polymer processes such as injection molding, compression molding, and 3D printing.



RPC pellets are produced on a compounding extruder

Influential Projects



2012 – Regolith Derived Heat Shields*



2014 – Additive Construction using Basalt Regolith Fines**




2015 – Additive Construction with Mobile Emplacement (ACME) Project***

*Hogue, Michael D., et al. "Regolith-derived heat shield for planetary body entry and descent system with in situ fabrication." *Earth and Space 2012: Engineering, Science, Construction, and Operations in Challenging Environments*. 2012. 526-536.

**Mueller, Robert P., et al. "Additive construction using basalt regolith fines." *Earth and Space 2014*. 2014. 394-403.

***Mueller, Robert P., et al. *Additive construction with mobile emplacement (ACME)*. International Astronautical Federation (IAF), 2017.

Early Ideation and Exploration



Premixed and heated regolith and plastic powder



Mixing regolith and plastic while hot shows promise



Extrusion is proven with low tech methods



Extrusion of premixed silicone and regolith



Various polymers and particle size ranges are evaluated




Machining RPC shows promise



RPC blocks are adhered by remelting adjacent surfaces

First "Print"



First generation RPC screw extruder works well despite the crude form




"Poor man's" 3 dof 3D printer



First RPC structure is printed showing feasibility


Zero Launch Mass (ZLM) 3D Printer



U. S. Patent No. 11,260,589



First "Print" on ZLM



Printing a subscale habitat prototype

Mueller, R. P., Gelino, N. J., Smith, J. D., Buckles, B. C., Lippitt, T., Schuler, J. M., ... & Townsend, I. I. (2018, April). Zero launch mass three-dimensional print head. In 16th Biennial International Conference on Engineering, Science, Construction, and Operations in Challenging Environments (pp. 219-232). Reston, VA: American Society of Civil Engineers.

3D Printed Habitat Centennial Challenge



AI Space Factory 3D prints a polymer-basalt fiber habitat prototype*

Foster + Partners and Branch Technology's structure defied gravity before load testing

Penn State 3D prints a cementitious habitat prototype



Keep Alive Mode



A partnership with Autodesk develops toolpath algorithms and 3D prints barricades/blast walls



A partnership with NASA's Exploration Ground Systems Project produces 3D printed concrete formwork



A partnership with KSC's Institution 3D prints a picnic table out of 100% recycled materials




Thermosetting Variant is Effective in Launch/Landing Conditions



Extrusion of high temperature composite




Paver grouting mitigates plume effects



High temp composite mitigates plume effects (~3100 C)

REACT


Relevant Environment Additive Construction Technology



REACT Overview




Swamp Works and AI SpaceFactory join forces




Intent is to mature this technology by exercising it in simulated lunar conditions and building a sub-scale unpressurized protective shelter

Advanced Ground Operations (ARGO) Test Bed



ARGO 3D Printer is installed in the ASSIST vacuum chamber



Software functionality is tested




Print quality is inspected

First Experiments Printing in Vacuum



RPC is printed at 0.250 torr on a heated build plate




Polypropylene has porosity issues
PLA does not



A compatibilizer additive
contributed to porosity

TVAC Testing



A thermal shroud surrounded the build volume and was kept below -190C. Vacuum pressure started at ~10⁻³ torr ends at ~0.8 torr likely due to water sublimation off the shroud when warmed by the extruder and printed structure




Printed test samples prior to water-jetting

Primary Results Summary

ISRU Construction of Vertical Structures Metric	Value
Energy consumption	~3 MWh/m ³
Deposition Rate	0.6 kg/hr
Construction System Mass	~175 kg
ISRU Weight Percent	75% (Targeted 80%)
Height	~0.5 m

- Vacuum pressure and temperature had minimal (if any) effects on construction process and resulting material characteristics
- 80:20 LHS-1:PLA had superior properties:
 - Flexural Modulus = 5.3 Gpa @ 0°
 - Flexural Strength = 24 MPa @ 0°
- Typical lumber properties
 - Flexural modulus of 6-10 GPa
 - Flexural strength of 4-8 Mpa
- Typical unreinforced concrete:
 - Flexural strength 3-5 GPa.
- Potentially suitable for lunar construction
- High performance polymers will likely improve performance
- Mechanical properties across the expected lunar thermal range must be determined
- Material lifecycle must be characterized




Gelino, N. J. et al., (2024, March). "Selection, Production, and Properties of Regolith Polymer Composites for Lunar Construction." IEEE Aerospace Conference, Big Sky, MT.

Lunar Infrastructure Asset (LINA) Structural Design




➤ Shelter Design Brief:


- Protect from radiation- OLTARIS Analysis
 - 2.3 m of 1.3 g/cm³ regolith overburden
- Protect from meteoroids- ConWep Analysis
 - 1 cm impactor at 70 km/s = 0.084 kg TNT (ConWep-Cratering)
 - 2.3 m of regolith stress results (ConWep – G-Shock)
- Withstand moonquakes- ASCE 7-16 Design Criteria
 - A randomly located lunar base would see 1 event of body wave magnitude 4.5 within 100 km every 400 years
 - Current moonquake ground acceleration data is not sufficient!
- Regolith bearing strength - Allowable bearing of 1000 kPa
- Polymer mass < 5 mt - Reasonable payload mass




3D Rhino model of the parabolic arch structure



Gravity Load




Moonquake Load




Meteoroid Impact Load


Subscale LINA Construction



Second generation protective shelter is printed at $\sim 10^{-4}$ torr on LHS-1 Simulant



First generation shelter design



Ground anchors secure the print


Full-scale LINA construction concept





Low TRL Innovation Best Practices



- Understand state of the art and its limitations
 - Confront the problem in new ways
- Take advantage of existing tech for new applications
- Build early to explore the tech and learn from fast, cheap, and safe iterations – finding bad assumptions later is costly
- Produce something physical that proves feasibility – funding comes easier if you have more than slides and reports
- Don't be too disappointed with early setbacks - its only a failure if you don't learn from them
 - Evidence of how much you have learned
- Engage the community – it plants seeds that can grow in unexpected ways
 - Free lessons
 - Rising tide raises all boats
- Explore adjacent applications to expand your customer base
 - New use cases
 - More potential funding sources
 - Synergies emerge



Mid TRL Innovation Best Practices



- Partnering is advantageous for complementary capabilities and access to experts
- Test in relevant environments as soon as possible, unexpected phenomenon happens
- Environments should be as close to real as possible, but they don't have to be perfect
- Don't be deterred by challenging problems, start working towards solutions early
- Formulate/communicate problems in a way that is actionable using terrestrial professional practices
- Understand your technology maturation path
- Share the results

Mid TRL Innovation Best Practices

Have a vision for full scale implementation

