



NASA Goddard Space Flight Center Cleanroom Filtration and HVAC Designs

Innovations and Challenges for Space Flight Cleanrooms




G O D D A R D S P A C E F L I G H T C E N T E R



GSFC Cleanrooms Through the Years

- First cleanroom built in late 1960s.
 - Still in operation today
- Very different requirements
 - Cleanliness standards barely established
- Very different size/mass
 - TIROS-1 (pictured right)
 - Weather satellite
 - Mass: 122.5 kg






GSFC Cleanrooms Through the Years

- First cleanrooms are still in operation
 - Older-style bag filters
 - Shared plenum with 3 different spaces
 - Upgraded most motors from belt driven to variable frequency drives (VFD)



Photo Credit: NASA Archive






GSFC Cleanrooms Now

- Large, hard-walled cleanrooms with dedicated HVAC
- Modular tents, filter banks, cleanrooms that can be deployed and taken down quickly



Photo Credit: NASA/ Sydney Rohde






NASA Builds Largest ISO 7 Cleanroom in the World

- Spacecraft System Design and Integration Facility (SSDIF)
- NASA's largest cleanroom
- Built in 1989
- 36,000 m³
- Certified ISO 7 cleanroom
- Horizontal laminar flow
- Originally designed to support 2 simultaneous shuttle missions



Photo Credit: NASA Archive







SSDIF Projects – James Webb Space Telescope



Photo Credit: NASA/Chris Gunn






SSDIF Projects – Roman Space Telescope






Photo Credit: NASA/Jolearra Tshiteya/Chris Gunn





SSDIF Design






SSDIF Design

- ISO Class 7 cleanroom
- Live particulate monitoring
- Temperature: 68 +/- 2F
- %RH: 45 +/- 5%
- 1 Pa room pressurization
- 690 kPa compressed air
- Ultra pure gaseous nitrogen (GN2) ports



Photo Credit: NASA/Jolearra Tshiteya/Chris Gunn






SSDIF Design

- 2 air handlers providing 6.4 m³/sec and 5.2 m³/sec
- Cooling provided by 6C center chilled water
- 103kPa steam provides pre-heat
- 6x150kW belt driven pressurization fans heat the room
- Secondary cooling wall removes heat from pressurization fan as needed
- 6 stages of HEPA filtration
 - 1x Carbon filter
 - 3x MERV 16 pre-filter
 - 2x MERV 18 HEPA filtration
- Controls by originally Honeywell EBI
- Cosmetic upgrades completed in 2018
- Hardware upgrades started in 2019
- Software upgrades started in 2022






SSDIF Cosmetic Upgrades 2018

- In 2018, the SSDIF shut down for the first time since 1989
- Cosmetic upgrades were completed, including:
 - New floors
 - Maintenance on roll up doors
 - Oil change for 2x 20T cranes
 - Upgrade to LED lighting



Photo Credit: NASA/Zao Huang






SSDIF Hardware Upgrades – Makeup Air Unit



Photo Credit: NASA/Zao Huang

- Provides 6.4 m³/sec of outside air
- 1x MERV 16 1x MERV 19 filtration
- Upgraded to direct drive fans.
- Automated outside air damper to open/close
- Updated pre-heat operations for freeze protection
- Easier serviceability
- Updated to 2019 standards for HVAC, electrical, and fire safety






SSDIF Hardware Upgrades – Recirculating Air Unit



Photo Credit: NASA/Zao Huang

- Provides 5.2 m³/sec of recirculated air
- 1xMERV 16 filtration
- Upgraded to direct drive fans
- Allows for additional humidification tie-in
- Easier serviceability
- Updated to 2019 standards for HVAC, electrical, and fire safety





SSDIF Hardware Upgrades – Pressurization




Photo Credit: NASA/Zao Huang



Photo Credit: NASA/Zao Huang

- Belt driven to direct drive
- 149 kW motor powers a 2.4m fan
- Allows for more consistent pressurization
- Allows for ramp up/ramp down due to room changes
- Allows for easier maintenance
- Variable frequency drives (VFD) required independent glycol cooling units





SSDIF Controls Hardware Upgrades






Photo Credit: NASA/Nafeez Talukder

- Proprietary Honeywell EBI[®] system
- Relied on RS485 serial comms
- Data averaging every 6 seconds
- No back up power on the controllers
- Lack of configuration management and constant patch work





SSDIF Controls Hardware Upgrades



- Open-source Tridium® system
- Ethernet comms with constant data stream
- Greater data redundancy
- Improved alarming to 24/7 on call team






Photo Credit: NASA/Nafeez Talukder


GODDARD SPACE FLIGHT CENTER




SSDIF Controls Software Upgrade




- Moved to cloud-based UI from virtual machine access
- Moved to Niagara[®] framework
- Improved UI interface and data layout






SSDIF Controls Software Upgrade




- Federal Information Security Modernization Act (FISMA) compliant
- Automated reporting and data reduction
- Future scalability
- Resolved Proportional-Integral-Derivative (PID) loop hunting for pressurization






Proportional-integral-derivative (PID) Resolution



Mission Support Directorate

E1405 MSX Fan Repairs




PID tuning chart pre and post repairs

Credit: NASA/Todd Sanders

- Tuned PID loop parameters using Ziegler-Nichol tuning method
- Allowed for more consistent air flow in the cleanroom
- Lowered oscillations on individual VFD





Rapidly Deployed Filtration





Photo Credit: NASA/Zao Huang

- Modular cleantents:
 - Polyurethane curtains
 - 1x MERV 13 pre-filter
 - 1x MERV 19 HEPA filter
 - Fan motor provides air flow
 - 208V/30A/3P
- Modular filter banks
 - 2 or more large filter banks
 - 1x MERV13 pre-filter
 - 1x MERV 19 HEPA filter
 - Fan motor provides air flow
 - 208V/30A/3P or
 - 440V/60A/3P







Rapidly Deployed Filtration



Photo Credit: NASA/Zao Huang







Rapidly Deployed Filtration



Photo Credit: ESA/M. Pedoussaut






Rapidly Deployed Filtration

- Advantages
 - Quick setup
 - Modular components
 - Good for subsystem/instrument development
 - Can move with the project
 - Much more cost effective
- Disadvantages
 - No dedicated HVAC
 - Less environmental control
 - Size limitations
 - Not much utilities
 - Loud (60+ dBs)







Support Services

- Pre-clean room for hardware processing
- Rapid chemistry lab for materials testing
 - NASA GSFC is a silicone-free complex
- Non-volatile residue (NVR) monitoring per IEST-STD-CC1246
- Continuous particle monitoring per ISO 14644
- On-call technicians and contamination control engineer 24/7



Photo Credit: NASA/ Sydney Rohde







Future Challenges

- NASA flight projects have increasingly stringent temperature and humidity control requirements
- Air flow restrictions due to hardware placement
- Material property and selection challenges



Photo Credit: NASA/Chris Gunn





Future Challenges

- Lack of shutdown time prevents full system maintenance
 - We run 24/7/365
- Construction within the cleanroom must happen while flight projects continue work
- Building maintenance moving towards predictive vs preventative time-based maintenance
 - Monthly vibration analysis
 - Differential pressure monitoring

