

The Hyperspectral Microwave Photonic Instrument (HyMPI): Technology Developments for Improved Planetary Boundary Layer Sounding

Fabrizio Gambini^{1,2,3}, Victor Torres¹, David Robles³, Edward Leong³, Priscilla Mohammed^{3,4}, Michael Coon³, Roger Banting³, Jeffrey Piepmeier³, Mark Stephen³, Antonia Gambacorta³



¹Univ. of Maryland Baltimore County, ²CRESST II, ³NASA Goddard Space Flight Center, ⁴Morgan State Univ.

Motivation:

This work presents an overview of the Hyperspectral Microwave Photonic Instrument (HyMPI) which aims at developing the very first hyperspectral microwave sensor to augment thermodynamic sounding capability from space, with a focus on the Earth's Planetary Boundary Layer.

Methodology



Antenna


Captures MW spectrum.



EOM:

G-Band Rx

Down-converts between 0-40 GHz and amplifies 40 GHz range spectra.



SAWG (PIC: 20 x 12.5 mm²):

Laser

Up-converts microwave spectrum to optical domain.

EOM

SAWG

Separates spectrum into 10 x 4 GHz sub-bands.

Laser

Sub-bands with structure are mixed with a new optical tone and digitized (**Hi-Res Channels**).

BPR

ASIC




ASIC:

PD


Sub-bands with minimal structure are measured directly (**Lo-Res Channel**).

Rx: receiver - EOM: electro-optical modulator - SAWG: serial arrayed waveguide grating - BPR: balanced photoreceiver - ASIC: application specific integrated circuit - PD: photodiode




- The instrument is based on photonic integrated circuits (PIC) – minimize size, weight and power consumption and cost (SWaP-C)
- HyMPI covers is a modular design, with simultaneous 40 GHz coverage
- It can be applied to multiple parts of the spectrum to obtain full coverage of the MW thermal domain
- PICs + ASICs = “PICASIC”: full, contiguous, hyperspectral resolution (thousands of channel) ultra-wideband coverage

Hyperspectral performance:




- The Noise Equivalent Differential Temperature (NEDT) values are related to the noise figure of the front-end
- The photonic link add only marginal noise

Window channels performance:



- The Noise Equivalent Differential Temperature (NEDT) values are related to the noise figure of the front-end

Spectrometric performance




- Add comment here...

Conclusions:

- We demonstrated the full end-to-end system performance at hyperspectral-resolution of HyMPI
- We demonstrated that PICs overcome the limitation of the current MW technology: they enhance the performance of the system and minimize SWaP-C

Next step: AURORA Pathfinder

Space-based technology demonstration of broad-spectrum and hyperspectral microwave photonics-based sounders for future NASA science missions



Project start:
December 1 2024

Lead: NASA GSFC
In collaboration with
NASA JPL