
Orion Artemis II Optical Communications (O2O)

Bryan S. Robinson

CCSDS Optical Comm Working Group

18 September 2025



DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited. This material is based upon work supported by the National Aeronautics and Space Administration under Air Force Contract No. FA8702-15-D-0001 or FA8702-25-D-B002. Any opinions, findings, conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Aeronautics and Space Administration.


© 2025 Massachusetts Institute of Technology.

Delivered to the U.S. Government with Unlimited Rights, as defined in DFARS Part 252.227-7013 or 7014 (Feb 2014). Notwithstanding any copyright notice, U.S. Government rights in this work are defined by DFARS 252.227-7013 or DFARS 252.227-7014 as detailed above. Use of this work other than as specifically authorized by the U.S. Government may violate any copyrights that exist in this work.

The Artemis Campaign

National Aeronautics and
Space Administration





ARTEMIS II


First Crewed Test Flight to the Moon Since Apollo

- 1 LAUNCH**
Astronauts lift off from Launch Pad 39B at Kennedy Space Center.
- 2 JETTISON SOLID ROCKET BOOSTERS, FAIRINGS, AND LAUNCH ABORT SYSTEM**
- 3 CORE STAGE MAIN ENGINE CUT OFF**
With separation.
- 4 PERIGEE RAISE MANEUVER**
- 5 APOGEE RAISE BURN TO HIGH EARTH ORBIT**
Begin 23.5-hour checkout of spacecraft.
- 6 ORION SEPARATION FROM INTERIM CRYOGENIC PROPULSION STAGE (ICPS) FOLLOWED BY PROX OPS DEMO**
Plus manual handling qualities assessment for up to 2 hours.
- 7 ORION UPPER STAGE SEPARATION (USS) BURN**
Begins high Earth orbit checkout. Life support, exercise, and habitation equipment evaluations.
- 8 PERIGEE RAISE BURN**
- 9 TRANS-LUNAR INJECTION (TLI) BY ORION'S MAIN ENGINE FOLLOWED BY PROX OPS DEMO**
Lunar free return trajectory initiated with European service module.
- 10 OUTBOUND TRANSIT TO MOON**
Outbound trajectory correction (OTC) burns as necessary for lunar free return trajectory; travel time approximately 4 days.
- 11 LUNAR FLYBY**
4,047 mi/6,513 km (mean) lunar far side flyby altitude.
- 12 TRANS-EARTH RETURN**
Return trajectory correction (RTC) burns as necessary to aim for Earth's atmosphere; travel time approximately 4 days.
- 13 CREW MODULE SEPARATION FROM SERVICE MODULE**
- 14 ENTRY INTERFACE (EI)**
Enter Earth's atmosphere.
- 15 SPLASHDOWN**
Ship recovers astronauts and capsule.


PROXIMITY OPERATIONS DEMONSTRATION SEQUENCE	9
1	10
2	11
3	12
4	13
5	14
6	15
7	16
8	17



Artemis II Mission Trajectory (Example)




Orion Orientation
(Tail to Sun)



NASA Artemis/Orion


- **NASA Artemis missions to return humans to moon in 2020's**
 - 2022 Artemis-1 uncrewed lunar flyby
 - 2026 Artemis-2 crewed lunar flyby
 - 2027 Artemis-3+ lunar landing
- **Moon provides staging ground for eventual missions to Mars**
- **Orion comm capability**
 - S-band phased array transmitters
 - Up to ~2 Mb/s from lunar ranges to NASA Deep Space Network
- **Orion Artemis-II Optical comm (O2O) to provide**
 - Up to 250 Mbps return
 - 20 Mbps forward





Orion Storage and Data Rates


- Orion subsystems expected to generate ~250 GB of data in first day of mission and ~300GB by end of mission
- Using S-Band continuously,
 - Downlink limited to ~ 7GB of data per day
 - 230 GB remains onboard at landing
- With planned 1 hour/day of 80Mbps optical comm,
 - Downlink 36GB of data per day
 - 6x increase per day!
- With 1 hour/day of 260 Mbps optical comm,
 - Downlink 117GB per day almost
 - All data downlinked after 4 days
- With 2 hour/day of 260Mbps optical comm
 - Downlink 234GB/day
 - All data downlinked after 2 days






O2O Mission Level Architecture Diagram

LEMNOS / O2O Optical Communication System






O2O Space Terminal Element



Three Space Payload "Islands"





Mass: 76 kg (incl. mounting & thermal control structure)
Power: 165W (incl. power conversion & thermal control)



Optical Module Island

- **Industry and MITLL-built optical module**
 - 10-cm off-axis telescope
 - Hemispherical field of regard
 - Coudé-path to small optics bench
 - Star tracker for attitude knowledge
 - Multiple fine-steering optics for simplifying alignment process and maintaining alignment during mission
- **Island structure allows mounting to Orion exterior panels**
 - Includes isolation system for mitigation of launch loads
 - Includes self-contained thermal control system
 - Radiator for small optics
 - Controller Electronics controls multiple operational heater zones




**Assembled Optical Module Island
Installed in Thermal Vacuum Tank**




Inner Wall Assembly

- **Industry-developed modem provides**
 - Data interfaces to spacecraft
 - Data encoding and modulation onto transmit laser
 - Pulse position modulation (CCSDS standard)
 - Downlink data rates of 20-260 Mbps
 - High power transmit signal amplifier (1W)
 - Low-noise optically-preamplified receiver
 - Pulse position modulation (CCSDS standard)
 - Uplink data rates of 10, 20 Mbps
 - Fiber interfaces to optical module
- **Avionics mounted on isolated plate inside Crew Module Adapter**



Inner Wall Assembly






Image Source: <https://images.nasa.gov/details/jsc2025e016293>



Image Source: <https://www.nasa.gov/general/nasa-progresses-toward-crewed-moon-mission-with-spacecraft-rocket-milestones/>