


NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Calibrated Clamp Facilitates Pressure Application



The problem:

Applying a specific clamping pressure to hold materials together or to hold work to a surface during bonding, machining, welding, and other similar operations.

The solution:

A spring-loaded clamp having two adjustable legs that are terminated in suction cups, permitting easy attachment to a surface.

How it's done:

The two threaded bolts connected to the crossbar are fitted with suction cups in a swivel connection, facilitating attachment to a curved surface. The pressure plate is attached to the spring-loaded rod passing through a hole in the center of the crossbar.

When the device is used to clamp materials together, the suction cups are placed on a supporting surface and fastened, if necessary, with a nonhardening adhesive. The screw bolts are then adjusted to apply the desired pressure to the pressure plate. The spring-loaded rod may be provided with calibrated markings to indicate the applied pressure.

Note:

Inquiries concerning this invention may be directed to:

Technology Utilization Officer
Manned Spacecraft Center
P.O. Box 1537
Houston, Texas, 77001
Reference: B66-10059

(continued overleaf)

Patent status :

Inquiries about obtaining rights for the commercial use of this invention may be made to NASA, Code AGP, Washington, D.C., 20546.

Source: North American Aviation, Inc.,
under contract to
Manned Spacecraft Center
(MSC-298)