

# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Run-In With Chemical Additive Protects Gear Surface

### The problem:

Scoring of highly loaded gears of the Mk 3 turbopump is a problem which lubricants such as MIL-L-25336, MIL-L-7808, and kerosenes in RP-1 rocket fuel and RJ-1 ramjet fuel have been unable to prevent.

### The solution:

Employ a run-in procedure on the turbopump gears prior to their actual use in an engine.

### How it's done:

The gear assembly is cleaned, vapor-honed, and subjected to controlled running-in on a back-to-back gear stand. During the run-in, the gears are step-loaded up to a point exceeding full operational loading while being subjected to a highly reactive, extreme pressure additive. The run-in treatment apparently applies a protective coating on the gear surfaces so that they are capable of operation under marginal

conditions in mineral oil (including kerosene) and diester lubricants.

### Notes:

1. This procedure can be used to protect highly loaded gears during relatively short-term operation.
2. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer  
Marshall Space Flight Center  
Huntsville, Alabama, 35812  
Reference: B66-10069

### Patent status:

No patent action is contemplated by NASA.

Source: M. A. Hartman  
of North American Aviation, Inc.,  
under contract to  
Marshall Space Flight Center  
(M-FS-548)

Category 05