https://ntrs.nasa.gov/search.jsp?R=19660007119 2018-07-23T05:32:48+00:00Z

LINE-REVERSAL MEASUREMENTS OF EXCITATION AND ELECTRON TEMPERATURE IN A SHOCK TUBE

--- ∘ ---

Scientific Report #8 NsG-438

by

W. R. S. Garton
Imperial College, London, England

and

W. H. Parkinson and E. M. Reeves
Harvard College Observatory
Cambridge, Massachusetts

November 1965

16408

ABSTRACT

The spectral line-reversal method has been applied to determine population-temperatures within an (argon-calcium) plasma, generated by a reflected aerodynamic shock. The measurements have been made simultaneously on (a) normal bound-bound Ca I lines, (b) lines involving strongly auto-ionizing levels. The agreement of the two sets of values identifies the electron-temperature with the temperature characterizing the populations of the bound excited-states, giving improved confidence in the existence of complete thermal equilibrium in the reflected shock.

Author

The spectral-line reversal method has been previously applied to transitions between normal bound electronic states of neutral atoms, ions or molecules, (Gaydon and Hurle 1963; Charatis and Wilkerson 1962; Parkinson and Reeves 1964). The technique yields the "excitation" or "population" temperature between the pair of states concerned, but has the great advantage over methods which depend only on relative intensities of emission or absorption lines, of avoiding involvement with transition probability values, as well as the complex issues which arise when account has to be taken of partition function termination and ionization potential depression, (Garton, Parkinson and Reeves 1964). In earlier experiments with shock-heated gases we have observed (Parkinson and Reeves loc. cit.) the line reversal temperature to be independent of the excitation energy, and on that basis have suggested the gas to be in thermal equilibrium.

We have now made further reversal-temperature measurements on lines possessing strongly autoionizing upper states, i.e., states lying in the continua above the normal series terms converging on the ground state of the ion. The population of an autoionizing level depends on the electron density and electron temperature. The autoionization-broadened line may, in fact, be regarded as a resonance in an ionization continuum (Fano 1961; Fano and Cooper 1965), the selection rules for autoionization requiring that the upper level can find an adjacent continuum of the same J and parity, and for LS-coupling the same L- and S-values. Departures from LS-coupling relax the latter requirement. If reversal-temperature measurements are made on the same plasma, respectively with lines which do and do not have autoionizing upper states, and identical values are found, it is a safe conclusion that the electron temperature has been measured

and found equal to the temperature characterizing the Boltzmann distribution of the normal bound states. In the measurements here reported, the two reversal temperatures did agree within experimental error, and the assumption of a good approach to thermal equilibrium in the shock-heated gas is thereby strengthened.

Not many autoionized lines have been identified in the wavelength region above 2800Å where line-reversal measurements are possible. Fortunately, however, the autoionizing transition 3d4p $^3F^\circ$ - 3d4d ^3G in neutral calcium has been identified at λ6362, λ6343 and λ6318. The normal transition 4p ^3P_o - 4d ^3D of Ca I also provides a suitable line at 4425.4Å. With the method of shock-heating powdered solids, calcium vapour can easily be introduced into the reflected shock region and simultaneous line-reversal temperature measurements can be made with one of the autoionized λ6350 lines and the normal λ4425 Ca I line. Since the ^3G upper level of the autoionizing transition lies in the continuum, the triplet of λ6350 has a lower level which is approximately 4.5 electron volts above the ground state. A temperature of approximately 6000°K in the reflected shock was required to populate the ^3G state sufficiently for the line to be observed in emission.

The experimental arrangement for these measurements was very similar to that reported earlier (Parkinson and Reeves loc. cit.). A Xenon flash tube (EGG FX-12 provided the background continuum for both atomic lines. Light from the same region of the reflected shock and from the FX-12 was divided by a beam-splitter, and images were formed on the entrance slits of two F/9 half-meter Jarrell-Ash scanning spectrometers. An RCA 1P28 photomultiplier was used to detect the 4425Å radiation, and an RCA 4463 recorded the autoionized line, with entrance and exit slits of both monochromators set at approximately 20 microns.

The optical system was calibrated with a Phillips tungsten-filament standard lamp. The shock waves were produced in a pressure-driven stainless-steel shock tube with a 9-ft. channel, 3-ft. driving section with uniform 2 inch square cross section. Hydrogen at 165 psi was used to generate the shocks in pure argon at an initial pressure of 10 Torr.

The measured temperatures and emissivities for the two wavelengths are listed in Table I. The average difference between the pairs of measured temperatures is approximately 50°K, and is within our estimated experimental error of 1.5%. To verify the estimate of the experimental error we made several runs with both monochromators on the 4425Å line and observed a temperature difference of about 90°K.

Because the calcium atoms were introduced into the reflected shock by the powdered solid technique, we were concerned about the uniformity in the distribution of powder and the concentration in the boundary layer. We observed, for optically thick lines, that the boundary layer in the shock tube could affect the temperature by as much as 300° in 6500°. For this reason, the emissivity was kept less than one so that the temperature that was measured would represent an average temperature across the shock tube. The distribution of atoms would, of course, be more uniform in an experiment where the atomic species could be introduced into the channel gas as a volatile vapour, and it would then be possible to compute the temperature. With the powdered solid technique one cannot calculate the temperature behind the reflected shock wave because of the unknown amounts of energy required to vaporize, dissociate, and excite the actual number of calcium atoms in the test gas. Attempts at this calculation have indicated that the energy involved would reduce the temperature from that of the pure argon case by approximately 15%.

We are continuing these experiments on other autoionized lines from atoms introduced to the shock as powdered solids and as volatile compounds. With the confirmation of thermodynamic equilibrium in the shock tube, it will be possible to measure the absolute intensity in the centers of autoionized lines. This method then offers the possibility of using the shock tube as an absolute standard of radiation at wavelengths where autoionized lines are observed.

ACKNOWLEDGEMENT

The work reported has been performed at Harvard College Observatory and has been supported by NASA (Grant NsG-438) and the Office of Naval Research (Contract NONr-1866(48)). The authors wish to thank Mr. J. Allen and Mr. D. Zitros for their help in the experiments.

TABLE I

Line	6362.4Å		4425Å		
	Temp. (°K)	ε	Temp. (°K)	ε	ΔT(°K)
	5760	0.76	5890	0.42	-130
	6258	0.70	6262	0.40	- 4
	6390	0.45	6360	0.633	+ 30
	6740	0.62	6798	0.76	- 58
	6800	0.36	6767	0.59	+ 33

Average $\Delta T = 51°$

REFERENCES

Charatis, G. and Wilkerson, T., 1962, Phys. of Fluids, 5, 1661.

Fano, U., 1961, Phys. Rev., 124, 1866.

Fano, U. and Cooper, J. W., 1965, Phys. Rev., 137, A1364.

Garton, W. R. S., Parkinson, W. H. and Reeves, E. M., 1964, Ap. J., 140, 1269.

Gaydon, A. G. and Hurle, I. R., 1963, "The Shock Tube in High-Temperature Chemical Physics," Chapman and Hall, Ltd., London.

Parkinson, W. H. and Reeves, E. M., 1964, Proc. Roy. Soc., 282, 265

Non-classified
Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY *(Corporate author)* Harvard University	2a. REPORT SECURITY CLASSIFICATION 2b. GROUP

3. REPORT TITLE

Line-Reversal Measurements of Excitation and Electron Temperature in a Shock Tube

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

Scientific Report, November 1965

5. AUTHOR(S) *(Last name, first name, initial)*

Garton, W.R.S. Reeves, E.M.
Parkinson, W.H.

6. REPORT DATE November 1965	7a. TOTAL NO. OF PAGES 8	7b. NO. OF REFS 6

8a. CONTRACT OR GRANT NO. NONr-1866(48), NsG-438 b. PROJECT NO. c. d.	9a. ORIGINATOR'S REPORT NUMBER(S) Scientific Report # 8 9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*

10. AVAILABILITY/LIMITATION NOTICES

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY

13. ABSTRACT

The spectral line-reversal method has been applied to determine population-temperatures within an (argon-calcium) plasma, generated by a reflected aerodynamic shock. The measurements have been made simultaneously on (a) normal bound-bound Ca I lines, (b) lines involving strongly autoionizing levels. The agreement of the two sets of values identifies the electron-temperature with the temperature characterizing the populations of the bound excited-states, giving improved confidence in the existence of complete thermal equilibrium in the reflected shock.

DD FORM 1 JAN 64 1473

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, or *(U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.