

# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Stress-Corrosion Characteristics of Aluminum Casting Alloy M-45

Aluminum alloy M-45 was developed primarily as a lightweight structural casting metal with high tensile, yield, and impact strengths at cryogenic temperatures. The composition and mechanical properties of this alloy are given in Tech Brief 65-10092. Tentative results of an experimental study undertaken to arrive at a heat-treatment cycle which would optimize both the strength and stress-corrosion resistance of M-45 are discussed in Tech Brief 67-10159.

In a recent investigation, the stress-corrosion characteristics of the M-45 aluminum alloy were evaluated for the nine aged conditions considered, from the earlier study, as most promising with regard to a combination of optimum strength and stress-corrosion resistance. The only specimens stressed to 75 percent of the yield strength which did not display stress corrosion cracking were those artificially aged at 400°F for 12 hours. Stress-corrosion cracking was evident in 4 of 6 specimens artificially aged at 375°F

for 26 hours. It is concluded from this investigation that the most favorable artificial aging cycle for this alloy, with regard to optimum strength and stress-corrosion resistance, appears to be 400°F for 12 hours. The practice of aging at 375°F for 26 hours does not result in an optimum combination of strength and stress-corrosion resistance.

### Note:

Complete details of this investigation may be obtained from:

Technology Utilization Officer  
Marshall Space Flight Center  
Huntsville, Alabama 35812  
Reference: B68-10184

### Patent status:

No patent action is contemplated by NASA.

Source: C. V. Lovoy  
(MFS-14817)

Category 03