


NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Miniature Backward-Diode Pressure Sensor Features Stability and Low Power Consumption



The pressure sensitivity of degenerate semiconductor junctions has recently been utilized very effectively in miniature pressure sensors (transducers).

Investigations of the tunnel diode as a pressure transducer (see Tech Brief 68-10563) proved that a shunting resistor was necessary to eliminate the

negative resistance. Negative resistance can cause unwanted oscillation and makes it difficult to bias the tunnel diode at the peak-current point. Addition of a shunt resistor solves the problem at the expense of greater package volume and added fabrication steps.

Use of a backward diode avoids the difficulties mentioned above, because it does not exhibit negative resistance. The backward-diode pressure transducer retains the advantages of a tunneling mechanism, requires no shunting resistor, operates at a low voltage level, and consumes little power.

Because of its exceedingly small size, this device may be valuable in biomedical and other applications requiring miniature pressure sensors.

Note:

Request for further information may be directed to:
 Technology Utilization Officer
 Electronics Research Center
 575 Technology Square
 Cambridge, Massachusetts 02139
 Reference: TSP69-10690

Patent status:

Inquiries about rights for commercial use of this invention may be made to NASA, Code GP, Washington, D.C. 20546

Source: W. Rindner and A. Garfein
 Electronics Research Center
 (ERC-10229)

Category 01