


NASA TECHNICAL NOTE



NASA TN D-5797

c. 1

NASA TN D-5797

LOAN COPY: RETURN TO
AFWL (WLOL)
KIRTLAND AFB, N ME



LASER HEATING OF IONIZED HELIUM

by Victor E. Scherrer

Electronics Research Center

Cambridge, Mass. 02139

LASER HEATING OF IONIZED HELIUM

By Victor E. Scherrer
Electronics Research Center

SUMMARY

A method of generating a plasma by combined electrical and laser heating has been developed. An arc, formed between two needle electrodes heated the helium gas to an electron temperature of 10 to 20 eV. At this temperature, the helium was partially ionized. The pre-ionized helium was further heated by a focused laser beam. With a laser power of 15 to 25 MW giving a power density of 3 to 5×10^{10} W/cm² at the focus, the helium temperature was increased to 26 to 42 eV. Time resolved spectral techniques (ref. 1) were used to measure the temperature of the gas.

INTRODUCTION

A method of generating high energy density plasmas by electrically heating He gas, which was then further heated by a focused laser beam, has been developed. The electrical preheating established a high density of free electrons in the plasma, which absorbed laser light. This electrical preheating arrangement has the advantage over laser heating of cold gas targets, of efficient laser heating. Therefore, only a small, low powered laser is required.

The objective of this study was to develop a high temperature He test gas for spectral and other plasma diagnostic measurements.

DESCRIPTION OF THE EXPERIMENT

In this experiment, two energy sources, a capacitor storing electrical energy, and a Q-switched ruby laser were used to heat helium gas to high temperatures for plasma diagnostic studies. The electrical discharge first heated the gas between two needle-shaped electrodes. When 2.5 J of electrical energy were deposited in helium, it was heated to a kinetic electron temperature of about 10 eV. When the arc current reached a maximum, a ruby laser beam, focused on the arc, further heated the helium gas, resulting in temperatures of 26 to 42 eV.

A schematic diagram of the experiment is shown in Figure 1. The electrical arc used tungsten electrodes with the tips separated 500 μ . The average tip radius was 25 μ . The arc tube was filled with He gas; the ambient gas pressure was 700 torr.

An arc was generated when the capacitor (.05 μ F) was connected across the electrodes by a triggered air gap switch. The capacitor stored 10 J of energy at a potential of 20 kV. The discharge frequency was 1 MHz. The initial arc diameter, midway between electrodes was 1 mm, and expanded to a diameter of 3 mm at peak current.

The arc was heated by a ruby laser (6943 \AA) having a 15-ns pulse; the peak power was 25 MW. Trigger circuits fired the laser at any preset time relative to the electrical discharge. The maximum time jitter was ± 10 ns.

In the electrical heating circuit, current through and voltage across the arc were monitored. The incident and transmitted laser light was monitored with 1.5-ns resolution. A Beckmann and Whitley Model 200 streak-framing camera was used to observe radial motion of ionized helium in the arc. Time resolution of the streak camera was 20 ns.

A SPEX Model 1700 spectrograph was used to observe the spectral distribution of emitted radiation. The electron temperature of the plasma was deduced from these measurements.

EXPERIMENTAL RESULTS

Figure 2 is a streak picture which shows the expansion of electrically heated helium midway between electrodes. It expanded to a diameter of 3 mm in 100 ns.

When the current through the arc reached its maximum, the Q-switch was triggered, resulting in a laser light pulse incident upon the ionized helium. Since the helium was ionized, much of the light was absorbed, thus further heating the helium plasma.

The mechanisms by which laser light was absorbed have not been positively established, but a likely mechanism is the "inverse bremsstrahlung effect" (ref. 2). For this energy absorption mechanism, the quantity of light absorbed depends upon the density of free electrons in the target.

Figure 3 shows the results of measuring the laser light absorbed in the transient arc source. The percent of incident laser light is plotted against the ambient helium gas pressure. As indicated in the figure, the target becomes more transparent for helium pressures below 300 torr. The percent of laser light absorbed is almost constant for ambient gas pressures above 400 torr.

He (ELECTRICAL ONLY)
PRESSURE = 660 TORR
ELECTRICAL ENERGY = 2.5J
N.D. = 2.0




Figure 2.- Streak picture showing plasma expansion due to electrical heating

Figures 4 and 5 show streak pictures taken during laser heating. The ambient helium pressure for the picture shown in Figure 4 was 160 torr. The direction of the incident laser light is indicated in the figure. The laser light was absorbed throughout the expanding plasma. The streak picture shown in Figure 5 shows laser heating of an arc occurring in helium having an ambient pressure of 400 torr. In this case, most of the laser heating occurred on the side of the helium plasma corresponding to the incident laser light.

The kinetic electron temperature of the plasma in the transient arc was measured with and without laser heating. The results are shown in Table I. The stored energy for the electrical discharge was 2.5 J. The average laser heating power for each of four shots is given in the first column. The estimated power density in the focused laser beam is given in the second column. The electron temperature, T_1 , of the arc at the instant of time when the laser was fired is shown in the third column.




Figure 3.- Absorbption of laser light in the helium arc

TABLE I.- LASER HEATING OF PRE-IONIZED TARGET

Average Input Laser Power MW	Focused Laser Power MW/cm ²	T ₁ eV	T ₂ eV
12	10^{10}	10	27
20	1.67×10^{10}	11	24
22	1.83×10^{10}	11	40
24	2×10^{10}	10	55

The temperature due to electrical heating alone varied from 10 to 15 eV. This temperature was determined by the intensity ratio of the HeI 4686-Å line to background continuum technique (ref. 1). The fourth column gives the peak electron temperature, T₂, attained due to laser heating. The temperature measurements were made using the intensity ratio of the spectral lines (ref. 1) HeI (4922 Å) to HeI (4713 Å).




Figure 4.- Streak picture showing laser heating of He at low pressure




Figure 5.- Streak picture showing effects of laser heating of He (400 torr)

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
WASHINGTON, D. C. 20546
OFFICIAL BUSINESS

FIRST CLASS MAIL



POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION

07U 001 41 51 3DS 70185 00903
AIR FORCE WEAPONS LABORATORY /WL0L/
KIRTLAND AFB, NEW MEXICO 87117

ATT E. LOU BOWMAN, CHIEF, TECH. LIBRARY

POSTMASTER: If Undeliverable (Section 158
Postal Manual) Do Not Return

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

— NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Notes, and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION DIVISION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546