

NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Laser Interferometry Method for Absolute Measurement of the Acceleration of Gravity

A laboratory model of an absolute gravimeter can measure the acceleration of gravity, g , with a significantly greater accuracy than has previously been attained. Experiments with the developmental gravimeter indicate that, with certain refinements and error analysis, the Potsdam values, which had been established for g at various locations on the earth's surface, can be corrected by approximately 138 microns/sec². The new gravimeter has potential as a more accurate and precise instrument for the absolute measurement of g without reference to the Potsdam values as absolute standards.

The device is basically a Michelson laser beam interferometer in which one arm, designated the "bird," is a mass fitted with a corner cube reflector. During operation, the bird is released to fall freely under the acceleration of gravity in a hard vacuum. The monochromatic light beam, emanating from a helium-neon continuous-wave laser at a wavelength of 0.633 micron, is highly collimated, with a beam divergence of 10 mrad. A collimating lens is mounted on the laser to decrease beam divergence even further. A polarizing filter that can be adjusted for best interference-fringe contrast is positioned behind the collimating lens. The laser unit, which emits a power of 100 μ W, is controlled by a servo system and has a frequency stability of ± 1 mHz per day. The laser beam is projected through a beam splitter, which breaks the light into two beams, one beam going to the mirror on the freely falling bird and the other to a fixed front-surface mirror. The two beams are reflected from both mirrors back to the

beam splitter, where they are superimposed and passed on to a photodetector. The interference fringes are detected by the photodetector, and the resultant output pulses are counted electronically. From these data, the distance fallen by the bird in a given time is ascertained, and the acceleration of gravity is easily computed.

Note:

The following documentation may be obtained from:

National Technical Information Service
Springfield, Virginia 22151
Single document price \$3.00
(or microfiche \$0.95)

Reference:

NASA-TM-X-53832 (N70-17316), Technical Documentation for the Mark I Model of the Laser Absolute Gravimeter

NASA-TM-X-53856 (N70-17389), Operation Manual for the Mark I Model of the Laser Absolute Gravimeter

NASA-TM-X-64503 (N70-35842), Gravity Gradient Measurements with a Laser Absolute Gravimeter

Patent status:

No patent action is contemplated by NASA.

Source: Dr. O. K. Hudson
Marshall Space Flight Center
(MFS-21225)

Category 03