

# NASA TECH BRIEF

## *Goddard Space Flight Center*



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

### Optical Design and Analysis Program

#### The problem:

Existing computer programs for optical system analysis and telescope design have several drawbacks: ambiguity in diagnosing input data errors; dependence on a specific system configuration; inconvenient input data format; bulky size, requiring the use of large computers; and function intradependence, preventing the program from being trimmed or modified to fit a particular computer or system.

#### The solution:

A new computer program provides efficient handling of optical analysis equations, from both the general skew and paraxial ray standpoints, and is sufficiently general in approach to accept a wide variety of systems which can be introduced in a convenient form. Meaningful diagnostic messages are generated to aid the user in pinpointing any inconsistencies in the system definition.

#### How it's done:

The program uses standard optical system analysis equations, as outlined in the "Military Standardization Handbook of Optical Design." It is designed to trace the exact paths of up to 800 representative rays through any number of symmetric or asymmetric optical systems. Rays may also be traced two at a time through a paraxial ray trace.

The functions of the program are segmented and the functions within each segment are defined such that, while the segments are not autonomous, the

program can be converted to other computers or other languages, and changes in method can be incorporated easily.

The program is sufficiently general in approach to accept a large spectrum of systems defined by normal, tilted, or decentered planar surfaces. Rotationally symmetric quadric, aspheric, and deformed spheric and conic surfaces may be input in any combination of up to 22 surfaces per system.

#### Notes:

1. This program is written in FORTRAN IV for the CDC-3000L computer, and is small enough to be executed on other small computers. The program uses approximately 21,000 24-bit words of core.
2. Requests for further information may be directed to:

COSMIC  
112 Barrow Hall  
University of Georgia  
Athens, Georgia 30601  
Reference: B71-10456

#### Patent status:

No patent action is contemplated by NASA.

Source: C. F. Meredith of  
Sperry Rand Corporation  
under contract to  
Goddard Space Flight Center  
(GSC-11393)

Category 09