https://ntrs.nasa.gov/search.jsp?R=19710000500 2018-03-17T16:13:19+00:00Z

December 1971

Brief 71-10503

NASA TECH BRIEF NASA Headquarters



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Metal-Shearing Energy Absorber

A device consisting of a tongue of thin aluminum alloy strip, a pull tab, a slotted steel plate which serves as a cutter, and a steel buckle (see Fig. 1), absorbs mechanical energy when its ends are subjected to tensile loading. As the tensile load is applied, the aluminum alloy metal on either side of curl up, absorbing additional energy, the amount of which depends on the width and radius of the curls. This version of the device is most effective when the shear strip is bent slightly so that the sheared outer strips roll up in opposite directions (not illustrated).





the tongue continuously shears away and the inner portion of the strip passes through the cutting slot. The mechanical energy dissipated depends on the material and thickness of the shear strip and on the duration of the applied tensile load.

In a second version of the device (see Fig. 2), the cutter is made by machining a central slot in a flat steel plate and then bending the plate into a U-shape. The action of this device is similar to that of the first version, except that the sheared metal edges auxiliary shock-absorbing anchor for safety belts in automobiles and airplanes.

Note:

No additional documentation is available. Specific questions, however, may be directed to:

Technology Utilization Officer NASA Headquarters Washington, D. C. 20546 Reference: B71-10503

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States

Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

Patent status:

Inquiries about obtaining rights for the commercial use of this invention may be made to:

Patent Counsel NASA Headquarters Code GP Washington, D. C. 20546

> Source: R. J. Fay and E. P. Wittrock of University of Denver under grant from NASA Headquarters (HQN-10638)