



AERONAUTICAL ENGINEERING

CASE FILE
COPY

A SPECIAL BIBLIOGRAPHY
WITH INDEXES
Supplement 72

JULY 1976

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

ACCESSION NUMBER RANGES

Accession numbers cited in this Supplement fall within the following ranges:

STAR (N-10000 Series) N 76-20062 - N 76-22149

IAA (A-10000 Series) A 76-25758 - A 76-28777

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by Informatics Information Systems Company.

AERONAUTICAL ENGINEERING

A Special Bibliography

Supplement 72

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in June 1976 in

- *Scientific and Technical Aerospace Reports (STAR)*
- *International Aerospace Abstracts (IAA)*



This Supplement is available from the National Technical Information Service (NTIS), Springfield, Virginia 22161, for \$4 00. For copies mailed to addresses outside the United States, add \$2 50 per copy for handling and postage.

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering. The first issue of this bibliography was published in September 1970 and the first supplement in January 1971. Since that time, monthly supplements have been issued.

This supplement to *Aeronautical Engineering—A Special Bibliography* (NASA SP-7037) lists 184 reports, journal articles, and other documents originally announced in June 1976 in *Scientific and Technical Aerospace Reports (STAR)* or in *International Aerospace Abstracts (IAA)*

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied in most cases by an abstract. The listing of the entries is arranged in two major sections, *IAA Entries* and *STAR Entries*, in that order. The citations, and abstracts when available, are reproduced exactly as they appeared originally in *IAA* or *STAR*, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances.

Three indexes—subject, personal author, and contract number—are included. An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A76-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc (AIAA) as follows. Paper copies are available at \$5 00 per document up to a maximum of 20 pages. The charge for each additional page is 25 cents. Microfiche⁽¹⁾ are available at the rate of \$1 50 per microfiche for documents identified by the # symbol following the accession number. A number of publications, because of their special characteristics, are available only for reference in the AIAA Technical Information Service Library. Minimum airmail postage to foreign countries is \$1 00. Please refer to the accession number, e.g., (A76-10091), when requesting publications.

STAR ENTRIES (N76-10000 Series)

One or more sources from which a document announced in *STAR* is available to the public is ordinarily given on the last line of the citation. The most commonly indicated sources and their acronyms or abbreviations are listed below. If the publication is available from a source other than those listed, the publisher and his address will be displayed on the availability line or in combination with the corporate source line.

Avail NTIS Sold by the National Technical Information Service to U.S. customers at the price shown in the citation following the letters HC (hard, paper, or facsimile copy). Customers outside the U.S. should add \$2 50 per copy for handling and postage charges to the price shown. (Prices shown in earlier *STAR* volumes, 1962-1975, have been superseded but may be calculated from the number of pages shown in the citation. The price schedule by page count was published in *STAR* Numbers 2 and 3 of 1976, or it may be obtained from NTIS.)

Microfiche⁽¹⁾ is available at a standard price of \$2 25 (plus \$1 50 for non-U.S. customers) regardless of source or the quality of the fiche, for those accessions followed by a # symbol. Accession numbers followed by a + sign are not available as microfiche because of size or reproducibility.

Initially distributed microfiche under the NTIS SRIM (Selected Research in Microfiche) is available at greatly reduced unit prices. For this service and for information concerning subscription to NASA printed reports, consult the NTIS Subscription Unit.

NOTE ON ORDERING DOCUMENTS When ordering NASA publications (those followed by the * symbol), use the N accession number. NASA patent applications (only the specifications are offered) should be ordered by the US-Patent-Appl-SN number. Non-NASA publications (no asterisk) should be ordered by the AD, PB, or other *report* number shown on the last line of the citation, not by the N accession number. It is also advisable to cite the title and other bibliographic identification.

Avail SOD (or GPO) Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The current price and order number are given following the availability line. (NTIS will fill microfiche requests, at the standard \$2 25 price, for those documents identified by a # symbol.)

(1) A microfiche is a transparent sheet of film, 105 by 148 mm in size, containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 26:1 reduction).

- Avail NASA Public Document Rooms Documents so indicated may be examined at or purchased from the National Aeronautics and Space Administration, Public Documents Room (Room 126), 600 Independence Ave., S.W., Washington, D.C. 20546, or public document rooms located at each of the NASA research centers, the NASA Space Technology Laboratories, and the NASA Pasadena Office at the Jet Propulsion Laboratory
- Avail ERDA Depository Libraries Organizations in U.S. cities and abroad that maintain collections of Energy Research and Development Administration reports, usually in microfiche form, are listed in *Nuclear Science Abstracts Services* available from the ERDA and its depositories are described in a booklet, *Science Information Available from the Energy Research and Development Administration* (TID-4550), which may be obtained without charge from the ERDA Technical Information Center
- Avail Univ Microfilms Documents so indicated are dissertations selected from *Dissertation Abstracts* and are sold by University Microfilms as xerographic copy (HC) at \$10.00 each and microfilm at \$4.00 each regardless of the length of the manuscript. Handling and shipping charges are additional. All requests should cite the author and the Order Number as they appear in the citation.
- Avail USGS Originals of many reports from the U.S. Geological Survey, which may contain color illustrations, or otherwise may not have the quality of illustrations preserved in the microfiche or facsimile reproduction, may be examined by the public at the libraries of the USGS field offices whose addresses are listed in this Introduction. The libraries may be queried concerning the availability of specific documents and the possible utilization of local copying services, such as color reproduction.
- Avail HMSO Publications of Her Majesty's Stationery Office are sold in the U.S. by Pendragon House, Inc. (PHI), Redwood City, California. The U.S. price (including a service and mailing charge) is given, or a conversion table may be obtained from PHI.
- Avail BLL (formerly NLL) British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England. Photocopies available from this organization at the price shown. (If none is given, inquiry should be addressed to the BLL.)
- Avail ZLDI Sold by the Zentralstelle für Luftfahrt-dokumentation und -Information, Munich, Federal Republic of Germany, at the price shown in Deutschmarks (DM).
- Avail Issuing Activity, or Corporate Author, or no indication of availability. Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.
- Avail U.S. Patent Office Sold by Commissioner of Patents, U.S. Patent Office, at the standard price of 50 cents each, postage free.
- Other availabilities If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line.

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA. A listing of public collections of NASA documents is included on the inside back cover.

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics
and Astronautics
Technical Information Service
750 Third Ave
New York, N Y 10017

British Library Lending Division,
Boston Spa, Wetherby, Yorkshire,
England

Commissioner of Patents
U S Patent Office
Washington, D C 20231

Energy Research and Development
Administration
Technical Information Center
P O Box 62
Oak Ridge, Tennessee 37830

ESA - Space Documentation Service
ESRIN
Via Galileo Galilei
00044 Frascati (Rome), Italy

Her Majesty's Stationery Office
P O Box 569, S E 1
London, England

NASA Scientific and Technical Information
Facility
P O Box 8757
B W I Airport, Maryland 21240

National Aeronautics and Space
Administration
Scientific and Technical Information
Office (KSI)
Washington, D C 20546

National Technical Information Service
Springfield, Virginia 22161

Pendragon House, Inc
899 Broadway Avenue
Redwood City, California 94063

Superintendent of Documents
U S Government Printing Office
Washington, D C 20402

University Microfilms
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

University Microfilms, Ltd
Tylers Green
London, England

U S Geological Survey
1033 General Services Administration Bldg
Washington, D C 20242

U S Geological Survey
601 E Cedar Avenue
Flagstaff, Arizona 86002

U S Geological Survey
345 Middlefield Road
Menlo Park, California 94025


U S Geological Survey
Bldg 25, Denver Federal Center
Denver, Colorado 80225

Zentralstelle für Luftfahrt-
dokumentation und -Information
8 München 86
Postfach 880
Federal Republic of Germany


TABLE OF CONTENTS

	Page
IAA Entries	199
STAR Entries	211
Subject Index	A-1
Personal Author Index	B-1
Contract Number Index	C-1

TYPICAL CITATION AND ABSTRACT FROM STAR



TYPICAL CITATION AND ABSTRACT FROM IAA



AERONAUTICAL ENGINEERING

A Special Bibliography (Suppl. 72)

JULY 1976

IAA ENTRIES

A76-25758 # The pulsed thermocouple for gas turbine application D Kretschmer, J Odgers, and A F Schlader (Université Laval, Quebec, Canada) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-1* 10 p 14 refs Members, \$150, nonmembers, \$3 00 Research sponsored by the National Research Council of Canada

A mechanically pulsed suction thermocouple has been developed. The gas to be measured is sucked through a sonic orifice, eliminating the influence of the velocity inside the combustor. The signal from the thermocouple is processed by an analogue circuit. A calibration of the probe was done. This calibration showed very little scatter and a good repeatability. The overall measurement accuracy was better than 1 percent. As a test of application, a partial survey of the temperature distribution within an aircraft gas turbine combustor was done. A satisfactory agreement was observed between temperatures measured by the thermocouple and those determined from gas analysis. The pulse thermocouple proved to be a reliable and fast tool for the measurement of local gas temperatures. (Author)

A76-25773 # An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade S Fleeter, A S Novick, R E Riffel, and J E Caruthers (General Motors Corp., Detroit Diesel Allison Div., Indianapolis, Ind.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-17* 9 p 9 refs Members, \$1 50, nonmembers, \$3 00 Contract No N00014-72-C-0351

A unique supersonic inlet flow field unsteady cascade experiment is described wherein the time dependent pressure distribution within an harmonically oscillating airfoil cascade is quantitatively determined. The torsional frequency of oscillation and the interblade phase angle are precisely controlled by means of on-line digital computers. The dynamic data obtained include the chordwise distribution of the unsteady pressure magnitude and its phase lag as referenced to the airfoil motion. Parameters varied include the cascade inlet Mach number, the interblade phase angle, and the reduced frequency. The time-dependent data are correlated with state-of-the-art analytical predictions. (Author)

A76-25781 # Composite inlays increase flutter resistance of turbine engine fan blades. W Troha (USAF, Aero Propulsion Laboratory, Wright-Patterson AFB, Ohio) and K Swain (General Motors Corp., Detroit Diesel Allison Div., Indianapolis, Ind.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-29* 8 p Members, \$1 50, nonmembers, \$3 00

A method for improving turbine engine blade flutter stability has been demonstrated on a TF41 fan rig and engine. The concept uses the high strength and stiffness properties of B/SiC-titanium composite, bonded into the leading edge tip section of a titanium fan

blade, to control the blade vibrational characteristics. Comparisons are made between the blade response characteristics with and without the composite inlay for blade natural frequency, untwist due to rotational speed, and shift in flutter boundary. Engine performance improvements due to shroud removal are also shown. (Author)

A76-25786 # Advanced Acoustic Nacelle concepts G W Painter (Lockheed-California Co., Burbank, Calif.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-35* 10 p 9 refs Members, \$1 50, nonmembers, \$3 00

The results of a recently completed study on the potential noise-reduction benefits that could be derived from the development of an 'Advanced Acoustic-Composite Nacelle' for future subsonic commercial transports are discussed. In this study, noise-reduction objectives were based on the acceptance of noise floors imposed by airframe noise during approach operation and jet noise during takeoff. The reduction of treatable source levels to these floors should result in aircraft noise levels below those of the already quiet current widebodied transports. It is predicted that the foregoing noise levels can be achieved in future widebodied transports by employing advanced acoustical duct liners, extending the (lined) fan duct, and incorporating jet mixing. (Author)

A76-25792 # Coupled bending-torsion vibrations of rotating blades S Banerjee and J S Rao (Indian Institute of Technology, Kharagpur, India) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-43* 14 p 41 refs Members, \$1 50, nonmembers, \$3 00

This paper presents analytical and experimental investigations to determine the coupled bending-torsion natural frequencies of cantilever blades mounted on a rotating disk. Galerkin method is applied to solve the coupled differential equations of motion for an aerofoil cross section blade with asymmetry about only one principal axis. The blade is considered to be mounted with the axis of symmetry in the plane of disk rotation. Results obtained are presented in non-dimensional form, showing the effects of rotation, disk radius, and asymmetry on the lowest three-coupled bending and lowest three-coupled torsion frequencies. An experimental rig is designed and fabricated to test rotating blades using piezoelectric crystals to excite the blades and also to pick up the response. The theoretical results are shown to be in good agreement with experimental observations. (Author)

A76-25812 # Noise technology requirements for future aircraft powerplants J D Kester and A A Peracchio (United Technologies Corp., Pratt and Whitney Aircraft Div., East Hartford, Conn.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La, Mar 21-25, 1976, Paper 76-GT-69* 14 p 17 refs Members, \$1 50, nonmembers, \$3 00

Noise technology requirements are surveyed for several future aircraft powerplants. The applications considered range from growth versions of current production engines to future advanced supersonic transport applications. Although a variety of complex and challenging noise-suppression problems are identified, a sampling of several basic problems common to a variety of engine designs are

discussed in more detail. Among these are the prediction of fan noise generation and propagation in treated ducts, the use of mixer nozzles to reduce jet exhaust noise, and the prediction and absorption of combustion noise. Discussed in the paper are analytical and experimental approaches applicable to solving these problems.

(Author)

A76-25813 # Inflight engine performance evaluations. W E Beck, Jr (Lockheed California Co., Burbank, Calif.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-70* 11 p. Members, \$1 50, nonmembers, \$3 00.

The measurement and determination of installed in-flight engine performance on an aircraft are complex tasks. To be successful requires that wind-tunnel-model and full-scale in-flight test programs be fully planned early in the development phase of the aircraft design. In particular, methodology and instrumentation requirements must be coordinated in these programs. This paper discusses the requirements and methodology for in-flight engine performance evaluations as applied to a subsonic antisubmarine-warfare aircraft. Data are presented which show that two independent methods of calculating steady-state engine net thrust levels agree to within plus or minus 1.5 percent of each other over the full operating regime of the aircraft. Finally, comparisons of calculated performance with that predicted from the engine manufacturer's cycle deck are presented.

(Author)

A76-25814 # A multi-variable control for a turbofan engine operating at sea level static. M S Weinberg (Charles Stark Draper Laboratory, Inc., Cambridge, Mass.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-71* 10 p. 8 refs. Members, \$1 50, nonmembers, \$3 00.

Based on modern control theory, a multi-variable control is formulated for a two-spool turbofan engine operating at sea level static conditions. The proposed control yields idle to intermediate transients in 40 percent of the time required by the conventional controls in non-linear simulations while maintaining similar stall and temperature overshoot characteristics. The formulated control is simpler than earlier proposed multi-variable controls and yields acceptable performance during small thrust changes and decelerations.

(Author)

A76-25818 # Advanced composite fan blade flight evaluation program. M H Chopin (USAF, Aeronautical Systems Div Wright Patterson AFB, Ohio.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-75* 6 p. Members, \$1 50, nonmembers, \$3 00.

The preparation for and conduct of the first flight by the U.S. Air Force of a turbine engine fan stage fabricated of advanced composite materials is discussed. Composite material properties and basic design philosophy is presented along with preliminary flight evaluation results. This is the first application of filamentary-reinforced metal matrix composites to a turbine engine structural component.

(Author)

A76-25821 # CFM56 turbofan engines - General Electric/SNECMA cooperative engineering development program. E Caffier (CFM56 SNECMA, Moissy-Cramayel, Seine-et-Marne, France) and A O Kohn (General Electric Co., CFM56 Dept., Evandale, Ohio.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-78* 8 p. Members, \$1 50, nonmembers, \$3 00.

A joint company has been formed by the General Electric Company, U.S., and the Societe Nationale d'Etude et de Construction de Moteurs d'Aviation (SNECMA), France, to develop a 'ten-ton' high bypass turbofan engine for commercial and military use. The engine, designated CFM56, is based to a large extent on the core of the F101 engine which powers the B-1 bomber. Hardware

design and development initiated in 1973 has led to the construction of four test engines. Management of the engineering aspects of the development program is discussed, and the division of responsibilities, interface definition and control, integration and communications and security procedures are described.

C K D

A76-25825 # A new system for preventing icing of gas turbine inlets. G R Gillingham (Donaldson Co., Inc., Minneapolis, Minn.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-84* 6 p. 5 refs. Members, \$1 50, nonmembers, \$3 00.

A new system for preventing condensate and precipitate icing of gas turbine inlet systems has been developed. This system uses a combination heat exchanger/moisture separator called an Anti-Ice Moisture Separator (AIMS) to provide icing protection without the need to heat the inlet air to 0 C or above. Turbine exhaust gas heats the AIMS surfaces and thereby prevents ice from forming on them. Turbine inlet air passing over these surfaces is heated by convection. No mixing of exhaust gas with inlet air occurs. Condensate icing is prevented by heating the air enough to prevent it from falling below the dew point temperature anywhere in the inlet system. Precipitate icing is prevented by separating most water droplets from the inlet air and evaporating the rest before they impact and freeze on cold surfaces. The AIMS system has successfully prevented turbine inlet icing in temperatures as low as -22 C (-8 F) during field tests. It is anticipated that AIMS systems will be able to prevent inlet icing at any ambient temperature that may be encountered.

(Author)

A76-25829 # High performance epicyclic gears for gas turbines. D E Imwalle (Cincinnati Gear Co., Cincinnati, Ohio.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-88* 11 p. Members, \$1 50, nonmembers, \$3 00.

The history and explanation of the Cinti-BHS load equalization system for epicyclic gears is discussed in detail. Equations for relating gearbox size and weight are presented for parallel shaft and epicyclic gears. A derivation for the maximum ratio for the number of planets is also included.

(Author)

A76-25833 # Primary system preliminary design for gas turbine HTGR power plant. C F McDonald, P Fortescue, and J M Kruse (General Atomic Co., San Diego, Calif.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-92* 16 p. 11 refs. Members, \$1 50, nonmembers, \$3 00.

The gas-turbine high-temperature gas-cooled reactor (GT-HTGR) power plant combines the existing HTGR core with a closed-cycle helium gas turbine power-conversion system directly in the reactor primary circuit. An integrated design concept in which the reactor core, turbomachinery, heat exchangers, and entire helium inventory are enclosed within the prestressed concrete reactor vessel (PCRV) was selected on the basis of both safety and economic reasons. The layout of the power-conversion loop (PCL) components, with envelope restraints associated with installation in cavities in the PCRV, and development of the primary-system gas-flow paths are discussed. This paper outlines the studies which led to the selection of the primary system for an integrated type of plant embodying multiple gas-turbine loops. With orientation and configuration of the major components in the PCL forming the basis of these studies, some of the preliminary design considerations for the turbomachinery, heat exchangers, and other components are discussed.

(Author)

A76-25835 # Aerodynamics and heat transfer at the trailing edge of transonic blades. O M Amana, H O Demuren, J F Louis (MIT, Cambridge, Mass.), C Sieverding, and J Chauvin (Institut von Karman de Dynamique des Fluides, Rhode-Saint-Genese, Belgium.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-95* 14 p. 15 refs. Members, \$1 50, nonmembers, \$3 00. Contract No. N00014-67-A-0204-0079.

A base flow model has been proposed which, apart from predicting the base pressure, also predicts the wake angle and the trailing edge shock system to a good degree of accuracy. The method may also handle a round trailing edge which is important in transonic blades for reducing losses. The base pressure found in the above is then used in the prediction of some of the parameters in the heat-transfer model. The trailing edge heat-transfer model explains and correlates experimental data, for film cooling the trailing edge, obtained using short duration techniques. The results show that film cooling may be used in cooling the trailing edges of transonic blades effectively, provided that the coolant port is located just beyond a critical distance upstream of the trailing edge. The critical distance is the distance required for the coolant flow which separates at injection to reattach downstream and depends on the momentum ratio of coolant to mainstream flows, on the angle of injection, and the flow Reynolds number (Author)

A76-25837 # Control of a gas turbine HTGR F Openshaw, E Estrine, and M Croft (General Atomic Co., San Diego, Calif.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-97* 12 p 7 refs. Members, \$1 50, nonmembers, \$3 00. Contract No. E(04-3)-167 ERDA Project 46

This paper presents a description of the control and protective preliminary system designs for the gas turbine high-temperature gas-cooled reactor power plant (GT-HTGR). The purpose of these systems is the control and safe operation of the plant in accordance with utility practice for large nuclear generation stations, and in the event of an abnormal or accident condition to shut the plant down in an orderly manner and maintain it in a safe shutdown condition. The control system is designed to regulate reactor power, control electric load and turbine speed, control the temperature of the helium delivered to the turbines, and control thermal transients experienced by reactor internal components. In addition, it provides the required control and programming for start-up, shutdown, load ramp, and other expected operations. The control system also handles conditions imposed on the system during upset and emergency conditions. Under these conditions, reactor power and helium flow are reduced in order to minimize temperature transients imposed on reactor components. The transient analysis and control system selection process which has been used to establish the reference GT-HTGR control system is illustrated in this paper (Author)

A76-26049 # Economics of air transport (Ekonomika grazhdanskoi aviatsii) A V Miroshnikov, I I Spotkai, N N Gromov, E V Makarov, G S Dibrova, E F Busalov, and A Ia Chernyshev. Moscow, Izdatel'stvo Transport, 1975 304 p 53 refs. In Russian

The book evaluates and characterizes in detail the role of air transport in the general transportation picture as well as the whole national economy. Most of the details apply to the Soviet economy and air transport system, though it is attempted to extend the discussion to general economies. Topics covered include the organization of the control of civil aviation, civil aviation planning principles, management of main civil aviation funds, indices and means of increasing the efficiency of the use of main funds, structure, normalization, and turnover of working capital, productivity and a system for remuneration of labor in civil aviation, material incentive systems, labor and salary planning, methods for determining prime costs in civil aviation, construction of tariff systems, comparison of expenditures and intakes and securing profitability, economic effectiveness of capital investments, and methods for determining the economic effectiveness of aircraft and engine utilization and of the introduction of new types of aircraft. P T H

A76-25851 # The potential of oxide dispersion strengthened superalloys for advanced gas turbines J S Oenjin (International Nickel Co., Inc., Suffern, N Y.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-118* 10 p 18 refs. Members, \$1 50, nonmembers, \$3 00

Both the performance and life of gas turbines are frequently

controlled by properties of materials in critical components. The different properties required simultaneously for a given part have placed extreme demands on conventional wrought or cast nickel-base superalloys. The recently developed mechanical alloying process has allowed achievement of a new combination of important properties, such as oxidation resistance, sulfidation resistance, and elevated temperature rupture strength. The interaction between the unique stress/temperature/time behavior of an oxide dispersion strengthened superalloy and blade configuration is treated. Significant potential for improvements in gas turbine performance is found based on a simplified energy exchange model (Author)

A76-25855 # XfV-12A propulsion system development J T Delany and G M Jenkins (Rockwell International Corp., Columbus Aircraft Div., Columbus, Ohio.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 76-GT-125* 15 p. Members, \$1 50, nonmembers, \$3 00. Navy-supported research

The XfV-12A total powered lift/thrust system being developed under contract for the U.S. Navy is described. The description includes design and development to date of the inlets, engine integration, the diverter valve with plug nozzle, the lift system augmentor supply ducting, and lift/thrust augmentor hardware. The development process description includes system design philosophy and criteria, analysis, test facilities utilized, model and full scale testing and evaluation (Author)

A76-25875 * # Advanced turbine disk designs to increase reliability of aircraft engines A Kaufman (NASA, Lewis Research Center, Cleveland, Ohio.) *American Society of Mechanical Engineers, Gas Turbine Conference and Products Show, New Orleans, La., Mar 21-25, 1976, Paper 32* p. NASA-supported research

Results of analytical studies to improve the low cycle fatigue lives and reliability of turbine disks in high performance gas turbine engines are presented. Advanced disk concepts were evaluated for the first-stage high pressure turbines of the CF6-50 and JT8D-17 engines. The advanced disk designs are compared to the existing disks on the bases of cycles to crack initiation and overspeed capability for initially unflawed disks, crack propagation cycles to failure for initially flawed disks, and available kinetic energy of disk burst fragments (Author)

A76-26048 # Engineering aspects of flight safety (Tekhnicheskie voprosy obespecheniia bezopasnosti poletov) P A Solomonov. Moscow, Voenizdat, 1975 119 p 21 refs. In Russian

The principal factors affecting flight safety are discussed, and methods that can be used to obtain quantitative flight safety estimates are reviewed. Attention is given to factors which must be taken into consideration in the design and development of reliable aircraft, and to onboard instruments which help the pilot to maintain a high safety level during flight. Techniques used to determine the causes of flight accidents are described. V P

A76-26049 # Economics of air transport (Ekonomika grazhdanskoi aviatsii) A V Miroshnikov, I I Spotkai, N N Gromov, E V Makarov, G S Dibrova, E F Busalov, and A Ia Chernyshev. Moscow, Izdatel'stvo Transport, 1975 304 p 53 refs. In Russian

The book evaluates and characterizes in detail the role of air transport in the general transportation picture as well as the whole national economy. Most of the details apply to the Soviet economy and air transport system, though it is attempted to extend the discussion to general economies. Topics covered include the organization of the control of civil aviation, civil aviation planning principles, management of main civil aviation funds, indices and means of increasing the efficiency of the use of main funds, structure, normalization, and turnover of working capital, productivity and a system for remuneration of labor in civil aviation, material incentive systems, labor and salary planning, methods for determining prime costs in civil aviation, construction of tariff systems, comparison of expenditures and intakes and securing profitability, economic effec-

tiveness of capital investments, and methods for determining the economic effectiveness of aircraft and engine utilization and of the introduction of new types of aircraft P T H

A76-26337 # Asymptotic representation of solutions on the hodograph plane in problems of subsonic flow past airfoil profiles (Ob asimptoticheskom predstavlenii resheniia na ploskosti godografa v zadachakh okolozvukovogo obtekaniiia profilei) Z N Dobrovolskaia *Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza*, Jan-Feb 1976, p 84-88 9 refs In Russian

The steady plane-parallel transonic flow of an ideal gas past a slender body is examined. The behavior of the perturbed flow in the region upstream from the shock waves at large distances from the body is analyzed. The conditions are determined that are satisfied by a solution on the hodograph plane, which corresponds to a flow without singularities on the limiting characteristic in the physical plane of the flow. The transonic flow at large distances from the body is described by Karman's approximate equation V P

A76-26338 # Optimal supersonic wing profile of given thickening (Ob optimal'nom sverkhzvukovom profile zadannogo utolscheniia) V I Zubov *Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza*, Jan-Feb 1976, p 89-96 6 refs In Russian

The problem of designing a closed profile for minimum wave drag in uniform supersonic flow is analyzed, assuming that the length and thickness of the profile and the angle of attack are prescribed. The analysis is limited to bodies with attached shock waves. Solutions are obtained for exact and model formulations of the problem. Numerical data are presented V P

A76-26339 # Interaction between an external shock wave and a blunted body in hypersonic flow (O vzaimodeistvii vneshnego skachka uplotneniia s zatuplennym telom v giperzvukovom potoke) G A Shmanenkova *Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza*, Jan-Feb 1976, p 97-103 6 refs In Russian

A complex shock wave configuration with two triple points can result from the interaction between an oblique shock wave and a separated shock wave in front of a blunted body (such as the wing leading edge). This may lead to the formation of a high-pressure low entropy stream filament. The flow regimes that correspond to these conditions are studied analytically and experimentally. An approximate method is proposed for determining the size of shock wave separations in the interaction region V P

A76-26384 * An aircraft noise pollution model for trajectory optimization A Barkana (DMMA, Eskisehir, Turkey) and G Cook (Virginia University, Charlottesville, Va) *IEEE Transactions on Aerospace and Electronic Systems*, vol AES-12, Mar 1976, p 109-116 Contract No NAS1-10210-B

A mathematical model describing the generation of aircraft noise is developed with the ultimate purpose of reducing noise (noise-optimizing landing trajectories) in terminal areas. While the model is for a specific aircraft (Boeing 737), the methodology would be applicable to a wide variety of aircraft. The model is used to obtain a footprint on the ground inside of which the noise level is at or above 70 dB B J

A76-26412 New developments in aeronautics technology (Nouveaux développements de la technologie aéronautique) J Pitrou *Matériaux et Techniques*, vol 64, Jan-Feb 1976, p 34-36 In French

The mechanical characteristics and applications of materials recently developed for use by the aviation industry are discussed. Among the materials described are high-resistance steels, the high-tensile strength alloy HP310, the nickel-chromium-copper alloy X12-6PH, the aluminum alloys 7049, 7050, and 7475, copper zirconium and copper-chromium alloys, and copper materials containing finely dispersed refractory oxides to improve the mechanical characteristics at temperatures around 200 C. The advantages of the

organic fiber Kevlar-49 and of epoxy-graphite resins are outlined. Developments in machining, fabrication, and finishing techniques are detailed C K D

A76-26450 Dynamics of helicopter flight G H Saunders (Southern California University, Los Angeles, Calif) New York, Wiley-Interscience, 1975 313 p 102 refs \$16 95

Dynamics of hovering and forward flight of helicopters is described on the basis of fundamental concepts of mechanics and essential laws of aerodynamics. The means by which the main rotor system of a helicopter derives lift while hovering in calm air are examined. Particular attention is devoted to the stability and control of modern helicopters, including the rapidly advancing application of stability augmentation concepts to helicopters. Some flying problems are examined from the pilot's standpoint, with special emphasis on autorotation maneuver, operation at high gross weight and density altitude, external sling load, instrument flying, winds and turbulence, retreating blade stall, and wake turbulence. Elements of helicopter structures from strength requirements to crashworthiness are also discussed S D

A76-26550 # Types and ideal propulsive efficiency of aeronautical propulsion systems (Denominazioni e rendimento propulsivo ideale dei motopropulsori aeronautici) G Gabrielli *Ingegneria*, Jan-Feb 1976, p 1-14 In Italian

A classification of propulsion systems, ranging from propeller engines to rocket engines, is given. The basic parameters and relations characterizing ideal propulsion are set forth, and some dimensionless factors are indicated which determine ideal propulsion on the hypothesis of constant translational velocity. Graphs are drawn which show the effect of individual parameters on ideal efficiency for propeller engines, gas turbine engines, and rocket engines P T H

A76-26584 Heat transfer in high-temperature GTE air-cooled turbine blades V I Lokai (*Aviatsionnaia Tekhnika*, vol 18, no 3, 1975, p 60-68) *Soviet Aeronautics*, vol 18, no 3, 1975, p 41-47 20 refs Translation

In the calculation of internally air cooled turbine blades, the boundary conditions of heat transfer from the gas and air are conventionally established on the basis of similarity equations derived from static test data. In the present analysis, the necessity is demonstrated to take into consideration such factors as the influence of the rotor's rotational speed on heat transfer intensity, the emission from the gas, the angle of incidence, etc. Expressions for evaluating these factors numerically are proposed. It is shown that heat transfer characteristics obtained indirectly from measurements of the mean blade wall temperature are not reliable V P

A76-26648 # Windshield Flight Environment Simulator L G Campbell and J W Marshall (Sierracin Corp., Sylmar, Calif) *Aircraft Engineering*, vol 48, Mar 1976, p 4-9

The Windshield Flight Environment Simulator (WFES), which reproduces the total operating environment of electrically-heated, pressurized aircraft windshields on a highly compressed time scale, is discussed. The facility has been used in the development and improvement of the 747 windshield and is easily modified to allow testing of other windshield installations. It has been operated to the following limits at a near-sea-level elevation: airspeed over windshield, 0-200 knots; maximum heat transfer coefficient, 35 BTU/hr/sq ft/deg F; outside air temperature, 100 to +150 deg F; cabin pressure differential, 15 psi. The system utilizes liquid nitrogen cooling. The windshield can be observed visually and photographically during testing, and instrumentation is provided for the display and recording of deflections, temperature, pressures, current, and voltages C K D

A76-26650 # Thrust reverser design for airframe compatibility J M D Sutton (Rolls Royce /1971/, Ltd, London, England). *Aircraft Engineering*, vol 48, Mar 1976, p 16-20

Aerodynamic design considerations involved in the optimization of thrust reverser configurations are examined. For cascaded designs a synthesis of the overall fan reverser configuration can be obtained by successive iteration using individual model cascades correlated against aerodynamic loading. For a given target reverser design, the reverse thrust and isolated nozzle suppression are predicted from generalized model data. The aerodynamic design considerations for thrust reversal are dependent on the initial definition of an acceptable installed discharge pattern rather than reverser type.

C K D

A76-26670 Propulsion systems (Triebwerksanlagen) W Alvermann (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Institut für Antriebssysteme, Braunschweig, West Germany) *VDI-Z*, vol 118, no 6, Mar 1976, p 287-291. 41 refs. In German.

The current status of development of aircraft engines is examined, taking into account a search for new fuels, economic demands for aircraft engines, the development of new engines with more favorable environmental characteristics, plans for the development of an acceptable engine for supersonic aircraft, and general studies concerned with the enhancement of the operational efficiency of the engine. Attention is given to current and future jet engines, turbine engines for helicopters, piston engines, and ramjet engines.

G R

A76-26751 Swept edge to reduce the noise generated by turbulent flow over the edge L Filler (Boeing Commercial Airplane Co., Seattle, Wash.) *Acoustical Society of America, Journal*, vol 59, Mar 1976, p 697-699. 6 refs.

When turbulent fluid flows over an edge, swept at an angle (α) to the flow direction, it is shown from simple physical arguments that the radiated sound intensity can be reduced by at least a factor of $\cos \alpha$. The anticipated sound reduction depends on the assumption that the normal component of turbulent momentum convected over the edge is the dominant contributor to the edge interaction noise mechanism at high Reynolds numbers. Some preliminary experimental results which confirm the noise reduction are presented for a jet flowing over an edge swept in a sawtooth configuration. (Author)

A76-27068 Can R-W aircraft provide efficient commercial transport. R H Miller (MIT, Cambridge, Mass.) *Vertiflite*, vol 22, Jan-Feb 1976, p. 4-7

Contributions by a panel of experts on the outlook for short-haul applications in transportation by rotary-wing aircraft are summarized. While the fuel efficiency of rotary-wing aircraft is only 50% that of fixed-wing aircraft, improvements in rotor profile design, elimination of parasite drag and induced drag, advanced rotor systems, and improvements in structures, aerodynamics, and propulsion are expected to narrow the gap. Rotary-wing aircraft offer most efficient utilization of terminal real estate, plus savings in time in interterminal hops (surpassing road vehicles and rail vehicles). Possible speed advantages with tilt-rotor aircraft are considered.

R D V

A76-27144 An update - Advanced aircraft oxygen systems A J Adduci (USAF, Life Support Systems Program Office, Wright-Patterson AFB, Ohio) *SAFE Journal*, vol 6, Spring 1976, p 16-19

This paper updates a report given at the Annual Survival and Flight Equipment Association Conference in 1973. The advancements in oxygen systems described concern physiological safety as well as reduction in total system cost. The cost savings are in servicing and maintenance, as opposed to the acquisition cost. Life cost savings are achieved by eliminating the use of liquid oxygen. The discussion covers two categories of oxygen systems, systems of the type that must be used constantly or intermittently during flight in order to perform the flight mission, and systems used in emergency

situations (including therapeutic oxygen systems). Particular attention is given to the Air Force C-5A passenger oxygen system and the helicopter oxygen system, as well as to an oxygen sorbent system equipped with a chemical that has a useful life of acceptable length. The problems which plagued a system of oxygen extraction by electrochemistry appear to have been overcome.

V P

A76-27274 * # Some considerations in the design of transport aircraft /The W Rupert Turnbull Lecture for 1975/ R T Jones (NASA, Ames Research Center, Moffett Field, Calif.) (*Canadian Aeronautics and Space Institute, Annual General Meeting, Montreal, Canada, May 13, 1975*) *Canadian Aeronautics and Space Journal*, vol 21, Nov 1975, p 332-337

The slow landing speeds (30 mph, 65 mph) and light wing loading required for safety in the early days of aviation are shown to be irrelevant to safe landings of propeller driven aircraft, while increases in wing loading and landing speed have been accompanied by improved safety records. This is attributed to length of runway and time available for approach maneuvers, plus immunity to wind gusts and turbulence conferred by higher wing loadings. Aerodynamical and mechanical aspects of safe landing are discussed, with no mention of instruments. Fuel savings achievable through high aspect ratio, variable sweep angle, and supercritical airfoils are also considered.

R D V

A76-27328 Iterative calculation of two-dimensional compressible flow around ellipse and circular arc profile (Iterative Berechnung der ebenen, kompressiblen Strömung um Ellipse und Kreisbogenzweieck) K Kern and R Mader (München, Fachhochschule, Munich, West Germany) *Acta Mechanica*, vol 24, no 1-2, 1976, p 47-61. 11 refs. In German.

Starting from incompressible flow, the irrotational plane flow of a perfect gas past both an ellipse and a circular arc profile is calculated using an iteration-method developed by Sauer (1952). No expansion of the flow potential in powers of any parameter is made. As the results show, the method works correctly even for speeds of the undisturbed flow slightly greater than the critical speed. The method is computer-oriented and useful for all profiles which allow conformal mapping onto the circle. (Author)

A76-27329 A linearized theory of three-dimensional airfoils in nonuniform flow D Homentcovschi and A Barsony-Nagy (Bucuresti, Institutul Politehnic, Bucharest, Rumania) *Acta Mechanica*, vol 24, no 1-2, 1976, p 63-86. 9 refs.

Linearized steady motion of a three-dimensional airfoil in a fluid flow whose velocity at infinity has a two-dimensional distribution is considered. The starting point of the analysis is the equations in distributions characterizing the fluid motion. The solution of the disturbance velocity is represented in the Fourier transform plane and its asymptotic behavior is studied. The integrodifferential equation of the problem is transformed into an equivalent equation with a strong singularity. The singular part of the kernel of this equation coincides with the kernel of the corresponding equation for uniform flow. The disturbance velocity components u and v are studied at infinity, and the existence of the disturbance velocity downstream of the airfoil is shown. The expression for the velocity jump when crossing this surface is in agreement with Prandtl's hypotheses concerning free vortices. Attention is given to lifting segment theory in nonuniform flow, and analog to Prandtl's equation is derived. Its kernel differs from the kernel of Prandtl's equation by a term with a weak singularity which depends only on the velocity distribution at infinity. (Author)

P T H

A76-27361 # Some basic questions concerning quality assurance in aircraft maintenance (Über einige Grundfragen der Qualitätssicherung in der Flugzeuginstandhaltung) P Bork (Gesellschaft für Internationalen Flugverkehr mbH, Berlin, East Germany) *Technisch-ökonomische Information der zivilen Luftfahrt*, vol 12, no 1, 1976, p 14-23. In German.

The significance of the quality concept from the point of view of aircraft maintenance is considered and aspects of quality

definition and evaluation are investigated. The approaches used in the areas of quality assurance and quality control are discussed and a table is provided with elements of the quality assurance system used for the technical operation of aircraft. Attention is also given to suitable organization and educational procedures for improving quality and avoiding cases of faulty performance. G R

A76-27362 # Quality assurance by standardization (Qualitätssicherung durch Standardisierung) H Nicklisch (Kombinat Spezialtechnik, Dresden, East Germany) *Technisch-ökonomische Information der zivilen Luftfahrt*, vol 12, no 1, 1976, p 24-28. In German

A number of relations between aspects of quality assurance and standardization are discussed, taking into account the effect of standardization procedures in operations related to the maintenance of aircraft and the manufacture of spare parts. Basic problems and questions of methodology are examined and the standardization of the materials of aerospace technology is considered. A brief description is given of an analysis of technological processes. The analysis had been conducted in connection with occasionally occurring defects concerning the quality of spare parts. It is proposed to review the specifications periodically to avoid a detrimental effect of standardization on technological progress. G R

A76-27363 # Licensing and the organization of the servicing process in aircraft maintenance (Erlaubniswesen und Organisation des Wartungsprozesses in der Flugzeugstandhaltung) H Bremer (Gesellschaft für Internationalen Flugverkehr mbH, Berlin, East Germany) *Technisch-ökonomische Information der zivilen Luftfahrt*, vol 12, no 1, 1976, p 39-46. In German

The currently used system of aircraft maintenance in the German Democratic Republic is briefly analyzed and compared with other systems. The investigation is to provide information concerning the approaches which can be used for a more effective utilization of the available maintenance personnel. The aircraft is examined from the viewpoint of systems analysis as an aggregate of various subsystems. Advantages and drawbacks of the current maintenance system are discussed. The qualifications and the general status of the training of the technical maintenance expert in relation to the range of his assigned duties are considered, taking into account the characteristics of a system in which the expert is only authorized to work with one type of aircraft. G R

A76-27364 # Determination of the realizable flight hours for aircraft (Bestimmung der realisierbaren Flugstunden von Flugzeugen) K Tomov, J Bobev, and V Boiadzhiev. *Technisch-ökonomische Information der zivilen Luftfahrt*, vol 12, no 1, 1976, p 56-63. In German (Translation)

A method is derived for the calculation of the maximum number of flight hours which can be obtained in a year in the case of an airliner. It is pointed out that at the present time it is not possible to take into account a number of secondary conditions. The described method should, therefore, be considered as an intermediate step on the way to a more perfect evaluation procedure. G R

A76-27741 # Non-linear effect due to flow separation on flow past wings and wing body combinations S V Ramakrishnan and N R Subramanian (Indian Institute of Technology, Madras, India) In *Nonlinear Ballistics Seminar*, Pune, India, June 21, 22, 1974, Proceedings. Pune, India, Institute of Armament Technology, 1975, p 183-190

The nonlinear phenomenon of flow separation from a slender delta wing in a conical supersonic flow is studied in the cross flow plane. An inviscid model is constructed by introducing the vortex sheet as a free boundary in the form of a spiral. All the vorticity in the fluid is assumed to be contained in this sheet, so that motion outside is irrotational. The entire inner part of the sheet is replaced by a line vortex. Shape of the vortex sheet, strength of the vortex sheet, position of the vortex core, and strength of the vortex core can then be found by simultaneous solution of the boundary

conditions and the equations for the smooth outflow condition and the condition of zero total force on the vortex. The method is extended to wing-body combinations, where the wing-body is transformed into a vertical slit. P T H

A76-27743 # Ballistics of ejection seats M R Patkar (Armament Research and Development Establishment, Pune, India) In *Nonlinear Ballistics Seminar*, Pune, India, June 21, 22, 1974, Proceedings. Pune, India, Institute of Armament Technology, 1975, p 241-258, Discussion, p 259-260. 10 refs

The paper reviews the evolution of ejection seats and then gives a state-of-the-art description of the ballistics of ejection with emphasis on pilot safety considerations. A method for calculating the trajectory of ejection seats for given initial data on ejection velocity, ejection angle, and flight envelope is outlined. Cartridge and propellant design are examined from the viewpoint that they should be such as to ensure an ejection velocity of about 80 ft/sec, peak accelerations of not more than 25 g, and rate of rise of acceleration not exceeding 300 g/sec. An experimental technique for evaluating ballistic parameters of ejection seats is described. Initial development of a vented vessel and final development of a 154-foot seat ejection tower with associated instrumentation are discussed. P T H

A76-27826 Symposium Transsonicum II, Gottingen, West Germany, September 8-13, 1975, Proceedings Symposium sponsored by IUTAM, DFG, DFVLR, AFSC, U.S. Army, et al. Edited by K Oswatitsch (Wien, Technische Hochschule, Vienna, Austria) and D Rues (Aerodynamische Versuchsanstalt, Gottingen, West Germany). Berlin, Springer-Verlag, 1976. 590 p. In English and German. \$36.10

Investigations in the area of unsteady flow are examined, taking into account asymptotic solutions for nonsteady transonic channel flows, shock oscillations in transonic flows and their prevention, a calculation of buffet onset for supercritical airfoils, and unsteady transonic supersonic flow over suddenly inserted bodies. Hodograph methods are considered along with methods in the physical space, studies of internal flow, investigations of viscous flow, and various applications. Descriptions of numerical methods are also provided, giving attention to numerical techniques for calculating supercritical airfoil flows, steady transonic flow through plane and axisymmetric nozzles, and a calculation of steady inviscid flow around nonlifting bodies.

G R

A76-27827 Some developments in unsteady transonic flow research M T Landahl (Kungl Tekniska Hogskolan, Stockholm, Sweden, MIT, Cambridge, Mass.) In *Symposium Transsonicum II, Gottingen, West Germany, September 8-13, 1975, Proceedings*. Berlin, Springer-Verlag, 1976, p 1-32. 37 refs

Some important properties of unsteady transonic flows are considered along with recent developments of methods for calculating oscillatory transonic flows and a procedure for finding the solution for an oscillatory source imbedded in a steady, nonuniform transonic potential flow. It is pointed out that the validity of the linearized theory is intimately connected with the stability of a steady transonic flow. Questions of flow stability are investigated. Attention is given to the solution of the linearized flow problem of a three-dimensional wing performing infinitesimal oscillations, taking into account an approach which employs the method of parametric differentiation. G R

A76-27830 On the motion of shock waves on an airfoil with oscillating flap H Tijdeman (Nationaal Luchtvaartlaboratorium, Amsterdam, Netherlands) In *Symposium Transsonicum II, Gottingen, West Germany, September 8-13, 1975, Proceedings*. Berlin, Springer-Verlag, 1976, p 49-56. 6 refs

Results are presented of measurements of the periodical motion of the shock waves on a NACA 64A006 airfoil with harmonically oscillating flap in two-dimensional attached transonic flow. It is

shown that three different types of shock wave motion can be distinguished. An analytical model is developed, with which a satisfactory explanation can be given of the observed types of shock wave motion. (Author)

A76-27832 Calculation of buffet onset for supercritical airfoils G Redeker (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Institut für Aerodynamik, Braunschweig, West Germany) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer Verlag, 1976, p 66-74 12 refs

The method of Thomas (1971) for calculating buffet onset has been improved in such a way that supercritical airfoils as well as high angles of attack and high lift coefficients can be treated. Calculated examples of buffet onset boundaries are shown and compared with experimental results. (Author)

A76-27837 Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils J W Boerstel (National Luchtvaart laboratorium, Amsterdam, Netherlands) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 109-133 29 refs. Research supported by the Netherlands Agency for Aerospace Programs

Hodograph theory is concerned with a flow which is plane and irrotational. It is assumed that the flow satisfies the mass conservation law, Bernoulli's law, and a pressure-density relation. The flow equations are transformed to hodograph equations by assuming that there exists a mapping from a physical plane to a surface called the hodograph surface. The partial differential equations obtained are linear. Computational design techniques for shock-free airfoils are discussed. In a review of the applications of the theory attention is given to the experimental existence of shock-free flow, examples of airfoils computed with advanced hodographic methods, the pressure distributions in the design condition, the maximum thickness of shock-free airfoils, and leading edge shapes and low drag. G R

A76-27838 The direct problem of the transonic airfoils on the hodograph. S Nocilla, G Geymonat (Torino, Politecnico, Turin, Italy), and B Gabutti (Torino, Università, Turin, Italy) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer Verlag, 1976, p 134-141 23 refs

The transonic shock-free flow past a given profile is here calculated with a direct procedure on the hodograph plane. The numerical results relative to the circular arc with various leading edges are presented and discussed. (Author)

A76-27844 Airfoil design for a prescribed velocity distribution in transonic flow by an integral method H Hansen (Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, Institut für Aerodynamik, Braunschweig, West Germany) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 183-190, 5 refs

In the present paper a method for the design of airfoils for a prescribed transonic contour velocity distribution is developed. It applies the fundamental ideas of the integral method after K. Oswatitsch for the prediction of the velocity distribution on a given airfoil in nonlinear compressible flow. (Author)

A76-27855 Design and test of a sonic roof-top pressure distribution wing. A L Gustavsson and S. G Hedman (Forsvarsdepartementet Flygtekniska Forsöksanstalten, Bromma, Sweden) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 273-280 6 refs

The PT2 wind tunnel model is a moderate aspect ratio wing of 'sonic roof-top design'. It was designed employing the Woodward

panel method (used to calculate camber and twist distribution) and has straight isobars and a plateau with local Mach number equal to one in the design point. Balance tests and pressure measurements were performed on the model at a Reynolds number of 1×10^6 to the 6. The measured pressures show that the flow is supercritical with a strong shock outwards from midspan with more lift towards the tip than was calculated. The transonic relaxation method was applied to a preliminary redesign of the wing. B J

A76-27856 Supercritical wing design for a fighter type experimental aircraft. R. Vanino and S. Rohlfis. In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 281-288 5 refs. Bundesministerium der Verteidigung Contract No TR-720-7600-43-094, Bundesministerium für Forschung und Technologie Contract No. LFF-28.

Two different versions of a supercritical wing for fighter aircraft were designed. Both are the same in the outer part of the wing but differ in the inner part as well as in section geometry and planform. A relaxation method for the inviscid transonic flow around wing-body combinations was used to carry out the aerodynamic design of the wing starting with initial conditions from the equivalent airfoil section flow. Viscous effects are taken into account by calculating the displacement thickness of the quasi three-dimensional boundary layer. The experimental wing will be mounted to the fuselage of the Alpha Jet. B J

A76-27857 An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1 N Pollock and B D Fairlie (Department of Supply, Aeronautical Research Laboratories, Melbourne, Australia) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 289-296 8 refs

Transonic wind tunnel tests have been carried out on a shockless lifting aerofoil designed by the method of Bauer, Garabedian and Korn. Two models of different chord lengths were tested to provide some information on tunnel wall interference. Close to the design point the analysis method of Garabedian and Korn agrees well with the experimental measurements. Optical flow visualization results indicate that the design point flow is, for practical purposes, shock free and measured pressure distributions provide further experimental verification of the design method. (Author)

A76-27860 An exact hodograph method for the design of supercritical wing sections A Eberle (Messerschmitt-Bölkow-Blohm GmbH, Ottobrunn, West Germany) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 314-321

This contribution describes a simple hodograph method for the design of transonic airfoils mainly based on Sobieczky's rheograph transformation. A classical panel method solves the elliptic part of the flow problem, whereas a method of characteristics is applied for the treatment of the imbedded supersonic region. (Author)

A76-27863 Mathematical method of designing a certain compressor type plane blade cascade M Ruzicka (Statni Vyzkumny Ustav Konstrukce Strojů, Bechovice, Czechoslovakia) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 340-349

The paper presents the method enabling the solution of so called indirect theory problem of blade cascades in case when the flowing medium is an ideal gas, inlet Mach number is supersonic and outlet Mach number subsonic. The supersonic part of the blade cascade is designed by the method of characteristics and the subsonic part by the hodograph method. (Author)

A76-27864 Transonic aerodynamics and the helicopter rotor. P G Wilby and J Grant (Royal Aircraft Establishment, Farnborough, Hants, England) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings

Berlin, Springer-Verlag, 1976, p 350-361 24 refs.

It is pointed out that advances in the area of transonic aerodynamics are leading to a revolution in helicopter rotor design. Aerodynamic limitations to rotor performance are considered along with blade section design aims, the interaction between rotor performance and geometry, and advancing blade tip aerodynamics. It is shown that transonic aerodynamics plays an important part in determining the characteristic of a helicopter rotor and that a full understanding of the transonic aerodynamic problems is required before a fully optimized design is possible. G R

A76-27865 A review of numerical techniques for calculating supercritical airfoil flows. M Holt (California, University, Berkeley, Calif.) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 362-368 12 refs

Three numerical methods for calculating transonic supercritical flow past airfoils are reviewed. The first is the complex characteristics approach of Garabedian, the second is the method of integral relations developed mostly by Tai, and the third is a development of Telenin's method initiated by Chattot in application to the double wedge problem. (Author)

A76-27869 Review of some numerical solutions of the transonic small disturbance equations. E M Murman (Flow Research, Inc., Kent, Wash.) In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 415-422 7 refs

The review takes into account solutions which have been computed during the past five years. Approaches which use difference equations to solve the nonlinear transonic small disturbance equation are considered. The difference equations may be solved by a number of relaxation algorithms and at least two semidirect procedures. The solution of a supercritical flow past a parabolic arc airfoil in a subsonic stream is discussed and attention is given to detached bow wave solutions for supersonic freestream Mach numbers. G R

A76-27874 Research in the UK on finite difference methods for computing steady transonic flows. R C Lock (Royal Aircraft Establishment, Farnborough, Hants, England). In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p. 457-486. 28 refs

The transonic small perturbation equation for inviscid two-dimensional flow over lifting airfoils is solved using a new RAE finite difference method essentially the same as that proposed by Murman and Cole (1970). The method is applied to the analysis of flow over the NACA 64A410, RAE 9550 and BGK II airfoils. The two-dimensional finite difference method developed by Fruman and Jones (1975) is described as is the two-dimensional Garabedian method (1973). Finite difference methods are proposed for the analysis of three-dimensional wings, including the direct calculation method and the wing design method. B.J

A76-27875 Some numerical results of a new three-dimensional transonic flow method. Y C-J Sedin and K R Karlsson (Saab-Scania AB, Linköping, Sweden). In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 487-494. 6 refs. Research supported by the Styrelsen for Teknisk Utveckling.

A study is made to extend a certain axisymmetric transonic flow method to apply to three-dimensional flow around wing-body combinations. The small perturbation potential is decomposed into two new functions forming a coupled system. Separately, these equations may be regarded as two 'parabolic' equations. The

directions of integration are laterally outwards and inwards. The equations are solved iteratively in a reciprocating manner between the considered configuration and a chosen outer boundary. The rate of convergence is high and the obtained results are consistent with other methods. Both lifting and nonlifting cases are treated. (Author)

A76-27877 Supercritical flow past airfoils at Mach numbers close to one. D Euvrard (Ecole Nationale Supérieure de Techniques Avancées, Paris, France) and Y Morchoisne (Société Nationales Industrielle Aérospatiale, Suresnes, Hauts-de-Seine, France). In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 507-514 8 refs. Direction des Recherches et Moyens d'Essais Contract No 73/030

A direct method already presented by Euvrard and Tournemine (1973) but including some recent improvements is used to compute the sonic flow over a given symmetrical airfoil. It is a shooting method, each iteration of which consists in integrating a mixed elliptic-hyperbolic system of nonlinear equations with initial and boundary data. This is achieved with a finite difference scheme involving an adequate artificial viscosity. The flow is then continued downstream of the transonic boundary using the method of characteristics. A number of comparisons are made with experimental data and with supercritical computations using relaxation methods. This clearly demonstrates the reality of the well-known 'freezing phenomenon'. The empirical rule from Sinnott and Osborne is also applied and discussed. (Author)

A76-27878 A direct method for computing non-symmetrical plane flows at Mach number one. F Grosjean and G. Tournemine (Brest, Université, Brest, France). In Symposium Transsonicum II Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 515-522. 7 refs. Direction des Recherches et Moyens d'Essais Contract No 73/030

A numerical method adapted to the computation of sonic or nearly sonic flows is applied to a non-symmetrical two-dimensional flow. The mixed elliptic-hyperbolic system of nonlinear flow equations is integrated using a finite difference scheme involving some numerical viscosity. The method is used to calculate the transonic flow past the NACA 0012 airfoil. B J

A76-27879 The analysis of arbitrary wingbody combinations in transonic flow using a relaxation method. W. Schmidt and R. Vanino (Dornier GmbH, Friedrichshafen, West Germany). In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p. 523-532. 12 refs. Bundesministerium der Verteidigung Contract No TR-720-R-7600-42-009

The Dornier relaxation method (1974) for the numerical simulation of various wing-body configurations is described. The method solves the transonic perturbation potential equation in a rectangular grid box with variable mesh size, taking account of the elliptic-hyperbolic nature of the equation by central and backward differences for the streamwise derivatives. The method is applied to different wing-body combinations to a 30 degree swept wing with biconvex section mounted on a circular body, on a rectangular body, and on a cylindrical body. B.J.

A76-27880 Numerical solutions for transonic flows past wing-body combinations. C M Albone, M G Hall, and G Joyce (Royal Aircraft Establishment, Farnborough, Hants, England). In Symposium Transsonicum II, Göttingen, West Germany, September 8-13, 1975, Proceedings. Berlin, Springer-Verlag, 1976, p 541-548 5 refs

A numerical method has been developed for calculating the inviscid flow past lifting wing-body combinations by solving a form of the transonic small-perturbation equation for the velocity potential. An outline is given of the formulation of the problem and the procedure for numerical solution. Numerical results are com-

pared with data from wind-tunnel tests on a wing-body configuration, and the variation of body interference with angle of incidence and free-stream Mach number is illustrated (Author)

A76-27930 # Improvement of the precision of aircraft control during completion of a plane turn maneuver (Povyshenie tochnosti upravleniia letatel'nym apparatom pri sovershenii manevraploskii razvorot) E Ia Sirotkin and A F Taratin (Leningradskii Institut Aviatsonnogo Priborostroeniia, Leningrad, USSR) *Priborostroenie*, vol 19, no 1, 1976, p 48-53 In Russian

The error in reproduction of a programmed trajectory of a plane turn due to the time lag of the aircraft is analyzed Numerical modeling shows that this error can be greatly reduced by advancing the time that the turn command is given by an interval determined from the parameters of the aircraft-autopilot system A numerical example is given C K D

A76-28029 * # Preparation of eutectic superalloys by EFG G F Hurley and N W Marr (Mobil Tyco Solar Energy Corp, Waltham, Mass) *American Institute of Mining, Metallurgical, and Petroleum Engineers, International Conference on In Situ Composites, 2nd, Lake George, N Y., Sept 2-5, 1975, Paper 10 p 5 refs* Contracts No NAS3-16790, No NAS3-18909

An attempt was made to produce airfoil shaped bars of three different eutectic superalloys by means of the edge-defined, film-fed growth (EFG) method The alloys used were a gamma + delta Ni-Cb alloy, a gamma/gamma prime + delta Ni-Cb-Al alloy and a Co-TaC alloy containing Ni and Cr The development of a new die material was essential in the investigation since these alloys are reactive toward known die materials Tantalum carbide was selected as a die material because it exhibited spontaneous capillary rise and slow rate of degradation in the liquid metals Eutectic bars up to 1 mm thick and 6 mm wide were grown from TaC dies in order to determine the growth characteristics and the thermal gradient Large bars of the gamma/gamma prime + delta alloy were grown and tensile tested A die with a blind central cavity was designed and several hollow, tear-shaped bars were grown B J

A76-28033 # Fundamental formulation of airship performance and flight dynamics A Azuma (Tokyo, University, Tokyo, Japan) *Tokyo University, Institute of Space and Aeronautical Science, Report*, no 536, vol 40, Dec 1975, p 457-489 14 refs

A fundamental analysis of airship performance and flight dynamics is presented From the performance calculations of four airships, it can be concluded that only large airships, the gross weight of which is more than about 500 tons, have good transport efficiency compared with other vehicles in the operational speed range of 50 to 200 km/hr The handling qualities of the airships are, however, very poor for larger sizes because of small control capability against huge virtual mass and moment of inertia of the hull Thus, large airships are very difficult to maneuver at and near hovering flight (Author)

A76-28100 # Rocket engines GDL-OKB V P Glushko (Academy of Sciences, Gas Dynamics Laboratory, USSR) Moscow, Agentstvo Pechati Novosti, 1975 70 p Translation

The organization and history of the Gas Dynamics Laboratory (GDL) and the Experimental Design Bureau (OKB) Aircraft liquid-propellant rocket engines of the USSR are outlined The development of chemical and pyrotechnical ignition, swirltype injectors, internal cooling systems, and suitable structural materials for liquid-propellant rocket engines using a nitric acid-kerosene propellant, and the subsequent evolution of the high-boiling-point liquid-propellant rocket engines in the ORM and RLA series, are reviewed The characteristics of the different engines of the RD series, used to launch satellites, unmanned lunar and planetary probes, and the manned Vostok, Voskhod, and Soyuz spacecraft, are discussed C K D

A76-28254 # Effect of the upper limit of distribution function of aircraft structure on the main failure's distribution M Samir Abdelsalam *Zprava VZLU*, no Z-26, 1975 7 p 8 refs

An estimation of distribution function of main failures of aircraft structures is carried out It is the case when taking in to consideration the location of the last failure - from the total failures forming the distribution function of the whole structure of an aircraft - as a random variable A practical example is given to show the application of the given method (Author)

A76-28255 # Estimation of population reliability function of aircraft structures from a limited fleet of aircraft M Samir Abdelsalam *Zprava VZLU*, no Z-27, 1975 6 p 10 refs

The population reliability function of aircraft structures is determined This is based on the knowledge about the course of failures of individual structures That is to say on the total number of failures, the location of main failures (they are such failures which cause stopping the normal operation of the structure) and the total number of structures under investigation A practical example is given to indicate the procedure (Author)

A76-28256 # Aerodynamic derivatives of the longitudinal motion of the whole aircraft (Aerodynamické derivace podélného pohybu celeho letounu) Z Skoda *Zpravodaj VZLU*, no 5, 1975, p 169-176 6 refs In Czech

A new minicomputer-oriented method for calculating the aerodynamic derivatives of steady-state longitudinal motion of an entire aircraft, ignoring compressibility of flow, is presented Direct mathematical formulas for flow around the aircraft as an integral body are employed The method of small perturbations is invoked to simplify the problem and arrive at a system of linear integral equations The resulting system is solvable by approximating a distributed loading of the wings by a system of discrete forces, whose values are computed via a system of linear algebraic equations The method is recommended for evaluating the properties of newly designed aircraft R D V

A76-28258 # Extension of slender body theory (Rozšíření teorie stíhého tělesa) O E A Hamid *Zpravodaj VZLU*, no 6, 1975, p 231-237 18 refs In Czech

The extension of slender body theory considered consists in retaining certain terms which were neglected during the derivation of the equations of the original theory The extended theory takes into account the effect of body shape and Mach number on the outcome of the solutions and refines the calculation of aerodynamic coefficients Applications of the extended theory are illustrated on the examples of a slender body oscillating in the flow of an incompressible fluid and of a flat delta wing in steady supersonic flow P T H

A76-28259 # Effect of gusts on helicopter loading (Vliv poryvu na zatížení vrtulníku) M Kucera *Zpravodaj VZLU*, no 6, 1975, p 239-252 In Czech

A method is proposed for aiding in the determination of the fatigue properties of helicopter designs by which the interpretation of the design loading can be made to approximate the level of the load spectra of fixed-wing aircraft In an experiment, the load factor spectrum was determined for a helicopter and the escort aircraft L-40 as well as the spectrum of stresses on the rotor blade and the rotor control level during flight through an isolated gust Because of the large range of flight speeds and helicopter specifications, a significant influence on loading is exerted by the gust alleviating factor, to obtain which is more difficult in the case of a helicopter than that of an airplane The results show that this method for determining helicopter gust spectra is acceptable and the gust stress spectra are significant for the rotor blade P T H

A76-28354 # Hydraulic systems for transport aircraft (Gidravlicheskie sistemy transportnykh samoletov) Zh S Chernenko, G S Lagosiuk, G N Nikulinski, and B Ia Shvets Moscow, Izdatel'stvo Transport, 1975 184 p 11 refs In Russian

The book gives an exposition of the chief requirements imposed on large aircraft hydraulic systems, describes the operational characteristics of working fluids, and illustrates aircraft hydraulic systems with functional diagrams and cross-sectional diagrams of the chief components. Factors influencing the reliability of tubing and seals are studied, and recommendations are given regarding the servicing and exploitation of linking equipment and sealing devices. The reliability characteristics of hydraulic systems are investigated, with analyses taking into account flight regimes and exploitation factors on reliability. P T H

A76-28469 Limitations of the flight regime of a supersonic transport /SST/ by the sonic boom (Die Beschränkung des Flugbereichs eines Überschallverkehrsflugzeugs /SST/ durch den Schallknall) M Kloster (München, Technische Universität, Munich, West Germany) *Zeitschrift für Flugwissenschaften*, vol 24, Mar-Apr 1976, p 82-89 31 refs In German

The characteristics of the height-Mach number diagram for an SST on the basis of data for an early design stage of the Concorde are considered and a description of flight performance calculations is given, taking into account an operation with and without afterburner. The limitations of the flight regime in the case of supersonic aircraft are indicated in a graph. An investigation is conducted concerning the effect of the sonic pressure and the influence of this parameter on the flight regime. It is found that considerations related to the sonic pressure reduce the range for the operational-parameter values. Attention is given to design changes for optimizing aircraft performance under the constraint of the given regulations regarding the permissible sonic pressure. G R

A76-28542 # Results of noise and vibration studies on An-24 aircraft (Wyniki badań hałasu i drgan samolotow An-24) C Puzyna (Centralny Instytut Ochrony Pracy, Warsaw, Poland) In *Ergonomics in aviation, National Scientific-Technological Conference, 1st, Warsaw, Poland, March 17-19, 1975, Proceedings* Warsaw, Instytut Lotnictwa, 1975, p 171-178 In Polish

Basic findings from a program of tests on the noise and vibration levels in selected areas of the An-24 aircraft in various flight phases and on the runway are discussed. This aircraft has two under-the-wing turboprop engines, each of rated power 2100 hp. The engines are located about 2.5 meters from the passenger cabin walls. It was determined in particular that the noise level in the crew cabin exceeds accepted norms. Some measures are proposed to ensure that the crew is not overloaded as a result of noise. P T H

A76-28543 # Ergonomics and the problem of aircraft-induced external noise (Ergonomia i problem hałasow zewnętrznych wywoływanych przez samolot) T Rappert (Zarząd Lotniskowy, Warsaw, Poland). In *Ergonomics in aviation, National Scientific-Technological Conference, 1st, Warsaw, Poland, March 17-19, 1975, Proceedings* Warsaw, Instytut Lotnictwa, 1975, p. 179-188 In Polish.

Some ergonomic problems are discussed, with particular reference to the aviation aspects of man/machine interaction. The characteristics of internal and external aircraft noise are studied, along with the effects of internal noise on the passenger and crew environments. Particular attention is given to the effect of external aircraft noise on the working conditions and performance of airport personnel and to the noise abatement problem. V P.

A76-28544 # Ergonomic analysis of maneuvers leading to inaudibility of a shock wave (Ergonomiczna analiza manewrow prowadzących do niesłyszalności fali uderzeniowej) R Makarewicz (Poznań, Uniwersytet, Poznań, Poland) In *Ergonomics in aviation, National Scientific-Technological Conference, 1st, Warsaw, Poland, March 17-19, 1975, Proceedings* Warsaw, Instytut Lotnictwa, 1975, p 189-195 In Polish

An analysis of supersonic flight with shock wave is presented in order to determine those combinations of flight parameters under

which the load factor attains a certain critical value for a critical length of time, ensuring that the shock wave is inaudible on the ground. Numerical values for the load factor and the time interval are obtained, which can serve as a basis for determining the optimal aircraft maneuver ensuring inaudibility of the shock wave, where optimality is understood in the sense of shortest time spent at the critical load factor for the minimal load factor value. P T H

A76-28545 # Selected problems of cockpit acoustic design (Wybrane zagadnienia akustycznego projektowania kabin) A Rudiuk (Instytut Lotnictwa, Warsaw, Poland) In *Ergonomics in aviation, National Scientific-Technological Conference, 1st, Warsaw, Poland, March 17-19, 1975, Proceedings* Warsaw, Instytut Lotnictwa, 1975, p 196-212 In Polish

Cockpit noise is broken down into external noise penetrating into the cockpit through the walls and glass surfaces, noise multiply reflected from internal surfaces of the cockpit, noise generated in the cockpit itself, and noise generated by vibrations of the cockpit's mechanical elements. The noise-absorbing and noise-damping properties of materials used to construct the cockpit walls are reviewed. The influence of discontinuities (such as doors, windows, etc.) on the insulating properties of aircraft walls is examined. V P

A76-28606 * # Subsonic loads on wings having sharp leading edges and tips O A Kandil, D T Mook, and A H Nayfeh (Virginia Polytechnic Institute and State University, Blacksburg, Va.) *Journal of Aircraft*, vol 13, Jan 1976, p 62, 63 10 refs Grant No NGR-74-004-090

A vortex-lattice method for predicting the aerodynamics of wings having separation at the sharp edges in incompressible flows is extended to compressible subsonic flows using a modified Prandtl-Glauert transformation. Numerical results showing the effect of freestream Mach number on the aerodynamic coefficients are compared with available experimental data for several planforms. It is shown that the proposed method is suitable for predicting the aerodynamic loads on low-aspect wings at moderate angles of attack for high subsonic freestream Mach number. The method is limited to angles of attack up to 12 deg for high subsonic freestream Mach number and to angles of attack up to 20 deg for Mach number not exceeding 0.5. S D

A76-28607 # Use of fracture mechanics in estimating structural life and inspection intervals M P Kaplan and J A Reiman (USAF, Aeronautical Systems Div., Wright-Patterson AFB, Ohio) *Journal of Aircraft*, vol 13, Feb 1976, p 99-103 20 refs

As structural efficiency of aircraft has increased in the recent past, the Air Force has found it necessary to include, in the newer systems, damage tolerance criteria for fracture critical parts. These criteria are explained briefly, and sample calculations indicating methods for determining component structural life are demonstrated. Implicit in this calculation is the definition of inspection intervals. The second portion of this discussion details some of the assumptions that go into this analysis and their sensitivity. A large portion centers on stress spectrum definition. It is shown that, from one set of occurrence data, alternative spectra may be derived which have substantial differences in life. (Author)

A76-28608 # Nozzle afterbody configuration development for the B-1 strategic bomber J C Sargent and J L Gunter (Rockwell International Corp., Los Angeles, Calif.) (*American Institute of Aeronautics and Astronautics and Society of Automotive Engineers, Propulsion Conference, 10th, San Diego, Calif., Oct 21-23, 1974, AIAA Paper 74-1102*) *Journal of Aircraft*, vol 13, Feb 1976, p 135-139

An experimental evaluation was conducted on several aft nacelle/nozzle configurations. The wind-tunnel data are presented for different nozzle shapes, variations of the nacelle fineness ratio, and different internozzle fairing configurations. These results were used in mission studies to define the aircraft configuration. A relatively short, light-weight nozzle was integrated with the nacelle to provide better mission performance than a longer, heavier design. Increasing

the nacelle fineness ratio by increasing the length reduced drag, but this was offset by the increased weight. A fixed internozzle fairing incorporating the precooler air discharge from the ECS was selected over other concepts (Author)

A76-28610 # Representation of the drag polar of a fighter aircraft. K S Yajnik and M V Subbaiah (National Aeronautical Laboratory, Bangalore, India) *Journal of Aircraft*, vol 13, Feb 1976, p 155, 156

A simple additive correction to the classical representation of the drag coefficient which is insignificant when the square of the lift coefficient is small has been derived. The resulting simplified representation can be described as a quadratic curve of regression of the drag coefficient on the square of the lift coefficient. Using data on the drag polars of YF-16, it is shown that the proposed approximation can be used in turn calculations for a fighter aircraft. C K D

A76-28611 # Analysis of circulation controlled airfoils. E H Gibbs and N Ness (West Virginia University, Morgantown, W Va) *Journal of Aircraft*, vol 13, Feb 1976, p 158-160 12 refs. Contract N00014-68-A-0512

A self contained analysis for circulation controlled airfoils of arbitrary shape in incompressible flow is presented. The potential flow is analyzed by the Theodorsen method (1933). Boundary-layer analyses are carried out for the upper and lower surfaces of the aircraft using the Cebeci-Smith finite-difference method (1969). The analysis of the turbulent wall jet region begins at the blowing slot and proceeds downstream until separation occurs. The Thwaites condition is satisfied by an iteration on a slot blowing momentum coefficient. The theoretical model gives reasonable agreement with limited test data. C K D

A76-28642 Note on a numerical scheme for the three-dimensional flow of a supercavitating wing or strut with thin cavity. B Yim (U.S. Naval Material Command, David W Taylor Naval Ship Research and Development Center, Bethesda, Md) In *Cavitation and polyphase flow forum - 1976, Proceedings of the Joint Meeting, New Orleans, La, March 21-25, 1976*. Meeting sponsored by the American Society of Mechanical Engineers, New York, American Society of Mechanical Engineers, 1976, p 35, 36 5 refs

A supercavitating wing with a given load distribution is treated numerically in a manner similar to that used in airfoil theory. The design problem for a given load distribution on the supercavitating airfoil is reduced to the solution of a Fredholm integral equation of the first kind for the cavity source strength, as in the problem of determining the vortex distribution in the thin airfoil problem. The specific features of the numerical scheme are demonstrated, and some results of numerical experiments are discussed. V P

A76-28693 Helicopter rotor blades - The new technology. R Mouille (Societe Nationale Industrielle Aérospatiale, Paris, France) *Shell Aviation News*, no 433, 1976, p 20-25

The use of reinforced plastics in the fabrication of helicopter rotor blades offers significant advantages over metal materials. In addition to relatively high fatigue strength to density ratios and lack of sensitivity to notch effect and fatigue-corrosion phenomena, it is possible to vary the plan form, relative thickness and airfoil camber of the plastic blade, as well as its torsional rigidity characteristics. Maintenance costs are minimized by the long life-time and ease of repair of plastic blades. The effect of a switch to all plastic rotor blades on the performance of the Puma is discussed. A 13 per cent reduction in the cost per kg/km is predicted as the result of decreased maintenance costs and fuel consumption and increased payload. C K D

Page intentionally left blank

Page intentionally left blank

STAR ENTRIES

N76-20063*# Hudson Inst Inc Croton-on-Hudson NY
THE OUTLOOK FOR AERONAUTICS, 1980 - 2000 - STUDY REPORT

Mar 1976 41 p
 (Contract NAS5-20852)
 (NASA-TM-X-72995) Avail NTIS HC \$4 00 CSCL 01B

Trends in civil and military aviation in the period 1980-2000 are examined in terms of the role that NASA should play in aeronautical research and development during this period. Factors considered include the pattern of industry and government relationships, the character of the aircraft to be developed, and the technology advances that will be required, as well as demographic, economic, and social factors. Trends are expressed in terms of the most probable developments in civil air transportation and air defense and several characteristically different directions for future development are defined. The longer term opportunities created by developments in air transportation extending into the next century are also examined. Within this framework, a preferred NASA role and a preferred set of objectives are formulated for the research and technology which should be undertaken by NASA during the period 1976-1985. Author

N76-20064*# Hudson Inst Inc Croton-on-Hudson NY
THE OUTLOOK FOR AERONAUTICS, 1980 - 2000 APPENDIX B STUDY GROUP REPORT ON AN INDUSTRY-UNIVERSITY-GOVERNMENT SURVEY

Mar 1976 46 p
 (Contract NAS5-20852)
 (NASA-TM-X-72996) Avail NTIS HC \$4 00 CSCL 01B

Results of a comprehensive survey of key representatives of the aeronautical community are presented. Emphasis is placed on trends in civil and military aviation, the role of NASA in aeronautical research and development, and the required technology advances for the development of new aircraft. J M S

N76-20065*# Hudson Inst Inc Croton-on-Hudson NY
DOMESTIC AND WORLD TRENDS AFFECTING THE FUTURE OF AVIATION (1980 - 2000), APPENDIX C

Mar 1976 78 p
 (Contract NAS5-20852)
 (NASA-TM-X-72997) Avail NTIS HC \$5 00 CSCL 01B

The results are presented of a study of variables affecting aviation in the United States during the last fifth of the twentieth century. A series of key trends relating to economic, social, political, technological, ecological, and environmental developments are identified and discussed with relation to their possible effects on aviation. From this analysis, a series of scenarios is developed representing an array of possibilities ranging from severe economic depression and high international tension on the one hand to a world of detente which enjoys an unprecedented economic growth rate and relaxation of tensions on the other. A scenario is presented which represents the manner in which events will most probably develop and their effect on the aviation industry. Author

N76-20066*# Hudson Inst Inc Croton-on-Hudson NY
THE OUTLOOK FOR AERONAUTICS, 1980 - 2000 EXECUTIVE SUMMARY

Mar 1976 18 p
 (Contract NAS5-20852)
 (NASA-TM-X-72998) Avail NTIS HC \$3 50 CSCL 01B

Trends in civil and military aviation in the period 1980-2000 are examined in terms of the role that NASA should play in aeronautical research and development during this period. Factors considered include the pattern of industry and government relationships, the character of the aircraft to be developed, and the technology advances that will be required, as well as demographic, economic, and social factors. Trends are expressed in terms of the most probable developments in civil air transportation and air defense and several characteristically different directions for future development are defined. The longer term opportunities created by developments in air transportation extending into the next century are also examined. Within this framework, a preferred NASA role and a preferred set of objectives are formulated for the research and technology which should be undertaken by NASA during the period 1976-1985. Author

N76-20067# Advisory Group for Aerospace Research and Development Paris (France)

AGARD HIGHLIGHTS, MARCH 1976

1 Mar 1976 33 p
 (AGARD-Highlights-76/1) Avail NTIS HC \$4 00

Reports of AGARD activities are presented. The articles presented concern hurricane Eloise, Von Karman medals for 1975, air traffic control, aircraft fire safety, and personnel changes.

F O S

N76-20068# Federal Aviation Administration Washington D C
 Aviation Forecast Branch

MILITARY AVIATION FORECASTS, FISCAL YEARS 1976 - 1987

Sep 1975 38 p refs
 (AD-A017622 FAA-AVP-75-12) Avail NTIS HC \$4 00 CSCL 01/2

Forecasts of military air traffic activity at facilities operated by the Federal Aviation Administration for the fiscal years 1976 through 1987 are presented. Data are given for all branches of the military and cover flight for the continental United States.

Author

N76-20069# Federal Aviation Administration Washington D C
 Aviation Forecast Branch

AVIATION FORECAST, FISCAL YEARS 1976 - 1987

Sep 1975 76 p
 (AD-A017095 FAA-AVP-75-7) Avail NTIS HC \$5 00 CSCL 01/2

The latest Federal Aviation Administration forecast of measures of workload and activity at towered airports, air route traffic control centers, and flight service stations for Fiscal Years 1976 to 1987 are given. The forecasts were made for the four major users of the system: air carriers, air taxi, general aviation, and the military. The impact is reflected on aviation activity of a more rapid rate of price increase, especially for fuel, and a slower rate of real income growth than had been assumed in previous forecasts. Author

N76-20070# Deutsche Gesellschaft fuer Luft- und Raumfahrt
 Cologne (West Germany)

HISTORY OF MESSERSCHMITT AIRCRAFT MANUFACTURING

Johann Baptist Kaiser 29 Oct 1975 43 p refs In GERMAN ENGLISH summary
 (DLR-Mitt-75-21) Avail NTIS HC \$4 00 DFVLR Cologne DM 22 20

The career of Willy Messerschmitt and the history of his firm is presented. Messerschmitt, constructor and research worker, aircraft builder and industrialist, is one of the last living pioneers from the start of the development of aeronautical technology at the beginning of this century. His contribution to this development is described. ESA

N76-20071# Federal Aviation Administration Washington D C
Office of Management Systems
THE 1974 US CIVIL AIRMEN STATISTICS Annual Study
May 1975 36 p
(AD-A013434) Avail NTIS CSCL 05/9

The 1974 U S Civil Airmen Statistics is the sixth edition of an annual study published to meet the demands of FAA other government agencies and industry for more detailed airmen statistics than those published in other FAA reports Statistics pertaining to airmen both pilot and nonpilot were obtained from the official airman certification records maintained by the Flight Services Technical Division FAA Aeronautical Center Oklahoma City Oklahoma GRA

N76-20072# Federal Aviation Administration Washington D C
Office of Aviation Policy
THE GENERAL AVIATION INDUSTRY, AN OVERVIEW Staff Study Report

Thomas F Henry and Maryann Froehlich Jul 1975 66 p
refs
(AD-A015871 FAA-AVP-75-4) Avail NTIS CSCL 01/3

This report presents background information and statistics on various aspects of the general aviation (GA) industry The report documents the impressive growth of the general aviation fleet particularly since the 1960's and illustrates recent trends in GA aircraft types and user categories It emphasizes that GA activities are becoming increasingly important in the National Aviation System of Airports and Airways and that this implies increased FAA workload The report also discusses trends in aircraft production and export and the relative market shares of the producers of GA aircraft as well as the industry's overall contribution to the U S balance of payments The discussion of energy considerations suggests that the Arab oil embargo and subsequent increases in oil prices brought on by the pricing policies of the Organization of Petroleum Exporting Countries (OPEC) had minimal effects on GA activities However legislative proposals designed to impose substantial taxes on gasoline production or sale might have depressing effects on future GA activities Author (GRA)

N76-20073 California Inst of Tech, Pasadena
EXPERIMENTS ON THIN AIRFOILS SPANNING A TRANSONIC SHEAR FLOW Ph D Thesis
Raymond Robert Cosner 1976 346 p
Avail Univ Microfilms Order No 76-6525

A wind tunnel was built at the California Institute of Technology to provide two uniform coflowing streams at Mach numbers of 0.6 and 1.4 with a plane mixing layer in between Preliminary studies were made of this free shear layer indicating a region of self-similar behavior and general agreement in growth rate with previous studies A program of experimental and theoretical work was completed in which wedges were installed in the supersonic stream to create shock waves incident on the

N76-20077*# Boston Univ Mass
FULLY UNSTEADY SUBSONIC AND SUPERSONIC POTENTIAL AERODYNAMICS FOR COMPLEX AIRCRAFT CONFIGURATIONS FOR FLUTTER APPLICATIONS

Kadin Tseng and Luigi Morino [1975] 14 p refs Presented at AIAA/ASME/SAE 17th Structures Structural Dynamics and Materials Conf
(Contract NGR-22-004-030)
(NASA-CR-146573) Avail NTIS HC \$3 50 CSCL 01A

A general theory for study oscillatory or fully unsteady potential compressible aerodynamics around complex configurations is presented Using the finite-element method to discretize the space problem one obtains a set of differential-delay equations in time relating the potential to its normal derivative which is expressed in terms of the generalized coordinates of the structure For oscillatory flow the motion consists of sinusoidal oscillations around a steady subsonic or supersonic flow For fully unsteady flow the motion is assumed to consist of constant subsonic or supersonic speed for time $t < 0$ and of small perturbations around the steady state for time $t > 0$ Author

N76-20078*# Scientific Translation Service Santa Barbara Calif
AIRCRAFT USE IN AGRICULTURE AND FORESTRY
V A Nazarov Washington Feb 1976 420 p Transl into ENGLISH of the book *Primeneniye Aviatsii v Selskom - Lesnom Khozyaystve* Moscow Transport 1975 p 1-311
(Contract NASw-2791)

(NASA-TT-F-16846) Avail NTIS HC \$11 00 CSCL 01C
Information is presented (a textbook) on the use of aircraft in agriculture and forestry agricultural equipment for airplanes and helicopters and the technology for performing organizing and standardizing aircraft application operations All forms of aerial agricultural chemical application operations are covered in detail with consideration for the latest data (1) combatting plant pests and diseases (2) weed suppression (3) mineral fertilizer application (4) crop defoliation (5) desiccation and so on The latest experience in crew operational procedures and the latest scientific advances are examined Photographs are included
Author

N76-20079*# National Aeronautics and Space Administration
Ames Research Center Moffett Field Calif
EXPERIMENTAL AERODYNAMIC CHARACTERISTICS FOR SLENDER BODIES WITH THIN WINGS AND TAIL AT ANGLES OF ATTACK FROM 0 DEG TO 58 DEG AND MACH NUMBERS FROM 0.6 TO 2.0

Leland H Jorgensen and Edgar R Nelson Washington Mar 1976 159 p refs
(NASA-TM-X-3310 A-6248) Avail NTIS HC \$6 75 CSCL 01A

An experimental investigation was conducted by wind tunnel to measure the static aerodynamic characteristics for bodies of circular and elliptic cross section with various thin flat plate wings and a thin tail consisting of horizontal and vertical parts The wings had aspect ratios of 4 and taper ratios of about 0.25 and 0.5 Two additional wings which had taper ratios near 0.25 and aspect ratios of about 3 and 5 were also tested in combination with the bodies and tail All wings had about the same planform area The exposed area of the horizontal portion of the tail was about 33 to 36 percent of the exposed area of the wings The exposed area of the vertical tail fin was about 22 to 24 percent of the exposed area of the wings The elliptic body with an $a/b = 2$ cross section had the same length and axial distribution of cross sectional area as the circular body The circular body had a cylindrical aftersection of fineness ratio 7 and it was tested with the wings and tail in combination with tangent ogive noses that had fineness ratios of 2.5, 3.0, 3.5 and 5.0 In addition an ogive nose with a rounded tip and an ogive nose with two different nose strike arrangements were used Nineteen configuration combinations were tested at Mach numbers of 0.6, 0.9, 1.5 and 2.0 at angles of attack from 0 to 58 deg The Reynolds numbers based on body base diameter were about 4.3×10^6 Author

N76-20081*# National Aeronautics and Space Administration
Langley Research Center Langley Station, Va
PRESSURE DISTRIBUTIONS ON A RECTANGULAR ASPECT-RATIO-6, SLOTTED SUPERCRITICAL AIRFOIL WING WITH EXTERNALLY BLOWN FLAPS

William G Johnson Jr Washington Apr 1976 254 p refs
(NASA-TM-X-3337 L-10558) Avail NTIS HC \$9 00 CSCL 01A

An investigation was made in the 5.18 m (17 ft) test section of the Langley 300 MPH 7 by 10 foot tunnel on a rectangular aspect ratio 6 wing which had a slotted supercritical airfoil section and externally blown flaps The 13 percent thick wing was fitted with two high lift flap systems single slotted and double slotted The designations single slotted and double slotted do not include the slot which exists near the trailing edge of the basic slotted supercritical airfoil Tests were made over an angle of attack range of -6 deg to 20 deg and a thrust-coefficient range up to 1.94 for a free-stream dynamic pressure of 5267 Pa (110 lb/sq ft) The results of the investigation are presented as curves and tabulations of the chordwise pressure distributions at the midspan station for the wing and each flap element
Author

**N76-20082*# Texas A&M Research Foundation College Station
TRANSONIC AIRFOIL DESIGN USING CARTESIAN
COORDINATES Final Report**

Leland A Carlson Washington NASA Apr 1976 35 p refs
(Grant NGR-44-001-157)

(NASA-CR-2578) Avail NTIS HC \$4 00 CSCL 01A

A numerical technique for designing transonic airfoils having a prescribed pressure distribution (the inverse problem) is presented. The method employs the basic features of Jameson's iterative solution for the full potential equation except that inverse boundary conditions and Cartesian coordinates are used. The method is a direct-inverse approach that controls trailing-edge closure. Examples show the application of the method to design aft-cambered and other airfoils specifically for transonic flight.

Author

**N76-20083# Deutsche Forschungs- und Versuchsanstalt fuer
Luft- und Raumfahrt Goettingen (West Germany) Abteilung
Angewandter Mathematik und Mechanik
VISUALIZATION OF THE SUBSONIC FLOW AROUND TWO
SPACE GLIDER CONFIGURATIONS**

Hans Bippes and Pavle Colak-Antic 16 Jul 1975 61 p refs
In GERMAN ENGLISH summary. Original contains color
illustrations. Report will also be announced as translation
(DLR-FB-75-49) Avail NTIS HC \$4 50, DFVLR Cologne
DM 79 90

The subsonic flow around two delta wing space glider configurations with rounded leading edges and fuselage was made visible in a water towing basin by means of the hydrogen bubble technique for different angles of attack and yaw with Re-numbers ranging from 0.03 million to 1.2 million. Special attention was devoted to the observation of the development of the leading edge and body vortices and their interaction on the stabilizer flow to leading edge vortex burst and to flow separation and turbulence generation. The relevant three-dimensional flow phenomena were recorded by stereo photographs and are reproduced in print as anaglyphs (double-color pictures).

Author (ESA)

**N76-20087# European Space Agency Paris (France)
A METHOD FOR THE CALCULATION OF THE TWIST AND
CAMBER OF A WING WITH A SPECIFIED LOAD DISTRIBUTION
IN THE PRESENCE OF A FUSELAGE**

Horst Koerner Dec 1975 76 p refs. Transl into ENGLISH
of Ein Verfahren zur Berechnung der Verwindung u Verwoelbung
des Fluegels bei vorgegebener Lastverteilung unter Beruecksichtigung
des Rumpfes. DFVLR Brunswick Report DLR-FB-75-12
1975. Original German report available from DFVLR Porz West
Ger DM 30 70

(ESA-TT-214 DLR-FB-75-12) Avail NTIS HC \$5 00

A theoretical potential flow method is described which can also be applied to wing-fuselage combinations providing the fuselage is of circular cross-section or has approximately this form. The method is derived for incompressible flow but by using the Goethert transformation it may also be used for compressible subsonic flow. The theory, several sample calculations, the program, and its input requirements are described.

Author (ESA)

**N76-20091# Air Force Aero Propulsion Lab Wright-Patterson
AFB Ohio**

**AN ANALYSIS OF HEAT TRANSFER ON A JOUKOWSKI
AIRFOIL WITH SEPARATION AND REATTACHMENT
Interim Report, 1 Jan 1973 - 1 Mar 1975**

Lucien Louis DeBruge Jul 1975 121 p refs
(AF Proj 3066)

(AD-A016457 AFAPL-TR-75-28) Avail NTIS CSCL 20/4

The problem of separation bubbles in subsonic flow has been the object of much attention because of its incidence on the performance of turbomachinery and airfoils in general. An analytical method depicting a two-dimensional incompressible steady-state flow over the convex side of a Joukowski airfoil on which a large separation bubble has developed is formulated. This method uses a potential flow configuration in cross flow and two equal but opposite vortices at rest behind the cylinder.

The vortex strength generating the flow recirculation inside the bubble and the perturbation of the inviscid velocity distribution outside the separation bubble are so chosen that the calculated separation in cross flow occurs at a Reynolds number of 100 000. The average heat transfer coefficient obtained is compared with predicted values of flow separation over a cavity. GRA

**N76-20093# Army Aviation Systems Command St Louis Mo
AIRFOIL PROFILE DRAG Final Report**

Milton A Schwartzberg Jun 1975 39 p refs
(DA Proj 1F2-62209-AH-76)

(AD-A017321 USAAVSCOM-TR-75-19) Avail NTIS CSCL 20/4

A method is presented for the estimation of the profile drag coefficient of airfoils at subsonic Mach numbers below the drag rise values. The method is applicable to smooth airfoils with fully turbulent boundary layers, at any Reynolds number. The method is simple to apply for rapid estimation purposes and to incorporate into an aircraft performance computation procedure. GRA

**N76-20095# General Motors Corp Indianapolis Ind Detroit
Diesel Allison Div**

**RESEARCH ON AEROELASTIC PHENOMENA IN AIRFOIL
CASCADES SUPERSONIC UNSTEADY AERODYNAMIC
PHENOMENA IN A CONTROLLED OSCILLATING CAS-
CADE**

Sanford Fleeter Allen S Novick and Ronald E Riffel Oct
1975 78 p refs

(Contract N00014-72-C-0351 NR Proj 094-369)

(AD-A017203 DDA-EDR-8617) Avail NTIS CSCL 20/4

A unique supersonic inlet flow field unsteady cascade experiment is described wherein the time-dependent pressure distribution within a harmonically oscillating airfoil cascade is quantitatively determined. The torsional frequency of oscillation and the interblade phase angle are precisely controlled by means of on-line digital computers. The dynamic data obtained include the chordwise distribution of the unsteady pressure magnitude and its phase lag as referenced to the airfoil motion. Parameters varied include the cascade inlet Mach number, the interblade phase angle, the torsional axis location, and the reduced frequency. All of the data are correlated with state-of-the-art analytical predictions. Author (GRA)

**N76-20096# Purdue Univ Lafayette Ind Project SQUID
Headquarters**

**UNSTEADY SURFACE FLOW BEHAVIOR ON A CASCADE
OF AIRFOILS OSCILLATING BELOW STALL Technical
Report, Mar - Sep 1975**

Franklin O Carta 29 Sep 1975 76 p refs

(Contract N00014-67-A-0226-0005 NR Proj 098-038)

(AD-A017073 SQUID-TR-UTRC-1-PU R75-912083-3) Avail
NTIS CSCL 20/4

Tests have been performed on a cascade of airfoils oscillating in pitch using hot films to detect unsteady changes in the flow over the suction surface. It was found that unsteady transition from laminar to turbulent flow propagates forward along the chord and that unsteady reattachment propagates rearward. At low incidence angle the turbulent flow region does not reach the leading edge and at higher incidence angle the laminar flow region does not extend rearward beyond mid chord.

Author (GRA)

**N76-20098# Naval Intelligence Support Center Washington,
DC Translation Div**

**THE GROUND EFFECT ON THE AERODYNAMIC CHARAC-
TERISTICS OF AN AIRCRAFT**

Ya M Serebrinski 23 Oct 1975 55 p refs. Transl into
ENGLISH from Uch Zap Tsentr Aerogidrodinamicheskii Inst
(USSR) v 267 1936 p 2-37

(AD-A017309 NISC-Trans-3700) Avail NTIS CSCL 01/1

An analysis of aerodynamic characteristics in steady horizontal flight near the ground is presented. Wieselsberg's formula representing the wing by a vortex sheet is derived and a formula

based on the Helmbold vortex system is proposed A mirror-image experiment conducted in a TsAGI T-5 wind tunnel with a conventional model wing and a wing with TsAP flaps is described Results indicate that experimental data agree with theoretical calculations from the formula based on a Helmbold vortex system for a conventional wing A model of a phenomenon similar to a hydraulic collector system is proposed to explain the phenomena occurring in the wing with flaps Results of longitudinal stability are also given Other methods of investigating steady horizontal flight near the ground are briefly reviewed Author

N76-20101*# National Aeronautics and Space Administration Ames Research Center, Moffett Field, Calif

A STUDY OF THE FINANCIAL HISTORY OF THE US SCHEDULED AIRLINES AND THE IMPROVEMENT OF AIRLINE PROFITABILITY THROUGH TECHNOLOGY

Darrell E Wilcox Jul 1975 64 p refs (NASA-TM-X-73109, A-6462) Avail NTIS HC \$4 50 CSCL 05C

The financial history of the US scheduled airline industry was investigated to determine the causes of the erratic profit performance of the industry and to evaluate potential economic gains from technology advances of recent years Operational and economic factors affecting past and future profitability of the industry are discussed, although no attempt was made to examine the profitability of individual carriers The results of the study indicate that the profit erosion of the late 1960s and early 1970s was due more to excess capacity than to inadequate fare levels but airline problems were severely compounded by the rapid fuel price escalation in 1974 and 1975 Near-term solutions to the airline financial problems depend upon the course of action by the industry and the CAB and the general economic health of the nation For the longer term the only acceptable alternative to continued fare increases is a reduction in unit operating costs through technological advance The next generation of transports is expected to incorporate technologies developed under Government sponsorship in the 1960s and 1970s with significant improvements in fuel consumption and operating costs Author

N76-20104*# Douglas Aircraft Co, Inc, Santa Monica Calif **OPERATIONAL FACTORS OF AIR SERVICE TO SMALL COMMUNITIES Final Report**

Dec 1975 162 p refs (Contract NAS2-8135) (NASA-CR-137820) Avail NTIS HC \$6 75 CSCL 05A

The feasibility of using 30-passenger jet aircraft to service low density, short haul markets was analyzed Aircraft characteristics market potential, and economic factors were among the areas evaluated D M L

N76-20106*# National Aeronautics and Space Administration Washington, D C

GENERAL AVIATION TECHNOLOGY PROGRAM

Mar 1976 20 p (NASA-TM-X-73051 NASA-News-Release-76-51) Avail NASA Scientific and Technical Information Facility P O Box 8757 B W I Airport, Md 21240 CSCL 01C

The research and technology program of the civil air transportation system is reported Research is discussed for stall/spin crashworthiness, pilot operations flight efficiency propulsion, and avionics F O S

N76-20112# AeroVironment Inc Pasadena Calif **INVESTIGATION OF VORTEX WAKE STABILITY NEAR THE GROUND Final Report, 1 Feb 1974 - 31 Mar 1975**

I H Tombach, S C Crow and E R Bate Jr 31 Jul 1975 75 p refs (Contract F44620-74-C-0058 AF Proj 9781) (AD-A017586, AV-FR-538 AFOSR-75-1501TR) Avail NTIS CSCL 20/4

Vortex wakes exist in a complicated environment near the

ground at airports Under many situations factors combine to move a wake sufficiently far from the runway approach corridor that it does not constitute a hazard to following aircraft Situations exist however where a wake can possibly linger at high strength long enough to present operational problems The sinusoidal mutual induction instability of a vortex pair has been investigated theoretically and experimentally in atmospheric conditions which prevail near the ground thereby extending previous work of Crow and Bate for the same instability aloft Two theoretical models were developed -- one for a vortex pair in the constant stress layer of the atmospheric boundary layer and the second for a vortex interacting with its image when in ground effect GRA

N76-20114*# National Aeronautics and Space Administration Langley Research Center Langley Station, Va

MAGNETIC HEADING REFERENCE Patent

Howell D Garner inventor (to NASA) Issued 16 Mar 1976 12 p Filed 11 Dec 1974 Supersedes N75-12947 (13 - 04 p 0382)

(NASA-Case-LAR-11387-1 US-Patent-3 943.763 US-Patent-Appl-SN-531647 US-Patent-Class-75-178R, US-Patent-Class-33-356) Avail US Patent Office CSCL 17G

A magnetometer is used as a magnetic heading reference for a vehicle such as a small aircraft The magnetometer is mounted on a directional dial in the aircraft in the vicinity of the pilot such that it is free to turn with the dial about the yaw axis of the aircraft A circuit is included for generating a signal proportional to the northerly turning error produced in the magnetometer due to the vertical component of the earth's magnetic field This generated signal is then subtracted from the output of the magnetometer to compensate for the northerly turning error Official Gazette of the U S Patent Office

N76-20122# Federal Aviation Administration Washington, D C Aviation Forecast Branch

PROFILES OF SCHEDULED AIR CARRIER OPERATIONS BY STATE LENGTH FEDERAL AVIATION ADMINISTRATION REGIONS TOP 100 US AIRPORTS, 1 NOVEMBER 1974

May 1975 344 p (AD-A016161) Avail NTIS CSCL 01/2

The first section of this report provides data on total scheduled air carrier aircraft operations by trip length by hour of the day for Friday, November 1 1974 for the top 100 airports within the 50 states of the United States and the District of Columbia The second section of the report shows the same information for each of the 11 Federal Aviation Administration regions The FAA regional information is for those airports in the region that are included in the top 100 airports GRA

N76-20124*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

ENERGY AND ECONOMIC TRADE OFFS FOR ADVANCED TECHNOLOGY SUBSONIC AIRCRAFT

Dal V Maddalon and Richard D Wagner 1 Apr 1976 25 p refs (NASA-TM-X-72833) Avail NTIS HC \$3 50 CSCL 01C

Changes in future aircraft technology which conserve energy are studied, along with the effect of these changes on economic performance Among the new technologies considered are laminar-flow control composite materials with and without laminar-flow control and advanced airfoils Aircraft design features studied include high-aspect-ratio wings thickness ratio and range Engine technology is held constant at the JT9D level It is concluded that wing aspect ratios of future aircraft are likely to significantly increase as a result of new technology and the push of higher fuel prices Composite materials may raise aspect ratio to about 11 to 12 and practical laminar flow-control systems may further increase aspect ratio to 14 or more Advanced technology provides significant reductions in aircraft take-off gross weight energy consumption and direct operating cost Author

**N76-20126*# Sikorsky Aircraft, Stratford, Conn
RSRA SIXTH SCALE WIND TUNNEL TEST Final Report,
Mar - Nov 1974**

R Flemming and A Ruddlell 4 Dec 1974 690 p refs
(Contract NAS1-13000)
(NASA-CR-144964 SER-72011) Avail NTIS HC \$16 25 CSCL
01A

The sixth scale model of the Sikorsky/NASA/Army rotor systems research aircraft was tested in an 18-foot section of a large subsonic wind tunnel for the purpose of obtaining basic data in the areas of performance stability and body surface loads. The model was mounted in the tunnel on the struts arranged in tandem. Basic testing was limited to forward flight with angles of yaw from -20 to +20 degrees and angles of attack from -20 to +25 degrees. Tunnel test speeds were varied up to 172 knots ($q = 96$ psf). Test data were monitored through a high speed static data acquisition system linked to a PDP-6 computer. This system provided immediate records of angle of attack, angle of yaw, six component force and moment data and static and total pressure information. The wind tunnel model was constructed of aluminum structural members with aluminum fiberglass, and wood skins. Tabulated force and moment data, flow visualization photographs, tabulated surface pressure data are presented for the basic helicopter and compound configurations. Limited discussions of the results of the test are included. Author

**N76-20127# Deutsche Forschungs- und Versuchsanstalt fuer
Luft- und Raumfahrt Brunswick (West Germany) Abteilung
Entwurfsaerodynamik**

**THREE COMPONENT MEASUREMENTS ON A LIGHT STOL
AIRCRAFT WITH CHORDWISE BLOWING**

Horst Koerner and Reinhard Loehr (A Piller KG, Osterode, West Ger) 7 Nov 1975 23 p refs In GERMAN ENGLISH summary. Report will also be announced as translation (DLR-FB-75-74) Avail NTIS HC \$3 50 DFVLR, Cologne DM 10,20

Investigations on a STOL-airplane with internally blown flaps are described. To avoid flow separation on the wing slots were located behind the nose flap and in front of the trailing edge flap. Maximum lift and optimum L/D were investigated as well as the effectiveness of the aileron and the horizontal tail.

Author (ESA)

**N76-20128# European Space Agency Paris (France)
THE DESIGN OF UNSWEPT LARGE ASPECT RATIO WINGS
WITH FLAPS FOR TWO FLIGHT CONDITIONS**

Guenter Redeker Dec 1975 37 p refs Transl into ENGLISH of Auslegung von ungefeilten Tragfluegeln grossen Seitenverhaeltnisses mit Woelbklappen fuer zwei Entwurfspunkte. DFVLR Brunswick Report DLR-FB-75-34 10 Apr 1975. Original German report available from DFVLR Cologne DM 14 80 (ESA-TT-224 DLR-FB-75-34) Avail NTIS HC \$4 00

The method described is carried out by using flaps covering the whole span which have to be deflected in such a way as to obtain a minimum drag. Calculations are done quickly with a computer program for the line lifting theory which incorporates the influence of flaps. The method is explained with the help of an example of an existing sailplane. Author (ESA)

**N76-20129# Ohio State Univ Columbus Dept of Mechanical
Engineering**

**INVESTIGATION OF ACCELERATED LIFE PREDICTION
TECHNIQUES Final Report, 1 Mar, 1974 - 28 Feb 1975**

Jack A Collins and Ben Tarver Hagan Jr Oct 1975 61 p refs
(Contract DAAJ02-74-C-0033 DA Proj 1F2-62203-AH-86)
(AD-A016925 USAAMRD-TR-75-38) Avail NTIS CSCL
01/3

The objectives of the work reported were to define potentially useful failure prediction models for the wear and fretting-wear modes of failure, to define the parameters of primary importance to incorporate the concept of accelerated testing both in the prediction models and in the design of a testing program and to design special testing machines capable of both real-time and accelerated-wear and fretting-wear tests using a UH-1H

helicopter cyclic servo support bearing as the test specimen. This particular component was selected because it was a relatively simple example of an actual component in which both wear and fretting-wear failure modes had been regularly observed in the field. GRA

**N76-20130# Lockheed-California Co Burbank
INCREASED ROTOR BLADE SURVIVABILITY Final Report,
1 Jul 1973 - 1 Jul 1975**

C F Griffin Aug 1975 88 p refs
(Contract DAAJ02-73-C-0101 DA Proj 1F1-63208-DB-52)
(AD-A016929 LR-26700 USAAMRD-TR-75-6) Avail NTIS
CSCL 01/3

Reported are results of a program to investigate the feasibility of using composite geodesic structure for the blade spar to increase survivability of helicopter main rotor blades. The design investigated consists of a geodesic truss structure spare of elliptical cross section comprised of elements forming a redundant grid-work. This spar is covered with a thin composite expendable skin that forms the airfoil contour. Parametric analyses were conducted to determine the effects of geometry and materials on the strength and stiffness of geodesic structures. Subscale sections of the graphite/epoxy geodesic main rotor blade box spar were fabricated and tested. A graphite/epoxy geodesic helicopter main rotor blade preliminary design was completed, and four full-scale segments of this blade were fabricated and subjected to structural and ballistic tests. GRA

**N76-20131# Army Air Mobility Research and Development
Lab Fort Eustis Va
FLIGHT TEST OF THE AEROSPATIALE SA-342 HELICOP-
TER**

Duane R Simon and Jimmie C Savage Aug 1975 74 p
(AD-A016921 USAAMRD-TR-75-44) Avail NTIS CSCL
01/3

The Eustis Directorate of the U S Army Air Mobility Research and Development Laboratory conducted an evaluation of the Aerospatiale Model SA-342 during November 1974. A total of 10 hours 20 minutes of flight time was accumulated during give test flights. Performance, stability and control tests were performed to evaluate the increased capabilities of the SA-342 over the SA-341 upon which the design of the SA-342 is based. Both helicopters have fan-in-fin type antitorque control. The SA-342's handling qualities were generally very good and it exhibited improved lateral-directional stability over the SA-341. However, trimming the aircraft directionally within the sideslip deadband was still difficult. The improved fan provided sufficient control moment to attain 50 knots in sideward flight. It is recommended that additional effort be expended to explore and resolve problems with the fan-in-fin design experimentally both by Aerospatiale and by Sikorsky Aircraft. GRA

**N76-20134# Air Force Systems Command Wright-Patterson
AFB Ohio Foreign Technology Div
COCKPIT SYSTEMS STUDY YAK 40 RATING OF COCKPIT
FACILITIES, FLIGHT AND SYSTEMS PROPERTIES OF THE
AIRCRAFT BY PILOTS**

K Steininger and G Neumann 25 Jun 1975 64 p refs
Transl into ENGLISH from Deut Luft Raumfahrt Forschungsber (Munich), v 75 no 15 1975 p 1-70
(AD-A017198, FTD-ID(RS)1-1265-75) Avail NTIS CSCL
01/2

An assessment by a representative sample of pilots employed by an airline to operate the Russian short haul jet transport plane YAK 40 is made of several features. Acceptability of the cockpit layout and instrumentation, handling qualities, feasibility of the systems with regard to the pilot's workload. GRA

**N76-20135# ARO Inc Arnold Air Force Station Tenn
EFFECT OF THE GBU-15 (CRUCIFORM WING) AND GBU-15
(PLANAR WING) STORES ON THE AERODYNAMIC
CHARACTERISTICS OF THE F-4C AIRCRAFT Final
Report**

Eddie S Washington AEDC Sponsored by the AF Nov 1975 69 p refs (AF Proj 2567)

(AD-A017378 ARO-PWT-TR-75-121 AEDC-TR-75-116 AFATL-TR-75-111) Avail NTIS CSCL 01/3

A wind tunnel investigation was conducted to assess the effect of carriage of the GBU-15 (cruciform wing) and the GBU-15 (planar wing) stores on the longitudinal stability and drag characteristics of the F-4C aircraft. Data were obtained for 15 external store loading configurations for angles of attack ranging from -4 to 20 deg at 0-deg roll angle. All data were obtained at a constant stagnation pressure of 2 500 psia for Mach numbers from 0.6 to 1.1. GRA

N76-20136# Perkin-Elmer Corp Norwalk Conn
DEVELOPMENT OF DEICING TECHNIQUES FOR DIELECTRIC WINDOWS Final Report, Apr 1973 - Apr 1975

Edward A Strouse Aug 1975 143 p refs (Contract F33615-73-C-1080 AF Proj 7371) (AD-A017097, PE-12464 AFML-TR-75-99) Avail NTIS CSCL 01/3

This report covers measurements and techniques that have led to the development of the first prototype windows coated with a continuous thin-film heater transparent in the 8 to 12 micron spectral region. The effort involved the measurement of the complex optical constants of indium-tin-oxide and the dependence of these values on both process parameters and the conductivity of the films. The performance of a full coated window has a transmission greater than 70% and a sheet resistance of 160 ohms/square is described. Also included is a thermo-optical analysis of conductive films and patterns for zinc sulfide, zinc selenide, and zinc sulfo-selenide windows. GRA

N76-20138+ Royal Netherlands Aircraft Factories Fokker Schiphol-Oost

BIBLIOGRAPHY ON AIRCRAFT NOISE

G K Troost Aug 1975 47 p refs (FOK-N-00-28) Avail NTIS HC \$4.00

Published literature concerning pure aerodynamic noise and its attenuation is listed. Noise from the intake and exhaust of the set engine of aircraft propeller noise, detached flow and boundary layer noise, slots and resonant cavities, local vortices and wakes of struts and antennas are considered. Propagation problems such as atmospheric attenuation, ground absorption and various shielding techniques are also discussed. ESA

N76-20146*# Pratt and Whitney Aircraft East Hartford Conn
DESIGN OF A 4 1/2 STAGE TURBINE WITH A STAGE LOADING FACTOR OF 4.66 AND HIGH SPECIFIC WORK OUTPUT Final Report

P F Webster Washington NASA Mar 1976 138 p refs (Contract NAS3-18033) (NASA-CR-2659, PWA-5101) Avail NTIS HC \$6.00 CSCL 21E

The aerodynamic design of a highly loaded multistage fan drive turbine is discussed. Turbine flowpath and airfoil sections are presented along with respective pressure and velocity distributions. Vibrational modes are identified in the expected turbine operating range. Author

N76-20148# Marquardt Corp Van Nuys Calif
LOW COST HYPERMIXING EJECTOR RAMJET PROGRAM Final Report, 15 Jun 1973 - 10 Feb 1975

Joseph G Bendot, Wallace G Harkins and Thomas G Piercy Wright-Patterson AFB Ohio ARL 8 Jun 1975 199 p refs (Contract F33615-73-C-4093, AF Proj 7116) (AD-A016430 MR-S-1322-A ARL-75-0219) Avail NTIS CSCL 21/5

The Air Force Aerospace Research Laboratories (ARL) recently made a technology breakthrough in the field of turbulent mixing. ARL experiments indicated that the spreading rate of a subsonic jet may be increased dramatically by the introduction of streamwise vortices in the flow. These vortices promote efficient turbulent mixing within an extremely short distance, i.e. hypermixing. The

basic objective of this program was to assess the payoff if any of applying hypermixing ejector technology to the design of a low cost ejector ramjet engine. Three variations of the ejector ramjet engine cycle were evaluated at the engine design point of Mach 0.75 at 20 000 feet altitude. The fuel addition-mix/diffuse/burn cycle variation was clearly superior. The selected fuel was UDMH. Engine performance was estimated for the specified flight envelope. Mo equals 0.70 to 1.20 and sea level to 30 000 feet altitude. An annular ring ejector which incorporated hypermixing technology was designed, fabricated and experimentally evaluated. Test results showed no improvement with the hypermixing ejector as compared to a conventional annular ejector. The test ejector was then modified. A second test series showed this modification to be very effective. Full mixing (maximum mixer total pressure) was achieved in one half the length required for the annular/initial hypermixing ejector. At the ejector design point, full mixing was accomplished in 1.7 duct diameters. GRA

N76-20151*# Systems Technology Inc Hawthorne Calif
MANUAL AND AUTOMATIC FLIGHT CONTROL DURING SEVERE TURBULENCE PENETRATION Final Report

Donald E Johnston, Richard H Klein and Roger H Hoh Washington NASA Apr 1976 110 p refs (Contract NASw-2624) (NASA-CR-2677 TR-1049-1) Avail NTIS HC \$5.50 CSCL 01C

An analytical and experimental investigation of possible contributing factors in jet aircraft turbulence upsets was conducted. Major contributing factors identified included autopilot and display deficiencies, the large aircraft inertia and associated long response time, and excessive pilot workload. An integrated flight and thrust energy management director system was synthesized. The system was incorporated in a moving-base simulation and evaluated using highly experienced airline pilots. The evaluation included comparison of pilot workload and flight performance during severe turbulence penetration utilizing four control/display concepts: manual control with conventional full panel display, conventional autopilot (A/P-A) with conventional full panel display, improved autopilot (A/P-B) with conventional full panel display plus thrust director display, and longitudinal flight director with conventional full panel display plus thrust director display. Simulation results show improved performance, reduced pilot workload, and a pilot preference for the autopilot system controlling to the flight director command and manual control of thrust following the trim thrust director. Author

N76-20152# European Space Agency Paris (France)
MEASUREMENTS OF THE VERTICAL MOVEMENTS OF AN AIRCRAFT

Heinz Winter et al Dec 1975 80 p refs. Transl into ENGLISH of Messung der Vertikalbewegungen eines Flugzeugs DFVLR, Brunswick Report DLR-FB-75-41 5 May 1975. Original German report available from DFVLR, Cologne DM 28.00 (ESA-TT-215 DLR-FB-75-41) Avail NTIS HC \$5.00

The measuring accuracy for aircraft altitude and vertical velocity, which can be obtained by combining the information of the vertical channel of an inertial navigation system of a barometric altimeter and of a tracking radar in a Kalman filter, was analyzed. Results are based on a flight test with the HFB 320 aircraft. Author (ESA)

N76-20153# Naval Postgraduate School Monterey Calif
A COMPARISON OF OPTIMAL CONTROL THEORY PREDICTIONS WITH ACTUAL PILOT PERFORMANCE IN A HELICOPTER LONGITUDINAL TRACKING TASK M S Thesis

Luther William Wheat Jun 1975 44 p refs (AD-A016441) Avail NTIS CSCL 01/3

A fixed base helicopter simulation was implemented which may be easily altered to represent a variety of conventional single rotor aircraft. Test subjects performed 90-second tracking tasks utilizing two cockpit displays for longitudinal control during landing approach. The performance data generated were compared with predicted values from an optimal pilot modeling technique. Tentative conclusions were drawn as to the effectiveness of each display as well as the predictive power of the pilot model. GRA

N76-20154# Honeywell Inc Minneapolis Minn Government and Aeronautical Products Div
ROLL-AXIS HYDROFLUIDIC STABILITY AUGMENTATION SYSTEM DEVELOPMENT Final Report, 29 Mar 1973 - 30 Sep 1974

Darroll Bengtson Thomas Dickovich, and Robert Helfenstine Sep 1975 137 p
 (Contract DAAJ02-73-C-0056, DA Proj 1F1-62204-AA-44)
 (AD-A016932 GAPD-W0528-FR USAAMRD L-TR-75-43)
 Avail NTIS CSCL 01/3

The objective of this program was to develop, design, and flight test a roll-axis Hydrofluidic Stability Augmentation System (HYSAS) for the OH-58A helicopter The system when used with a yaw HYSAS provides increased vehicle damping which improves the handling characteristics Flight test evaluations were performed with satisfactory results GRA

N76-20156# National Research Council of Canada, Ottawa (Ontario)
[MECHANICAL ENGINEERING AND AERONAUTICAL RESEARCH PROJECTS] Quarterly Bulletin, 1 Oct - 31 Dec 1975

31 Dec 1975 90 p refs
 (DME/NAE-1975(4) ISSN-0047-9055) Avail NTIS HC \$5 00

Lift fan noise reduction and a Canadian playback and flight recording center for aircraft accident and/or incident investigations are summarized

N76-20169# Air Force Flight Dynamics Lab Wright Patterson AFB Ohio

FEASIBILITY DETERMINATION OF A DYNAMIC TAXI FACILITY FOR EVALUATING MILITARY LANDING GEAR SYSTEMS Final Report, May - Dec 1973

Howard T Anderle and Joseph G Mercer Jul 1975 103 p refs
 (AF Proj 1369)
 (AD-A017038 AFFDL-TR-74-111) Avail NTIS CSCL 01/3

A feasibility study of using a hydraulic vibration machine in conjunction with a drop tower to evaluate ride quality characteristics of a landing gear was made For sinusoidal inputs over a frequency-double amplitude range of 1.5 Hz and 0.6 to 1.0 inches amplitude-ratio frequency response of the drop jig was measured This was done while varying strut pneumatic stiffness and strut friction This work definitely shows feasibility of a laboratory experimental setup to test ride quality effectiveness of a landing gear GRA

N76-20232# Southwest Research Inst San Antonio Tex
DESIGN OF A TEST MACHINE FOR BIAXIAL TESTING OF COMPOSITE-LAMINATE CYLINDERS Final Report, May 1974 - Apr 1975

U S Lindholm A Nagy L M Yeakley and W L Ko Wright-Patterson AFB, Ohio AFFDL Jul 1975 82 p refs
 (Contract F33616-74-C-0043 AF Proj 1467)
 (AD-A016961 AFFDL-TR-75-83) Avail NTIS CSCL 14/2

A design is presented for a facility to test composite laminate tubes under generalized plane stress loading conditions The system is designed around multiple closed-loop servo-controlled hydraulic load actuators to provide independent programmable axial, circumferential and torsional stress to tubular specimens The unique feature of the design is an actively controlled hydraulic, collet-type grip The grip is designed to provide radial displacement of the collet to compensate for deformation in the specimen during loading This radial compensation is shown to significantly reduce the grip induced constraint stresses which previously have been a serious problem in the testing of composite tubes GRA

N76-20301# Transportation Systems Center Cambridge Mass
AIRCRAFT L-BAND BALLOON SIMULATED SATELLITE EXPERIMENTS VOLUME 1 EXPERIMENT DESCRIPTION AND DATA MODEM TEST RESULTS Final Report, Sep 1971 - Nov 1973

Peter D Engels and Robert A Wilson Oct 1975 140 p refs
 (AD-A017090 DOT-TSC-FAA-74-24-Vol-1
 FAA-RD-75-174-Vol-1) Avail NTIS HC \$6 00 CSCL 17/2

The result of an experiment intended to evaluate candidate voice and data modulation systems for use in an L-Band Air Traffic Control System was described The experiment was designed to evaluate performance in the presence of oceanic multipath using a high altitude balloon carrying an L-Band transponder as a geostationary satellite simulator The voice modems chosen were Delta Modulation Pulse Duration Modulation and Adaptive Narrow-Band Frequency Modulation The data modems used employed PSK modulation with coherent demodulation Author

N76-20339# Michigan Univ Ann Arbor Radiation Lab
A STUDY OF AXIAL SLOT ARRAYS ON A CIRCULAR CYLINDER FOR USE ON ELECTRICALLY SMALL VEHICLES Final Report, 15 Sep 1974 - 30 Jun 1975

Dipak L Sengupta and Joseph E Ferris Sep 1975 67 p refs

(Contract F19628-75-C-0036 AF Proj 5635)
 (AD-A016564 UMICH-013367-1-f, AFCLR-TR-75-0466) Avail NTIS CSCL 09/5

Radiation patterns produced by arrays of axial slots on a conducting cylinder are studied theoretically and experimentally to develop directive antenna systems for use on electrically small aircraft or missiles The design of the array is mainly governed by the considerations of required field discriminations between various directions A method has been developed for the design of a reduced-height waveguide cavity-backed slot which can be used as an individual radiating element of the array Impedance and radiating properties of the slot element are studied and discussed GRA

N76-20360# Army Electronics Command Fort Monmouth NJ
ROTOR BLADE EFFECTS ON L-BAND SIGNALS RECEIVED BY HELICOPTER ANTENNAS MOUNTED ABOVE THE ROTOR BLADE (CW) EXPERIMENTS Final Experimental Report for 1974

C M DeSantis and F Schwering Oct 1975 118 p
 (DA Proj 1T1-61102-B-31A)
 (AD-A016866 ECOM-4357) Avail NTIS CSCL 09/5

Rotor effects on L-Band signals received by helicopter antennas have been examined experimentally CW data for two receiving-antenna locations above the rotor blade viz at the turning axis of the blade and on the tail, is presented This data shows the amplitude and phase variations to be expected as a function of the direction of the incident signal The effects of counterpoise size and height above the main rotor are also studied In general it is shown that the signal variations were typically < plus or minus 3 db for polar angles of arrival $\theta < 90$ deg but that for greater angles the signal amplitude changes by as much as plus or minus 7 db For $\theta = 90$ deg (an arrival angle obtained for instance during a turning and banking maneuver) signal levels can decrease by minus 15 db and the phase variation can exceed 180 deg The tail location appears to be a better choice for the antenna than the center location A worst-case analysis of CW rotor effects is presented in Appendix I Appendices II and III contain some of the data measured at both antenna locations and should be referred to for a better understanding of the signal variations involved

Author (GRA)

N76-20386# Aerospace Corp, El Segundo Calif Lab Operations

FLIGHT TEST EVALUATION OF A 240 TO 400 MHz CAVITY-BACKED CROSS OPEN-SLEEVE DIPOLE ANTENNA Test Report

Lowell R Nawman and Howard E King 10 Oct 1975 34 p refs
(Contract F04701-75-C-0076)
(AD-A017298 TR-0076(6401)-1 SAMSO-TR-75-241) Avail
NTIS CSCL 09/5

The gain and radiation patterns of a cavity-backed open-sleeve cross dipole antenna mounted on a C135-type aircraft were measured via a satellite-to-aircraft link at 249.1 MHz. The antenna was designed for operation over the 240 to 400 MHz frequency band and has maximum dimensions of 21.5 in square by 6 in deep. For the purposes of the aircraft flight tests, the antenna was externally mounted to the fuselage and covered with a radome. The gain and radiation patterns of the antenna measured in the antenna range with the cavity mounted on a 9.5-ft by 9.5-ft cylindrically curved ground plane are also shown for comparison. GRA

N76-20387# Aerospace Corp El Segundo Calif Lab Operations

CHARACTERISTICS OF A 240 TO 400 MHz 6-INCH DEPTH CAVITY-BACKED CROSS OPEN-SLEEVE DIPOLE ANTENNA ON A CURVED GROUND PLANE Final Report, Dec 1973 - May 1974

H E King J L Wong and C E Ermatinger 31 Oct 1975 31 p refs
(Contract F04701-75-C-0076)
(AD-A017367 TR-0076(6401)-2 SAMSO-TR-75-224) Avail
NTIS CSCL 09/5

An open-sleeve cross dipole antenna contained within a 21.5 in square x 6 in deep cavity is described for operation in the 240 to 400 MHz band. The antenna was developed for an aircraft flight test evaluation using a satellite-to-air communication link. For the purposes of these flight tests on a KC-135 aircraft the antenna was externally mounted to the fuselage and covered with a radome. Measured VSWR radiation patterns and gain with the antenna mounted on a 9.5 ft x 9.5 ft cylindrically curved ground plane are shown. GRA

N76-20455# Air Force Aero Propulsion Lab Wright-Patterson AFB Ohio

TESTING A FLUIDIC TEMPERATURE SENSOR ON A SUBSCALE RAMJET ENGINE COMBUSTION CHAMBER Technical Report, Sep - Dec 1973

John T Hojnacki Jun 1975 135 p refs
(AF Proj 3012)

(AD-A016455 AFAPL-TR-75-1) Avail NTIS CSCL 13/7

Data obtained from 26 tests that used three fluidic temperature sensors to measure gas temperatures in a subscale ramjet engine combustion chamber are presented. The test variables for the combustion chamber were chamber pressure and chamber temperature. Tests were conducted using nominal chamber pressures of 35 and 70 psia and chamber total temperatures of 2500 R, 3000 R and 3800 R. One of the sensors used various insulator materials which were magnesium oxide, Hastelloy X and zirconium oxide. These materials varied the conduction heat losses from the sensor body to the outer case. The mass flow through a sensor was increased by a factor of three to see if improvements could be made in reducing steady state error or increasing thermal response. Lastly one test was conducted using an ablative lined combustion chamber that provided a long duration run. GRA

N76-20545# Naval Intelligence Support Center Washington DC

CALCULATION OF THE REINFORCED THIN-WALLED STRUCTURES BY THE METHOD OF FINITE ELEMENTS

Yu I Ivanov 30 Sep 1975 15 p Transl into ENGLISH from Tsentralnyi Aerogidrodinamicheskii Inst Uchenye Zapiski (USSR) v 3 no 1 1972 p 51-60

(AD-A016387 NISC-Trans-3692) Avail NTIS CSCL 13/13

One variant of the finite element method is presented as applicable for calculations of the reinforced thin-walled structures (flat and curved panels, wings and empennage) of different schemes

(fuselage sections). The applicability of the method coupled with a computer programming is illustrated by several actual calculations. Theoretical results are compared with experimental data. GRA

N76-20695# Committee on Science and Technology (U S House)

AIRCRAFT NOISE ABATEMENT

Washington GPO 1975 300 p refs Hearings before Subcomm on Aviation and Transportation R and D of Comm on Sci and Technol 94th Congr, 1st sess No 38 29 Sep 1-2 Oct 1975

(GPO-62-786) Avail Subcomm on Aviation and Transportation R and D

Developments in aircraft noise abatement technology are assessed. Topics discussed include control and identification of aircraft noise sources, the noise path between the aircraft and the observer on the ground, and identification of community noise exposure and psychoacoustic responses. Emphasis is placed on development of future research and development programs dealing with noise abatement technology. J M S

N76-20940*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

PREDICTION OF LIGHT AIRCRAFT INTERIOR NOISE

James T Howlett and David A Morales Apr 1976 21 p refs

(NASA-TM-X-72838) Avail NTIS HC \$3.50 CSCL 20A

A computerized interior noise prediction method for light aircraft is described. An existing analytical program development for commercial jets forms the basis of some modal analysis work which is described. The accuracy of this modal analysis technique for predicting low-frequency coupled acoustic-structural natural frequencies is discussed along with trends indicating the effects of varying parameters such as fuselage length and diameter, structural stiffness, and interior acoustic absorption. Author

N76-20941*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

A COMPARISON OF MATRIX METHODS FOR CALCULATING EIGENVALUES IN ACOUSTICALLY LINED DUCTS

Willie Watson and Donald L Lansing Washington Mar 1976 47 p refs

(NASA-TN-D-8186 L-10607) Avail NTIS HC \$4.00 CSCL 20A

Three approximate methods - finite differences, weighted residuals, and finite elements - were used to solve the eigenvalue problem which arises in finding the acoustic modes and propagation constants in an absorptively lined two-dimensional duct without airflow. The matrix equations derived for each of these methods were solved for the eigenvalues corresponding to various values of wall impedance. Two matrix orders, 20 x 20 and 40 x 40, were used. The cases considered included values of wall admittance for which exact eigenvalues were known and for which several nearly equal roots were present. Ten of the lower order eigenvalues obtained from the three approximate methods were compared with solutions calculated from the exact characteristic equation in order to make an assessment of the relative accuracy and reliability of the three methods. The best results were given by the finite element method using a cubic polynomial. Excellent accuracy was consistently obtained even for nearly equal eigenvalues by using a 20 x 20 order matrix. Author

N76-20942# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt Berlin (West Germany) Inst fuer Turbulenzforschung

THE AMPLIFICATION OF BROADBAND JET NOISE BY PURE TONE EXCITATION

Dietrich Bechert and Eberhard Pfizenmaier 6 Nov 1975 25 p refs In GERMAN ENGLISH summary Report will also be announced as translation

(DLR-FB-75-72) Avail NTIS HC \$3.50 DFVLR Cologne DM 10.40

It was found experimentally that broad band jet noise can be amplified as much as 6 to 7 dB. The jet noise amplification

effect takes place at sound pressure levels present in real aircraft engines. The experimental investigation was restricted to a cold jet at high subsonic Mach numbers excited by a plane sound wave coming from inside the nozzle. Based on a simplified mathematical model an attenuator was developed which reduces the jet noise amplification significantly. Author (ESA)

N76-21017# Air Force Inst of Tech Wright-Patterson AFB Ohio School of Systems and Logistics
THE IDENTIFICATION OF A PRECEDENCE NETWORK ASSOCIATED WITH BASE LEVEL AIRCRAFT MAINTENANCE M S Thesis
 Clark D Hubbard and Charles R Lindke Aug 1975 157 p refs
 (AD-A016389 SLSR-12-75B) Avail NTIS CSCL 15/5

The objective of this study was to develop a method of identifying precedence networks associated with aircraft maintenance that is more efficient than totally relying on the memory and experience of mechanics in the field. A precedence network is the sequence in which tasks should be performed because of their interdependencies. An example of this type of dependency would be the necessity to repair a fuel cell before refueling an aircraft. This research involved the use of the Logistic Composite Model (L-COM) developed by Headquarters Air Force Logistics Command and the Rand Corporation the F-4E data base which had been constructed as part of Headquarters Tactical Air Command's L-COM Study and Maintenance Data Collection System records for F-4E aircraft. GRA

N76-21024# General Dynamics/Convair San Diego Calif
WEAPON SYSTEM COSTING METHODOLOGY FOR AIRCRAFT AIRFRAMES AND BASIC STRUCTURES VOLUME 2 ESTIMATING HANDBOOK AND USER'S MANUAL, PART 1 Final Report, Jul 1972 - Feb 1975
 R E Kenyon May 1975 184 p
 (Contract F33615-72-C-2083 AF Proj 1368)
 (AD-A016409 AFFDL-TR-75-44-Vol-2-Pt-1) Avail NTIS CSCL 01/3

This volume provides a detailed description of the function and use of two weapon system costing methodologies for aircraft airframes and basic structures developed for the Air Force Flight Dynamics Laboratory for use in conceptual and preliminary design phases of weapon system development. The methods are a trade study costing method for detailed cost analysis of trades-off between weight cost type of construction and type of material and a system costing method for determining the projected cost of a complete airframe within the context of a weapon system development. This volume describes how to make an estimate using either technique and shows the results of a demonstration case. Tradeoff capability has been provided for a range of alternative structure and material combinations. A technique for independent assessing complexity factor has been developed and demonstrated. Manufacturing costs are separately estimated for the primary elements of substructure ribs spars covers leading edges trailing edges tips etc. The trade study method provides an iterative capability stemming from a direct interface with design synthesis programs. A detailed cost data base and system for data expansion are provided. The methods are designed for ease in changing cost estimating relationships and estimating coefficients resulting from cost data update. Author (GRA)

N76-21152 Engineering Sciences Data Unit London (England)
CRITICAL PRESSURE COEFFICIENT AND COMPONENT OF LOCAL MACH NUMBER NORMAL TO THE SURFACE ISOBAR FOR A SWEEP WING
 Oct 1975 6 p
 (ESDU-75027) For information on availability of series sub-series and other individual data items, write, NTIS Attn ESDU, Springfield Va 22161 HC \$74 50

In the analysis of measured pressure distribution data on a swept wing at high speeds it is often required to establish those areas over which supercritical flow exists to interpret the flow in terms of local Mach number (particularly the maximum value) and to identify the location and strength at the wing surface of

any shock waves that might occur in the flow. These features are governed by the distribution over the wing surface to the component of local Mach number normal to the isobars. The report provides a means of estimating the component of local Mach number normal to the surface isobar and the critical pressure coefficient for a swept wing. The method is based on simple-sweep theory and would therefore be expected to apply to wings of moderate to high aspect ratio and low taper. ESDU

N76-21153 Engineering Sciences Data Unit, London (England)
DRAG DUE TO GROOVES IN A FLAT PLATE WITH TURBULENT BOUNDARY LAYER, AT SUBSONIC AND SUPERSONIC SPEEDS
 Nov 1975 13 p
 (ESDU-75028) For information on availability of series sub-series and other individual data items write NTIS Attn ESDU Springfield Va 22161 HC \$122 50

Item No 75028 is the third in the series of items concerning excrescence drag estimation. It provides a method for estimating incremental drag coefficients due to grooves in a flat plate with a turbulent boundary layer at subsonic (M less than or equal to 0.8) and supersonic (M greater than or equal to 1.4) speeds. Grooves normal, streamwise and oblique to the flow are catered for, although the data for other than normal grooves are somewhat tentative, being based on very limited experimental data for low-speed flow only. In the design of an aircraft the item will be found useful in assessing the drag penalty due to gaps around say access hatch doors and at the skin butt joint between two wing on fuselage panels. ESDU

N76-21158*# Cincinnati Univ Ohio Dept of Aerospace Engineering
DYNAMICS AND IDENTIFICATION OF FLEXIBLE AIRCRAFT
 William R Wells Washington NASA Apr 1976 68 p refs
 (Grant NGR-36-004-061)
 (NASA-CR-2672) Avail NTIS HC \$4 50 CSCL 01C

The equations of motion and a maximum likelihood parameter identification formulation are developed for a flexible aircraft. The various levels of approximation associated with the modal substitution representation of the elastic displacement field are discussed and illustrated when appropriate. The necessary extension of the parameter set of stability and control derivatives due to the aeroelastic effects is obtained. Author

N76-21159*# Rockwell International Corp Los Angeles Calif Aircraft Div
SMALL SCALE NOISE AND WIND TUNNEL TESTS OF UPPER SURFACE BLOWING NOZZLE FLAP CONCEPTS VOLUME 1 AERODYNAMIC TEST RESULTS
 Dirk J Renselaer Roy S Nishida and Clayton A Wilkin Dec 1975 143 p refs
 (Contract NAS2-8607)
 (NASA-CR-137747) Avail NTIS HC \$6 00 CSCL 01A

The results and analyses of aerodynamic and acoustic studies conducted on the small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts are presented. Various types of nozzle flap concepts were tested. These are an upper surface blowing concept with a multiple slot arrangement with seven slots (seven slotted nozzle) an upper surface blowing type with a large nozzle exit at approximately mid-chord location in conjunction with a powered trailing edge flap with multiple slots (split flow or partially slotted nozzle). In addition aerodynamic tests were continued on a similar multi-slotted nozzle flap but with 14 slots. All three types of nozzle flap concepts tested appear to be about equal in overall aerodynamic performance but with the split flow nozzle somewhat better than the other two nozzle flaps in the landing approach mode. All nozzle flaps can be deflected to a large angle to increase drag without significant loss in lift. The nozzle flap concepts appear to be viable aerodynamic drag modulation devices for landing. Author

N76-21160*# Rockwell International Corp Los Angeles Calif
SMALL SCALE NOISE AND WIND TUNNEL TESTS OF UPPER SURFACE BLOWING NOZZLE FLAP CONCEPTS VOLUME 2 ACOUSTIC TEST RESULTS

Yoram Kadman Jan 1976 100 p refs Prepared by Bolt Beranek and Newman Inc Cambridge Mass (Contract NAS2-8607) (NASA-CR-137748 BBN-3130) Avail NTIS HC \$5 00 CSCL 01A

Results are summarized of acoustic tests on two advanced concepts of upper-surface-blowing propulsive lift devices Author

N76-21161*# National Aeronautics and Space Administration Langley Research Center Langley Station Va
VORTEX MANEUVER LIFT FOR SUPER-CRUISE CONFIGURATIONS

James F Campbell, Blair B Gloss and John E Lamar Feb 1976 26 p refs (NASA-TM-X-72836) Avail NTIS HC \$4 00 CSCL 01A

Some of the theoretical and experimental research conducted at the NASA Langley Research Center is presented to investigate the subsonic vortex-lift producing capabilities for two classes of Super-Cruise designs a close-coupled wing-canard arrangement and a slender wing configuration In addition several analytical methods are discussed for estimating critical structural design loads for thin highly swept wings having separated leading-edge vortex flows Author

N76-21162*# National Aeronautics and Space Administration Ames Research Center Moffett Field Calif
STABILITY OF ELASTIC BENDING AND TORSION OF UNIFORM CANTILEVER ROTOR BLADES IN HOVER WITH VARIABLE STRUCTURAL COUPLING

Dewey H O'Ormiston Hodges Robert A Washington Apr 1976 77 p refs Prepared jointly with Army Air Mobility Res and Dev Lab (NASA-TN-D-8192 A-6375) Avail NTIS HC \$5 00 CSCL 01C

The stability of elastic flap bending lead-lag bending and torsion of uniform untwisted cantilever rotor blades without chordwise offsets between the elastic mass tension and aerodynamic center axes is investigated for the hovering flight condition The equations of motion are obtained by simplifying the general nonlinear partial differential equations of motion of an elastic rotating cantilever blade The equations are adapted for a linearized stability analysis in the hovering flight condition by prescribing aerodynamic forces applying Galerkin's method and linearizing the resulting ordinary differential equations about the equilibrium operating condition The aerodynamic forces are obtained from strip theory based on a quasi-steady approximation of two-dimensional unsteady airfoil theory Six coupled mode shapes calculated from free vibration about the equilibrium operating condition are used in the linearized stability analysis The study emphasizes the effects of two types of structural coupling that strongly influence the stability of hingeless rotor blades The first structural coupling is the linear coupling between flap and lead-lag bending of the rotor blade The second structural coupling is a nonlinear coupling between flap bending lead-lag bending, and torsion deflections Results are obtained for a wide variety of hingeless rotor configurations and operating conditions in order to provide a reasonably complete picture of hingeless rotor blade stability characteristics Author

N76-21163# Advisory Group for Aerospace Research and Development Paris (France)

TECHNICAL EVALUATION REPORT OF AGARD SPECIALISTS MEETING ON WINGWITH-STORES FLUTTER

Walter J Mykytow (AFFDL) Feb 1976 13 p refs Meeting held at Munich 9 oct 1974 during 39th Meeting of Struct and Mater Panel (AGARD-AR-96 ISBN-92-835-1209-X) Avail NTIS HC \$3 50

The carriage of stores on wings significantly changes their dynamic characteristics and often adversely affects their flutter properties as a result of reduced wing frequencies and the introduction of critical frequency ratios together with inertia elastic and aerodynamic coupling between loads Adverse flutter characteristics and significantly lowered flutter speeds occur and these restrictions severely constrain the speed -- altitude performance envelope that can be achieved by an aircraft The

variety of stores that can be carried on modern tactical airplanes generates a need to accurately evaluate the literally thousands of possible store combinations which can be carried by such aircraft Results are presented from a conference on information and procedures in use in the various NATO nations to solve the flutter problems associated with the carriage of external stores on wings Nine presentations were given and are summarized Recommendations concerning possible future efforts on the subject are given Author

N76-21164*# Virginia Polytechnic Inst and State Univ Blacksburg Dept of Aerospace and Ocean Engineering
FLUTTER OF ASYMMETRICALLY SWEEPED WINGS

Terrence A Weisshaar and J B Crittenden 12 Mar 1976 32 p refs Backup document for AIAA Synoptic scheduled for publication in AIAA Journal in Aug 1976 (Grant NsG-2016) (NASA-CR-146815) Avail NTIS HC \$4 00 CSCL 01A

Two formulations of the oblique wing flutter problem are presented one formulation allows only simple wing bending deformations and rigid body roll as degrees of freedom while the second formulation includes a more complex bending-torsional deformation together with the roll freedom Flutter is found to occur in two basic modes The first mode is associated with wing bending-aircraft roll coupling and occurs at low values of reduced frequency The second instability mode closely resembles a classical bending-torsion wing flutter event This latter mode occurs at much higher reduced frequencies than the first The occurrence of the bending-roll coupling mode is shown to lead to lower flutter speeds while the bending-torsion mode is associated with higher flutter speeds The ratio of the wing mass moment of inertia in roll to the fuselage roll moment of inertia is found to be a major factor in the determination of which of the two instabilities is critical Author

N76-21165# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany) Unternehmensbereich Flugzeuge
COMPUTER PROGRAM FOR CALCULATING PRESSURE DISTRIBUTION AND COEFFICIENTS OF WINGS, BODIES, WING-BODY COMBINATIONS AND WING-TAIL COMBINATIONS IN SUBSONIC, SUPERSONIC AND HYPERSONIC FLOW

Werner Kraus 13 Nov 1973 147 p refs In GERMAN ENGLISH summary (MBB-UFE-1014-O) Avail NTIS HC \$6 00

The program developed by Boeing was set up on an MBB IBM 370 computer for calculations based on potential theory A comparison with measurements shows the usefulness and universal application of the method Written in FORTRAN 4 the program may be used in design work and calculation within the subsonic supersonic and hypersonic speed range ESA

N76-21167# Cranfield Inst of Technology (England) Aerodynamics Div

SUPERSONIC FLOW PAST A SLENDER DELTA WING AN EXPERIMENTAL INVESTIGATION COVERING THE INCIDENCE RANGE MINUS 5 DEG LESS THAN OR EQUAL TO ANGLE OF INCIDENCE LESS THAN OR EQUAL TO 50 DEG

I C Richards Oct 1975 36 p refs Sponsored by Min of Defence (Cranfield-Memo-7512) Avail NTIS HC \$4 00

A detailed survey of a delta wing of 70 deg sweep was performed at 25 m in order to produce a delta wing model which could be tested over a wide range of incidence (from -5 to 50 deg) The development of the flow over the delta wing was studied and the transition region between regimes of attached and separated flow on the lee surface investigated The measurements include upper and lower surface pressure distributions schlieren photographs vapor screen photographs, and surface oil flow visualization Results were compared with thin shock-layer theory and various other predictions

Author (ESA)

N76-21168# Bristol Univ (England) Dept of Aeronautical Engineering

THE PRESSURE DISTRIBUTION OVER THE OGIVE NOSE OF A CYLINDER AT LARGE ANGLES OF INCLINATION TO A UNIFORM STREAM

D J Inker and M Renshaw Jun 1974 188 p refs (BU-173) Avail NTIS HC \$7 50

A wind-tunnel was investigated in regard to the surface pressures on an ogive nose of a circular cylinder at angles of inclination between 40 and 70 deg to a uniform airstream for laminar flow Reynolds numbers of $6 \times 10\,000$ and $1.2 \times 100\,000$. Circumferential distributions of pressure coefficient based on the cross flow dynamic pressure at several axial stations along the nose were calculated for each setting of inclination and Reynolds number. Corresponding axial distributions of out-of-plane and in-plane force coefficients per unit length were calculated from the pressure distributions. The results were interpreted in relation to those predicted by the impulsively-started cross flow analogy for a constant diameter cylinder and it was found that the analogy predicts, qualitatively but not quantitatively, the flow development and axial distribution of forces acting on the inclined body. It was found that the asymmetry of the flow as seen in the pressure distributions, occurred in two distinct forms. Author (ESA)

N76-21169# Bristol Univ (England) Dept of Aeronautical Engineering

AN INVESTIGATION INTO THE EFFECT OF CASTELLATING A BLUNT TRAILING EDGE IN SUPERSONIC FLOW

P R Hosking and D Q Self Jun 1974 38 p refs (BU-175) Avail NTIS HC \$4 00

The possibility of reducing the base drag of the blunt trailing edges on Concorde by a method of castellating the trailing edges was examined. It is concluded that castellations produce a 30% decrease in the base drag but that the same improvement may be achieved from a uniform extension along the whole span of the wing. The investigation was carried out with a value of boundary layer momentum thickness to base height much less than that on Concorde. It is suggested that reductions in base pressures obtained in flight tests are due to effects known to occur with castellations at subsonic velocities rather than any unknown mechanism at supersonic velocities. Author (ESA)

N76-21170# Bristol Univ (England) Dept of Aeronautical Engineering

AN INVESTIGATION INTO THE EFFECTS OF ASPECT RATIO AND CENTRE KEEL CAMBER ON THE AERODYNAMIC CHARACTERISTICS OF CONICAL PARAWINGS

G P Dave and P L R Martin Jun 1974 51 p refs (BU-176) Avail NTIS HC \$4 50

A comparison was made of high and low aspect ratio straight boomed parawings (aspect ratios of 2 and 4) where results similar to those from other investigations were found. The aspect ratio 2 wing produced (L/D) ratios of up to 7 and for the aspect ratio 4 wing after a correction for leading edge boom diameter had been applied (L/D) ratios of over 10 were obtained. Center keel cambers were introduced onto the same two wings. The cambers were such that the spanwise and chordwise slackness ratios of the canopies were the same. Although the maximum values of (L/D) ratios were lower for the cambered wing than the uncambered versions the values of lift coefficient at which they occurred were much higher. There were also large increases in the ranges of incidence for which high (L/D) ratio values were maintained. Using information from previous reports and simple rigid wing theory predictions were made as to the changes in characteristics with changes in aspect ratio and camber. In general the predictions were found to hold the exceptions being due to canopy shape changes. Author (ESA)

N76-21172# Air Force Cambridge Research Labs L G Hanscom Field Mass

INTERACTION OF A BUOYANT TURBULENT PLANAR JET WITH A CO-FLOWING WIND Air Force Surveys in Geophysics

Milton M Klein and Bruce A Kunkel 10 Jul 1975 38 p refs

(AF Proj 7605)

(AD-A018060 AFCRL-TR-75-0368, AFCRL-AFSG-313) Avail NTIS CSCL 01/2

The classic theory of buoyant motion of a free planar heated jet in still air is extended to account for environmental winds from the same direction as the jet that is co-flowing winds. The model is applicable for wind and jet velocities up to 100 m/sec and jet temperatures up to three times the ambient. Calculations are made for initial jet velocities of 5 and 20 m/sec and temperature excesses, relative to ambient temperature, of 0.3 and 1. For light winds relative to the initial jet velocity the vertical velocity and centerline trajectory of the plume rise rapidly with distance from the jet source. This is similar to that found with the classic theory for still air. As the wind speed approaches the initial jet velocity the rise of the jet plume with distance from the source is much more gradual. For all wind speeds the axial jet velocity and temperature decrease rapidly with distance from the jet source, until they become almost constant at short distances downstream. A similarity rule is derived which preserves dynamic similarity in scaling from a given system to another system. For low wind speeds the procedure is close to that based on constant Froude number. Author (GRA)

N76-21173*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

IMPACT DYNAMICS RESEARCH FACILITY FOR FULL-SCALE AIRCRAFT CRASH TESTING

Victor L Jr Vaughan and Emilio Alfaro-Bou Washington Apr 1976 57 p

(NASA-TN-D-8179 L-10514) Avail NTIS HC \$4 50 CSCL 14B

An impact dynamics research facility (IDRF) was developed to crash test full-scale general aviation aircraft under free-flight test conditions. The aircraft are crashed into the impact surface as free bodies. A pendulum swing method is used to obtain desired flight paths and velocities. Flight paths up to -60 deg and aircraft velocities along the flight paths up to about 270 m/s can be obtained with a combination of swing-cable lengths and release heights made available by a large gantry. Seven twin engine 2721-kg aircraft were successfully crash tested at the facility and all systems functioned properly. Acquisition of data from signals generated by accelerometers on board the aircraft and from external and onboard camera coverage was successful in spite of the amount of damage which occurred during each crash. Test parameters at the IDRF are controllable with flight path angles accurate within 8 percent, aircraft velocity accurate within 6 percent, pitch angles accurate to 4.25 deg and roll and yaw angles acceptable under wind velocities up to 4.5 m/s. Author

N76-21175*# National Aeronautics and Space Administration Ames Research Center Moffett Field Calif

CHARACTERISTICS OF WAKE VORTEX GENERATED BY A BOEING 727 JET TRANSPORT DURING TWO-SEGMENT AND NORMAL ILS APPROACH FLIGHT PATHS

R L Kurkowski, M R Barber and L J Garodz Washington Apr 1976 107 p refs

(NASA-TN-D-8222 A-6208) Avail NTIS HC \$5 50 CSCL 01C

A series of flight tests was conducted to evaluate the vortex wake characteristics of a Boeing 727 (B727-200) aircraft during conventional and two-segment ILS approaches. Twelve flights of the B727 which was equipped with smoke generators for vortex marking, were flown and its vortex wake was intentionally encountered by a Lear Jet model 23 (LR-23) and a Piper Twin Comanche (PA-30). Location of the B727 vortex during landing approach was measured using a system of photo-theodolites.

The tests showed that at a given separation distance there were no readily apparent differences in the upsets resulting from deliberate vortex encounters during the two types of approaches. Timed mappings of the position of the landing configuration vortices showed that they tended to descend approximately 91 m (300 ft) below the flight path of the B727. The flaps of the B727 have a dominant effect on the character of the trailed wake vortex. The clean wing produces a strong concentrated vortex but as the flaps are lowered, the vortex system becomes more diffuse. Pilot opinion and roll acceleration data indicate that 4.5 nmi would be a minimum separation distance at which roll control of light aircraft (less than 5,670 kg (12,500 lb) could be maintained during parallel encounters of the B727's landing configuration wake. This minimum separation distance is generally in scale with results determined from previous tests of other aircraft using the small roll control criteria. Author

N76-21178# Naval Aerospace Medical Research Lab., Pensacola Fla

MAJOR ORIENTATION-ERROR ACCIDENTS IN REGULAR ARMY UH-1 AIRCRAFT DURING FISCAL YEAR 1971 (ACCIDENT FACTORS)

W Carroll Hixson and Emil Spezia 7 Jul 1975 32 p refs
Prepared in cooperation with Army Aeromed Res Lab Fort Rucker Ala
(MF51524005)
(AD-A017665 NAMRL-1219 USAARL-76-1) Avail NTIS CSCL 01/2

This report is the fifth in a longitudinal series of reports dealing with the pilot disorientation/vertigo problem in Regular Army UH-1 helicopter operations. Individual case history data extracted from the USAAVS master aircraft accident files are presented on major orientation-error accidents that occurred in UH-1 aircraft during fiscal year 1971. Summary data listings involving a variety of operational and pilot-related accident factors are presented for each of the 31 cases. The listings are arranged to distinguish between those factors and events present before takeoff i.e. the initial conditions associated with a given accident and those which occurred or were manifested during the actual airborne phase of the accident flight. GRA

N76-21188*# Analytical Mechanics Associates, Inc Jericho NY

STUDIES OF AIRCRAFT DIFFERENTIAL MANEUVERING REPORT 75-27 CALCULATING OF DIFFERENTIAL-TURNING BARRIER SURFACES REPORT 75-26 A USER'S GUIDE TO THE AIRCRAFT ENERGY-TURN AND TANDEM-MOTION COMPUTER PROGRAMS REPORT 75-7 A USER'S GUIDE TO THE AIRCRAFT ENERGY-TURN HODOGRAPH PROGRAM, Technical Report, Feb 1975 - Jan 1976

Henry J Kelley and Leon Lefton Feb 1976 58 p refs
(Contract NAS2-8738)
(NASA-CR-137819 Rept-75-27) Avail NTIS HC \$4 50 CSCL 01C

The numerical analysis of composite differential-turn trajectory pairs was studied for fast-evader and neutral-evader attitude dynamics idealization for attack aircraft. Transversality and generalized corner conditions are examined and the joining of trajectory segments discussed. A criterion is given for the screening of tandem-motion trajectory segments. Main focus is upon the computation of barrier surfaces. Fortunately from a computational viewpoint the trajectory pairs defining these surfaces need not be calculated completely the final subarc of multiple-subarc pairs not being required. Some calculations for pairs of example aircraft are presented. A computer program used to perform the calculations is included. Author

N76-21189*# Boeing Commercial Airplane Co Seattle Wash
PHASE 2 PROGRAM ON GROUND TEST OF REFANNED JT8D TURBOFAN ENGINES AND NACELLES FOR THE 727 AIRPLANE VOLUME 3 GROUND TESTS Final Report
Dec 1975 350 p refs
(Contract NAS3-17842)
(NASA-CR-134799 D6-42440-3-Vol-3) Avail NTIS
HC \$10 00 CSCL 01C

The NASA Refan Program included full-scale performance and noise ground tests of both a current production (JT8D-15) and a refanned (JT8D-115) engine. A description of the two ground tests including detailed propulsion, noise and structural test results is presented. The primary objectives of the total test program were comparison of JT8D-15 and JT8D-115 overall propulsion system performance and noise characteristics and determination of incremental component noise levels. Other objectives of the test program included (1) determination of acoustic treatment effectiveness (2) measurement of internal sound pressure levels (3) measurement of inlet and exhaust hardware performance (4) determination of center-engine surge margin and (5) evaluation of certain structural characteristics associated with the 727 refan center-engine inlet duct and JT8D refan engine exhaust system. The JT8D-15 and -115 tests were conducted during September 1974 and January to March 1975 respectively. Analyses of the test data indicated that the JT8D-115 as compared to the JT8D-15, demonstrates a 12.5 percent to 13.2 percent reduction in static specific fuel consumption and a reduction of 6 to 7 PNdB in a weighted average value of static tone corrected perceived noise level. Separated into noise components a significant reduction was shown for the inlet fan, aft fan exhaust duct flow turbine and jet noises. However core noise was increased. Photographs of test stands and test equipment are shown. Author

N76-21190*# Boeing Commercial Airplane Co Seattle Wash
PHASE 2 PROGRAM ON GROUND TEST OF REFANNED JT8D TURBOFAN ENGINES AND NACELLES FOR THE 727 AIRPLANE VOLUME 4 AIRPLANE EVALUATION AND ANALYSIS Final Report
Dec 1975 323 p refs
(Contract NAS3-17842)
(NASA-CR-134800 D6-42440-4-Vol-4) Avail NTIS
HC \$9 75 CSCL 01C

The retrofit of JT8D-109 (refan) engines are evaluated on a 727-200 airplane in terms of airworthiness performance and noise. Design of certifiable hardware manufacture, and ground testing of the essential nacelle components is included along with analysis of the certifiable airplane design to ensure airworthiness compliance and to predict the in-flight performance and noise characteristics of the modified airplane. The analyses confirm that the 727 refan airplane is certifiable. The refan airplane range would be 15% less than that of the baseline airplane and block fuel would be increased by 1.5% to 3%. However, with this particular 727-200 model with a brake release gross weight of 172,500 lb (78,245 kg) it is possible to operate the airplane (with minor structural modifications) at higher gross weights and increase the range up to 15% over the 727-200 (baseline) airplane. The refan airplane FAR Part 36 noise levels would be 6 to 8 EPNdB (effective perceived noise in decibels) below the baseline. Noise footprint studies showed that approach noise contour areas are small compared to takeoff areas. The 727 refan realizes a 68% to 83% reduction in annoyance-weighted area when compared to the 727-200 over a range of gross weights and operational procedures. Author

N76-21191# National Aviation Facilities Experimental Center Atlantic City NJ
RESPONSES OF SMALL RIGID AIRCRAFT TO DISCRETE AND CONTINUOUS GUST ANALYSIS, PHASE 1 Final Report, Nov 1972 - Nov 1974

John Petrakis and Nelson Miller Dec 1975 121 p refs
(AD-A020103/8 FAA-RD-74-160 FAA-NA-74-44) Avail
NTIS HC \$5 50 CSCL 01/1

An evaluation is made of methods developed for estimating longitudinal and lateral rigid-body responses of airplanes to random atmospheric turbulence. A computer program, evolved from this study calculates general aviation aircraft stability derivatives from known geometric properties used as inputs for the calculation of aircraft response (also a developed part of the computer program). It was found that the two degrees-of-freedom rigid-body power spectral density analysis produced lower normal load factor responses than a similar single degree-of-freedom analysis for aircraft of gross weight from 3,000 to 17,500 pounds. Also to

produce an equivalent discrete load factor for the two degrees-of-freedom analysis, a higher spectral velocity value must be used compared to that of the single degree-of-freedom approach
Author

N76-21193# AMC Inventory Research Office Philadelphia Pa
DEMAND FORECASTING WITH PROGRAM FACTORS Final Report

Martin Cohen Sep 1975 74 p refs
(AD-A017858 IRO-182) Avail NTIS CSCL 15/5

Empirical demand forecasting studies have raised doubt about the often-made assumption that repair part demand is proportional to end-item usage. The study was made to test this assumption using a data base consisting of demands on the Army Aviation Systems Command National Inventory Point (AVSCOM NIPC) for thousands of stocked items. A simulation of the NIPC supply function was used to test the assumption and various proposed forecasting algorithms. The criterion was least holding and ordering cost for constant time-weighted requisitions short. The assumption that demand is proportional to end-item program was supported at least for the items responsible for the largest part of the costs and an improved algorithm was found. GRA

N76-21194# General Dynamics/Convair, San Diego Calif
WEAPON SYSTEM COSTING METHODOLOGY FOR AIRCRAFT AIRFRAMES AND BASIC STRUCTURES VOLUME 1 TECHNICAL VOLUME Final Report, Jul 1972 - Mar 1975

R E Kenyon Jun 1975 343 p refs
(Contract F33615-72-C-2083 AF Proj 1368)
(AD-A016408 AFFDL-TR-75-44-Vol-1) Avail NTIS CSCL 01/3

This volume provides a detailed description of the function and use of two weapon system costing methodologies for aircraft airframes and basic structures developed for the Air Force Flight Dynamics Laboratory for use in conceptual and preliminary design phases of weapon system development. The methods are a trade study costing method for detailed cost analysis of trade-offs between weight, cost, type of construction and type of material and a system costing method for determining the projected cost of a complete airframe within the context of a weapon system development. This volume provides a technical discussion of method development. Trade-off capability has been provided for a range of alternative structure and material combinations. A technique for independently assessing complexity factors has been developed and demonstrated. Manufacturing costs are separately estimated for the primary elements of substructure: ribs, spars, covers, leading edges, trailing edges, tips, etc. The trade study method provides an iterative capability stemming from a direct interface with design synthesis programs. A detailed cost data base and system for data expansion is provided. The methods are designed for ease in changing cost estimating relationships and estimating coefficients resulting from cost data update.
Author (GRA)

N76-21195# General Dynamics/Convair, San Diego Calif
WEAPON SYSTEM COSTING METHODOLOGY FOR AIRCRAFT AIRFRAMES AND BASIC STRUCTURES VOLUME 2 ESTIMATING HANDBOOK AND USER'S MANUAL, PART 2 Final Report, Jul 1972 - Feb 1975

R E Kenyon May 1975 371 p refs
(Contract F33615-72-C-2083 AF Proj 1368)
(AD-A016410 AFFDL-TR-75-44-Vol-2-Pt-2) Avail NTIS CSCL 01/3

For abstract see N76-21194

N76-21196# Air Force Systems Command Wright-Patterson AFB Ohio Foreign Technology Div
ANALYSIS OF FAILURES IN THE PARTS OF AN AIRCRAFT UNDERCARRIAGE

Z S Kulyshcheva and A G Yamov 12 Nov 1975 11 p refs
Transl into ENGLISH from Tr Rizhskii Inst Inzh Gradzhanskoi Aviatsii (USSR) no 202 p 54-59
(AD-A017928 FTD-ID(RSI)-2308-75) Avail NTIS CSCL 01/3

Variable loads of aircraft undercarriages are discussed. Loads from nonquality landing, the nature of the motion of the aircraft, the degree of unevenness of the airfield, and the rigidity of shock absorption are considered. Fatigue cracks and bolted joints are the most frequently caused defects.
JMS

N76-21205*# Pratt and Whitney Aircraft East Hartford Conn
MODELING AND ANALYSIS OF THE TF30-P-3 COMPRESSOR SYSTEM WITH INLET PRESSURE DISTORTION
R S Mazzawy and G A Banks Apr 1976 133 p refs
(Contract NAS3-18535)
(NASA-CR-134996 PWA-5302) Avail NTIS HC \$6 00 CSCL 21E

Circumferential inlet distortion testing of a TF30-P-3 afterburning turbofan engine was conducted at NASA-Lewis Research Center. Pratt and Whitney Aircraft analyzed the data using its multiple segment parallel compressor model and classical compressor theory. Distortion attenuation analysis resulted in a detailed flow field calculation with good agreement between multiple segment model predictions and the test data. Sensitivity of the engine stall line to circumferential inlet distortion was calculated on the basis of parallel compressor theory to be more severe than indicated by the data. However, the calculated stall site location was in agreement with high response instrumentation measurements.
Author

N76-21206*# National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio
NOISE REDUCTION FROM THE REDESIGN OF A FAN STAGE TO MINIMIZE STATOR LIFT FLUCTUATIONS

James H Dittmar and Richard P Woodward 1976 10 p refs
Proposed for presentation at 3d Aero-Acoustics Conf Palo Alto Calif 20-23 Jul 1976 sponsored by AIAA
(NASA-TM-X-71896 E-8682) Avail NTIS HC \$3 50 CSCL 20A

An existing fan stage redesigned to reduce stator lift fluctuations was acoustically tested for reduced noise generation. The lift fluctuations on the stator were reduced by increasing the stator chord, adjusting incidence angles and by adjusting the rotor velocity diagrams. The experiments showed significantly reduced broadband noise levels in the middle to high frequencies. Blade passage tone power was not reduced but decreases in the harmonics were observed. Aerodynamic improvements in both performance and efficiency were obtained.
Author

N76-21208*# National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio
STIMULATION OF A TURBOFAN ENGINE FOR EVALUATION OF MULTIVARIABLE OPTIMAL CONTROL CONCEPTS

Kurt Seldner 1976 12 p refs
Prepared for Presentation at Joint Autom Control Conf Lafayette Ind 27-30 Jul 1976 sponsored by the Am Autom Control Council
(NASA-TM-X-71912 E-8703) Avail NTIS HC \$3 50 CSCL 21E

The development of control systems for jet engines requires a real-time computer simulation. The simulation provides an effective tool for evaluating control concepts and problem areas prior to actual engine testing. The development and use of a real-time simulation of the Pratt and Whitney F100-PW100 turbofan engine is described. The simulation was used in a multi-variable optimal controls research program using linear quadratic regulator theory. The simulation is used to generate linear engine models at selected operating points and evaluate the control algorithm. To reduce the complexity of the design, it is desirable to reduce the order of the linear model. A technique to reduce the order of the model is discussed. Selected results between high and low order models are compared. The LQR control algorithms can be programmed on digital computer. This computer will control the engine simulation over the desired flight envelope.
Author

N76-21209*# National Aeronautics and Space Administration Langley Research Center Langley Station Va
HYPERSONIC RESEARCH ENGINE/AEROTHERMODYNAMIC INTEGRATION MODEL, EXPERIMENTAL

RESULTS VOLUME 4 MACH 5 COMPONENT INTEGRATION AND PERFORMANCE

Earl H Andrews Jr and Ernest A Mackley Apr 1976 526 p refs Prepared in cooperation with AirResearch Mfg Co) 3 Vol (Contract NAS1-6666)

(NASA-TM-X-72824) Avail NTIS HC \$13 00 CSCL 21E

Tabulated computer program results of wind tunnel tests for Mach 5 components are presented Author

N76-21210*# Pratt and Whitney Aircraft East Hartford Conn COUPLING OF HELMHOLTZ RESONATORS TO IMPROVE ACOUSTIC LINERS FOR TURBOFAN ENGINES AT LOW FREQUENCY

L W Dean Aug 1975 66 p refs

(Contract NAS3-18552)

(NASA-CR-134912 PWA-5311) Avail NTIS HC \$4 50 CSCL 21E

An analytical and test program was conducted to evaluate means for increasing the effectiveness of low frequency sound absorbing liners for aircraft turbine engines Three schemes for coupling low frequency absorber elements were considered These schemes were analytically modeled and their impedance was predicted over a frequency range of 50 to 1 000 Hz An optimum and two off-optimum designs of the most promising a parallel coupled scheme were fabricated and tested in a flow duct facility Impedance measurements were in good agreement with predicted values and validated the procedure used to transform modeled parameters to hardware designs Measurements of attenuation for panels of coupled resonators were consistent with predictions based on measured impedance All coupled resonator panels tested showed an increase in peak attenuation of about 50% and an increase in attenuation bandwidth of one one-third octave band over that measured for an uncoupled panel These attenuation characteristics equate to about 35% greater reduction in source perceived noise level (PNL) relative to the uncoupled panel or a reduction in treatment length of about 24% for constant PNL reduction The increased effectiveness of the coupled resonator concept for attenuation of low frequency broad spectrum noise is demonstrated Author

N76-21211# McDonnell-Douglas Corp Long Beach Calif AIRCRAFT NOISE DEFINITION PHASE 2 ANALYSIS OF FLYOVER-NOISE DATA FOR DC-8-61 AIRCRAFT Final Report, Nov 1973 - Aug 1974

R E DeLapp Aug 1974 177 p refs

(Contract DOT-FA73WA-3161)

(AD-A019759/0 MDC-J4443 FAA-EQ-74-5) Avail NTIS HC \$6 75 CSCL 20/1

Phase II of the Aircraft Noise Definition program consisted of a DC-8-61 flight test program with an objective to improve the statistical accuracy of the noise data reported in Phase I of the program and to broaden the data base to include measurements at long distances and at a thrust required for a steep approach Noise measurements were made during flyovers up to an altitude of 8 000 feet at sideline distances up to 8 000 feet and at target thrusts of 15 000 10 000 5 000 3 200 and 2000 pounds This document reports the data acquisitions, the analysis procedure and the results in terms of variations in reference-day EPNL and A-weighted sound level with slant range overhead to sideline noise level relationship and data showing lateral noise attenuations Data accuracy is described in terms of assignable confidence limits A comparison was made between reference-day noise levels determined for surface weather conditions and by a method that accounts for upper-air variations in the sound-path weather A method that adjusts for lateral noise attenuation in computing EPNLs for sideline locations was suggested Photographs and descriptions of airborne computers and ground equipment employed (mobile sound recording equipment) are included Author

N76-21216*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

A SIMULATION STUDY OF CURVED, DESCENDING, DECELERATING, LANDING APPROACHES FOR TRANSPORT AIRCRAFT

James E Dieudonne Randall D Grove and George G Steinmetz Washington Apr 1976 43 p refs

(NASA-TN-D-8190 L-10584) Avail NTIS HC \$4 00 CSCL 01C

A system which is capable of controlling an aircraft automatically along a curved descending decelerating approach was described A simulation study was conducted to determine the necessary modifications to the basic flight-proven control system This basic system is presently being used to accomplish straight-in automatic landing approaches on a short-haul transport aircraft (B-737 terminal configured vehicle) This study shows that both 3 deg (normal) and 5 deg (steep) approaches could be accomplished with only minor modifications to the basic control system Author

N76-21601# Laboratorium fuer Betriebsfestigkeit Darmstadt (West Germany)

REVIEW OF INVESTIGATIONS ON AERONAUTICAL FATIGUE IN THE FEDERAL REPUBLIC OF GERMANY, JULY 1973 - APRIL 1975

O Buxbaum Apr 1975 169 p refs Presented at the 14th Conf of the Intern Comm on Aeron Fatigue Lausanne Switz, 1975

(LBF-S-119) Avail NTIS HC \$6 75

Work carried out in the field of fatigue of aircraft structures is reviewed Topics covered include the measurement and analysis of operational loads fatigue tests under random or randomized sequences the fatigue behavior of notched specimens and joints, cyclic stress-strain behavior and low cycles fatigue crack propagation fracture mechanics, and residual static strength

ESA

N76-21990*# National Aeronautics and Space Administration Langley Research Center Langley Station Va

SOURCES AND CHARACTERISTICS OF INTERIOR NOISE IN GENERAL AVIATION AIRCRAFT

John J Catherines and Sunil K Jha (Cranfield Inst of Technol England) Apr 1976 24 p refs Presented at 91st Meeting Acoust Soc Am Washington D C 5-9 Apr 1976

(NASA-TM-X-72839) Avail NTIS HC \$3 50 CSCL 20A


A field study was conducted to examine the interior noise characteristics of a general aviation aircraft The goals were to identify the major noise sources and their relative contribution and to establish the noise transmission paths and their relative importance Tests were performed on an aircraft operating under stationary conditions on the ground Results show that the interior noise level of light aircraft is dominated by broadband low frequencies (below 1 000 Hz) Both the propeller and the engine are dominant sources however the contribution from the propeller is significantly more than the engine at its fundamental blade passage frequency The data suggest that the airborne path is more dominant than the structure-borne path in the transmission of broadband low frequency noise which apparently results from the exhaust Author

SUBJECT INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl 72)

JULY 1976

Typical Subject Index Listing



The title is used to provide a description of the subject matter. When the title is insufficiently descriptive of the document content a title extension is added separated from the title by three hyphens. The NASA or AIAA accession number is included in each entry to assist the user in locating the abstract in the abstract section of this supplement. If applicable a report number is also included as an aid in identifying the document.

A

- COMBUSTION PHYSICS**
 Combustion generated noise in gas turbine combustors
 --- engine noise/noise reduction
 [NASA-CR-134843] N76-10123
- ACCELERATED LIFE TESTS**
 Investigation of accelerated life prediction techniques
 [AD-A016925] N76-20129
- ACOUSTIC ATTENUATION**
 Selected problems of cockpit acoustic design
 A76-28545
- Coupling of Helmholtz resonators to improve acoustic liners for turbofan engines at low frequency
 [NASA-CR-134912] N76-21210
- ACOUSTIC DUCTS**
 Advanced Acoustic Nacelle concepts
 [ASME PAPER 76-GT-35] A76-25786
- A comparison of matrix methods for calculating eigenvalues in acoustically lined ducts
 [NASA-TN-D-8186] N76-20941
- ACOUSTIC EXCITATION**
 The amplification of broadband jet noise by pure tone excitation
 [DLR-FB-75-72] N76-20942
- AERODYNAMIC CHARACTERISTICS**
 Dynamics of helicopter flight --- Book
 A76-26450
- Aerodynamic derivatives of the longitudinal motion of the whole aircraft
 A76-28256
- Extension of slender body theory
 A76-28258
- Experimental aerodynamic characteristics for slender bodies with thin wings and tail at angles of attack from 0 deg to 58 deg and Mach numbers from 0.6 to 2.0
 [NASA-TM-X-3310] N76-20079
- Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade
 [AD-A017203] N76-20095
- The ground effect on the aerodynamic characteristics of an aircraft --- steady horizontal flight
 [AD-A017309] N76-20098
- Effect of the GBU-15 (cruciform wing) and GBU-15 (planar wing) stores on the aerodynamic characteristics of the F-4C aircraft
 [AD-A017378] N76-20135
- Design of a 4 1/2 stage turbine with a stage loading factor of 4.66 and high specific work output
 [NASA-CR-2659] N76-20146
- Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results
 [NASA-CR-137747] N76-21159
- AERODYNAMIC COEFFICIENTS**
 Subsonic loads on wings having sharp leading edges and tips
 A76-28606
- Representation of the drag polar of a fighter aircraft
 A76-28610
- Airfoil profile drag
 [AD-A017321] N76-20093
- Computer program for calculating pressure distribution and coefficients of wings, bodies, wing-body combinations and wing-tail combinations in subsonic, supersonic and hypersonic flow --- based on potential theory
 [MBB-UFE-1014-0] N76-21165
- AERODYNAMIC CONFIGURATIONS**
 Thrust reverser design for airframe compatibility
 A76-26650
- AERODYNAMIC DRAG**
 Representation of the drag polar of a fighter aircraft
 A76-28610
- Airfoil profile drag
 [AD-A017321] N76-20093
- Drag due to grooves in a flat plate with turbulent boundary layer, at subsonic and supersonic speeds
 [ESDU-75028] N76-21153
- AERODYNAMIC HEAT TRANSFER**
 Aerodynamics and heat transfer at the trailing edge of transonic blades
 [ASME PAPER 76-GT-95] A76-25835
- AERODYNAMIC LOADS**
 Vortex maneuver lift for super-cruise configurations
 [NASA-TM-X-72836] N76-21161
- AERODYNAMIC NOISE**
 Bibliography on aircraft noise
 [FOK-N-00-28] N76-20138
- AERODYNAMIC STABILITY**
 An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
 [ASME PAPER 76-GT-17] A76-25773
- Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling
 [NASA-TN-D-8192] N76-21162
- Flutter of asymmetrically swept wings
 [NASA-CR-146815] N76-21164
- AERODYNAMICS**
 Fully unsteady subsonic and supersonic potential aerodynamics for complex aircraft configurations for flutter applications
 [NASA-CR-146573] N76-20077
- AEROELASTICITY**
 Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade
 [AD-A017203] N76-20095
- Flutter of asymmetrically swept wings
 [NASA-CR-146815] N76-21164
- AERONAUTICAL ENGINEERING**
 New developments in aeronautics technology --- alloys and composite materials review
 A76-26412
- Thrust reverser design for airframe compatibility
 A76-26650
- AFTERBODIES**
 Nozzle afterbody configuration development for the B-1 strategic bomber
 [AIAA PAPER 74-1102] A76-28608

AGRICULTURE

SUBJECT INDEX

AGRICULTURE

Aircraft use in agriculture and forestry --- spraying with helicopters and light aircraft in the U.S.S.R. [NASA-TT-F-16846]	N76-20078	Flight test evaluation of a 240 to 400 MHz cavity-backed cross open-sleeve dipole antenna [AD-A017298]	N76-20386
AIR COOLING Heat transfer in high-temperature GTE air-cooled turbine blades	A76-26584	Characteristics of a 240 to 400 MHz 6-inch depth cavity-backed cross open-sleeve dipole antenna on a curved ground plane [AD-A017367]	N76-20387
AIR DEFENSE The outlook for aeronautics, 1980 - 2000 - Study report --- trends affecting civil air transportation and defense [NASA-TM-X-72995]	N76-20063	AIRCRAFT COMMUNICATION Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results [AD-A017090]	N76-20301
The outlook for aeronautics, 1980 - 2000: Appendix B: Study group report on an industry-university-government survey [NASA-TM-X-72996]	N76-20064	AIRCRAFT COMPARTMENTS Development of deicing techniques for dielectric windows [AD-A017097]	N76-20136
Domestic and world trends affecting the future of aviation (1980 - 2000), appendix C [NASA-TM-X-72997]	N76-20065	AIRCRAFT CONFIGURATIONS Nozzle afterbody configuration development for the B-1 strategic bomber [AIAA PAPER 74-1102]	A76-28608
The outlook for aeronautics, 1980 - 2000: Executive summary --- trends affecting civil air transportation and air defense [NASA-TM-X-72998]	N76-20066	Fully unsteady subsonic and supersonic potential aerodynamics for complex aircraft configurations for flutter applications [NASA-CR-146573]	N76-20077
AIR FLOW A linearized theory of three-dimensional airfoils in nonuniform flow	A76-27329	AIRCRAFT CONTROL Improvement of the precision of aircraft control during completion of a plane turn maneuver	A76-27930
AIR INTAKES A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator [ASME PAPER 76-GT-84]	A76-25825	Fundamental formulation of airship performance and flight dynamics	A76-28033
AIR TRAFFIC Military aviation forecasts, fiscal years 1976 - 1987 [AD-A017622]	N76-20068	AIRCRAFT DESIGN Advanced Acoustic Nacelle concepts [ASME PAPER 76-GT-35]	A76-25786
Aviation forecast, fiscal years 1976 - 1987 --- air traffic in commercial and military aviation [AD-A017095]	N76-20069	Status report - Subsonic aircraft noise reduction [ASME PAPER 76-GT-116]	A76-25849
AIR TRANSPORTATION The outlook for aeronautics, 1980 - 2000 - Study report --- trends affecting civil air transportation and defense [NASA-TM-X-72995]	N76-20063	Engineering aspects of flight safety --- Russian book	A76-26048
The outlook for aeronautics, 1980 - 2000: Appendix B: Study group report on an industry-university-government survey [NASA-TM-X-72996]	N76-20064	Some considerations in the design of transport aircraft /The W. Rupert Turnbull Lecture for 1975/	A76-27274
Domestic and world trends affecting the future of aviation (1980 - 2000), appendix C [NASA-TM-X-72997]	N76-20065	Calculation of buffet onset for supercritical airfoils	A76-27832
The outlook for aeronautics, 1980 - 2000: Executive summary --- trends affecting civil air transportation and air defense [NASA-TM-X-72998]	N76-20066	Design and test of a sonic roof-top pressure distribution wing	A76-27855
Operational factors of air service to small communities [NASA-CR-137820]	N76-20104	Aerodynamic derivatives of the longitudinal motion of the whole aircraft	A76-28256
Profiles of scheduled air carrier operations by state length. Federal Aviation Administration regions top 100 US airports, 1 November 1974 [AD-A016161]	N76-20122	Hydraulic systems for transport aircraft --- Russian book	A76-28354
AIRCRAFT Prediction of light aircraft interior noise [NASA-TM-X-72838]	N76-20940	Selected problems of cockpit acoustic design	A76-28545
AIRCRAFT ACCIDENT INVESTIGATION Engineering aspects of flight safety --- Russian book	A76-26048	Use of fracture mechanics in estimating structural life and inspection intervals --- airframe damage tolerance defined design	A76-28607
Mechanical engineering and aeronautical research projects [DME/NAE-1975(4)]	N76-20156	The design of unswept large aspect ratio wings with flaps for two flight conditions [ESA-TT-224]	N76-20128
AIRCRAFT ACCIDENTS Major orientation-error accidents in regular Army UH-1 aircraft during fiscal year 1971 (accident factors) [AD-A017665]	N76-21178	AIRCRAFT ENGINES The pulsed thermocouple for gas turbine application [ASME PAPER 76-GT-1]	A76-25758
AIRCRAFT ANTENNAS A study of axial slot arrays on a circular cylinder for use on electrically small vehicles [AD-A016564]	N76-20339	Noise technology requirements for future aircraft powerplants [ASME PAPER 76-GT-69]	A76-25812
Rotor blade effects on L-band signals received by helicopter antennas mounted above the rotor blade (CW) experiments [AD-A016866]	N76-20360	Advanced composite fan blade flight evaluation program [ASME PAPER 76-GT-75]	A76-25818
		XPV-12A propulsion system development [ASME PAPER 76-GT-125]	A76-25855
		Advanced turbine disk designs to increase reliability of aircraft engines	A76-25875
		Types and ideal propulsive efficiency of aeronautical propulsion systems	A76-26550
		Propulsion systems --- aircraft engine technology review	A76-26670
		Rocket engines GDL-OKB --- Soviet liquid propellant engine development history	A76-28100
		Sources and characteristics of interior noise in general aviation aircraft [NASA-TM-X-72839]	N76-21990

- AIRCRAFT HYDRAULIC SYSTEMS**
Hydraulic systems for transport aircraft ---
Russian book A76-28354
- AIRCRAFT INDUSTRY**
History of Messerschmitt aircraft manufacturing
[DLR-MITT-75-21] N76-20070
The general aviation industry; an overview
[AD-A015871] N76-20072
- AIRCRAFT INSTRUMENTS**
Magnetic heading reference
[NASA-CASE-LAR-11387-1] N76-20114
- AIRCRAFT LANDING**
Interaction of a buoyant turbulent planar jet with
a co-flowing wind N76-21172
[AD-A018060]
A simulation study of curved, descending,
decelerating, landing approaches for transport
aircraft N76-21216
[NASA-TN-D-8190]
- AIRCRAFT MAINTENANCE**
Some basic questions concerning quality assurance
in aircraft maintenance A76-27361
Quality assurance by standardization --- for
aircraft maintenance and spare parts manufacturing
A76-27362
Licensing and the organization of the servicing
process in aircraft maintenance A76-27363
The identification of a precedence network
associated with base level aircraft maintenance
[AD-A016389] N76-21017
- AIRCRAFT MANEUVERS**
Improvement of the precision of aircraft control
during completion of a plane turn maneuver
A76-27930
Ergonomic analysis of maneuvers leading to
inaudibility of a shock wave A76-28544
Vortex maneuver lift for super-cruise configurations
[NASA-TM-X-72836] N76-21161
Studies of aircraft differential maneuvering.
Report 75-27: Calculating of
differential-turning barrier surfaces. Report
75-26: A user's guide to the aircraft
energy-turn and tandem-motion computer programs.
Report 75-7: A user's guide to the aircraft
energy-turn hodograph program --- numerical
analysis of tactics and aircraft maneuvers of
supersonic attack aircraft N76-21188
[NASA-CR-137819]
- AIRCRAFT NOISE**
Status report - Subsonic aircraft noise reduction
[ASME PAPER 76-GT-116] A76-25849
An aircraft noise pollution model for trajectory
optimization A76-26384
Results of noise and vibration studies on A-24
aircraft A76-28542
Ergonomics and the problem of aircraft-induced
external noise A76-28543
Selected problems of cockpit acoustic design
A76-28545
Bibliography on aircraft noise
[FOK-N-00-28] N76-20138
Aircraft noise abatement
[GPO-62-786] N76-20695
Prediction of light aircraft interior noise
[NASA-TM-X-72838] N76-20940
- AIRCRAFT PARTS**
Windshield Flight Environment Simulator
A76-26648
Quality assurance by standardization --- for
aircraft maintenance and spare parts manufacturing
A76-27362
Analysis of failures in the parts of an aircraft
undercarriage N76-21196
[AD-A017928]
- AIRCRAFT PERFORMANCE**
Limitations of the flight regime of a supersonic
transport /SST/ by the sonic boom A76-28469
Measurements of the vertical movements of an
aircraft --- altitude and velocity measurement
accuracy N76-20152
[ESA-TT-215]
- Phase 2 program on ground test of refanned JT8D
turbofan engines and nacelles for the 727
airplane. Volume 4: Airplane evaluation and
analysis
[NASA-CR-134800] N76-21190
- AIRCRAFT PRODUCTION**
History of Messerschmitt aircraft manufacturing
[DLR-MITT-75-21] N76-20070
- AIRCRAFT RELIABILITY**
Effect of the upper limit of distribution function
of aircraft structure on the main failure's
distribution A76-28254
Estimation of population reliability function of
aircraft structures from a limited fleet of
aircraft A76-28255
- AIRCRAFT SAFETY**
Some considerations in the design of transport
aircraft /The W. Rupert Turnbull Lecture for 1975/
A76-27274
- AIRCRAFT STABILITY**
The ground effect on the aerodynamic
characteristics of an aircraft --- steady
horizontal flight
[AD-A017309] N76-20098
Roll-axis hydrofluidic stability augmentation
system development N76-20154
[AD-A016932]
- AIRCRAFT STRUCTURES**
Thrust reverser design for airframe compatibility
A76-26650
Effect of the upper limit of distribution function
of aircraft structure on the main failure's
distribution A76-28254
Estimation of population reliability function of
aircraft structures from a limited fleet of
aircraft A76-28255
Use of fracture mechanics in estimating structural
life and inspection intervals --- airframe
damage tolerance defined design A76-28607
- Weapon system costing methodology for aircraft
airframes and basic structures. Volume 2:
Estimating handbook and user's manual, part 1
[AD-A016409] N76-21024
Dynamics and identification of flexible aircraft
[NASA-CR-2672] N76-21158
Flutter of asymmetrically swept wings
[NASA-CR-146815] N76-21164
Weapon system costing methodology for aircraft
airframes and basic structures. Volume 1:
Technical volume
[AD-A016408] N76-21194
Weapon system costing methodology for aircraft
airframes and basic structures. Volume 2:
Estimating handbook and user's manual, part 2
[AD-A016410] N76-21195
Review of investigations on aeronautical fatigue
in the Federal Republic of Germany, July 1973 -
April 1975 N76-21601
[LBP-S-119]
- AIRCRAFT SURVIVABILITY**
Impact dynamics research facility for full-scale
aircraft crash testing N76-21173
[NASA-TN-D-8179]
- AIRCRAFT WAKES**
Investigation of vortex wake stability near the
ground N76-20112
[AD-A017586]
Characteristics of wake vortex generated by a
boeing 727 jet transport during two-segment and
normal ILS approach flight paths N76-21175
[NASA-TN-D-8222]
- AIRFOIL PROFILES**
Asymptotic representation of solutions on the
hodograph plane in problems of subsonic flow
past airfoil profiles A76-26337
Iterative calculation of two-dimensional
compressible flow around ellipse and circular
arc profile A76-27328
A linearized theory of three-dimensional airfoils
in nonuniform flow A76-27329

AIRFOILS

SUBJECT INDEX

- On the motion of shock waves on an airfoil with oscillating flap
A76-27830
- Calculation of buffet onset for supercritical airfoils
A76-27832
- Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils
A76-27837
- Airfoil design for a prescribed velocity distribution in transonic flow by an integral method
A76-27844
- Mathematical method of designing a certain compressor type plane blade cascade
A76-27863
- A review of numerical techniques for calculating supercritical airfoil flows
A76-27865
- Review of some numerical solutions of the transonic small disturbance equations
A76-27869
- Research in the UK on finite difference methods for computing steady transonic flows
A76-27874
- A direct method for computing non-symmetrical plane flows at Mach number one
A76-27878
- Preparation of eutectic superalloys by EFG --- Edge-defined Film-fed Growth for directional solidification in airfoil structures
A76-28029
- Analysis of circulation controlled airfoils
A76-28611
- AIRFOILS**
- An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade [ASME PAPER 76-GT-17]
A76-25773
- An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1
A76-27857
- Supercritical flow past airfoils at Mach numbers close to one
A76-27877
- Experiments on thin airfoils spanning a transonic shear flow
N76-20073
- Transonic airfoil design using Cartesian coordinates [NASA-CR-2578]
N76-20082
- An analysis of heat transfer on a Joukowski airfoil with separation and reattachment [AD-A016457]
N76-20091
- Airfoil profile drag [AD-A017321]
N76-20093
- Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade [AD-A017203]
N76-20095
- Unsteady surface flow behavior on a cascade of airfoils oscillating below stall [AD-A017073]
N76-20096
- Design of a 4 1/2 stage turbine with a stage loading factor of 4.66 and high specific work output [NASA-CR-2659]
N76-20146
- AIRFRAMES**
- Thrust reverser design for airframe compatibility
A76-26650
- Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 1 [AD-A016409]
N76-21024
- Weapon system costing methodology for aircraft airframes and basic structures. Volume 1: Technical volume [AD-A016408]
N76-21194
- Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 2 [AD-A016410]
N76-21195
- AIRLINE OPERATIONS**
- Economics of air transport --- Russian book
A76-26049
- Some basic questions concerning quality assurance in aircraft maintenance
A76-27361
- Licensing and the organization of the servicing process in aircraft maintenance
A76-27363
- Determination of the realizable flight hours for aircraft
A76-27364
- A study of the financial history of the U.S. scheduled airlines and the improvement of airline profitability through technology [NASA-TM-X-73109]
N76-20101
- Profiles of scheduled air carrier operations by state length. Federal Aviation Administration regions top 100 US airports, 1 November 1974 [AD-A016161]
N76-20122
- AIRPORTS**
- Military aviation forecasts, fiscal years 1976 - 1987 [AD-A017622]
N76-20068
- Profiles of scheduled air carrier operations by state length. Federal Aviation Administration regions top 100 US airports, 1 November 1974 [AD-A016161]
N76-20122
- AIRSHIPS**
- Fundamental formulation of airship performance and flight dynamics
A76-28033
- AN-24 AIRCRAFT**
- Results of noise and vibration studies on An-24 aircraft
A76-28542
- ANGLE OF ATTACK**
- Experimental aerodynamic characteristics for slender bodies with thin wings and tail at angles of attack from 0 deg to 58 deg and Mach numbers from 0.6 to 2.0 [NASA-TM-X-3310]
N76-20079
- ANTENNA ARRAYS**
- A study of axial slot arrays on a circular cylinder for use on electrically small vehicles [AD-A016564]
N76-20339
- APPROACH**
- Characteristics of wake vortex generated by a boeing 727 jet transport during two-segment and normal ILS approach flight paths [NASA-TN-D-8222]
N76-21175
- A simulation study of curved, descending, decelerating, landing approaches for transport aircraft [NASA-TN-D-8190]
N76-21216
- ATTACK AIRCRAFT**
- Technical evaluation report of AGARD Specialists Meeting on Wing-With-Stores Flutter --- for attack aircraft [AGARD-AR-96]
N76-21163
- Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program --- numerical analysis of tactics and aircraft maneuvers of supersonic attack aircraft [NASA-CR-137819]
N76-21188
- AUTOMATIC FLIGHT CONTROL**
- Manual and automatic flight control during severe turbulence penetration [NASA-CR-2677]
N76-20151
- AUTOMATIC PILOTS**
- Improvement of the precision of aircraft control during completion of a plane turn maneuver
A76-27930
- AXISYMMETRIC FLOW**
- Some numerical results of a new three-dimensional transonic flow method
A76-27875
- B**
- B-1 AIRCRAFT**
- Nozzle afterbody configuration development for the B-1 strategic bomber [AIAA PAPER 74-1102]
A76-28608
- BALLISTIC RANGES**
- Non-linear effect due to flow separation on flow past wings and wing body combinations
A76-27741

- BALLISTICS**
Ballistics of ejection seats
A76-27743
- BEARING (DIRECTION)**
Major orientation-error accidents in regular Army
UH-1 aircraft during fiscal year 1971 (accident
factors)
[AD-A017665] N76-21178
- BENDING VIBRATION**
Coupled bending-torsion vibrations of rotating
blades
[ASME PAPER 76-GT-43] A76-25792
- BLOWING**
Analysis of circulation controlled airfoils
A76-28611
Three component measurements on a light STOL
aircraft with chordwise blowing
[DLR-PB-75-74] N76-20127
- BLUNT BODIES**
Interaction between an external shock wave and a
blunted body in hypersonic flow
A76-26339
- BODY-WING AND TAIL CONFIGURATIONS**
Experimental aerodynamic characteristics for
slender bodies with thin wings and tail at
angles of attack from 0 deg to 58 deg and Mach
numbers from 0.6 to 2.0
[NASA-TM-X-3310] N76-20079
A method for the calculation of the twist and
camber of a wing with a specified load
distribution in the presence of a fuselage ---
theoretical potential flow method
[ESA-TT-214] N76-20087
Computer program for calculating pressure
distribution and coefficients of wings, bodies,
wing-body combinations and wing-tail
combinations in subsonic, supersonic and
hypersonic flow --- based on potential theory
[HBB-UPE-1014-0] N76-21165
- BODY-WING CONFIGURATIONS**
Non-linear effect due to flow separation on flow
past wings and wing body combinations
A76-27741
Design and test of a sonic roof-top pressure
distribution wing
A76-27855
Some numerical results of a new three-dimensional
transonic flow method
A76-27875
The analysis of arbitrary wingbody combinations in
transonic flow using a relaxation method
A76-27879
Numerical solutions for transonic flows past
wing-body combinations
A76-27880
- BOEING 707 AIRCRAFT**
Characteristics of wake vortex generated by a
boeing 727 jet transport during two-segment and
normal ILS approach flight paths
[NASA-TN-D-8222] N76-21175
- BOEING 727 AIRCRAFT**
Phase 2 program on ground test of refanned JT8D
turbofan engines and nacelles for the 727
airplane. Volume 3: Ground tests
[NASA-CR-134799] N76-21189
Phase 2 program on ground test of refanned JT8D
turbofan engines and nacelles for the 727
airplane. Volume 4: Airplane evaluation and
analysis
[NASA-CR-134800] N76-21190
- BOEING 737 AIRCRAFT**
An aircraft noise pollution model for trajectory
optimization
A76-26384
- BOMBER AIRCRAFT**
An update - Advanced aircraft oxygen systems
A76-27144
- BORON REINFORCED MATERIALS**
Advanced composite fan blade flight evaluation
program
[ASME PAPER 76-GT-75] A76-25818
- BOUNDARY LAYER FLOW**
Analysis of circulation controlled airfoils
A76-28611
- BOUNDARY LAYER SEPARATION**
Unsteady surface flow behavior on a cascade of
airfoils oscillating below stall
[AD-A017073] N76-20096
- BROADBAND**
The amplification of broadband jet noise by pure
tone excitation
[DLR-PB-75-72] N76-20942
- BUBBLE TECHNIQUE**
Visualization of the subsonic flow around two
space glider configurations --- using hydrogen
bubble technique in water basin
[DLR-PB-75-49] N76-20083
- BUFFETING**
Calculation of buffet onset for supercritical
airfoils
A76-27832
- BUOYANCY**
Fundamental formulation of airship performance and
flight dynamics
A76-28033
- C**
- C-135 AIRCRAFT**
Flight test evaluation of a 240 to 400 MHz
cavity-backed cross open-sleeve dipole antenna
[AD-A017298] N76-20386
Characteristics of a 240 to 400 MHz 6-inch depth
cavity-backed cross open-sleeve dipole antenna
on a curved ground plane
[AD-A017367] N76-20387
- CAMBER**
An investigation into the effects of aspect ratio
and centre keel camber on the aerodynamic
characteristics of conical parawings
[BU-176] N76-21170
- CARTESIAN COORDINATES**
Transonic airfoil design using Cartesian coordinates
[NASA-CR-2578] N76-20082
- CASCADE CONTROL**
An experimental determination of the unsteady
aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
- CASCADE FLOW**
Mathematical method of designing a certain
compressor type plane blade cascade
A76-27863
Research on aeroelastic phenomena in airfoil
cascades supersonic unsteady aerodynamic
phenomena in a controlled oscillating cascade
[AD-A017203] N76-20095
Unsteady surface flow behavior on a cascade of
airfoils oscillating below stall
[AD-A017073] N76-20096
- CAST ALLOYS**
Preparation of eutectic superalloys by EFG ---
Edge-defined Film-fed Growth for directional
solidification in airfoil structures
A76-28029
- CERMETS**
Preparation of eutectic superalloys by EFG ---
Edge-defined Film-fed Growth for directional
solidification in airfoil structures
A76-28029
- CERTIFICATION**
The 1974 US civil airmen statistics
[AD-A013434] N76-20071
- CIRCULAR CYLINDERS**
The pressure distribution over the ogive nose of a
cylinder at large angles of inclination to a
uniform stream
[BU-173] N76-21168
- CIVIL AVIATION**
Economics of air transport --- Russian book
A76-26049
Licensing and the organization of the servicing
process in aircraft maintenance
A76-27363
Determination of the realizable flight hours for
aircraft
A76-27364
The outlook for aeronautics, 1980 - 2000 - Study
report --- trends affecting civil air
transportation and defense
[NASA-TM-X-72995] N76-20063
The outlook for aeronautics, 1980 - 2000: Appendix
B: Study group report on an
industry-university-government survey
[NASA-TM-X-72996] N76-20064
Domestic and world trends affecting the future of
aviation (1980 - 2000), appendix C
[NASA-TM-X-72997] N76-20065

CLASSIFICATIONS

SUBJECT INDEX

The outlook for aeronautics, 1980 - 2000:
 Executive summary --- trends affecting civil air
 transportation and air defense
 [NASA-TM-X-72998] N76-20066

Military aviation forecasts, fiscal years 1976 -
 1987
 [AD-A017622] N76-20068

Aviation forecast, fiscal years 1976 - 1987 ---
 air traffic in commercial and military aviation
 [AD-A017095] N76-20069

The 1974 US civil airman statistics
 [AD-A013434] N76-20071

Operational factors of air service to small
 communities
 [NASA-CR-137820] N76-20104

General aviation technology program
 [NASA-TM-X-73051] N76-20106

Cockpit systems study YAK 40: Rating of cockpit
 facilities, flight and systems properties of the
 aircraft by pilots
 [AD-A017198] N76-20134

CLASSIFICATIONS
 Types and ideal propulsive efficiency of
 aeronautical propulsion systems
 A76-26550

COCKPITS
 Selected problems of cockpit acoustic design
 A76-28545

Cockpit systems study YAK 40: Rating of cockpit
 facilities, flight and systems properties of the
 aircraft by pilots
 [AD-A017198] N76-20134

COMBINED STRESS
 Coupled bending-torsion vibrations of rotating
 blades
 [ASME PAPER 76-GT-43] A76-25792

COMBUSTION CHAMBERS
 Testing a fluidic temperature sensor on a subscale
 ramjet engine combustion chamber
 [AD-A016455] N76-20455

COMMAND GUIDANCE
 Improvement of the precision of aircraft control
 during completion of a plane turn maneuver
 A76-27930

COMMERCIAL AIRCRAFT
 Can R-W aircraft provide efficient commercial
 transport
 A76-27068

COMMUNICATION SATELLITES
 Aircraft L-band balloon simulated satellite
 experiments. Volume 1: Experiment description
 and data modem test results
 [AD-A017090] N76-20301

COMMUNITIES
 Operational factors of air service to small
 communities
 [NASA-CR-137820] N76-20104

COMPOSITE MATERIALS
 New developments in aeronautics technology ---
 alloys and composite materials review
 A76-26412

Design of a test machine for biaxial testing of
 composite-laminate cylinders
 [AD-A016961] N76-20232

COMPOSITE STRUCTURES
 Composite inlays increase flutter resistance of
 turbine engine fan blades
 [ASME PAPER 76-GT-29] A76-25781

Advanced composite fan blade flight evaluation
 program
 [ASME PAPER 76-GT-75] A76-25818

Increased rotor blade survivability --- composite
 geodesic structure
 [AD-A016929] N76-20130

COMPRESSIBLE FLOW
 Iterative calculation of two-dimensional
 compressible flow around ellipse and circular
 arc profile
 A76-27328

Subsonic loads on wings having sharp leading edges
 and tips
 A76-28606

COMPRESSOR BLADES
 Mathematical method of designing a certain
 compressor type plane blade cascade
 A76-27863

COMPUTATION
 Calculation of the reinforced thin-walled
 structures by the method of finite elements ---
 for reinforced shells such as fuselages
 [AD-A016387] N76-20545

COMPUTER PROGRAMS
 Prediction of light aircraft interior noise
 [NASA-TM-X-72838] N76-20940

Computer program for calculating pressure
 distribution and coefficients of wings, bodies,
 wing-body combinations and wing-tail
 combinations in subsonic, supersonic and
 hypersonic flow --- based on potential theory
 [MBB-UFE-1014-0] N76-21165

COMPUTERIZED SIMULATION
 Stimulation of a turbofan engine for evaluation of
 multivariable optimal control concepts ---
 (computerized simulation)
 [NASA-TM-X-71912] N76-21208

A simulation study of curved, descending,
 decelerating, landing approaches for transport
 aircraft
 [NASA-TN-D-8190] N76-21216

CONCORDE AIRCRAFT
 Limitations of the flight regime of a supersonic
 transport /SST/ by the sonic boom
 A76-28469

An investigation into the effect of castellating a
 blunt trailing edge in supersonic flow
 [BU-175] N76-21169

CONFERENCES
 Symposium Transsonicum II, Goettingen, West
 Germany, September 8-13, 1975, Proceedings
 A76-27826

Technical evaluation report of AGARD Specialists
 Meeting on WingWith-Stores Flutter --- for
 attack aircraft
 [AGARD-AR-96] N76-21163

CONFORMAL MAPPING
 Iterative calculation of two-dimensional
 compressible flow around ellipse and circular
 arc profile
 A76-27328

CONGRESSIONAL REPORTS
 Aircraft noise abatement
 [GPO-62-786] N76-20695

CONICAL BODIES
 An investigation into the effects of aspect ratio
 and centre keel camber on the aerodynamic
 characteristics of conical parawings
 [BU-176] N76-21170

CONSTRUCTION MATERIALS
 New developments in aeronautics technology ---
 alloys and composite materials review
 A76-26412

CONTINUOUS RADIATION
 Rotor blade effects on L-band signals received by
 helicopter antennas mounted above the rotor
 blade (CW) experiments
 [AD-A016866] N76-20360

CONTROLLABILITY
 Fundamental formulation of airship performance and
 flight dynamics
 A76-28033

COST ESTIMATES
 Weapon system costing methodology for aircraft
 airframes and basic structures. Volume 2:
 Estimating handbook and user's manual, part 1
 [AD-A016409] N76-21024

Weapon system costing methodology for aircraft
 airframes and basic structures. Volume 1:
 Technical volume
 [AD-A016408] N76-21194

Weapon system costing methodology for aircraft
 airframes and basic structures. Volume 2:
 Estimating handbook and user's manual, part 2
 [AD-A016410] N76-21195

CRASHES
 Impact dynamics research facility for full-scale
 aircraft crash testing
 [NASA-TN-D-8179] N76-21173

CRITICAL PRESSURE
 Critical pressure coefficient and component of
 local Mach number normal to the surface isobar
 for a swept wing
 [ESDU-75027] N76-21152

CURVES (GEOMETRY)

A simulation study of curved, descending, decelerating, landing approaches for transport aircraft
[NASA-TN-D-8190] N76-21216

CYLINDRICAL BODIES

A study of axial slot arrays on a circular cylinder for use on electrically small vehicles
[AD-A016564] N76-20339

D

DATA ACQUISITION

The identification of a precedence network associated with base level aircraft maintenance
[AD-A016389] N76-21017

DATA BASES

The identification of a precedence network associated with base level aircraft maintenance
[AD-A016389] N76-21017

DATA TRANSMISSION

Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results
[AD-A017090] N76-20301

DECELERATION

A simulation study of curved, descending, decelerating, landing approaches for transport aircraft
[NASA-TN-D-8190] N76-21216

DEICERS

Development of deicing techniques for dielectric windows
[AD-A017097] N76-20136

DELTA WINGS

Non-linear effect due to flow separation on flow past wings and wing body combinations
A76-27741

Extension of slender body theory
A76-28258

Supersonic flow past a slender delta wing. An experimental investigation covering the incidence range minus 5 deg less than or equal to angle of incidence less than or equal to 50 deg
[CRANFIELD-MEMO-7512] N76-21167

DESIGN ANALYSIS

Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils
A76-27837

Design of a 4 1/2 stage turbine with a stage loading factor of 4.66 and high specific work output
[NASA-CR-2659] N76-20146

DIELECTRICS

Development of deicing techniques for dielectric windows
[AD-A017097] N76-20136

DIFFERENCE EQUATIONS

Review of some numerical solutions of the transonic small disturbance equations
A76-27869

DIPOLE ANTENNAS

Flight test evaluation of a 240 to 400 MHz cavity-backed cross open-sleeve dipole antenna
[AD-A017298] N76-20386

Characteristics of a 240 to 400 MHz 6-inch depth cavity-backed cross open-sleeve dipole antenna on a curved ground plane
[AD-A017367] N76-20387

DISTRIBUTION FUNCTIONS

Effect of the upper limit of distribution function of aircraft structure on the main failure's distribution
A76-28254

DRAG REDUCTION

An investigation into the effect of castellating a blunt trailing edge in supersonic flow
[BU-175] N76-21169

DYNAMIC RESPONSE

Responses of small rigid aircraft to discrete and continuous gust analysis, phase 1
[AD-A020103/8] N76-21191

DYNAMIC STRUCTURAL ANALYSIS

Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling
[NASA-TN-D-8192] N76-21162

E

ECONOMIC ANALYSIS

Economics of air transport --- Russian book
A76-26049

A study of the financial history of the U.S. scheduled airlines and the improvement of airline profitability through technology
[NASA-TN-X-73109] N76-20101

Energy and economic trade offs for advanced technology subsonic aircraft
[NASA-TN-X-72833] N76-20124

EIGENVALUES

A comparison of matrix methods for calculating eigenvalues in acoustically lined ducts
[NASA-TN-D-8186] N76-20941

EJECTION SEATS

Ballistics of ejection seats
A76-27743

EJECTORS

Low cost hypermixing ejector ramjet program
[AD-A016430] N76-20148

ELASTIC BENDING

Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling
[NASA-TN-D-8192] N76-21162

ELECTRONIC EQUIPMENT TESTS

Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results
[AD-A017090] N76-20301

ELLIPTICITY

An investigation into the effect of castellating a blunt trailing edge in supersonic flow
[BU-175] N76-21169

ENERGY DISTRIBUTION

Energy and economic trade offs for advanced technology subsonic aircraft
[NASA-TN-X-72833] N76-20124

ENERGY TECHNOLOGY

Propulsion systems --- aircraft engine technology review
A76-26670

ENGINE CONTROL

A multi-variable control for a turbofan engine operating at sea level static
[ASME PAPER 76-GT-71] A76-25814

Control of a gas turbine HTGR --- High Temperature Gas-cooled Reactors
[ASME PAPER 76-GT-97] A76-25837

ENGINE DESIGN

Noise technology requirements for future aircraft powerplants
[ASME PAPER 76-GT-69] A76-25812

CPM56 turbofan engines - General Electric/SNECHA cooperative engineering development program
[ASME PAPER 76-GT-78] A76-25821

Primary system preliminary design for gas turbine HTGR power plant --- High Temperature Gas-cooled Reactors
[ASME PAPER 76-GT-92] A76-25833

Advanced turbine disk designs to increase reliability of aircraft engines
A76-25875

Propulsion systems --- aircraft engine technology review
A76-26670

Rocket engines GDL-OKB --- Soviet liquid propellant engine development history
A76-28100

ENGINE MONITORING INSTRUMENTS

Inflight engine performance evaluations --- applied to S-3A aircraft
[ASME PAPER 76-GT-70] A76-25813

ENGINE NOISE

Noise technology requirements for future aircraft powerplants
[ASME PAPER 76-GT-69] A76-25812

Results of noise and vibration studies on An-24 aircraft
A76-28542

ENGINE TESTS

The pulsed thermocouple for gas turbine application
[ASME PAPER 76-GT-1] A76-25758

A multi-variable control for a turbofan engine operating at sea level static
[ASME PAPER 76-GT-71] A76-25814

- Hypersonic research engine/aerothermodynamic integration model, experimental results. Volume 4: Mach 5 component integration and performance [NASA-TM-X-72824] N76-21209
- ENVIRONMENT SIMULATORS**
Windshield Flight Environment Simulator A76-26648
- ESCAPE SYSTEMS**
Ballistics of ejection seats A76-27743
- EUTECTIC ALLOYS**
Preparation of eutectic superalloys by EFG --- Edge-defined Film-fed Growth for directional solidification in airfoil structures A76-28029
- EXPERIMENTATION**
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results [AD-A017090] N76-20301
- EXTERNAL STORES**
Effect of the GBU-15 (cruciform wing) and GBU-15 (planar wing) stores on the aerodynamic characteristics of the F-4C aircraft [AD-A017378] N76-20135
Technical evaluation report of AGARD Specialists Meeting on WingWith-Stores Flutter --- for attack aircraft [AGARD-AR-96] N76-21163
- EXTERNALLY BLOWN FLAPS**
Swept edge to reduce the noise generated by turbulent flow over the edge A76-26751
Pressure distributions on a rectangular aspect-ratio-6, slotted supercritical airfoil wing with externally blown flaps [NASA-TM-X-3337] N76-20081
- F**
- F-4 AIRCRAFT**
Effect of the GBU-15 (cruciform wing) and GBU-15 (planar wing) stores on the aerodynamic characteristics of the F-4C aircraft [AD-A017378] N76-20135
- FAILURE ANALYSIS**
Investigation of accelerated life prediction techniques [AD-A016925] N76-20129
Analysis of failures in the parts of an aircraft undercarriage [AD-A017928] N76-21196
- FATIGUE LIFE**
Advanced turbine disk designs to increase reliability of aircraft engines A76-25875
Effect of gusts on helicopter loading A76-28259
Use of fracture mechanics in estimating structural life and inspection intervals --- airframe damage tolerance defined design A76-28607
Analysis of failures in the parts of an aircraft undercarriage [AD-A017928] N76-21196
- FATIGUE TESTS**
Review of investigations on aeronautical fatigue in the Federal Republic of Germany, July 1973 - April 1975 [LBF-S-119] N76-21601
- FIGHTER AIRCRAFT**
An update - Advanced aircraft oxygen systems A76-27144
Supercritical wing design for a fighter type experimental aircraft A76-27856
Representation of the drag polar of a fighter aircraft A76-28610
- FILM COOLING**
Aerodynamics and heat transfer at the trailing edge of transonic blades [ASME PAPER 76-GT-95] A76-25835
- FINITE DIFFERENCE THEORY**
Research in the UK on finite difference methods for computing steady transonic flows A76-27874
- A direct method for computing non-symmetrical plane flows at Mach number one A76-27878
- FINITE ELEMENT METHOD**
Calculation of the reinforced thin-walled structures by the method of finite elements --- for reinforced shells such as fuselages [AD-A016387] N76-20545
- FLAPS (CONTROL SURFACES)**
On the motion of shock waves on an airfoil with oscillating flap A76-27830
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results [NASA-CR-137747] N76-21159
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 2. Acoustic test results [NASA-CR-137748] N76-21160
- FLAT PLATES**
Drag due to grooves in a flat plate with turbulent boundary layer, at subsonic and supersonic speeds [ESDU-75028] N76-21153
- FLEXIBLE BODIES**
Dynamics and identification of flexible aircraft [NASA-CR-2672] N76-21158
- FLIGHT ALTITUDE**
Measurements of the vertical movements of an aircraft --- altitude and velocity measurement accuracy [ESA-TT-215] N76-20152
- FLIGHT CHARACTERISTICS**
Fundamental formulation of airship performance and flight dynamics A76-28033
Flight test of the aerospatiale SA-342 helicopter [AD-A016921] N76-20131
- FLIGHT CONTROL**
Roll-axis hydrofluidic stability augmentation system development [AD-A016932] N76-20154
- FLIGHT CREWS**
The 1974 US civil airmen statistics [AD-A013434] N76-20071
- FLIGHT MECHANICS**
Dynamics of helicopter flight --- Book A76-26450
- FLIGHT OPTIMIZATION**
Limitations of the flight regime of a supersonic transport /SST/ by the sonic boom A76-28469
- FLIGHT PATHS**
A simulation study of curved, descending, decelerating, landing approaches for transport aircraft [NASA-TN-D-8190] N76-21216
- FLIGHT RECORDERS**
Mechanical engineering and aeronautical research projects [DME/NAE-1975(4)] N76-20156
- FLIGHT SAFETY**
Engineering aspects of flight safety --- Russian book A76-26048
AGARD highlights, March 1976 [AGARD-HIGHLIGHTS-76/1] N76-20067
- FLIGHT SIMULATION**
Windshield Flight Environment Simulator A76-26648
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results [AD-A017090] N76-20301
- FLIGHT TESTS**
Inflight engine performance evaluations --- applied to S-3A aircraft [ASME PAPER 76-GT-70] A76-25813
Advanced composite fan blade flight evaluation program [ASME PAPER 76-GT-75] A76-25818
Flight test of the aerospatiale SA-342 helicopter [AD-A016921] N76-20131
Flight test evaluation of a 240 to 400 MHz cavity-backed cross open-sleeve dipole antenna [AD-A017298] N76-20386

SUBJECT INDEX

GERMANY

- Aircraft noise definition. Phase 2: Analysis of flyover-noise data for DC-8-61 aircraft --- flight tests for noise measurement of jet aircraft noise [AD-A019759/0] N76-21211
- FLIGHT TIME**
Determination of the realizable flight hours for aircraft A76-27364
- FLOW DISTORTION**
The direct problem of the transonic airfoils on the hodograph A76-27838
Supercritical flow past airfoils at Mach numbers close to one A76-27877
Numerical solutions for transonic flows past wing-body combinations A76-27880
Note on a numerical scheme for the three-dimensional flow of a supercavitating wing or strut with thin cavity A76-28642
Vortex maneuver lift for super-cruise configurations [NASA-TM-X-72836] N76-21161
- FLOW EQUATIONS**
A direct method for computing non-symmetrical plane flows at Mach number one A76-27878
- FLOW THEORY**
A linearized theory of three-dimensional airfoils in nonuniform flow A76-27329
Extension of slender body theory A76-28258
- FLOW VISUALIZATION**
An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1 A76-27857
Visualization of the subsonic flow around two space glider configurations --- using hydrogen bubble technique in water basin [DLR-FB-75-49] N76-20083
Supersonic flow past a slender delta wing. An experimental investigation covering the incidence range minus 5 deg less than or equal to angle of incidence less than or equal to 50 deg [CRANFIELD-MEMO-7512] N76-21167
- FLUIDICS**
Testing a fluidic temperature sensor on a subscale ramjet engine combustion chamber [AD-A016455] N76-20455
- FLUTTER**
Fully unsteady subsonic and supersonic potential aerodynamics for complex aircraft configurations for flutter applications [NASA-CR-146573] N76-20077
Technical evaluation report of AGARD Specialists Meeting on Wing-With-Stores Flutter --- for attack aircraft [AGARD-AR-96] N76-21163
Flutter of asymmetrically swept wings [NASA-CR-146815] N76-21164
- FLUTTER ANALYSIS**
Composite inlays increase flutter resistance of turbine engine fan blades [ASME PAPER 76-GT-29] A76-25781
- FOG DISPERSAL**
Interaction of a buoyant turbulent planar jet with a co-flowing wind [AD-A018060] N76-21172
- FORECASTING**
The outlook for aeronautics, 1980 - 2000 - Study report --- trends affecting civil air transportation and defense [NASA-TM-X-72995] N76-20063
Domestic and world trends affecting the future of aviation (1980 - 2000), appendix C [NASA-TM-X-72997] N76-20065
The outlook for aeronautics, 1980 - 2000: Executive summary --- trends affecting civil air transportation and air defense [NASA-TM-X-72998] N76-20066
Military aviation forecasts, fiscal years 1976 - 1987 [AD-A017622] N76-20068
Aviation forecast, fiscal years 1976 - 1987 --- air traffic in commercial and military aviation [AD-A017095] N76-20069
- Demand forecasting with program factors [AD-A017858] N76-21193
- FORESTS**
Aircraft use in agriculture and forestry --- spraying with helicopters and light aircraft in the U.S.S.R. [NASA-TT-F-16846] N76-20078
- FRACTURE STRENGTH**
Use of fracture mechanics in estimating structural life and inspection intervals --- airframe damage tolerance defined design A76-28607
- FREE FLOW**
Subsonic loads on wings having sharp leading edges and tips A76-28606
- FUEL CONSUMPTION**
Can R-W aircraft provide efficient commercial transport A76-27068
- FUSELAGES**
Calculation of the reinforced thin-walled structures by the method of finite elements --- for reinforced shells such as fuselages [AD-A016387] N76-20545
- FV-12A AIRCRAFT**
XFV-12A propulsion system development [ASME PAPER 76-GT-125] A76-25855
- G**
- GAS FLOW**
Iterative calculation of two-dimensional compressible flow around ellipse and circular arc profile A76-27328
- GAS TURBINE ENGINES**
The pulsed thermocouple for gas turbine application [ASME PAPER 76-GT-1] A76-25758
High performance epicyclic gears for gas turbines --- for marine and industrial applications [ASME PAPER 76-GT-88] A76-25829
Primary system preliminary design for gas turbine HTGR power plant --- High Temperature Gas-cooled Reactors [ASME PAPER 76-GT-92] A76-25833
Control of a gas turbine HTGR --- High Temperature Gas-cooled Reactors [ASME PAPER 76-GT-97] A76-25837
Advanced turbine disk designs to increase reliability of aircraft engines A76-25875
Heat transfer in high-temperature GTE air-cooled turbine blades A76-26584
- GAS TURBINES**
A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator [ASME PAPER 76-GT-84] A76-25825
The potential of oxide dispersion strengthened superalloys for advanced gas turbines [ASME PAPER 76-GT-118] A76-25851
- GEARS**
High performance epicyclic gears for gas turbines --- for marine and industrial applications [ASME PAPER 76-GT-88] A76-25829
- GENERAL AVIATION AIRCRAFT**
The general aviation industry; an overview [AD-A015871] N76-20072
Impact dynamics research facility for full-scale aircraft crash testing [NASA-TM-D-8179] N76-21173
Responses of small rigid aircraft to discrete and continuous gust analysis, phase 1 [AD-A020103/8] N76-21191
Sources and characteristics of interior noise in general aviation aircraft [NASA-TM-X-72839] N76-21990
- GEODESIC LINES**
Increased rotor blade survivability --- composite geodesic structure [AD-A016929] N76-20130
- GERMANY**
Review of investigations on aeronautical fatigue in the Federal Republic of Germany, July 1973 - April 1975 [LBP-S-119] N76-21601

GLIDERS

GLIDERS

- Visualization of the subsonic flow around two space glider configurations --- using hydrogen bubble technique in water basin
[DIR-FB-75-49] N76-20083
- GOVERNMENT/INDUSTRY RELATIONS**
The outlook for aeronautics, 1980 - 2000: Appendix B: Study group report on an industry-university-government survey
[NASA-TM-X-72996] N76-20064
- GROUND EFFECT**
The ground effect on the aerodynamic characteristics of an aircraft --- steady horizontal flight
[AD-A017309] N76-20098
Investigation of vortex wake stability near the ground
[AD-A017586] N76-20112
- GROUND TESTS**
Phase 2 program on ground test of refanned JT8D turbofan engines and nacelles for the 727 airplane. Volume 3: Ground tests
[NASA-CR-134799] N76-21189
Phase 2 program on ground test of refanned JT8D turbofan engines and nacelles for the 727 airplane. Volume 4: Airplane evaluation and analysis
[NASA-CR-134800] N76-21190
- GUST LOADS**
Effect of gusts on helicopter loading
A76-28259
Responses of small rigid aircraft to discrete and continuous gust analysis, phase 1
[AD-A020103/8] N76-21191

H

HARMONIC OSCILLATION

- An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
On the motion of shock waves on an airfoil with oscillating flap
A76-27830
- HEAT EXCHANGERS**
A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator
[ASME PAPER 76-GT-84] A76-25825
- HEAT RESISTANT ALLOYS**
The potential of oxide dispersion strengthened superalloys for advanced gas turbines
[ASME PAPER 76-GT-118] A76-25851
New developments in aeronautics technology --- alloys and composite materials review
A76-26412
- HEAT TRANSFER**
An analysis of heat transfer on a Joukowski airfoil with separation and reattachment
[AD-A016457] N76-20091
- HEAT TRANSFER COEFFICIENTS**
Heat transfer in high-temperature GTE air-cooled turbine blades
A76-26584
- HELICOPTER CONTROL**
Dynamics of helicopter flight --- Book
A76-26450
A comparison of optimal control theory predictions with actual pilot performance in a helicopter longitudinal tracking task
[AD-A016441] N76-20153
- HELICOPTER DESIGN**
Transonic aerodynamics and the helicopter rotor
A76-27864
Effect of gusts on helicopter loading
A76-28259
Increased rotor blade survivability --- composite geodesic structure
[AD-A016929] N76-20130
Flight test of the aerospace SA-342 helicopter
[AD-A016921] N76-20131
- HELICOPTER PERFORMANCE**
Dynamics of helicopter flight --- Book
A76-26450
Transonic aerodynamics and the helicopter rotor
A76-27864
- HELICOPTER PROPELLER DRIVE**
Helicopter rotor blades - The new technology
A76-28693

SUBJECT INDEX

HELICOPTERS

- Aircraft use in agriculture and forestry --- spraying with helicopters and light aircraft in the U.S.S.R.
[NASA-TT-F-16846] N76-20078
- Investigation of accelerated life prediction techniques
[AD-A016925] N76-20129
Flight test of the aerospace SA-342 helicopter
[AD-A016921] N76-20131
- HIGH ALTITUDE BALLOONS**
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modern test results
[AD-A017090] N76-20301
- HIGH ASPECT RATIO**
The design of unswept large aspect ratio wings with flaps for two flight conditions
[ESA-TT-224] N76-20128
- HIGH TEMPERATURE GAS COOLED REACTORS**
Primary system preliminary design for gas turbine HTGR power plant --- High Temperature Gas-cooled Reactors
[ASME PAPER 76-GT-92] A76-25833
Control of a gas turbine HTGR --- High Temperature Gas-cooled Reactors
[ASME PAPER 76-GT-97] A76-25837
- HIGH TEMPERATURE GASES**
Heat transfer in high-temperature GTE air-cooled turbine blades
A76-26584
- HISTORIES**
History of Messerschmitt aircraft manufacturing
[DLR-MITT-75-21] N76-20070
- HODOGRAPHS**
Asymptotic representation of solutions on the hodograph plane in problems of subsonic flow past airfoil profiles
A76-26337
Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils
A76-27837
The direct problem of the transonic airfoils on the hodograph
A76-27838
An exact hodograph method for the design of supercritical wing sections
A76-27860
- HORIZONTAL FLIGHT**
The ground effect on the aerodynamic characteristics of an aircraft --- steady horizontal flight
[AD-A017309] N76-20098
- HOVERING**
Dynamics of helicopter flight --- Book
A76-26450
Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling
[NASA-TN-D-8192] N76-21162
- HUMAN FACTORS ENGINEERING**
Selected problems of cockpit acoustic design
A76-28545
- HUMAN PERFORMANCE**
Ergonomics and the problem of aircraft-induced external noise
A76-28543
- HURRICANES**
AGARD highlights, March 1976
[AGARD-HIGHLIGHTS-76/1] N76-20067
- HYDRAULIC CONTROL**
Hydraulic systems for transport aircraft --- Russian book
A76-28354
- HYDRAULIC EQUIPMENT**
Roll-axis hydrofluidic stability augmentation system development
[AD-A016932] N76-20154
- HYPERSONIC FLIGHT**
Hypersonic research engine/aerothermodynamic integration model, experimental results. Volume 4: Mach 5 component integration and performance
[NASA-TM-X-72824] N76-21209
- HYPERSONIC FLOW**
Interaction between an external shock wave and a blunted body in hypersonic flow
A76-26339

- I**
- ICE PREVENTION**
A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator
[ASME PAPER 76-GT-84] A76-25825
- IMPACT DAMAGE**
Impact dynamics research facility for full-scale aircraft crash testing
[NASA-TN-D-8179] N76-21173
- IN-FLIGHT MONITORING**
Inflight engine performance evaluations --- applied to S-3A aircraft
[ASME PAPER 76-GT-70] A76-25813
- INCOMPRESSIBLE FLOW**
Analysis of circulation controlled airfoils A76-28611
- INDUSTRIAL MANAGEMENT**
Economics of air transport --- Russian book A76-26049
- INLET FLOW**
An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator
[ASME PAPER 76-GT-84] A76-25825
- INLET PRESSURE**
Modeling and analysis of the TF30-P-3 compressor system with inlet pressure distortion
[NASA-CR-134996] N76-21205
- INSPECTION**
Use of fracture mechanics in estimating structural life and inspection intervals --- airframe damage tolerance defined design A76-28607
- INSTRUMENT LANDING SYSTEMS**
Characteristics of wake vortex generated by a boeing 727 jet transport during two-segment and normal ILS approach flight paths
[NASA-TN-D-8222] N76-21175
- INTAKE SYSTEMS**
A new system for preventing icing of gas turbine inlets --- combination heat exchanger/moisture separator
[ASME PAPER 76-GT-84] A76-25825
- INTEGRAL EQUATIONS**
Airfoil design for a prescribed velocity distribution in transonic flow by an integral method A76-27844
- INTERNATIONAL COOPERATION**
CFM56 turbofan engines - General Electric/SNECMA cooperative engineering development program
[ASME PAPER 76-GT-78] A76-25821
- INVENTORY CONTROLS**
Demand forecasting with program factors
[AD-A017858] N76-21193
- INVISID FLOW**
Research in the UK on finite difference methods for computing steady transonic flows A76-27874
Numerical solutions for transonic flows past wing-body combinations A76-27880
- ITERATIVE SOLUTION**
Iterative calculation of two-dimensional compressible flow around ellipse and circular arc profile A76-27328
- J**
- JET AIRCRAFT**
Cockpit systems study YAK 40: Rating of cockpit facilities, flight and systems properties of the aircraft by pilots
[AD-A017198] N76-20134
Effect of the GBU-15 (cruciform wing) and GBU-15 (planar wing) stores on the aerodynamic characteristics of the F-4C aircraft
[AD-A017378] N76-20135
Manual and automatic flight control during severe turbulence penetration
[NASA-CR-2677] N76-20151
- The identification of a precedence network associated with base level aircraft maintenance
[AD-A016389] N76-21017
- JET AIRCRAFT NOISE**
Advanced Acoustic Nacelle concepts A76-25786
[ASME PAPER 76-GT-35]
Noise technology requirements for future aircraft powerplants A76-25812
[ASME PAPER 76-GT-69]
Swept edge to reduce the noise generated by turbulent flow over the edge A76-26751
- The amplification of broadband jet noise by pure tone excitation
[DLR-PB-75-72] N76-20942
Aircraft noise definition. Phase 2: Analysis of flyover-noise data for DC-8-61 aircraft --- flight tests for noise measurement of jet aircraft noise
[AD-A019759/0] N76-21211
- JET MIXING FLOW**
Low cost hypermixing ejector ramjet program
[AD-A016430] N76-20148
- K**
- KEELS**
An investigation into the effects of aspect ratio and centre keel camber on the aerodynamic characteristics of conical parawings
[BU-176] N76-21170
- L**
- LAMINAR FLOW**
The pressure distribution over the ogive nose of a cylinder at large angles of inclination to a uniform stream
[BU-173] N76-21168
- LAMINATES**
Design of a test machine for biaxial testing of composite-laminate cylinders
[AD-A016961] N76-20232
- LANDING GEAR**
Feasibility determination of a dynamic taxi facility for evaluating military landing gear systems
[AD-A017038] N76-20169
- LANDING SPEED**
Some considerations in the design of transport aircraft /The W. Rupert Turnbull Lecture for 1975/
A76-27274
- LEADING EDGE SWEEP**
Swept edge to reduce the noise generated by turbulent flow over the edge A76-26751
- LEADING EDGES**
Non-linear effect due to flow separation on flow past wings and wing body combinations A76-27741
- LIFT DRAG RATIO**
An investigation into the effects of aspect ratio and centre keel camber on the aerodynamic characteristics of conical parawings
[BU-176] N76-21170
- LIFT FANS**
Mechanical engineering and aeronautical research projects
[DME/NAE-1975(4)] N76-20156
- LIFTING BODIES**
An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1 A76-27857
- LIGHT AIRCRAFT**
Aircraft use in agriculture and forestry --- spraying with helicopters and light aircraft in the U.S.S.R.
[NASA-TT-F-16846] N76-20078
- LINEARIZATION**
A linearized theory of three-dimensional airfoils in nonuniform flow A76-27329
- LININGS**
A comparison of matrix methods for calculating eigenvalues in acoustically lined ducts
[NASA-TN-D-8186] N76-20941
- LIQUID OXYGEN**
An update - Advanced aircraft oxygen systems A76-27144

LIQUID PROPELLANT ROCKET ENGINES

Rocket engines GDL-OKB --- Soviet liquid propellant engine development history A76-28100

LOAD DISTRIBUTION (FORCES)
High performance epicyclic gears for gas turbines --- for marine and industrial applications [ASME PAPER 76-GT-88] A76-25829

LOGISTICS MANAGEMENT
The identification of a precedence network associated with base level aircraft maintenance [AD-A016389] N76-21017
Demand forecasting with program factors [AD-A017858] N76-21193

LONGITUDINAL CONTROL
A comparison of optimal control theory predictions with actual pilot performance in a helicopter longitudinal tracking task [AD-A016441] N76-20153

LONGITUDINAL STABILITY
Aerodynamic derivatives of the longitudinal motion of the whole aircraft A76-28256

LOW COST
Low cost hypermixing ejector ramjet program [AD-A016430] N76-20148

LOW FREQUENCIES
Prediction of light aircraft interior noise [NASA-TM-X-72838] N76-20940

M

MAGNETOMETERS
Magnetic heading reference [NASA-CASE-LAR-11387-1] N76-20114

MAN MACHINE SYSTEMS
Ergonomics and the problem of aircraft-induced external noise A76-28543

MANUAL CONTROL
Manual and automatic flight control during severe turbulence penetration [NASA-CR-2677] N76-20151

MARKET RESEARCH
Domestic and world trends affecting the future of aviation (1980 - 2000), appendix C [NASA-TM-X-72997] N76-20065

MATHEMATICAL MODELS
An aircraft noise pollution model for trajectory optimization A76-26384

MATRIX METHODS
A comparison of matrix methods for calculating eigenvalues in acoustically lined ducts [NASA-TN-D-8186] N76-20941

MECHANICAL PROPERTIES
New developments in aeronautics technology --- alloys and composite materials review A76-26412
Helicopter rotor blades - The new technology A76-28693

METAL MATRIX COMPOSITES
Advanced composite fan blade flight evaluation program [ASME PAPER 76-GT-75] A76-25818

METAL OXIDES
The potential of oxide dispersion strengthened superalloys for advanced gas turbines [ASME PAPER 76-GT-118] A76-25851

MILITARY AIR FACILITIES
Aviation forecast, fiscal years 1976 - 1987 --- air traffic in commercial and military aviation [AD-A017095] N76-20069

MILITARY AIRCRAFT
Military aviation forecasts, fiscal years 1976 - 1987 [AD-A017622] N76-20068
Feasibility determination of a dynamic taxi facility for evaluating military landing gear systems [AD-A017038] N76-20169
Demand forecasting with program factors [AD-A017858] N76-21193

MINIMUM DRAG
Optimal supersonic wing profile of given thickening A76-26338

MISSILE ANTENNAS

A study of axial slot arrays on a circular cylinder for use on electrically small vehicles [AD-A016564] N76-20339

MODEMS
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results [AD-A017090] N76-20301

MOTION STABILITY
Aerodynamic derivatives of the longitudinal motion of the whole aircraft A76-28256

N

NACELLES
Advanced Acoustic Nacelle concepts [ASME PAPER 76-GT-35] A76-25786
Nozzle afterbody configuration development for the B-1 strategic bomber [AIAA PAPER 74-1102] A76-28608
Phase 2 program on ground test of refanned JT8D turbofan engines and nacelles for the 727 airplane. Volume 3: Ground tests [NASA-CR-134799] N76-21189

NAVIGATION AIDS
Magnetic heading reference [NASA-CASE-LAR-11387-1] N76-20114

NICKEL ALLOYS
The potential of oxide dispersion strengthened superalloys for advanced gas turbines [ASME PAPER 76-GT-118] A76-25851
Preparation of eutectic superalloys by EFG --- Edge-defined Film-fed Growth for directional solidification in airfoil structures A76-28029

NOISE GENERATORS
Selected problems of cockpit acoustic design A76-28545
Sources and characteristics of interior noise in general aviation aircraft [NASA-TM-X-72839] N76-21990

NOISE MEASUREMENT
Results of noise and vibration studies on An-24 aircraft A76-28542
Ergonomics and the problem of aircraft-induced external noise A76-28543
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results [NASA-CR-137747] N76-21159
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 2. Acoustic test results [NASA-CR-137748] N76-21160
Aircraft noise definition. Phase 2: Analysis of flyover-noise data for DC-8-61 aircraft --- flight tests for noise measurement of jet aircraft noise [AD-A019759/0] N76-21211

NOISE POLLUTION
An aircraft noise pollution model for trajectory optimization A76-26384
Ergonomics and the problem of aircraft-induced external noise A76-28543

NOISE REDUCTION
Aircraft noise abatement [GPO-62-786] N76-20695
Advanced Acoustic Nacelle concepts [ASME PAPER 76-GT-35] A76-25786
Noise technology requirements for future aircraft powerplants [ASME PAPER 76-GT-69] A76-25812
Status report - Subsonic aircraft noise reduction [ASME PAPER 76-GT-116] A76-25849
An aircraft noise pollution model for trajectory optimization A76-26384
Swept edge to reduce the noise generated by turbulent flow over the edge A76-26751
Ergonomics and the problem of aircraft-induced external noise A76-28543

- Bibliography on aircraft noise
[POK-N-00-28] N76-20138
- Mechanical engineering and aeronautical research projects
[DME/NAE-1975(4)] N76-20156
- Noise reduction from the redesign of a fan stage to minimize stator lift fluctuations
[NASA-TM-X-71896] N76-21206
- Coupling of Helmholtz resonators to improve acoustic liners for turbofan engines at low frequency
[NASA-CR-134912] N76-21210
- NONLINEAR EQUATIONS**
Review of some numerical solutions of the transonic small disturbance equations
A76-27869
- NONUNIFORM FLOW**
A linearized theory of three-dimensional airfoils in nonuniform flow
A76-27329
- NOZZLE DESIGN**
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results
[NASA-CR-137747] N76-21159
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 2. Acoustic test results
[NASA-CR-137748] N76-21160
- NOZZLE GEOMETRY**
Nozzle afterbody configuration development for the B-1 strategic bomber
[AIAA PAPER 74-1102] A76-28608
- NUMERICAL ANALYSIS**
A review of numerical techniques for calculating supercritical airfoil flows
A76-27865
Some numerical results of a new three-dimensional transonic flow method
A76-27875
Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program --- numerical analysis of tactics and aircraft maneuvers of supersonic attack aircraft
[NASA-CR-137819] N76-21188
- NUMERICAL INTEGRATION**
A direct method for computing non-symmetrical plane flows at Mach number one
A76-27878
Transonic airfoil design using Cartesian coordinates
[NASA-CR-2578] N76-20082
- O**
- OBLIQUE SHOCK WAVES**
Interaction between an external shock wave and a blunted body in hypersonic flow
A76-26339
- OGIVES**
The pressure distribution over the ogive nose of a cylinder at large angles of inclination to a uniform stream
[BU-173] N76-21168
- OH-58 HELICOPTER**
Roll-axis hydrofluidic stability augmentation system development
[AD-A016932] N76-20154
- ONBOARD EQUIPMENT**
Magnetic heading reference
[NASA-CASE-LAR-11387-1] N76-20114
- OPTIMAL CONTROL**
A comparison of optimal control theory predictions with actual pilot performance in a helicopter longitudinal tracking task
[AD-A016441] N76-20153
Stimulation of a turbofan engine for evaluation of multivariable optimal control concepts --- (computerized simulation)
[NASA-TM-X-71912] N76-21208
- OSCILLATING FLOW**
Some developments in unsteady transonic flow research
A76-27827
- Unsteady surface flow behavior on a cascade of airfoils oscillating below stall
[AD-A017073] N76-20096
- OSCILLATIONS**
Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade
[AD-A017203] N76-20095
- OXYGEN SUPPLY EQUIPMENT**
An update - Advanced aircraft oxygen systems
A76-27144
- P**
- PARAWINGS**
An investigation into the effects of aspect ratio and centre keel camber on the aerodynamic characteristics of conical parawings
[BU-176] N76-21170
- PERFORMANCE TESTS**
Inflight engine performance evaluations --- applied to S-3A aircraft
[ASME PAPER 76-GT-70] A76-25813
- PERSONNEL MANAGEMENT**
Licensing and the organization of the servicing process in aircraft maintenance
A76-27363
- PERTURBATION THEORY**
The analysis of arbitrary wingbody combinations in transonic flow using a relaxation method
A76-27879
- PILOT ERROR**
Major orientation-error accidents in regular Army UH-1 aircraft during fiscal year 1971 (accident factors)
[AD-A017665] N76-21178
- PILOT PERFORMANCE**
A comparison of optimal control theory predictions with actual pilot performance in a helicopter longitudinal tracking task
[AD-A016441] N76-20153
- PIPES (TUBES)**
Design of a test machine for biaxial testing of composite-laminate cylinders
[AD-A016961] N76-20232
- PLAYBACKS**
Mechanical engineering and aeronautical research projects
[DME/NAE-1975(4)] N76-20156
- POLLUTION CONTROL**
Aircraft noise abatement
[GPO-62-786] N76-20695
- POTENTIAL FLOW**
Some developments in unsteady transonic flow research
A76-27827
Analysis of circulation controlled airfoils
A76-28611
A method for the calculation of the twist and camber of a wing with a specified load distribution in the presence of a fuselage --- theoretical potential flow method
[ESA-TT-214] N76-20087
- POTENTIAL THEORY**
Computer program for calculating pressure distribution and coefficients of wings, bodies, wing-body combinations and wing-tail combinations in subsonic, supersonic and hypersonic flow --- based on potential theory
[HBB-UPE-1014-0] N76-21165
- PRECIPITATION HARDENING**
The potential of oxide dispersion strengthened superalloys for advanced gas turbines
[ASME PAPER 76-GT-118] A76-25851
- PREDICTION ANALYSIS TECHNIQUES**
Prediction of light aircraft interior noise
[NASA-TM-X-72838] N76-20940
- PRESSURE DISTRIBUTION**
Calculation of buffet onset for supercritical airfoils
A76-27832
Pressure distributions on a rectangular aspect-ratio-6, slotted supercritical airfoil wing with externally blown flaps
[NASA-TM-X-3337] N76-20081
Critical pressure coefficient and component of local Mach number normal to the surface isobar for a swept wing
[ESDU-75027] N76-21152

PRODUCT DEVELOPMENT

SUBJECT INDEX

Computer program for calculating pressure distribution and coefficients of wings, bodies, wing-body combinations and wing-tail combinations in subsonic, supersonic and hypersonic flow --- based on potential theory [NBB-UPE-1014-0] N76-21165

Supersonic flow past a slender delta wing. An experimental investigation covering the incidence range minus 5 deg less than or equal to angle of incidence less than or equal to 50 deg [CRANFIELD-MEMO-7512] N76-21167

The pressure distribution over the ogive nose of a cylinder at large angles of inclination to a uniform stream [BU-173] N76-21168

PRODUCT DEVELOPMENT

Rocket engines GDL-OKB --- Soviet liquid propellant engine development history A76-28100

PROFILES

Transonic airfoil design using Cartesian coordinates [NASA-CR-2578] N76-20082

PROJECT MANAGEMENT

CPM56 turbofan engines - General Electric/SNECMA cooperative engineering development program [ASME PAPER 76-GT-78] A76-25821

PROPELLERS

Sources and characteristics of interior noise in general aviation aircraft [NASA-TM-X-72839] N76-21990

PROPULSION SYSTEM CONFIGURATIONS

XPV-12A propulsion system development [ASME PAPER 76-GT-125] A76-25855

PROPULSION SYSTEM PERFORMANCE

Types and ideal propulsive efficiency of aeronautical propulsion systems A76-26550

Propulsion systems --- aircraft engine technology review A76-26670

PROPULSIVE EFFICIENCY

Propulsion systems --- aircraft engine technology review A76-26670

Q

QUALITY CONTROL

Some basic questions concerning quality assurance in aircraft maintenance A76-27361

Quality assurance by standardization --- for aircraft maintenance and spare parts manufacturing A76-27362

R

RAMJET ENGINES

Low cost, hypermixing ejector ramjet program [AD-A016430] N76-20148

Testing a fluidic temperature sensor on a subscale ramjet engine combustion chamber [AD-A016455] N76-20455

Hypersonic research engine/aerothermodynamic integration model, experimental results. Volume 4: Mach 5 component integration and performance [NASA-TM-X-72824] N76-21209

REACTOR SAFETY

Control of a gas turbine HTGR --- High Temperature Gas-cooled Reactors [ASME PAPER 76-GT-97] A76-25837

REATTACHED FLOW

An analysis of heat transfer on a Joukowski airfoil with separation and reattachment [AD-A016457] N76-20091

REENTRY VEHICLES

Visualization of the subsonic flow around two space glider configurations --- using hydrogen bubble technique in water basin [DLR-FB-75-49] N76-20083

REFRACTORY METAL ALLOYS

Preparation of eutectic superalloys by EFG --- Edge-defined Film-fed Growth for directional solidification in airfoil structures A76-28029

REINFORCED PLASTICS

Helicopter rotor blades - The new technology A76-28693

REINFORCED SHELLS

Calculation of the reinforced thin-walled structures by the method of finite elements --- for reinforced shells such as fuselages [AD-A016387] N76-20545

REINFORCEMENT (STRUCTURES)

Calculation of the reinforced thin-walled structures by the method of finite elements --- for reinforced shells such as fuselages [AD-A016387] N76-20545

RELAXATION METHOD (MATHEMATICS)

The analysis of arbitrary wingbody combinations in transonic flow using a relaxation method A76-27879

RELIABILITY ANALYSIS

Estimation of population reliability function of aircraft structures from a limited fleet of aircraft A76-28255

RELIABILITY ENGINEERING

Advanced turbine disk designs to increase reliability of aircraft engines A76-25875

Engineering aspects of flight safety --- Russian book A76-26048

RESEARCH MANAGEMENT

The outlook for aeronautics, 1980 - 2000 - Study report --- trends affecting civil air transportation and defense [NASA-TM-X-72995] N76-20063

The outlook for aeronautics, 1980 - 2000: Executive summary --- trends affecting civil air transportation and air defense [NASA-TM-X-72998] N76-20066

RESONATORS

Coupling of Helmholtz resonators to improve acoustic liners for turbofan engines at low frequency [NASA-CR-134912] N76-21210

RIGID ROTORS

Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling [NASA-TN-D-8192] N76-21162

RIGID STRUCTURES

Responses of small rigid aircraft to discrete and continuous gust analysis, phase 1 [AD-A020103/8] N76-21191

ROTARY WING AIRCRAFT

Can R-W aircraft provide efficient commercial transport A76-27068

ROTARY WINGS

Transonic aerodynamics and the helicopter rotor A76-27864

Effect of gusts on helicopter loading A76-28259

Helicopter rotor blades - The new technology A76-28693

Increased rotor blade survivability --- composite geodesic structure [AD-A016929] N76-20130

Rotor blade effects on L-band signals received by helicopter antennas mounted above the rotor blade (CW) experiments [AD-A016866] N76-20360

Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling [NASA-TN-D-8192] N76-21162

ROTATING DISKS

Coupled bending-torsion vibrations of rotating blades [ASME PAPER 76-GT-43] A76-25792

ROTOR AERODYNAMICS

Aerodynamics and heat transfer at the trailing edge of transonic blades [ASME PAPER 76-GT-95] A76-25835

Dynamics of helicopter flight --- Book A76-26450

Transonic aerodynamics and the helicopter rotor A76-27864

Effect of gusts on helicopter loading A76-28259

Design of a 4 1/2 stage turbine with a stage loading factor of 4.66 and high specific work output [NASA-CR-2659] N76-20146

Noise reduction from the redesign of a fan stage
to minimize stator lift fluctuations
[NASA-TM-X-71896] N76-21206

ROTOR BLADES
Aerodynamics and heat transfer at the trailing
edge of transonic blades
[ASMP PAPER 76-GT-95] A76-25835

ROTOR BLADES (TURBOMACHINERY)
Helicopter rotor blades - The new technology
A76-28693

S

S-3 AIRCRAFT
Inflight engine performance evaluations ---
applied to S-3A aircraft
[ASME PAPER 76-GT-70] A76-25813

SAFETY FACTORS
An update - Advanced aircraft oxygen systems
A76-27144

SCALE MODELS
RSRA sixth scale wind tunnel test --- of scale
model of Sikorsky Whirlwind Helicopter
[NASA-CR-144964] N76-20126

SEPARATED FLOW
Non-linear effect due to flow separation on flow
past wings and wing body combinations
A76-27741

An analysis of heat transfer on a Joukowski
airfoil with separation and reattachment
[AD-A016457] N76-20091

SHARP LEADING EDGES
Subsonic loads on wings having sharp leading edges
and tips
A76-28606

SHEAR LAYERS
Experiments on thin airfoils spanning a transonic
shear flow
N76-20073

SHOCK WAVE ATTENUATION
Ergonomic analysis of maneuvers leading to
inaudibility of a shock wave
A76-28544

SHOCK WAVE INTERACTION
Optimal supersonic wing profile of given thickening
A76-26338

Interaction between an external shock wave and a
blunted body in hypersonic flow
A76-26339

SHOCK WAVE PROPAGATION
On the motion of shock waves on an airfoil with
oscillating flap
A76-27830

SHORT HAUL AIRCRAFT
Can R-W aircraft provide efficient commercial
transport
A76-27068

Operational factors of air service to small
communities
[NASA-CR-137820] N76-20104

SHORT TAKEOFF AIRCRAFT
Three component measurements on a light STOL
aircraft with chordwise blowing
[DLR-FB-75-74] N76-20127

SIGNAL RECEPTION
Rotor blade effects on L-band signals received by
helicopter antennas mounted above the rotor
blade (CW) experiments
[AD-A016866] N76-20360

SIKORSKY WHIRLWIND HELICOPTER
RSRA sixth scale wind tunnel test --- of scale
model of Sikorsky Whirlwind Helicopter
[NASA-CR-144964] N76-20126

SLENDER BODIES
Asymptotic representation of solutions on the
hodograph plane in problems of subsonic flow
past airfoil profiles
A76-26337

Extension of slender body theory
A76-28258

Experimental aerodynamic characteristics for
slender bodies with thin wings and tail at
angles of attack from 0 deg to 58 deg and Mach
numbers from 0.6 to 2.0
[NASA-TM-X-3310] N76-20079

SLOT ANTENNAS
A study of axial slot arrays on a circular
cylinder for use on electrically small vehicles
[AD-A016564] N76-20339

SONIC BOOMS
Limitations of the flight regime of a supersonic
transport /SST/ by the sonic boom
A76-28469

Ergonomic analysis of maneuvers leading to
inaudibility of a shock wave
A76-28544

SOUND AMPLIFICATION
The amplification of broadband jet noise by pure
tone excitation
[DLR-FB-75-72] N76-20942

SOUND PROPAGATION
A comparison of matrix methods for calculating
eigenvalues in acoustically lined ducts
[NASA-TN-D-8186] N76-20941

SPARE PARTS
Demand forecasting with program factors
[AD-A017858] N76-21193

SPRAYING
Aircraft use in agriculture and forestry ---
spraying with helicopters and light aircraft in
the U.S.S.R.
[NASA-TT-F-16846] N76-20078

STABILITY DERIVATIVES
Aerodynamic derivatives of the longitudinal motion
of the whole aircraft
A76-28256

STANDARDIZATION
Quality assurance by standardization --- for
aircraft maintenance and spare parts manufacturing
A76-27362

STATIC TESTS
A multi-variable control for a turbofan engine
operating at sea level static
[ASME PAPER 76-GT-71] A76-25814

Experimental aerodynamic characteristics for
slender bodies with thin wings and tail at
angles of attack from 0 deg to 58 deg and Mach
numbers from 0.6 to 2.0
[NASA-TM-X-3310] N76-20079

STATOR BLADES
Noise reduction from the redesign of a fan stage
to minimize stator lift fluctuations
[NASA-TM-X-71896] N76-21206

STEADY FLOW
Research in the UK on finite difference methods
for computing steady transonic flows
A76-27874

STRESS ANALYSIS
Responses of small rigid aircraft to discrete and
continuous gust analysis, phase 1
[AD-A020103/8] N76-21191

STRUCTURAL ANALYSIS
Calculation of the reinforced thin-walled
structures by the method of finite elements ---
for reinforced shells such as fuselages
[AD-A016387] N76-20545

Review of investigations on aeronautical fatigue
in the Federal Republic of Germany, July 1973 -
April 1975
[LBP-S-119] N76-21601

STRUCTURAL DESIGN
Transonic airfoil design using Cartesian coordinates
[NASA-CR-2578] N76-20082

STRUCTURAL DESIGN CRITERIA
Thrust reverser design for airframe compatibility
A76-26650

STRUCTURAL FAILURE
Effect of the upper limit of distribution function
of aircraft structure on the main failure's
distribution
A76-28254

STRUCTURAL RELIABILITY
Estimation of population reliability function of
aircraft structures from a limited fleet of
aircraft
A76-28255

STRUCTURAL STABILITY
Composite inlays increase flutter resistance of
turbine engine fan blades
[ASME PAPER 76-GT-29] A76-25781

SUBSONIC AIRCRAFT
Advanced Acoustic Nacelle concepts
[ASME PAPER 76-GT-35] A76-25786

Status report - Subsonic aircraft noise reduction
[ASME PAPER 76-GT-116] A76-25849

Energy and economic trade offs for advanced
technology subsonic aircraft
[NASA-TM-X-72833] N76-20124

SUBSONIC FLOW

SUBJECT INDEX

SUBSONIC FLOW
 Subsonic loads on wings having sharp leading edges and tips A76-28606
 Fully unsteady subsonic and supersonic potential aerodynamics for complex aircraft configurations for flutter applications [NASA-CR-146573] N76-20077
 Visualization of the subsonic flow around two space glider configurations --- using hydrogen bubble technique in water basin [DLR-FB-75-49] N76-20083

SUBSONIC SPEED
 Drag due to grooves in a flat plate with turbulent boundary layer, at subsonic and supersonic speeds [ESDU-75028] N76-21153

SUPERCAVITATING FLOW
 Note on a numerical scheme for the three-dimensional flow of a supercavitating wing or strut with thin cavity A76-28642

SUPERCritical FLOW
 A review of numerical techniques for calculating supercritical airfoil flows A76-27865
 Review of some numerical solutions of the transonic small disturbance equations A76-27869
 Supercritical flow past airfoils at Mach numbers close to one A76-27877
 Critical pressure coefficient and component of local Mach number normal to the surface isobar for a swept wing [ESDU-75027] N76-21152

SUPERCritical WINGS
 Calculation of buffet onset for supercritical airfoils A76-27832
 Airfoil design for a prescribed velocity distribution in transonic flow by an integral method A76-27844
 Supercritical wing design for a fighter type experimental aircraft A76-27856
 An exact hodograph method for the design of supercritical wing sections A76-27860
 Pressure distributions on a rectangular aspect-ratio-6, slotted supercritical airfoil wing with externally blown flaps [NASA-TM-X-3337] N76-20081

SUPERSONIC AIRCRAFT
 Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program --- numerical analysis of tactics and aircraft maneuvers of supersonic attack aircraft [NASA-CR-137819] N76-21188

SUPERSONIC AIRFOILS
 Optimal supersonic wing profile of given thickening A76-26338

SUPERSONIC FLIGHT
 Ergonomic analysis of maneuvers leading to inaudibility of a shock wave A76-28544

SUPERSONIC FLOW
 Fully unsteady subsonic and supersonic potential aerodynamics for complex aircraft configurations for flutter applications [NASA-CR-146573] N76-20077
 Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade [AD-A017203] N76-20095
 Supersonic flow past a slender delta wing. An experimental investigation covering the incidence range minus 5 deg less than or equal to angle of incidence less than or equal to 50 deg [CRANFIELD-HEMO-7512] N76-21167

SUPERSONIC FLUTTER
 Extension of slender body theory A76-28258

SUPERSONIC INLETS
 An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade [ASME PAPER 76-GT-17] A76-25773

SUPERSONIC SPEEDS
 Drag due to grooves in a flat plate with turbulent boundary layer, at subsonic and supersonic speeds [ESDU-75028] N76-21153

SUPERSONIC TRANSPORTS
 Limitations of the flight regime of a supersonic transport /SST/ by the sonic boom A76-28469

SWEEP WINGS
 Design and test of a sonic roof-top pressure distribution wing A76-27855
 Critical pressure coefficient and component of local Mach number normal to the surface isobar for a swept wing [ESDU-75027] N76-21152
 Flutter of asymmetrically swept wings [NASA-CR-146815] N76-21164

SYSTEM FAILURES
 Estimation of population reliability function of aircraft structures from a limited fleet of aircraft A76-28255

SYSTEMS ENGINEERING
 Primary system preliminary design for gas turbine HTGR power plant --- High Temperature Gas-cooled Reactors [ASME PAPER 76-GT-92] A76-25833

T

TACTICS
 Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program --- numerical analysis of tactics and aircraft maneuvers of supersonic attack aircraft [NASA-CR-137819] N76-21188

TECHNOLOGY ASSESSMENT
 New developments in aeronautics technology --- alloys and composite materials review A76-26412
 Ballistics of ejection seats A76-27743
 Helicopter rotor blades - The new technology A76-28693
 General aviation technology program [NASA-TM-X-73051] N76-20106
 Energy and economic trade offs for advanced technology subsonic aircraft [NASA-TM-X-72833] N76-20124

TEMPERATURE PROBES
 The pulsed thermocouple for gas turbine application [ASME PAPER 76-GT-1] A76-25758

TEMPERATURE SENSORS
 Testing a fluidic temperature sensor on a subscale ramjet engine combustion chamber [AD-A016455] N76-20455

TEST EQUIPMENT
 Design of a test machine for biaxial testing of composite-laminate cylinders [AD-A016961] N76-20232

TEST FACILITIES
 Windshield Flight Environment Simulator A76-26648

THERMOCOUPLES
 The pulsed thermocouple for gas turbine application [ASME PAPER 76-GT-1] A76-25758

THIN AIRFOILS
 Asymptotic representation of solutions on the hodograph plane in problems of subsonic flow past airfoil profiles A76-26337
 Airfoil design for a prescribed velocity distribution in transonic flow by an integral method A76-27844

- THIN WALLS**
 Calculation of the reinforced thin-walled structures by the method of finite elements --- for reinforced shells such as fuselages [AD-A016387] N76-20545
- THREE DIMENSIONAL FLOW**
 A linearized theory of three-dimensional airfoils in nonuniform flow A76-27329
 Some numerical results of a new three-dimensional transonic flow method A76-27875
 Note on a numerical scheme for the three-dimensional flow of a supercavitating wing or strut with thin cavity A76-28642
- THRUST AUGMENTATION**
 XPV-12A propulsion system development [ASME PAPER 76-GT-125] A76-25855
- THRUST REVERSAL**
 Thrust reverser design for airframe compatibility A76-26650
- TORSIONAL VIBRATION**
 Coupled bending-torsion vibrations of rotating blades [ASME PAPER 76-GT-43] A76-25792
- TRAILING EDGES**
 Aerodynamics and heat transfer at the trailing edge of transonic blades [ASME PAPER 76-GT-95] A76-25835
 An investigation into the effect of castellating a blunt trailing edge in supersonic flow [BU-175] N76-21169
- TRAJECTORY OPTIMIZATION**
 An aircraft noise pollution model for trajectory optimization A76-26384
- TRANSONIC FLIGHT**
 Transonic airfoil design using Cartesian coordinates [NASA-CR-2578] N76-20082
- TRANSONIC FLOW**
 Aerodynamics and heat transfer at the trailing edge of transonic blades [ASME PAPER 76-GT-95] A76-25835
 Asymptotic representation of solutions on the hodograph plane in problems of subsonic flow past airfoil profiles A76-26337
 Symposium Transsonicum II, Goettingen, West Germany, September 8-13, 1975, Proceedings A76-27826
 Some developments in unsteady transonic flow research A76-27827
 On the motion of shock waves on an airfoil with oscillating flap A76-27830
 Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils A76-27837
 The direct problem of the transonic airfoils on the hodograph A76-27838
 Airfoil design for a prescribed velocity distribution in transonic flow by an integral method A76-27844
 Supercritical wing design for a fighter type experimental aircraft A76-27856
 An exact hodograph method for the design of supercritical wing sections A76-27860
 Mathematical method of designing a certain compressor type plane blade cascade A76-27863
 Transonic aerodynamics and the helicopter rotor A76-27864
 A review of numerical techniques for calculating supercritical airfoil flows A76-27865
 Review of some numerical solutions of the transonic small disturbance equations A76-27869
 Research in the UK on finite difference methods for computing steady transonic flows A76-27874
- Some numerical results of a new three-dimensional transonic flow method A76-27875
 Supercritical flow past airfoils at Mach numbers close to one A76-27877
 A direct method for computing non-symmetrical plane flows at Mach number one A76-27878
 The analysis of arbitrary wingbody combinations in transonic flow using a relaxation method A76-27879
 Numerical solutions for transonic flows past wing-body combinations A76-27880
 Experiments on thin airfoils spanning a transonic shear flow N76-20073
- TRANSONIC WIND TUNNELS**
 An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1 A76-27857
- TRANSPORT AIRCRAFT**
 Advanced Acoustic Nacelle concepts [ASME PAPER 76-GT-35] A76-25786
 Can R-W aircraft provide efficient commercial transport A76-27068
 Some considerations in the design of transport aircraft /The W. Rupert Turnbull Lecture for 1975/ A76-27274
 Determination of the realizable flight hours for aircraft A76-27364
 Hydraulic systems for transport aircraft --- Russian book A76-28354
 A simulation study of curved, descending, decelerating, landing approaches for transport aircraft [NASA-TN-D-8190] N76-21216
- TURBINE BLADES**
 Composite inlays increase flutter resistance of turbine engine fan blades [ASME PAPER 76-GT-29] A76-25781
 Advanced composite fan blade flight evaluation program [ASME PAPER 76-GT-75] A76-25818
 Heat transfer in high-temperature GTE air-cooled turbine blades A76-26584
- TURBINE WHEELS**
 Advanced turbine disk designs to increase reliability of aircraft engines A76-25875
- TURBOCOMPRESSORS**
 Modeling and analysis of the TF30-P-3 compressor system with inlet pressure distortion [NASA-CR-134996] N76-21205
- TURBOFAN ENGINES**
 A multi-variable control for a turbofan engine operating at sea level static [ASME PAPER 76-GT-71] A76-25814
 CFM56 turbofan engines - General Electric/SNECMA cooperative engineering development program [ASME PAPER 76-GT-78] A76-25821
 Phase 2 program on ground test of refanned JT8D turbofan engines and nacelles for the 727 airplane. Volume 3: Ground tests [NASA-CR-134799] N76-21189
 Phase 2 program on ground test of refanned JT8D turbofan engines and nacelles for the 727 airplane. Volume 4: Airplane evaluation and analysis [NASA-CR-134800] N76-21190
 Modeling and analysis of the TF30-P-3 compressor system with inlet pressure distortion [NASA-CR-134996] N76-21205
 Noise reduction from the redesign of a fan stage to minimize stator lift fluctuations [NASA-TM-X-71896] N76-21206
 Stimulation of a turbofan engine for evaluation of multivariable optimal control concepts --- (computerized simulation) N76-21208
 Coupling of Helmholtz resonators to improve acoustic liners for turbofan engines at low frequency [NASA-CR-134912] N76-21210

TURBOMACHINE BLADES

Coupled bending-torsion vibrations of rotating blades
[ASME PAPER 76-GT-43] A76-25792

TURBOPROP ENGINES
Results of noise and vibration studies on An-24 aircraft A76-28542

TURBULENCE
Manual and automatic flight control during severe turbulence penetration
[NASA-CR-2677] N76-20151

TURBULENT BOUNDARY LAYER
Drag due to grooves in a flat plate with turbulent boundary layer, at subsonic and supersonic speeds
[ESDU-75028] N76-21153

TURBULENT FLOW
Swept edge to reduce the noise generated by turbulent flow over the edge A76-26751

TURBULENT JETS
Interaction of a buoyant turbulent planar jet with a co-flowing wind
[AD-A018060] N76-21172

TURBULENT MIXING
Low cost hypermixing ejector ramjet program
[AD-A016430] N76-20148

TWISTING
A method for the calculation of the twist and camber of a wing with a specified load distribution in the presence of a fuselage --- theoretical potential flow method
[ESA-TT-214] N76-20087

TWO DIMENSIONAL FLOW
Iterative calculation of two-dimensional compressible flow around ellipse and circular arc profile A76-27328

A direct method for computing non-symmetrical plane flows at Mach number one A76-27878

U

U.S.S.R.
Aircraft use in agriculture and forestry --- spraying with helicopters and light aircraft in the U.S.S.R.
[NASA-TT-F-16846] N76-20078

U.S.S.R. SPACE PROGRAM
Rocket engines GDL-OKB --- Soviet liquid propellant engine development history A76-28100

UH-1 HELICOPTER
Major orientation-error accidents in regular Army UH-1 aircraft during fiscal year 1971 (accident factors)
[AD-A017665] N76-21178

ULTRAHIGH FREQUENCIES
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results
[AD-A017090] N76-20301

Rotor blade effects on L-band signals received by helicopter antennas mounted above the rotor blade (CW) experiments
[AD-A016866] N76-20360

UNDERCARRIAGES
Analysis of failures in the parts of an aircraft undercarriage
[AD-A017928] N76-21196

UNIVERSITY PROGRAM
The outlook for aeronautics, 1980 - 2000: Appendix B: Study group report on an industry-university-government survey
[NASA-TM-X-72996] N76-20064

UNSTEADY FLOW
Some developments in unsteady transonic flow research A76-27827

UNSWEPT WINGS
The design of unswept large aspect ratio wings with flaps for two flight conditions
[ESA-TT-224] N76-20128

V

VELOCITY DISTRIBUTION
Airfoil design for a prescribed velocity distribution in transonic flow by an integral method A76-27844

VELOCITY MEASUREMENT
Measurements of the vertical movements of an aircraft --- altitude and velocity measurement accuracy
[ESA-TT-215] N76-20152

VERTICAL FLIGHT
Measurements of the vertical movements of an aircraft --- altitude and velocity measurement accuracy
[ESA-TT-215] N76-20152

VERTICAL MOTION
Measurements of the vertical movements of an aircraft --- altitude and velocity measurement accuracy
[ESA-TT-215] N76-20152

VIBRATION DAMPING
Composite inlays increase flutter resistance of turbine engine fan blades
[ASME PAPER 76-GT-29] A76-25781

Selected problems of cockpit acoustic design A76-28545

VIBRATION MEASUREMENT
Results of noise and vibration studies on An-24 aircraft A76-28542

VIBRATION TESTS
Feasibility determination of a dynamic taxi facility for evaluating military landing gear systems
[AD-A017038] N76-20169

VORTEX SHEETS
Non-linear effect due to flow separation on flow past wings and wing body combinations A76-27741

VORTICES
Investigation of vortex wake stability near the ground
[AD-A017586] N76-20112

Vortex maneuver lift for super-cruise configurations
[NASA-TM-X-72836] N76-21161

Characteristics of wake vortex generated by a boeing 727 jet transport during two-segment and normal ILS approach flight paths
[NASA-TM-D-8222] N76-21175

VULNERABILITY
Increased rotor blade survivability --- composite geodesic structure
[AD-A016929] N76-20130

W

WEAPON SYSTEMS
Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 1
[AD-A016409] N76-21024

Weapon system costing methodology for aircraft airframes and basic structures. Volume 1: Technical volume
[AD-A016408] N76-21194

Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 2
[AD-A016410] N76-21195

WIND TUNNEL MODELS
Design and test of a sonic roof-top pressure distribution wing A76-27855

WIND TUNNEL TESTS
Design and test of a sonic roof-top pressure distribution wing A76-27855

An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1 A76-27857

Nozzle afterbody configuration development for the B-1 strategic bomber
[AIAA PAPER 74-1102] A76-28608

RSRA sixth scale wind tunnel test --- of scale model of Sikorsky Whirlwind Helicopter
[NASA-CR-144964] N76-20126


- Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results
[NASA-CR-137747] N76-21159
- Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 2. Acoustic test results
[NASA-CR-137748] N76-21160
- Hypersonic research engine/aerothermodynamic integration model, experimental results. Volume 4: Mach 5 component integration and performance
[NASA-TM-X-72824] N76-21209
- WIND VELOCITY**
Interaction of a buoyant turbulent planar jet with a co-flowing wind
[AD-A018060] N76-21172
- WINDSHIELDS**
Windshield Flight Environment Simulator A76-26648
Development of deicing techniques for dielectric windows
[AD-A017097] N76-20136
- WING CAMBER**
A method for the calculation of the twist and camber of a wing with a specified load distribution in the presence of a fuselage --- theoretical potential flow method
[ESA-TT-214] N76-20087
- WING FLAPS**
Three component measurements on a light STOL aircraft with chordwise blowing
[DLR-PB-75-74] N76-20127
The design of unswept large aspect ratio wings with flaps for two flight conditions
[ESA-TT-224] N76-20128
- WING LOADING**
Some considerations in the design of transport aircraft /The W. Rupert Turnbull Lecture for 1975/
A76-27274
Aerodynamic derivatives of the longitudinal motion of the whole aircraft A76-28256
Effect of gusts on helicopter loading A76-28259
Subsonic loads on wings having sharp leading edges and tips A76-28606
A method for the calculation of the twist and camber of a wing with a specified load distribution in the presence of a fuselage --- theoretical potential flow method
[ESA-TT-214] N76-20087
- WING OSCILLATIONS**
Extension of slender body theory A76-28258
- WING PROFILES**
Optimal supersonic wing profile of given thickening A76-26338
The direct problem of the transonic airfoils on the hodograph A76-27838
Supercritical wing design for a fighter type experimental aircraft A76-27856
An exact hodograph method for the design of supercritical wing sections A76-27860
Research in the UK on finite difference methods for computing steady transonic flows A76-27874
- WING SLOTS**
Three component measurements on a light STOL aircraft with chordwise blowing
[DLR-PB-75-74] N76-20127
- WINGS**
Note on a numerical scheme for the three-dimensional flow of a supercavitating wing or strut with thin cavity A76-28642
- WORKLOADS (PSYCHOPHYSIOLOGY)**
Manual and automatic flight control during severe turbulence penetration
[NASA-CR-2677] N76-20151
- Y**
- YAK 40 AIRCRAFT**
Cockpit systems study YAK 40: Rating of cockpit facilities, flight and systems properties of the aircraft by pilots
[AD-A017198] N76-20134
- YF-16 AIRCRAFT**
Representation of the drag polar of a fighter aircraft A76-28610

PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING / A Special Bibliography (Suppl 72)

JULY 1976

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g. NASA report translation, NASA contractor report). The accession number is located beneath and to the right of the title (e.g. N76 11042). Under any one author's name the accession numbers are arranged in sequence with the IAA accession numbers appearing first.

A

- ADDUCI, A. J.**
An update - Advanced aircraft oxygen systems
A76-27144
- ALBONE, C. M.**
Numerical solutions for transonic flows past wing-body combinations
A76-27880
- ALPARO-BOU, E.**
Impact dynamics research facility for full-scale aircraft crash testing
[NASA-TN-D-8179]
N76-21173
- ALVERMANN, W.**
Propulsion systems
A76-26670
- AMANA, O. M.**
Aerodynamics and heat transfer at the trailing edge of transonic blades
[ASME PAPER 76-GT-95]
A76-25835
- ANDERLE, H. T.**
Feasibility determination of a dynamic taxi facility for evaluating military landing gear systems
[AD-A017038]
N76-20169
- ANDREWS, E. H., JR.**
Hypersonic research engine/aerothermodynamic integration model, experimental results. Volume 4: Mach 5 component integration and performance
[NASA-TM-X-72824]
N76-21209
- AZUMA, A.**
Fundamental formulation of airship performance and flight dynamics
A76-28033

B

- BABERJEE, S.**
Coupled bending-torsion vibrations of rotating blades
[ASME PAPER 76-GT-43]
A76-25792
- BANKS, G. A.**
Modeling and analysis of the TP30-P-3 compressor system with inlet pressure distortion
[NASA-CR-134996]
N76-21205
- BARBER, H. R.**
Characteristics of wake vortex generated by a Boeing 727 jet transport during two-segment and normal ILS approach flight paths
[NASA-TN-D-8222]
N76-21175

- BARKANA, A.**
An aircraft noise pollution model for trajectory optimization
A76-26384
- BARSONY-NAGY, A.**
A linearized theory of three-dimensional airfoils in nonuniform flow
A76-27329
- BATE, E. R., JR.**
Investigation of vortex wake stability near the ground
[AD-A017586]
N76-20112
- BECHERT, D.**
The amplification of broadband jet noise by pure tone excitation
[DLR-FB-75-72]
N76-20942
- BECK, W. E., JR.**
Inflight engine performance evaluations
[ASME PAPER 76-GT-70]
A76-25813
- BENDOT, J. G.**
Low cost hypermixing ejector ramjet program
[AD-A016430]
N76-20148
- BENGTSON, D.**
Roll-axis hydrofluidic stability augmentation system development
[AD-A016932]
N76-20154
- BIPPES, H.**
Visualization of the subsonic flow around two space glider configurations
[DLR-FB-75-49]
N76-20083
- BOBEV, J.**
Determination of the realizable flight hours for aircraft
A76-27364
- BOERSTOEL, J. W.**
Review of the application of hodograph theory to transonic aerofoil design and theoretical and experimental analysis of shock-free aerofoils
A76-27837
- BOJADZHIEV, V.**
Determination of the realizable flight hours for aircraft
A76-27364
- BORK, P.**
Some basic questions concerning quality assurance in aircraft maintenance
A76-27361
- BREMER, H.**
Licensing and the organization of the servicing process in aircraft maintenance
A76-27363
- BUSALOV, E. P.**
Economics of air transport
A76-26049
- BUXBAUM, O.**
Review of investigations on aeronautical fatigue in the Federal Republic of Germany, July 1973 - April 1975
[LBF-S-119]
N76-21601

C

- CAFFIER, E.**
CPM56 turbofan engines - General Electric/SNECMA cooperative engineering development program
[ASME PAPER 76-GT-78]
A76-25821
- CAMPBELL, J. F.**
Vortex maneuver lift for super-cruise configurations
[NASA-TM-X-72836]
N76-21161
- CAMPBELL, L. G.**
Windshield Flight Environment Simulator
A76-26648
- CARLSON, L. A.**
Transonic airfoil design using Cartesian coordinates
[NASA-CR-2578]
N76-20082

- CARTA, F. O.
Unsteady surface flow behavior on a cascade of airfoils oscillating below stall
[AD-A017073] N76-20096
- CARUTHERS, J. E.
An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
- CATHERINES, J. J.
Sources and characteristics of interior noise in general aviation aircraft
[NASA-TM-X-72839] N76-21990
- CHAUVIN, J.
Aerodynamics and heat transfer at the trailing edge of transonic blades
[ASME PAPER 76-GT-95] A76-25835
- CHEKRENKO, ZH. S.
Hydraulic systems for transport aircraft
A76-28354
- CHEKUNYSHEV, A. IA.
Economics of air transport
A76-26049
- CHOPIN, M. H.
Advanced composite fan blade flight evaluation program
[ASME PAPER 76-GT-75] A76-25818
- COHEN, M.
Demand forecasting with program factors
[AD-A017858] N76-21193
- COLAK-ANTIC, P.
Visualization of the subsonic flow around two space glider configurations
[DLR-PB-75-49] N76-20083
- COLLINS, J. A.
Investigation of accelerated life prediction techniques
[AD-A016925] N76-20129
- COOK, G.
An aircraft noise pollution model for trajectory optimization
A76-26384
- COSNER, R. R.
Experiments on thin airfoils spanning a transonic shear flow
N76-20073
- CRITTENDEN, J. B.
Flutter of asymmetrically swept wings
[NASA-CR-146815] N76-21164
- CROFT, M.
Control of a gas turbine HTGR
[ASME PAPER 76-GT-97] A76-25837
- CROW, S. C.
Investigation of vortex wake stability near the ground
[AD-A017586] N76-20112
- D**
- DAVE, G. P.
An investigation into the effects of aspect ratio and centre keel camber on the aerodynamic characteristics of conical parawings
[BU-176] N76-21170
- DEAN, L. W.
Coupling of Helmholtz resonators to improve acoustic liners for turbofan engines at low frequency
[NASA-CR-134912] N76-21210
- DEBRUGE, L. L.
An analysis of heat transfer on a Joukowski airfoil with separation and reattachment
[AD-A016457] N76-20091
- DELANEY, J. T.
XPV-12A propulsion system development
[ASME PAPER 76-GT-125] A76-25855
- DELAPP, R. E.
Aircraft noise definition. Phase 2: Analysis of flyover-noise data for DC-8-61 aircraft
[AD-A019759/0] N76-21211
- DEMUREN, H. O.
Aerodynamics and heat transfer at the trailing edge of transonic blades
[ASME PAPER 76-GT-95] A76-25835
- DESANTIS, C. E.
Rotor blade effects on L-band signals received by helicopter antennas mounted above the rotor blade (CW) experiments
[AD-A016866] N76-20360
- DIBROVA, G. S.
Economics of air transport
A76-26049
- DICKOVICH, T.
Roll-axis hydrofluidic stability augmentation system development
[AD-A016932] N76-20154
- DIEUDONNE, J. E.
A simulation study of curved, descending, decelerating, landing approaches for transport aircraft
[NASA-TN-D-8190] N76-21216
- DITTHAR, J. H.
Noise reduction from the redesign of a fan stage to minimize stator lift fluctuations
[NASA-TM-X-71896] N76-21206
- DOBROVOLSKAYA, Z. N.
Asymptotic representation of solutions on the hodograph plane in problems of subsonic flow past airfoil profiles
A76-26337
- E**
- EBERLE, A.
An exact hodograph method for the design of supercritical wing sections
A76-27860
- ENGELS, P. D.
Aircraft L-band balloon simulated satellite experiments. Volume 1: Experiment description and data modem test results
[AD-A017090] N76-20301
- ERNATINGER, C. E.
Characteristics of a 240 to 400 MHz 6-inch depth cavity-backed cross open-sleeve dipole antenna on a curved ground plane
[AD-A017367] N76-20387
- ESTRINE, E.
Control of a gas turbine HTGR
[ASME PAPER 76-GT-97] A76-25837
- EUVRARD, D.
Supercritical flow past airfoils at Mach numbers close to one
A76-27877
- F**
- FAIRLIE, B. D.
An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1
A76-27857
- FERRIS, J. E.
A study of axial slot arrays on a circular cylinder for use on electrically small vehicles
[AD-A016564] N76-20339
- FILLER, L.
Swept edge to reduce the noise generated by turbulent flow over the edge
A76-26751
- FLEETER, S.
An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade
[AD-A017203] N76-20095
- FLEMING, R.
ESRA sixth scale wind tunnel test
[NASA-CR-144964] N76-20126
- FORTESCUE, P.
Primary system preliminary design for gas turbine HTGR power plant
[ASME PAPER 76-GT-92] A76-25833
- FRERLICH, M.
The general aviation industry; an overview
[AD-A015871] N76-20072
- G**
- GABRIELLI, G.
Types and ideal propulsive efficiency of aeronautical propulsion systems
A76-26550
- GABUTTI, B.
The direct problem of the transonic airfoils on the hodograph
A76-27838

- GARNER, H. D.
Magnetic heading reference
[NASA-CASE-LAR-11387-1] N76-20114
- GARODZ, L. J.
Characteristics of wake vortex generated by a boeing 727 jet transport during two-segment and normal ILS approach flight paths
[NASA-TN-D-8222] N76-21175
- GEYMONAT, G.
The direct problem of the transonic airfoils on the hodograph N76-27838
- GIBBS, E. H.
Analysis of circulation controlled airfoils N76-28611
- GILLINGHAM, G. R.
A new system for preventing icing of gas turbine inlets
[ASME PAPER 76-GT-84] N76-25825
- GLOSS, B. B.
Vortex maneuver lift for super-cruise configurations
[NASA-TN-X-72836] N76-21161
- GLUSHKO, V. P.
Rocket engines GDL-OKB N76-28100
- GRAFT, J.
Transonic aerodynamics and the helicopter rotor N76-27864
- GRIFFIN, C. F.
Increased rotor blade survivability
[AD-A016929] N76-20130
- GHOMOV, N. N.
Economics of air transport N76-26049
- GROSJEAN, F.
A direct method for computing non-symmetrical plane flows at Mach number one N76-27878
- GROVE, R. D.
A simulation study of curved, descending, decelerating, landing approaches for transport aircraft
[NASA-TN-D-8190] N76-21216
- GUNTER, J. L.
Nozzle afterbody configuration development for the B-1 strategic bomber
[AIAA PAPER 74-1102] N76-28608
- GUSTAVSSON, A. L.
Design and test of a sonic roof-top pressure distribution wing N76-27855
- ## H
- HAGAN, B. T., JR.
Investigation of accelerated life prediction techniques
[AD-A016925] N76-20129
- HALL, M. G.
Numerical solutions for transonic flows past wing-body combinations N76-27880
- HAMID, O. E. A.
Extension of slender body theory N76-28258
- HANSEN, H.
Airfoil design for a prescribed velocity distribution in transonic flow by an integral method N76-27844
- HARKINS, W. G.
Low cost hypermixing ejector ramjet program
[AD-A016430] N76-20148
- HEDMAN, S. G.
Design and test of a sonic roof-top pressure distribution wing N76-27855
- HELPERSTINE, R.
Roll-axis hydrofluidic stability augmentation system development
[AD-A016932] N76-20154
- HENRY, T. P.
The general aviation industry: an overview
[AD-A015871] N76-20072
- HIXSON, W. C.
Major orientation-error accidents in regular Army UH-1 aircraft during fiscal year 1971 (accident factors)
[AD-A017665] N76-21178
- HODGES, D. H., ROBERTA.
Stability of elastic bending and torsion of uniform cantilever rotor blades in hover with variable structural coupling
[NASA-TN-D-8192] N76-21162
- HOE, R. H.
Manual and automatic flight control during severe turbulence penetration
[NASA-CR-2677] N76-20151
- HOJNACKI, J. T.
Testing a fluidic temperature sensor on a subscale ramjet engine combustion chamber
[AD-A016455] N76-20455
- HOLT, H.
A review of numerical techniques for calculating supercritical airfoil flows N76-27865
- HOMENTCOVSKI, D.
A linearized theory of three-dimensional airfoils in nonuniform flow N76-27329
- HOSKING, P. R.
An investigation into the effect of castellating a blunt trailing edge in supersonic flow
[BU-175] N76-21169
- HOWLETT, J. T.
Prediction of light aircraft interior noise
[NASA-TN-X-72838] N76-20940
- HUBBARD, C. D.
The identification of a precedence network associated with base level aircraft maintenance
[AD-A016389] N76-21017
- HURLEY, G. F.
Preparation of eutectic superalloys by EFG N76-28029
- ## I
- INWALLE, D. E.
High performance epicyclic gears for gas turbines
[ASME PAPER 76-GT-88] N76-25829
- INKER, D. J.
The pressure distribution over the ogive nose of a cylinder at large angles of inclination to a uniform stream
[BU-173] N76-21168
- IVANOV, Y. I.
Calculation of the reinforced thin-walled structures by the method of finite elements
[AD-A016387] N76-20545
- ## J
- JENKINS, G. M.
XPV-12A propulsion system development
[ASME PAPER 76-GT-125] N76-25855
- JHA, S. K.
Sources and characteristics of interior noise in general aviation aircraft
[NASA-TN-X-72839] N76-21990
- JOHNSON, W. G., JR.
Pressure distributions on a rectangular aspect-ratio-6, slotted supercritical airfoil wing with externally blown flaps
[NASA-TN-X-3337] N76-20081
- JOHNSTON, D. E.
Manual and automatic flight control during severe turbulence penetration
[NASA-CR-2677] N76-20151
- JONES, R. T.
Some considerations in the design of transport aircraft /The W. Rupert Turnbull Lecture for 1975/ N76-27274
- JORGENSEN, L. H.
Experimental aerodynamic characteristics for slender bodies with thin wings and tail at angles of attack from 0 deg to 58 deg and Mach numbers from 0.6 to 2.0
[NASA-TN-X-3310] N76-20079
- JOYCE, G.
Numerical solutions for transonic flows past wing-body combinations N76-27880

K

- KADMAN, Y.
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 2. Acoustic test results' [NASA-CR-137748] N76-21160
- KAISER, J. B.
History of Messerschmitt aircraft manufacturing [DLR-MITT-75-21] N76-20070
- KANDIL, O. A.
Subsonic loads on wings having sharp leading edges and tips A76-28606
- KAPLAN, M. P.
Use of fracture mechanics in estimating structural life and inspection intervals A76-28607
- KARLSSON, K. R.
Some numerical results of a new three-dimensional transonic flow method A76-27875
- KAUFMAN, A.
Advanced turbine disk designs to increase reliability of aircraft engines A76-25875
- KELLEY, H. J.
Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program [NASA-CR-137819] N76-21188
- KENYON, R. E.
Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 1 [AD-A016409] N76-21024
Weapon system costing methodology for aircraft airframes and basic structures. Volume 1: Technical volume [AD-A016408] N76-21194
Weapon system costing methodology for aircraft airframes and basic structures. Volume 2: Estimating handbook and user's manual, part 2 [AD-A016410] N76-21195
- KERN, K.
Iterative calculation of two-dimensional compressible flow around ellipse and circular arc profile A76-27328
- KESTER, J. D.
Noise technology requirements for future aircraft powerplants [ASME PAPER 76-GT-69] A76-25812
- KING, H. E.
Flight test evaluation of a 240 to 400 MHz cavity-backed cross open-sleeve dipole antenna [AD-A017298] N76-20386
Characteristics of a 240 to 400 MHz 6-inch depth cavity-backed cross open-sleeve dipole antenna on a curved ground plane [AD-A017367] N76-20387
- KLEIN, H. H.
Interaction of a buoyant turbulent planar jet with a co-flowing wind [AD-A018060] N76-21172
- KLEIN, R. E.
Manual and automatic flight control during severe turbulence penetration [NASA-CR-2677] N76-20151
- KLOSTER, H.
Limitations of the flight regime of a supersonic transport /SST/ by the sonic boom A76-28469
- KO, W. L.
Design of a test machine for biaxial testing of composite-laminate cylinders [AD-A016961] N76-20232
- KOERNER, H.
A method for the calculation of the twist and camber of a wing with a specified load distribution in the presence of a fuselage [ESA-TT-214] N76-20087
- Three component measurements on a light STOL aircraft with chordwise blowing [DLR-FB-75-74] N76-20127
- KOHN, A. O.
CFM56 turbofan engines - General Electric/SNECMA cooperative engineering development program [ASME PAPER 76-GT-78] A76-25821
- KRASE, J. M.
Primary system preliminary design for gas turbine HTGR power plant [ASME PAPER 76-GT-92] A76-25833
- KRAUS, W.
Computer program for calculating pressure distribution and coefficients of wings, bodies, wing-body combinations and wing-tail combinations in subsonic, supersonic and hypersonic flow [MBB-UPE-1014-0] N76-21165
- KRETSCHMER, D.
The pulsed thermocouple for gas turbine application [ASME PAPER 76-GT-1] A76-25758
- KUCERA, M.
Effect of gusts on helicopter loading A76-28259
- KULYSHEVA, Z. S.
Analysis of failures in the parts of an aircraft undercarriage [AD-A017928] N76-21196
- KUNKEL, B. A.
Interaction of a buoyant turbulent planar jet with a co-flowing wind [AD-A018060] N76-21172
- KURKOWSKI, R. L.
Characteristics of wake vortex generated by a boeing 727 jet transport during two-segment and normal ILS approach flight paths [NASA-TN-D-8222] N76-21175

L

- LAGOSIUK, G. S.
Hydraulic systems for transport aircraft A76-28354
- LAMAR, J. E.
Vortex maneuver lift for super-cruise configurations [NASA-TN-X-72836] N76-21161
- LANDAHL, M. T.
Some developments in unsteady transonic flow research A76-27827
- LANSING, D. L.
A comparison of matrix methods for calculating eigenvalues in acoustically lined ducts [NASA-TN-D-8186] N76-20941
- LEPTON, L.
Studies of aircraft differential maneuvering. Report 75-27: Calculating of differential-turning barrier surfaces. Report 75-26: A user's guide to the aircraft energy-turn and tandem-motion computer programs. Report 75-7: A user's guide to the aircraft energy-turn hodograph program [NASA-CR-137819] N76-21188
- LINDHOLM, U. S.
Design of a test machine for biaxial testing of composite-laminate cylinders [AD-A016961] N76-20232
- LINDKE, C. R.
The identification of a precedence network associated with base level aircraft maintenance [AD-A016389] N76-21017
- LITTLE, J. W.
Status report - Subsonic aircraft noise reduction [ASME PAPER 76-GT-116] A76-25849
- LOCK, R. C.
Research in the UK on finite difference methods for computing steady transonic flows A76-27874
- LOEHR, R.
Three component measurements on a light STOL aircraft with chordwise blowing [DLR-FB-75-74] N76-20127
- LOKAI, V. I.
Heat transfer in high-temperature GTE air-cooled turbine blades A76-26584

LOUIS, J. P.
Aerodynamics and heat transfer at the trailing
edge of transonic blades
[ASME PAPER 76-GT-95] A76-25835

M

MACKLEY, E. A.
Hypersonic research engine/aerothermodynamic
integration model, experimental results. Volume
4: Mach 5 component integration and performance
[NASA-TM-X-72824] N76-21209

MADDALON, D. V.
Energy and economic trade offs for advanced
technology subsonic aircraft
[NASA-TM-X-72833] N76-20124

MADEB, E.
Iterative calculation of two-dimensional
compressible flow around ellipse and circular
arc profile A76-27328

MAKAREWICZ, R.
Ergonomic analysis of maneuvers leading to
inaudibility of a shock wave A76-28544

MAKAROV, E. V.
Economics of air transport A76-26049

MARR, N. W.
Preparation of eutectic superalloys by EFG A76-28029

MARSHALL, J. W.
Windshield Flight Environment Simulator A76-26648

MARTIN, P. L. R.
An investigation into the effects of aspect ratio
and centre keel camber on the aerodynamic
characteristics of conical parawings
[BU-176] N76-21170

MAZZAWY, R. S.
Modeling and analysis of the TF30-P-3 compressor
system with inlet pressure distortion N76-21205

MCDONALD, C. P.
Primary system preliminary design for gas turbine
HTGR power plant
[ASME PAPER 76-GT-92] A76-25833

MERCER, J. G.
Feasibility determination of a dynamic taxi
facility for evaluating military landing gear
systems
[AD-A017038] N76-20169

MILLER, H.
Responses of small rigid aircraft to discrete and
continuous gust analysis, phase 1
[AD-A020103/8] N76-21191

MILLER, R. H.
Can R-W aircraft provide efficient commercial
transport A76-27068

MIROSHNIKOV, A. V.
Economics of air transport A76-26049

HOOK, D. T.
Subsonic loads on wings having sharp leading edges
and tips A76-28606

MOEALLES, D. A.
Prediction of light aircraft interior noise
[NASA-TM-X-72838] N76-20940

MOECHOISSE, Y.
Supercritical flow past airfoils at Mach numbers
close to one A76-27877

MOEINO, L.
Fully unsteady subsonic and supersonic potential
aerodynamics for complex aircraft configurations
for flutter applications
[NASA-CR-146573] N76-20077

MOUILLE, R.
Helicopter rotor blades - The new technology A76-28693

MOYMAN, E. H.
Review of some numerical solutions of the
transonic small disturbance equations A76-27869

MYKTYOW, W. J.
Technical evaluation report of AGARD Specialists
Meeting on Wing-With-Stores Flutter
[AGARD-AR-96] N76-21163

N

NAGY, A.
Design of a test machine for biaxial testing of
composite-laminate cylinders N76-20232

NAWHAB, L. B.
Flight test evaluation of a 240 to 400 MHz
cavity-backed cross open-sleeve dipole antenna
[AD-A017298] N76-20386

NAYFER, A. B.
Subsonic loads on wings having sharp leading edges
and tips A76-28606

NAZAROV, V. A.
Aircraft use in agriculture and forestry
[NASA-TT-P-16846] N76-20078

NELSON, E. B.
Experimental aerodynamic characteristics for
slender bodies with thin wings and tail at
angles of attack from 0 deg to 58 deg and Mach
numbers from 0.6 to 2.0
[NASA-TM-X-3310] N76-20079

NESS, N.
Analysis of circulation controlled airfoils A76-28611

NEUMANN, G.
Cockpit systems study YAK 40: Rating of cockpit
facilities, flight and systems properties of the
aircraft by pilots
[AD-A017198] N76-20134

NICKLISCH, H.
Quality assurance by standardization A76-27362

NIKULINSKII, G. N.
Hydraulic systems for transport aircraft A76-28354

NISHIDA, R. S.
Small scale noise and wind tunnel tests of upper
surface blowing nozzle flap concepts. Volume 1.
Aerodynamic test results
[NASA-CR-137747] N76-21159

NOCILLA, S.
The direct problem of the transonic airfoils on
the hodograph A76-27838

NOVICK, A. S.
An experimental determination of the unsteady
aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773
Research on aeroelastic phenomena in airfoil
cascades supersonic unsteady aerodynamic
phenomena in a controlled oscillating cascade
[AD-A017203] N76-20095

O

ODGERS, J.
The pulsed thermocouple for gas turbine application
[ASME PAPER 76-GT-1] A76-25758

OHJIN, J. S.
The potential of oxide dispersion strengthened
superalloys for advanced gas turbines
[ASME PAPER 76-GT-118] A76-25851

OPENSHAW, F.
Control of a gas turbine HTGR
[ASME PAPER 76-GT-97] A76-25837

OSWATITSCH, K.
Symposium Transsonicum II, Goettingen, West
Germany, September 8-13, 1975, Proceedings A76-27826

P

PAINTER, G. W.
Advanced Acoustic Nacelle concepts
[ASME PAPER 76-GT-35] A76-25786

PATKAR, M. B.
Ballistics of ejection seats A76-27743

PEBACCHIO, A. A.
Noise technology requirements for future aircraft
powerplants
[ASME PAPER 76-GT-69] A76-25812

PETRAKIS, J.
Responses of small rigid aircraft to discrete and continuous gust analysis, phase 1
[AD-A020103/8] N76-21191

PFIZENHAUER, E.
The amplification of broadband jet noise by pure tone excitation
[DLR-FB-75-72] N76-20942

PIERCY, T. G.
Low cost hypermixing ejector ramjet program
[AD-A016430] N76-20148

PITROU, J.
New developments in aeronautics technology
A76-26412

POLLOCK, M.
An experimental investigation of Garabedian and Korn's shockless lifting aerofoil No. 1
A76-27857

PUZYNA, C.
Results of noise and vibration studies on An-24 aircraft
A76-28542

R

RAJPERT, T.
Ergonomics and the problem of aircraft-induced external noise
A76-28543

RAMAKRISHNAN, S. V.
Non-linear effect due to flow separation on flow past wings and wing body combinations
A76-27741

HAO, J. S.
Coupled bending-torsion vibrations of rotating blades
[ASME PAPER 76-GT-43] A76-25792

REDEKER, G.
Calculation of buffet onset for supercritical airfoils
A76-27832

The design of unswept large aspect ratio wings with flaps for two flight conditions
[ESA-TT-224] N76-20128

REIHAN, J. A.
Use of fracture mechanics in estimating structural life and inspection intervals
A76-28607

RENSELAER, D. J.
Small scale noise and wind tunnel tests of upper surface blowing nozzle flap concepts. Volume 1. Aerodynamic test results
[NASA-CR-137747] N76-21159

RENSHAW, M.
The pressure distribution over the ogive nose of a cylinder at large angles of inclination to a uniform stream
[BU-173] N76-21168

RICHARDS, I. C.
Supersonic flow past a slender delta wing. An experimental investigation covering the incidence range minus 5 deg less than or equal to angle of incidence less than or equal to 50 deg
[CRANFIELD-MEMO-7512] N76-21167

RIFPEL, R. E.
An experimental determination of the unsteady aerodynamics in a controlled oscillating cascade
[ASME PAPER 76-GT-17] A76-25773

Research on aeroelastic phenomena in airfoil cascades supersonic unsteady aerodynamic phenomena in a controlled oscillating cascade
[AD-A017203] N76-20095

ROHLFS, S.
Supercritical wing design for a fighter type experimental aircraft
A76-27856

RUDELL, A.
RSRA sixth scale wind tunnel test
[NASA-CR-144964] N76-20126

RUDIUK, A.
Selected problems of cockpit acoustic design
A76-28545

RUES, D.
Symposium Transsonicum II, Goettingen, West Germany, September 8-13, 1975, Proceedings
A76-27826

RUSSELL, R. E.
Status report - Subsonic aircraft noise reduction
[ASME PAPER 76-GT-116] A76-25849

RUZICKA, E.
Mathematical method of designing a certain compressor type plane blade cascade
A76-27863

S

SAMIR ABDELSALAM, M.
Effect of the upper limit of distribution function of aircraft structure on the main failure's distribution
A76-28254

Estimation of population reliability function of aircraft structures from a limited fleet of aircraft
A76-28255

SARGENT, J. C.
Nozzle afterbody configuration development for the B-1 strategic bomber
[AIAA PAPER 74-1102] A76-28608

SAUNDERS, G. H.
Dynamics of helicopter flight
A76-26450

SAVAGE, J. C.
Flight test of the aerospatiale SA-342 helicopter
[AD-A016921] N76-20131

SCHLADER, A. P.
The pulsed thermocouple for gas turbine application
[ASME PAPER 76-GT-1] A76-25758

SCHMIDT, W.
The analysis of arbitrary wingbody combinations in transonic flow using a relaxation method
A76-27879

SCHWARTZBERG, M. A.
Airfoil profile drag
[AD-A017321] N76-20093

SCHWERING, F.
Rotor blade effects on L-band signals received by helicopter antennas mounted above the rotor blade (CW) experiments
[AD-A016866] N76-20360

SEBIN, Y. C.-J.
Some numerical results of a new three-dimensional transonic flow method
A76-27875

SELDNER, K.
Stimulation of a turbofan engine for evaluation of multivariable optimal control concepts
[NASA-TN-X-71912] N76-21208

SELF, D. Q.
An investigation into the effect of castellating a blunt trailing edge in supersonic flow
[BU-175] N76-21169

SENGUPTA, D. L.
A study of axial slot arrays on a circular cylinder for use on electrically small vehicles
[AD-A016564] N76-20339

SEREBIISKII, Y. M.
The ground effect on the aerodynamic characteristics of an aircraft
[AD-A017309] N76-20098

SHMARENKOVA, G. A.
Interaction between an external shock wave and a blunted body in hypersonic flow
A76-26339

SHVETS, B. IA.
Hydraulic systems for transport aircraft
A76-28354

SIEVERDING, C.
Aerodynamics and heat transfer at the trailing edge of transonic blades
[ASME PAPER 76-GT-95] A76-25835

SIMON, D. R.
Flight test of the aerospatiale SA-342 helicopter
[AD-A016921] N76-20131

SIROTKIN, E. IA.
Improvement of the precision of aircraft control during completion of a plane turn maneuver
A76-27930

SKODA, Z.
Aerodynamic derivatives of the longitudinal motion of the whole aircraft
A76-28256

SOLOMONOV, P. A.
Engineering aspects of flight safety
A76-26048

SPEZIA, B.
Major orientation-error accidents in regular Army
UH-1 aircraft during fiscal year 1971 (accident
factors)
[AD-A017665] N76-21178

SPOPKAI, I. I.
Economics of air transport
A76-26049

STEININGER, K.
Cockpit systems study YAK 40: Rating of cockpit
facilities, flight and systems properties of the
aircraft by pilots
[AD-A017198] N76-20134

STEINMETZ, G. G.
A simulation study of curved, descending,
decelerating, landing approaches for transport
aircraft
[NASA-TN-D-8190] N76-21216

STROUSE, E. A.
Development of deicing techniques for dielectric
windows
[AD-A017097] N76-20136

SUBBAIAN, M. V.
Representation of the drag polar of a fighter
aircraft
A76-28610

SUBRAMANIAN, M. R.
Non-linear effect due to flow separation on flow
past wings and wing body combinations
A76-27741

SUTTON, J. M. D.
Thrust reverser design for airframe compatibility
A76-26650

SWAIN, K.
Composite inlays increase flutter resistance of
turbine engine fan blades
[ASME PAPER 76-GT-29] A76-25781

T

TARATIN, A. F.
Improvement of the precision of aircraft control
during completion of a plane turn maneuver
A76-27930

TIJDEMAN, H.
On the motion of shock waves on an airfoil with
oscillating flap
A76-27830

TOMBACH, I. H.
Investigation of vortex wake stability near the
ground
[AD-A017586] N76-20112

TOMOV, K.
Determination of the realizable flight hours for
aircraft
A76-27364

TOURNEMINE, G.
A direct method for computing non-symmetrical
plane flows at Mach number one
A76-27878

TROHA, W.
Composite inlays increase flutter resistance of
turbine engine fan blades
[ASME PAPER 76-GT-29] A76-25781

TROOST, G. K.
Bibliography on aircraft noise
[FOK-N-00-28] N76-20138

TSENG, K.
Fully unsteady subsonic and supersonic potential
aerodynamics for complex aircraft configurations
for flutter applications
[NASA-CR-146573] N76-20077

V

VANINO, R.
Supercritical wing design for a fighter type
experimental aircraft
A76-27856

The analysis of arbitrary wingbody combinations in
transonic flow using a relaxation method
A76-27879

VAUGHAN, V. L. J.
Impact dynamics research facility for full-scale
aircraft crash testing
[NASA-TN-D-8179] N76-21173

W

WAGNER, R. D.
Energy and economic trade offs for advanced
technology subsonic aircraft
[NASA-TN-X-72833] N76-20124

WASHINGTON, E. S.
Effect of the GBU-15 (cruciform wing) and GBU-15
(planar wing) stores on the aerodynamic
characteristics of the F-4C aircraft
[AD-A017378] N76-20135

WATSON, W.
A comparison of matrix methods for calculating
eigenvalues in acoustically lined ducts
[NASA-TN-D-8186] N76-20941

WEBSTER, P. F.
Design of a 4 1/2 stage turbine with a stage
loading factor of 4.66 and high specific work
output
[NASA-CR-2659] N76-20146

WEINBERG, M. S.
A multi-variable control for a turbofan engine
operating at sea level static
[ASME PAPER 76-GT-71] A76-25814

WEISSHAAR, T. A.
Flutter of asymmetrically swept wings
[NASA-CR-146815] N76-21164

WELLS, W. R.
Dynamics and identification of flexible aircraft
[NASA-CR-2672] N76-21158

WHEAT, L. W.
A comparison of optimal control theory predictions
with actual pilot performance in a helicopter
longitudinal tracking task
[AD-A016441] N76-20153

WILBY, P. G.
Transonic aerodynamics and the helicopter rotor
A76-27864

WILCOX, D. E.
A study of the financial history of the U.S.
scheduled airlines and the improvement of
airline profitability through technology
[NASA-TN-X-73109] N76-20101

WILKIN, C. A.
Small scale noise and wind tunnel tests of upper
surface blowing nozzle flap concepts. Volume 1.
Aerodynamic test results
[NASA-CR-137747] N76-21159

WILSON, R. A.
Aircraft L-band balloon simulated satellite
experiments. Volume 1: Experiment description
and data modem test results
[AD-A017090] N76-20301

WINTER, H.
Measurements of the vertical movements of an
aircraft
[ESA-TT-215] N76-20152

WONG, J. L.
Characteristics of a 240 to 400 MHz 6-inch depth
cavity-backed cross open-sleeve dipole antenna
on a curved ground plane
[AD-A017367] N76-20387

WOODWARD, R. P.
Noise reduction from the redesign of a fan stage
to minimize stator lift fluctuations
[NASA-TN-X-71896] N76-21206

Y

YAJNIK, K. S.
Representation of the drag polar of a fighter
aircraft
A76-28610

YAMOV, A. G.
Analysis of failures in the parts of an aircraft
undercarriage
[AD-A017928] N76-21196

YEAKLEY, L. H.
Design of a test machine for biaxial testing of
composite-laminate cylinders
[AD-A016961] N76-20232



YIM, B.
Note on a numerical scheme for the
three-dimensional flow of a supercavitating wing
or strut with thin cavity
A76-28642

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / *A Special Bibliography (Suppl 72)*

JULY 1976

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF PROJ. 1368	N76-21024	P33616-74-C-0043
	N76-21194	N76-20232
	N76-21195	P44620-74-C-0058
AF PROJ. 1369	N76-20169	N76-20112
AF PROJ. 1467	N76-20232	MP51524005 N76-21178
AF PROJ. 2567	N76-20135	NASW-2624 N76-20151
AF PROJ. 3012	N76-20455	NASW-2791 N76-20078
AF PROJ. 3066	N76-20091	NAS1-6666 N76-21209
AF PROJ. 5635	N76-20339	NAS1-10210-8 A76-26384
AF PROJ. 7116	N76-20148	NAS1-13000 N76-20126
AF PROJ. 7371	N76-20136	NAS2-8135 N76-20104
AF PROJ. 7605	N76-21172	NAS2-8607 N76-21159
AF PROJ. 9781	N76-20112	N76-21160
BMFT-LFF-28	A76-27856	NAS2-8738 N76-21188
BVVG-TR-720-R-7600-42-009	A76-27879	NAS3-16790 A76-28029
BVVG-TR-720-7600-43-094	A76-27856	NAS3-17842 N76-21189
DA PROJ. 1F1-62204-AA-44	N76-20154	N76-21190
DA PROJ. 1F1-63208-DB-52	N76-20130	NAS3-18033 N76-20146
DA PROJ. 1F2-62203-AH-86	N76-20129	NAS3-18535 N76-21205
DA PROJ. 1F2-62209-AH-76	N76-20093	NAS3-18552 N76-21210
DA PROJ. 1T1-61102-B-31A	N76-20360	NAS3-18909 A76-28029
DAAJ02-73-C-0056	N76-20154	NAS5-20852 N76-20063
DAAJ02-73-C-0101	N76-20130	N76-20064
DAAJ02-74-C-0033	N76-20129	N76-20065
DOT-FA73WA-3161	N76-21211	N76-20066
DRME-73/030	A76-27877	NGR-22-004-030
E(04-3)-167	A76-25837	N76-20077
ERDA PROJECT 46	A76-25837	NGR-36-004-061
F04701-75-C-0076	N76-20386	N76-21158
F19628-75-C-0036	N76-20387	NGR-44-001-157
F33615-72-C-2083	N76-21024	N76-20082
	N76-21194	NGR-74-004-090
	N76-21195	A76-28606
F33615-73-C-1080	N76-20136	NR PROJ. 094-369
F33615-73-C-4093	N76-20148	N76-20095

1 Report No NASA SP-7037(72)	2 Government Accession No	3 Recipient's Catalog No	
4 Title and Subtitle AERONAUTICAL ENGINEERING A Special Bibliography (Supplement 72)		5 Report Date July 1976	6 Performing Organization Code
		8 Performing Organization Report No	
7 Author(s)		10 Work Unit No	
9 Performing Organization Name and Address National Aeronautics and Space Administration Washington, D. C. 20546		11 Contract or Grant No	
		13 *Type of Report and Period Covered	
12 Sponsoring Agency Name and Address		14 Sponsoring Agency Code	
		15 Supplementary Notes	
16 Abstract <p style="text-align: center;">This bibliography lists 184 reports, articles, and other documents introduced into the NASA scientific and technical information system in June 1976.</p>			
17 Key Words (Suggested by Author(s)) Aerodynamics Aeronautical Engineering Aeronautics Bibliographies		18 Distribution Statement Unclassified - Unlimited	
19 Security Classif (of this report) Unclassified	20 Security Classif (of this page) Unclassified	21 No of Pages 66	22 Price* \$4.00 HC

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA distributes its technical documents and bibliographic tools to ten special libraries located in the organizations listed below. Each library is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

PENNSYLVANIA

Carnegie Library of Pittsburgh

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library

MISSOURI

Kansas City Public Library

St. Louis Public Library

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati Public Library

Cleveland Public Library

Dayton Public Library

Toledo Public Library

OKLAHOMA

Oklahoma County Libraries, Oklahoma City

TENNESSEE

Memphis Public Library

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 750 Third Avenue, New York, New York, 10017.

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England. By virtue of arrangements other than with NASA, the British Library Lending Division also has available many of the non-NASA publications cited in STAR. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "#" and "*", from ESRO/ELDO Space Documentation Service, European Space Research Organization, 114, av. Charles de Gaulle, 92-Neuilly-sur-Seine, France.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
WASHINGTON D C 20546

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

SPECIAL FOURTH CLASS MAIL
Book

POSTAGE AND FEES PAID
NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION
NASA-451



POSTMASTER If Undeliverable (Section 158
Postal Manual) Do Not Return

NASA CONTINUING BIBLIOGRAPHY SERIES

NUMBER	TITLE	FREQUENCY
NASA SP-7011	AEROSPACE MEDICINE AND BIOLOGY <i>Aviation medicine, space medicine, and space biology</i>	Monthly
NASA SP-7037	AERONAUTICAL ENGINEERING <i>Engineering, design, and operation of aircraft and aircraft components</i>	Monthly
NASA SP-7039	NASA PATENT ABSTRACTS BIBLIOGRAPHY <i>NASA patents and applications for patent</i>	Semiannually
NASA SP-7041	EARTH RESOURCES <i>Remote sensing of earth resources by aircraft and spacecraft</i>	Quarterly
NASA SP-7043	ENERGY <i>Energy sources, solar energy, energy conversion, transport, and storage</i>	Quarterly
NASA SP-7500	MANAGEMENT <i>Program, contract, and personnel management, and management techniques</i>	Annually

Details on the availability of these publications may be obtained from

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Washington, D.C. 20546