

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

03

STIP

NASA-CR-149253 II

E77-10047

"Made available under NASA sponsorship in the interest of early and wide dissemination of Earth Resources Survey information and without liability for any use made thereof."

DETECTION AND MAPPING OF MINERALIZED AREAS IN THE CORTEZ-UINTA BELT, UTAH-NEVADA USING COMPUTER-ENHANCED ERTS IMAGERY

Type II Progress Report

Lawrence C. Rowan, U.S. Geological Survey, Reston, Va. 22092
Alexander F.H. Goetz, Jet Propulsion Laboratory, Pasadena, Ca. 91103
Roger P. Ashley, U.S. Geological Survey, Menlo Park, Ca. 94025

N77-14546

Unclass 00047

(E77-10047) DETECTION AND MAPPING OF MINERALIZED AREAS IN THE CORTEZ-UINTA BELT, UTAH-NEVADA USING COMPUTER-ENHANCED ERTS IMAGERY Progress Report (Geological Survey, Reston, Va.) 2 P HC A02/MF A01 CSCL 08B G3/43

SUMMARY OF RESULTS

1. The reflectance spectra of most hydrothermally altered rocks are characterized by broad ferric-iron absorption bands short of 1.1 μm and a sharper hydroxyl band near 2.2 μm ; maximum reflectance occurs near 1.6 μm . These features become more prominent as albedo increases.
2. MSS color-ratio composite images are the most effective and practical means for detecting and mapping limonitic rocks in areas having less than about 50 percent desert-brush cover and less than 25-35 percent coniferous-tree cover.
3. However, limonitic altered and limonitic unaltered rocks cannot be distinguished in MSS color-ratio composite images. In addition, some important altered rocks are not limonitic and therefore are not distinctive in MSS color-ratio composites. Significantly, most of these iron-deficient altered rocks have a prominent 2.2 μm absorption band.
4. Preliminary analysis of NASA 24-channel images for two contrasting sites shows, as indicated by analysis of the field spectra, that color-ratio composite images using 1.6/2.2 μm as one color and ratios of

23890

RECEIVED

NOV 22 1976

SIS/902.6

shorter wavelength bands for the other two colors are highly effective for distinguishing between limonitic unaltered and limonitic rocks and for detecting iron-deficient hydrated altered rocks. The importance of the 1.6/2.2 μm ratio image results from the general absence of the 2.2 μm hydroxyl band in unaltered rocks and the persistence of this band in altered rocks.

5. Comparison of the respective estimated costs of using the MSS color-ratio composite images and conventional field methods for mapping hydrothermally altered rocks suggests that a 10:1 benefit can be obtained for large well-exposed areas where limonitic altered rocks are widespread and limonitic unaltered rocks are not common. The benefit declines sharply as the abundances of limonitic unaltered rocks and iron-poor altered rocks increases. The availability of spectral information in the 1.6 μm and 2.2 μm regions would restore the above mentioned benefit. The cost benefit declines as the size of the map area decreases. However, continuously rising manpower and field-operating costs work to the advantage of the MSS approach. Higher spatial resolution would also increase the cost benefit.