

## General Disclaimer

### One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

CR 151339

PROGRAM DOCUMENTATION  
FOR  
ELAPSED TIME TO OXYGEN AND HYDROGEN  
CAUTION AND WARNING SYSTEM  
FOR CAPTIVE/ACTIVE 1 AND 3 FLIGHTS  
CPD 710

(NASA-CR-151339) PROGRAM DOCUMENTATION FOR  
ELAPSED TIME TO OXYGEN AND HYDROGEN CAUTION  
AND WARNING SYSTEM FOR CAPTIVE/ACTIVE 1 AND  
3 FLIGHTS (Lockheed Electronics Co.) 8 p  
HC A02/MF A01

N77-23187

Unclas  
26141

CSCI 22A G3/18

Prepared By

Lockheed Electronics Company, Inc.  
Systems and Services Division  
Houston, Texas

Contract NAS 9-15200

For

Avionics Systems Engineering Division



*National Aeronautics and Space Administration*  
**LYNDON B. JOHNSON SPACE CENTER**

*Houston, Texas*  
Apr 11 1977


PROGRAM DOCUMENTATION  
FOR  
ELAPSED TIME TO OXYGEN AND HYDROGEN  
CAUTION AND WARNING SYSTEM  
FOR CAPTIVE/ACTIVE 1 AND 3 FLIGHTS

Job Order 81-147  
CPD 710

PREPARED BY

  
James E. Hurst

APPROVED BY

  
H. T. Crenshaw, Supervisor  
Applied Physics Section

  
W. J. Reicks, Manager  
Applied Mechanics Department

Lockheed Electronics Company, Inc.  
Systems and Services Division  
Houston, Texas  
April 1977

## 1. INTRODUCTION

This memorandum provides the results for special High Pressur  Gas Storage (HPGS) simulation runs that were made to compute the elapsed time from T-0 disconnect (transfer to onboard reactant) to the caution and warning pressures for the primary oxygen ( $O_2$ ) and hydrogen ( $H_2$ ) systems of Orbiter Vehicle (OV) 101. The simulation runs were made for Approach and Landing Test (ALT) flights Captive/Active 1 and Captive/Active 3. The data for this memorandum were drawn from the simulation runs described in reference 1.

## 2. SYMBOLS

ALT	Approach and Landing Test
C/A	Captive/Active
C/W	Caution and Warning
H <sub>2</sub>	Hydrogen
HPGS	High Pressure Gas Storage
hr	Hour
lb	Pounds
O <sub>2</sub>	Oxygen
OV	Orbiter Vehicle
psia	Pounds per Square Inch Absolute

### 3. METHOD

Special simulation runs were made using the HPGS program to determine the amount of elapsed time required for primary O<sub>2</sub> and primary H<sub>2</sub> tanks to cross over to the secondary O<sub>2</sub> and H<sub>2</sub> tanks (ref. 1). From these simulation runs, elapsed time to caution and warning pressures and quantities remaining in the primary systems at these pressures were taken.

To determine the required data values, the following assumptions were used in performing the analyses, together with the assumptions and constraints described in reference 1.

O<sub>2</sub> and H<sub>2</sub> caution and warning (C/W) pressures are defined as:

- a. O<sub>2</sub> C/W pressure is 1170 psia.
- b. H<sub>2</sub> C/W pressure is 720 psia.

#### 4. RESULTS

The results for the analyses are presented in table I, which shows the elapsed time from T-0 disconnect to the C/W pressures, the quantity remaining at the C/W pressures, and the elapsed time from C/W to primary/secondary system cross over.

This memorandum fulfills the requirement request made by T. Davies of NASA/EP5.

TABLE I. - CAPTIVE/ACTIVE 1 AND 3 CAUTION AND WARNING DATA

	CAPTIVE ACTIVE 1		CAPTIVE ACTIVE 3	
	O <sub>2</sub>	H <sub>2</sub>	O <sub>2</sub>	H <sub>2</sub>
Elapsed time to C/W, hr.....	3.3230.....	3.710.....	3.3233.....	3.716
Quantity remaining in primary system, lb.....	55.899.....	2.956.....	55.898.....	2.947
Elapsed time from C/W to primary/secondary crossover, hr.....	1.530.....	1.490.....	1.526.....	1.489

## 5. REFERENCES

1. Hurst, J.E.: Captive Active 1 and 3 Energy Requirements for Primary/secondary Crossover, AMD 037, Lockheed Electronics Company, Inc., March 15, 1977.