

N79-31178

D12

FIREMEN PROGRAM

STATUS REPORT

R.A. Anderson and G.A. Johnson
Boeing Commercial Airplane Company
March 1979

PRECEDING PAGE BLANK NOT FILMED

DEVELOPMENT AND FABRICATION PROGRAMS

DEVELOPMENT PROGRAM



OVERVIEW

- **BEGAN IN 1975**
- **FOUR PHASE PARTICIPATION**
- **INTERIOR SANDWICH PANEL DEVELOPMENT**

OBJECTIVES

- **IMPROVE**
 - **FLAMMABILITY**
 - **SMOKE EMISSION**
 - **TOXICITY**
- **MAINTAIN**
 - **MECHANICAL PROPERTIES**
 - **AESTHETICS**
 - **SERVICEABILITY**
 - **COSTS**

SANDWICH PANEL MAKEUP



- **PHASE I – BASELINE LAVATORY BURN
(NAS2 – 8700)**
- **PHASE II – RESIN SYSTEM DEVELOPMENT
(NAS2 – 8700)**
- **PHASE III – DECORATIVE FILM DEVELOPMENT
(NAS2 – 8700)**
- **PHASE IV – DECORATIVE INK DEVELOPMENT
(NAS2 – 9864)**


PHASE I – BASELINE LAVATORY BURN

- **747 LAVATORY MODULE**
- **TEST CONDITIONS**
 - **30 MINUTES**
 - **DOOR CLOSED**
 - **10 POUNDS TRASH**
- **INFLIGHT, UNOBSERVED FIRE**

RESULTS

- **FIRE CONTAINED**
- **CURRENT CONSTRUCTION ADEQUATE**
- **NASA CR-152074**

PHASE II – RESIN SYSTEM DEVELOPMENT




APPROACH

- **CANDIDATE RESIN SYSTEMS**
 - **BASELINE EPOXY**
 - **BISMALEIMIDE**
 - **PHENOLIC**
 - **POLYIMIDE**
- **TESTING MATRIX**
 - **FLAMMABILITY, SMOKE, AND TOXICITY**
 - **MECHANICALS AND AESTHETICS**



RESULTS

- **PHENOLICS**
 - **FLAMMABILITY, SMOKE, AND TOXICITY**
 - **MATERIAL AND FABRICATION COSTS**
 - **LABORATORY SCALE TESTING**
- **PROBLEM**
 - **AESTHETICS**
- **NASA CR-152120**

DECORATIVE LAMINATE MAKEUP



PHASE III – DECORATIVE FILM DEVELOPMENT



OVERVIEW

- **NUMEROUS CANDIDATES**
- **TESTING MATRIX**
 - **FLAMMABILITY, SMOKE, AND TOXICITY**
 - **MECHANICALS AND AESTHETICS**

APPROACH

- **SINGLE FILM**
- **SOFT DECORATIVE LAMINATE**
- **HARD DECORATIVE LAMINATE**
- **SANDWICH PANEL**

SINGLE FILM EVALUATION

- **LOI**
- **D_S AT 1.5 AND 4 MINUTES**
- **D_M**
- **CO, HF, AND HCL AT 4 MINUTES**
- **18 CANDIDATES**

EVALUATION FORMULAS

$$A = \left(\frac{LOI}{300} \right) + \left(\frac{50 - D_S(1.5)}{450} + \frac{100 - D_S(4.0)}{900} + \frac{200 - D_M}{1800} \right) + \left(\frac{100 - CO}{900} + \frac{10 - HCL}{90} + \frac{100 - HF}{900} \right)$$


200

$$B = \left(\frac{LOI}{100} \right)^{1/3} \times \left[\left(\frac{50 - D_S(1.5)}{50} \right) \left(\frac{100 - D_S(4.0)}{100} \right) \left(\frac{200 - D_M}{200} \right) \right]^{1/9} \times \left[\left(\frac{100 - CO}{100} \right) \left(\frac{10 - HCL}{10} \right) \left(\frac{100 - HF}{100} \right) \right]^{1/9}$$

FURTHER EVALUATION


- **PRINTABILITY**
- **EMBOSSABILITY**
- **UV STABILITY**
- **HEAT RELEASE**
- **SMOKE EMISSION**
- **TOXIC GAS EMISSION**
- **FLAME SPREAD INDEX**
- **5 CANDIDATES**

SMOKE EMISSION




TOXIC GAS EMISSION

203



FLAME SPREAD INDEX



EVALUATION FORMULAS

$$A = \left(\frac{35 - I_S}{105} \right) + \left(\frac{50 - D_S(1.5)}{450} + \frac{100 - D_S(4.0)}{900} + \frac{100 - D_M}{900} \right) \\ + \left(\frac{200 - CO}{2400} + \frac{10 - HCN}{120} + \frac{10 - NO_X}{120} + \frac{150 - HF}{1800} \right)$$

2015

$$B = \left(\frac{35 - I_S}{35} \right)^{1/3} \times \left[\left(\frac{50 - D_S(1.5)}{50} \right) \left(\frac{100 - D_S(4.0)}{100} \right) \left(\frac{100 - D_M}{100} \right) \right]^{1/9} \\ \times \left[\left(\frac{200 - CO}{200} \right) \left(\frac{10 - HCN}{10} \right) \left(\frac{10 - NO_X}{10} \right) \left(\frac{150 - HF}{150} \right) \right]^{1/12}$$


CURRENT CANDIDATES

- **TOP FILM**
 - **PVF (CLEAR)**
- **SUBSTRATE FILMS**
 - **ARAMID**
 - **FM-PVF**
 - **PVF (WHITE)**
 - **PVF₂**
 - **DUPONT EXPERIMENTAL**
 - **FPE-P**

FUTURE WORK

- **SOFT DECORATIVE LAMINATES**
 - **SMOKE AND TOXIC GAS EMISSION**
 - **60 SEC VERTICAL FLAMMABILITY**
 - **PEEL STRENGTH**
- **HARD DECORATIVE LAMINATES**
 - **PEEL STRENGTH**
 - **AESTHETICS**
 - **ABRASION RESISTANCE**

PHASE IV – DECORATIVE INK DEVELOPMENT




MATERIAL REQUIREMENTS

- **5 MIL FILM**
- **LOI \geq 35**
- **$D_S \leq 20$ (2.5 W/CM², 4 MINUTES)**
- **TGA (N₂ AND AIR) RT \rightarrow 250° C**
- **LC₅₀ \geq 70 MG/L**


APPROACH

- **UV CURED INKS**
 - **VISCOSITY VARIATION**
 - **AIR QUALITY REGULATIONS**
 - **TECHNOLOGY AVAILABLE**
- **SUBCONTRACT**
 - **K.C. COATINGS, INC.**
 - **6-MONTH EFFORT**
 - **NEGOTIATIONS IN PROGRESS**

SMOKE EMISSION



TOXIC GAS EMISSION



FABRICATION PROGRAMS


OVERVIEW

- **BEGAN IN DECEMBER, 1977**
- **INTERIOR SANDWICH PANELS**
- **LAVATORY PANEL FABRICATION
(NAS9 – 13000)**
- **INTERIOR PANEL FABRICATION
(NAS2 – 10004)**

LAVATORY PANEL FABRICATION



- **NASA-JSC**
- **9 PANELS**
- **DC-10 LAVATORY SIMULATION**

LAVATORY SCHEMATIC





DOUBLE DECORATED PANEL

217



SINGLE DECORATED PANEL


ORIGINAL PAGE IS
OF POOR QUALITY



UNDECORATED PANEL

FOR BEST PAGE IS
OF WORK
QUALITY


219



CIBA GEIGY 917G

NOMEX CORE


CIBA GEIGY 917G



INTERIOR PANEL FABRICATION

- **NASA-ARC**
- **56 PANELS**
- **40 X 96 X 1 INCH**
- **FAA-NAFEC**
- **VARIOUS THERMOPLASTIC FILMS**

PANEL MAKEUP



PANEL MATERIALS

| DECORATIVE FILM | | | ADHESIVE | PREPREG | |
|-------------------------|---------|------------------------|----------|----------|----------|
| TOP | INK | SUBSTRATE | | 181 | 120 |
| 1 MIL PVF | ACRYLIC | 2 MIL PVF | — | EPOXY | EPOXY |
| 1 MIL PVF +3 MIL PVC | ACRYLIC | 2 MIL PVF | TF-252 | EPOXY | EPOXY |
| — | — | 3 MIL PC | TF-252 | PHENOLIC | PHENOLIC |
| 1 MIL PVF | — | 2 MIL PVF | TF-252 | PHENOLIC | PHENOLIC |
| 1 MIL PVF | — | 5 MIL PC | TF-252 | PHENOLIC | PHENOLIC |
| — | — | 3 MIL PVF ₂ | TF-252 | PHENOLIC | PHENOLIC |
| — | — | 3 MIL PES | TF-252 | PHENOLIC | PHENOLIC |
| 1 MIL PVF | ACRYLIC | 2 MIL PVF | TF-252 | PHENOLIC | PHENOLIC |

222

A