

## N O T I C E

THIS DOCUMENT HAS BEEN REPRODUCED FROM  
MICROFICHE. ALTHOUGH IT IS RECOGNIZED THAT  
CERTAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RELEASED  
IN THE INTEREST OF MAKING AVAILABLE AS MUCH  
INFORMATION AS POSSIBLE

8.0-10255

NASA CR-

160718

JSC-14556

"Made available under NASA sponsorship  
in the interest of early and wide dis-  
semination of Earth Resources Survey  
Program information and without liability  
for any use made thereof."

DESIGN SPECIFICATION  
FOR  
MERGE OF BTREAD, PHASE1 AND PHASE2  
ACCURACY ASSESSMENT PROGRAMS

Job Order 71-475

(TIRF 78-0008)

(E80-10255) DESIGN SPECIFICATION FOR MERGE  
OF BTREAD, PHASE 1 AND PHASE 2 ACCURACY  
ASSESSMENT PROGRAMS (Lockheed Electronics  
Co.) 11 p HC A02/MF A01 CSCL 09B

880-30838

Unclas  
00255

63/43

Prepared By  
Lockheed Electronics Company, Inc.  
Systems and Services Division  
Houston, Texas  
Contract NAS 9-15200

For  
EARTH OBSERVATIONS DIVISION  
SPACE AND LIFE SCIENCES DIRECTORATE



*National Aeronautics and Space Administration*  
**LYNDON B. JOHNSON SPACE CENTER**  
*Houston, Texas*

October 1978

LEC-12833

JSC-14556

DESIGN SPECIFICATION  
FOR  
MERGE OF BTREAD, PHASE1 AND PHASE2  
ACCURACY ASSESSMENT PROGRAMS

Job Order 71-475

(TIRF 78-0008)

Prepared by  
A. Rios

LEC

*James A. Wilkinson*  
for Philip L. Krumm, Acting Supervisor  
Scientific Applications Section

*Elinor M. Hsu*  
E. M. Hsu, Supervisor  
Accuracy Assessment Section

NASA

*James M. Sulester*  
James M. Sulester, Technical Monitor  
Systems & Facilities Branch

*David E. Pitts*  
David E. Pitts, Manager  
Accuracy Assessment

Prepared By  
Lockheed Electronics Company, Inc.  
For  
Earth Observations Division

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION  
LYNDON B. JOHNSON SPACE CENTER  
HOUSTON, TEXAS

October 1978

LEC-12833

## CONTENTS

Section	Page
1. SCOPE. . . . .	1-1
2. APPLICABLE DOCUMENTS. . . . .	2-1
3. DESIGN OF SPECIFICATION. . . . .	3-1

## FIGURES

Figure	Page
1. Program Data Flow . . . . .	3-2
2. Functional Diagram of BTMAIN . . . . .	3-3

1. Report No. JSC-14556		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Design Specification for Merge of BTREAD, PHASE1 and PHASE2 Accuracy Assessment Programs				5. Report Date October 1978	
				6. Performing Organization Code	
7. Author(s) A. Rios				8. Performing Organization Report No. LEC-12833	
9. Performing Organization Name and Address Lockheed Electronics Company, Inc. Systems and Services Division 1830 NASA Road 1 Houston, Texas 77058				10. Work Unit No.	
				11. Contract or Grant No. NAS 9-15200	
				13. Type of Report and Period Covered Technical Report	
12. Sponsoring Agency Name and Address				14. Sponsoring Agency Code	
15. Supplementary Notes Reference: Implementation Specification Document for Merge of BTREAD, PHASE1, and PHASE2 Accuracy Assessment Program. (JSC-14277)					
16. Abstract  Program modules BTREAD, PHASE1, and PHASE2 convert digitized ground truth data to a line and sample image format which is in registration with LACIE blind site segments. These registered line and sample ground truth data are then used to generate reports which are required to assess the accuracy of the CAMS classification and proportion estimates.  This document presents the design specification for the merge of these programs into one module					
17. Key Words (Suggested by Author(s))				18. Distribution Statement	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 10	22. Price*

\*For sale by the National Technical Information Service, Springfield, Virginia 22161

## 1. SCOPE

Program modules BTREAD, PHASE1 and PHASE2 are three stand-alone programs which are executed in sequence to convert and process data from a Bendix-100 tape and create a Universal Ground Truth Tape (UGTT). The present requirement is to merge these three programs.

The merged program will increase efficiency through the elimination of the tape currently used to transmit data between BTREAD and PHASE1 and through the simplification of RUN procedures for the user. An option will be included to select the disk instead of tape for the final output.

## 2. APPLICABLE DOCUMENTS

1. Implementation Specification Document for Merge of BTREAD, PHASE1, and PHASE2 Accuracy Assessment Programs, JSC-14277, LEC-12348, May 1978.
2. "As-Built" Design Specification for PDP 11/45 Accuracy Assessment System Using Disk Data File, LEC-11881.
3. LEC IDC, from D. McCarley to A. Anderson,  
Subject: Accuracy Assessment Data Flow, PC714-149.
4. TIRF 78-0008, Modification to AA Software BTREAD, PHASE1 & PHASE2.

### 3. DESIGN MODIFICATION

Programs BTREAD, PHASE1 and PHASE2 will be merged by changing each to a subroutine and developing a program to serve as a driver. However, the functions will not be performed in turn. PHASE1 will be merged with BTREAD to eliminate the need for an interim tape. Figure 1 shows the data flow through the program. A flow diagram of the program is shown in Figure 2.

Following are the actions to be taken to accomplish the merge:

- o BTMAIN will be developed to serve as the driver program.
- o BTREAD will become a subroutine. As each data record from the B100 tape is converted, the converted array will be passed to PHASE1. The data file, LABEL2.DAT will no longer be created. LABEL1.DAT or LABEL3.DAT will be selected by the user and created as LABEL.DAT but merely as a scratch file.

Several of the error conditions resulting from the data from the input tape will be handled differently. Instead of aborting the run, an error message will be printed, but the program will continue without processing the record in which the error occurred. The primary reason for this is to find all of the errors on the tape on one run.

- o PHASE1 will be changed to a subroutine and will be called by BTREAD. The data array will be passed to it through a calling argument.

The two data files created by this routine, HEAD.DAT and INTCPT.DAT, will be temporary files which will be deleted upon termination of the run.




Figure 1. Program data flow

~~3-2~~  
4




Figure 2. Flow Diagram of BTMAIN

The limitation that a field boundary cannot intersect an output line more than 10 times will be changed. The limitation will be increased to 20 by increasing the dimension of array X5 from (200,11) to (200,21). The corresponding array X6 will be changed from 512 to 1000.

- o PHASE2 will be changed to a subroutine to be called by BTMAIN. The output will be a Universal Ground Truth Tape or a disk file at the option of the user.

The dimension of array X2 will be changed from (392,80) to (392,40) along with the necessary logic in order to permit the program to fit within the core limitations. The increase in the array size in PHASE1 will require an increase in array X1 from 512 to 1000.

If a data file is selected for the output rather than a tape, the name of the data file will be created dynamically. The conversion of the segment number from integer to ASCII and the computation of the Julian date will be performed internally.

- o BTREAD.DAT will be used for user input. Four lines of data will be required:

- |   |                  |
|---|------------------|
| 1. B-100 tape ID.<br>Ex. MT 1 1   | FORMAT<br>A2,2I2 |
| 2. Segment number, day, month, year, suffix for DR<br>Ex. _1005_ _ _10_ _ _10_ _ _78A | 4I5,A1           |
| 3. Flag to select LABEL.DAT data.<br>1 = LABEL1.DAT<br>3 = LABEL3.DAT                 | I1               |
| 4. Output tape ID or disk selection<br>MT_0_1 or XT_0_1 for tape<br>DB_0 for disk.    | A2,2I2           |

If neither MT nor XT are entered, the selection will default to disk. However, an entry must be available to the program.

- o The program will be overlaid by using an Overlay Description Language (ØDL) file.
- o The system tape I/O routines, WTQIØ will be used instead of LECTAP.

Through coordination and with the concurrence of the user, two modifications suggested in Reference 1 will not be made. The first is the modification suggested in the second paragraph of 3.2.2 PHASE1 MODIFICATIONS. The second is in paragraph 1 of 3.3.1 PHASE2 MODIFICATIONS. It has been determined that the implementation of these modifications would not be cost effective.