

Advanced Space Transportation Systems

**Space Station Evolution
Beyond the Baseline 1991
(2nd Symposium Evolution of SSF)**

**Robert J. Davies
Chief, Advanced Transportation Branch
Advanced Program Development
Office of Space Flight**

2348

NCA52981
60387
56-16
N92-17104

Agenda

- **Heavy Lift Launch Vehicle**
- **Cargo Transfer Vehicle**
- **Space Transfer Vehicle Concepts**
- **Two-Way Personnel Transport**
- **Transportation Node Requirements**
- **Technology Needs**

National Space Launch Strategy

a. The National Space Launch Strategy is composed of four elements:


- (1) Ensuring that existing space launch capabilities, including support facilities, are sufficient to meet U.S. Government manned and unmanned space launch needs.
- (2) Developing a new unmanned, but man-rateable, space launch system to greatly improve national launch capability with reductions in operating costs and improvements in launch system reliability, responsiveness, and mission performance.
- (3) Sustaining a vigorous space launch technology program to provide cost effective improvements to current launch systems, and to support development of advanced launch capabilities, complementary to the new launch system.
- (4) Actively considering commercial space launch needs and factoring them into decisions on improvements in launch facilities and launch vehicles.

b. These strategy elements will be implemented within the overall resource and policy guidance provided by the President.


Heavy Lift Launch Vehicle Requirements/Needs

- **High Reliability**
- **Good Availability/Operability**
- **Payload Capability 50–80k and 100–200k**
- **Modular and Evolvable**
- **Available in Late 1990 ~ to Early 2000**
- **Potential Applications**
 - **Space Station**
 - **Space Exploration (Lunar and Mars)**
 - **Low and High Orbit DoD Applications**

Basic Heavy Lift Vehicle Options




Future Launch Vehicle Concept



105

External Tank Application Potential


Std ET



Modifications/Changes

- Add Avionics/Payload Adapter
- Add Forward Skirt
- Add Fwd Dome (Same as LH₂ Fwd Dome)
- Add Barrel Section
- Modify Feedline Outlet
- Stiffen Panels
- Add Feedline
- Stiffen Barrels 1, 2, 3, & 4
- Modify Aft Dome Frame for Engine Module Attach
- Modify Feedline Outlet
- Add Aft Skirt
- Add Engine Module

Common Core




1.5 Stage Driven
 HLLV Driven
 Applicable to Both Vehicles

Representative NLS Reference Vehicle Performance


Vehicles	Payload ~ Klbs			
	SSF Mission		80 x 150 N.M. Orbit	
	Eng. Out	No Eng. Out	Eng. Out	No Eng. Out
	STME	STME	STME	STME
HLLV (2 ASRMs)				
- Core w 3 Engines	-	117	-	-
- Core w 4 Engines	101	109	-	-
1.5 Stage (6 Engines)	14	-	49	~65
1.5 Stage (5 Engines)	-	-	-	64

Cargo Transfer Vehicle (CTV)

In-LEO Transportation Functions




Cargo Transfer Vehicle Concept



109

Cargo Transfer Vehicle (CTV)


Existing Stage Candidates



Features


- Performs Circularization & Phasing Burns
- Controls During Prox Ops
- Deorbits Strongback & Recovers
- Independent Return Flight to SSF
- Returns on STS

Evolution Flow




111

Space Transfer Vehicle Concepts




Lunar Transportation Options


Lunar Transfer




Chemical/Aerobrake
Single Stage



Chemical/Aerobrake
1 1/2 Stage



Chemical/Aerobrake
Single P/A




Chemical - All Propulsive
Module w/Recoverable P/A




Chemical - All Propulsive
Expendable


Lunar Lander



Single Stage




Two Stage




Single P/A

* Not to Scale *


Mars Transportation Options



Cryogenic/Aerobrake Reference Configuration




Cryogenic/All Propulsive Configuration




Nuclear Thermal Propulsion Configuration

114

Solar Electric Propulsion Configuration



Nuclear Electric Propulsion Configuration



Gas Core Nuclear Reactor Configuration

Augustine Committee Recommendation

"That NASA initiate design effort so that manned activity in the Space Station could be supported in the absence of the Space Shuttle. Crew recovery capability must be available immediately, and *provision made for the relatively rapid introduction of a two-way personnel transport module* on a selected expendable launch vehicle.

ACRV-D Baseline Concept

Summary of Design Deltas from ACRV-CERV

Crew Module

(12,000 to 15,000 lbm)

New Components


- External Structure for LES Support
- 2 string laser docking system
- Hand controllers

Replaced Components

- Berthing with docking mechanism

Increased Components

- 2 more battery modules
- 1 more EPDC string
- ECLSS LiOH expendables
- 2 more RCS jet drivers
- S-band data capability
- UHF voice comm capability
- 1 more multi-function display
- 2 more GPS strings
- Parachute size
- 33% more wiring



Service Module

(2900 to 7400 lbm)

New Components

- Cold gas RCS

Replaced Components

- Hydrazine with MMH/NTO
- Integrated OMS/RCS system

Increased Components

- 5 more battery modules
- 1 more EPDC string
- ECLSS consumables
- 33% more wiring


Additional Elements

- Launch Escape System (4750 lbm)
- Launch Shroud (900 lbm)
- Launch Vehicle Adapter (160 lbm)

Liftoff Mass


28,210 lbm

Two-way Transportation System Options




**ACRV-derived
(ACRV-D)**

- JSC Inhouse Design
- SCRAM Based with more robust Service Module



Biconic





HL-20

Lifting Body

- LaRC Preferred Concept

SEI Transportation Nodes Options

	PRO's	CON's
 SSF Based	<ul style="list-style-type: none"> • Enhanced SSF Utilization • No New Major SSF Elements • No Crew Transfer For Operations 	<ul style="list-style-type: none"> • Additional Free Flying Science Platforms • Dynamic μ-g environment may Interfere With Science • Assembly Intensive Philosophy • Increased SSF Resource Requirements • SSF Hooks And Scars
  Free Flying Node	<ul style="list-style-type: none"> • No Interference With Science Programs • Removes Potentially Hazardous Systems (Nuclear, Etc.) • Reduced Schedule Risk • No Propellant Venting at SSF • Node Utilizes SSF Hardware 	<ul style="list-style-type: none"> • Man Tended System • New Platform Required • Crew Transport for EVA Contingencies • Additional Logistics Operations

Technology Needs

- **Launch Vehicles**
 - Propulsion
 - Avionics
 - Materials
 - Operations

- **Space Transfer Vehicles**
 - Propulsion
 - Avionics
 - Aerobraking
 - Cryogenic Fluid Storage and Transfer