

NASA/CR-1998-207647
ICASE Interim Report No. 32



Barriers to Achieving Textbook Multigrid Efficiency (TME) in CFD

Achi Brandt
The Weizmann Institute of Science, Israel

Institute for Computer Applications in Science and Engineering
NASA Langley Research Center
Hampton, VA

Operated by Universities Space Research Association



National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

Prepared for Langley Research Center
under Contracts NAS1-97046 & NAS1-19480

April 1998

Available from the following:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 487-4650

Barriers to Achieving Textbook Multigrid Efficiency (TME) in CFD

Achi Brandt[†]

Abstract

“Textbook multigrid efficiency” (TME) means solving a discrete PDE problem in a computational work which is only a small (less than 10) multiple of the operation count in the discretized system of equations itself. As a guide to attaining this optimal performance for general CFD problems, the table below lists every foreseen kind of computational difficulty for achieving that goal, together with the possible ways for resolving that difficulty, their current state of development, and references.

Included in the table are staggered and nonstaggered, conservative and non-conservative discretizations of viscous and inviscid, incompressible and compressible flows at various Mach numbers, as well as a simple (algebraic) turbulence model and comments on chemically reacting flows. The listing of associated computational barriers involves: non-alignment of streamlines or sonic characteristics with the grids; recirculating flows; stagnation points; discretization and relaxation on and near shocks and boundaries; far-field artificial boundary conditions; small-scale singularities (meaning important features, such as the complete airplane, which are not visible on some of the coarse grids); large grid aspect ratios; boundary layer resolution; and grid adaption.

Introduction (by James L. Thomas, NASA LaRC)

Computational fluid dynamics (CFD) is becoming a more important part of the complete aircraft design cycle because of the availability of faster computers with more memory and improved numerical algorithms. As an example, all of the external cruise-surface shapes of the new Boeing 777 wide-body subsonic transport were designed with CFD [R1]. The cruise shape of such a vehicle is designed to minimize viscous and shock wave losses at transonic speeds and can be analyzed with potential flow methods coupled with interacting boundary layers. Off-design performance associated with maximum lift, buffet, and flutter and the determination of stability and control derivatives, involving unsteady separated and vortical

[†] Department of Applied Mathematics and Computer Science, The Weizmann Institute of Science, Rehovot 76100, Israel. mabrandt@weizmann.weizmann.ac.il This research was supported by the National Aeronautics and Space Administration under NASA Contract Nos. NAS1-19480 and NAS1-97046 while the author was in residence at the Institute for Computer Applications in Science and Engineering (ICASE), Mail Stop 403, NASA Langley Research Center, Hampton, VA 23681-2199.

flows with stronger shock waves, are determined largely by experimental methods. Computational simulations of these flowfields require the use of Reynolds-averaged Navier-Stokes (RANS) methods; these computations for high-Reynolds flows over complex geometries are very expensive, the turnaround time is too long to impact the design cycle, and the turbulence models for separated flows have a high degree of variability. Thus in these areas experiments, rather than computations, are preferred for reasons of cost and uncertainty

Inroads are being made into these off-design areas with RANS methods. A major lesson learned from industrial use of RANS methods is that both the numerics and the physics must be improved substantially for a new procedure to replace an older procedure. Also, there is a synergistic interplay between the speed of the simulation and the fidelity of the turbulence model, since a larger parameter variation and/or model formulation can be explored on fine enough grids with a faster simulation. For example, the TLNS3D Navier-Stokes code [R2] found its way into use because it was the first three-dimensional Navier-Stokes code to show true multigrid performance, in which the cost scales linearly with the number of unknowns, and it incorporated a better turbulence model than the algebraic models then in use. Solutions with 1 million grid points could be converged in approximately 1 hr of Cray-2 time, which allowed spatial convergence studies to be conducted to ensure that the level of truncation error is sufficiently low, and the prediction of the angle of attack to attain a desired lift coefficient was improved over interacted potential methods [R3]. The faster turnaround of the multigrid procedure enabled the extension and calibration of the original two-dimensional turbulence model to three-dimensions, thus allowing a more accurate prediction of the transonic shock/boundary-layer interaction.

The current RANS solvers with multigrid require on the order of 1500 residual evaluations to converge the lift and drag to one percent of their final values for wing-body geometries near transonic cruise conditions. Complex geometry and complex physics simulations require many more residual evaluations to converge, if indeed convergence can even be attained. It is well-known for elliptic problems that solutions can be attained using full multigrid (FMG) processes in far fewer, on the order of 3-6, residual evaluations; this efficiency is known as textbook multigrid efficiency (TME). Thus, there is a potential gain of two orders of magnitude in operation count reduction if TME could be attained for the RANS equation sets. This possible two order of magnitude improvement in convergence represents an algorithmic floor since it is unlikely that faster convergence for these nonlinear equations could be attained. This algorithmic speed-up, however, coupled with further increases in computational speed can open up avenues and accelerate progress in many areas, including: the application of steady and time-dependent simulations in the high-lift, off-design, and stability and control areas; the usage of RANS solvers in the aerodynamic and multidisciplinary design areas; and the development of improved turbulence models.

The RANS equation sets are a system of coupled nonlinear equations which

are not, even for subsonic Mach numbers, fully elliptic, but contain hyperbolic factors. The theory of multigrid for hyperbolic and mixed-type equations is much less developed than that for purely elliptic equations. Resolution of complex geometries and the thin boundary layers at high Reynolds number cause the grid to be highly irregular and stretched, leading to a slowdown in convergence. Discontinuities, such as shocks and slip surfaces, introduce additional difficulties. These difficulties are illustrated in the sketch in Fig. 1 for a typical multi-element section of a three-dimensional wing with the flaps deployed at takeoff and landing conditions. Overcoming these difficulties poses a formidable challenge, especially because in order to attain optimal and robust convergence rates for the applications of interest in aircraft design, they must all be overcome.

Brandt, in 1984 [G84], summarized the state of the art for attaining multigrid performance for fluid dynamics. Since that time, there has been considerable progress in the field, although optimal results have only been shown for inviscid flows, viscous flows at low Reynolds number, and simple geometries. The methodology and theory that Brandt and others have developed is applicable to the RANS equations and can lead to optimal convergence rates; however, a rational and systematic attack on the barriers which stand in the way needs to be mounted. The purpose of this paper is to delineate clearly the barriers which exist to attaining optimal convergence rates for solutions to the fluid dynamic equations for complex geometries. The following sections identify the barriers, possible solutions, and current status of the problem. The paper is intended as a guide to attaining the optimal convergence goal and is written for the most part in a tabular form so that new solutions and updates to the current status can be made. When completed, the document is intended to list every type of computational difficulty encountered on the road to attaining TME for RANS and the solution paths taken. The insights, lessons learned, and methodologies gained from aerodynamic applications should be applicable to other areas such as acoustics, electromagnetics, hypersonic propulsion, and aerothermodynamics.

Preliminary comments

The table below does *not* refer to a vast literature on multigrid methods in CFD (see for example [AJ]), in which enormous improvements over previous (single-grid) techniques have been achieved, but without adopting the systematic TME approach. This approach insists on obtaining basically the same ideal efficiency to *every* problem, by a very systematic study of each type of difficulty, through a carefully chosen sequence of model problems. Several fundamental techniques are typically absent in the multigrid codes that have not adopted the TME strategy. Most important, those codes fail to decompose the solution process into separate treatments of each factor of the PDE principal determinant, and therefore do not identify, let alone treat, the separate obstacles associated with each such factor. Indeed, depending on flow conditions, each of those factors may have different ellipticity measures (some are uniformly elliptic, others are non elliptic at some or all of the relevant scales) and/or different set of characteristic surfaces,

requiring different combinations of relaxation and coarsening procedures.

The table deals only with *steady-state* flows and their *direct* multigrid solvers, i.e., not through pseudo-time marching. Time-accurate solvers for genuine *time-dependent* flow problems are in principle simpler to develop than their steady-state counterparts. Using semi implicit or fully implicit discretizations, large and adaptable time steps can be used, and parallel processing across space *and time* is feasible [R88]. The resulting system of equations (i.e., the system to be solved at each time step) is much easier than the steady-state system because it has better ellipticity measures (due to the time term), it does not involve the difficulties associated with recirculations, and it comes with a good first approximation (from the previous time step). A simple multigrid “*F* cycle” at each time step can solve the equations much below the discretization errors of that step [Par]. It is thus believed that fully efficient multigrid methods for the steady-state equations will also yield fully efficient and highly parallelizable methods for time-accurate integrations.


Acknowledgement

Contributions to the table were made by David Sidilkover (ICASE), Jerry C. South (NASA Langley Research Center, retired), R. Charles Swanson (NASA Langley Research Center), and Shlomo Ta’asan (Carnegie Mellon University).

Textbook Multigrid Barriers (After Brandt, 1997)

Far-Field Boundary Conditions

Grid Aligned with Characteristics



Attaining Ideal Multigrid Efficiency in CFD: Difficulties and Cures

<i>Difficulty</i>	<i>Possible Solutions</i>	<i>Status</i>
<ul style="list-style-type: none"> ● Uniformly elliptic scalar equation on uniform grids in general domains 	<p>Multigrid cycles, guided by local mode analyses + FMG</p>	<p>TME demonstrated 1971 [B73], [B77] and rigorously proved [RLMA], [RQMA]</p>
<ul style="list-style-type: none"> ● Nonlinearity 	<p>FAS + FMG continuation</p>	<p>Demonstrated 1975 [South], [B77], [G, §8.3.2]</p>
<ul style="list-style-type: none"> ● Fluid dynamics – general 	<p>See a review in [R88, §2]; at some points it is not fully up to date, but it concisely summarizes the main procedures needed for obtaining TME</p>	
<ul style="list-style-type: none"> ● Non-scalar PDE systems 	<ol style="list-style-type: none"> (1) General rules for the inter-grid transfers are given in [G, §4.3], with some more details in [RQMA, §3.3] (2) General approach to the design of relaxation, based on the operator principal matrix L and on the factors of $\det L$. Distribution matrix M and weighting (or preconditioning) matrix P are constructed so that PLM is triangular, containing the factors of $\det L$ on the main diagonal (separated from each other as much as possible, to avoid the complication described next). This (if necessary – together with the technique described next), leads to decomposing relaxation into simple schemes for the (scalar) factors of $\det L$ (3) For systems of PDE which are of mixed type (elliptic-hyperbolic) another possibility is to introduce new unknowns in terms of which elliptic and hyperbolic parts are separated 	<p>TME demonstrated in a number of cases (see below). TME <i>proved</i> for uniformly elliptic systems [RLMA], [RQMA]</p> <p>TME demonstrated for incompressible and compressible cases [T1]–[T5]</p>

Difficulty

Possible Solutions

Status

- *Product operator*: an equation $LU = f$, where $L = L_2L_1$, with the Fourier symbols $L_j(\theta) = e^{-i\theta \cdot x/h} L e^{i\theta \cdot x/h}$.

Assume a relaxation process for L_j is given, with the amplification factor $\mu_j(\theta)$ and the smoothing factor $\bar{\mu}_j$, ($j = 1, 2$)

Two possible approaches:

- (1) Introduce an explicit new unknown function V , replacing the equation with the pair of equations $L_1U - V = 0$ and $L_2V = f$, throughout the MG solution process (including, e.g., transferring residuals of both equations to coarse grids and correcting both u and v by interpolations from the corresponding coarse-grid values). The smoothing factor for this process is $\bar{\mu} = \max(\bar{\mu}_1, \bar{\mu}_2)$
- (2) Use V only as an auxiliary function in relaxation. That is: starting with $v = L_1u$, where u is the current approximation to U , perform ν_2 sweeps on the equation $L_2V = f$, yielding a new value \tilde{v} . Then perform ν_1 sweeps on the equation $L_1u = \tilde{v}$. The resulting amplification factor is $\mu(\theta) = \mu_1(\theta)^{\nu_1} + [1 - \mu_1(\theta)^{\nu_1}] L_1(\theta)^{-1} \mu_2(\theta)^{\nu_2} L_1(\theta)$, so in scalar cases $\bar{\mu} < \bar{\mu}_1^{\nu_1} + \bar{\mu}_2^{\nu_2}$

Not tried

Difficulty**Possible Solutions****Status**

⊙ **Smoothing for special CFD systems**

- Cauchy Riemann on staggered grid

$$L = \begin{pmatrix} \partial_x & \partial_y \\ \partial_y & -\partial_x \end{pmatrix}$$

- Stokes on staggered grid

$$L = \begin{pmatrix} -\Delta & 0 & \partial_x \\ 0 & -\Delta & \partial_y \\ \partial_x & \partial_y & 0 \end{pmatrix}$$

- Stokes, non-staggered

- (1) Quasi-elliptic discretization

$$L = \begin{pmatrix} -\Delta & 0 & \partial_x^{2h} \\ 0 & -\Delta & \partial_y^{2h} \\ \partial_x^{2h} & \partial_y^{2h} & 0 \end{pmatrix}$$

with averaging of the resulting pressure

- (2) h -elliptic discretization, e.g.

$$L = \begin{pmatrix} -\Delta & 0 & \partial_x^{2h} \\ 0 & -\Delta & \partial_y^{2h} \\ \partial_x^{2h} & \partial_y^{2h} & -\alpha h^2 \Delta \end{pmatrix}$$

M = distribution operator

P = preconditioner

(1) $M = L, \quad P = I$

(2) $P = L, \quad M = I$

(1) $M = \begin{pmatrix} 1 & 0 & -\partial_x \\ 0 & 1 & -\partial_y \\ 0 & 0 & -\Delta \end{pmatrix}, \quad P = I$

(2) $P = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ \partial_x & \partial_y & -\Delta \end{pmatrix}, \quad M = I$

Analogous to the staggered case:

$$M = \begin{pmatrix} 1 & 0 & -\partial_x^{2h} \\ 0 & 1 & -\partial_y^{2h} \\ 0 & 0 & -\Delta \end{pmatrix}$$

No modifications of the FMG algorithm is required, even in the quasi-elliptic case (as explained in [G84, §18.6]). In generalization to NS, pressure averaging is required of coarse-level results before their interpolation to the next finer level (whenever the coarse-level employs the quasi-elliptic discretization)

(1) TME demonstrated [BD], [Dinar]

(2) TME validated [T6]

(1) TME demonstrated [BD], [Dinar]

(2) TME validated [T6]

(1) In a quasi-elliptic approach, TME demonstrated [G84, §18.6], [quasi]

(2) TME demonstrated? (perhaps by J. Linden)

Difficulty

Possible Solutions

Status

- Non-conservative incompressible Euler

$$L = \begin{pmatrix} \underline{u} \cdot \underline{\nabla} & 0 & \partial_x \\ 0 & \underline{u} \cdot \underline{\nabla} & \partial_y \\ \partial_x & \partial_y & 0 \end{pmatrix}$$

(similarly 3D) on staggered grid, second (or higher) order discretization

- (1) Employ cycle index $\gamma = 2^p$, where p is the order of discretization

$$(2) M = \begin{pmatrix} 1 & 0 & -\partial_x \\ 0 & 1 & -\partial_y \\ 0 & 0 & \underline{u} \cdot \underline{\nabla} \end{pmatrix}$$

For each of the momentum equations employ a relaxation scheme which is fast *converging* for the advection operator $\underline{u} \cdot \underline{\nabla}$ (i.e., converging fast not only for $h-f$, but also for smooth characteristic components; see discussion of advection below)

- (3) Use canonical variable (u, v, P) on staggered grid, where $P = (u^2 + v^2)/2 + p$. Upwind only P , use central discretization for (u, v) . Relaxation is marching for P , and weighted (preconditioning) for (u, v)

- (1) TME for first-order discretization using W cycles shown in [BD], [Dinar]

- (2) TME demonstrated for 2D entering flows with second-order discretization [BY2] and for recirculating flows with first-order discretization [BY3]

- (3) TME in [T1-T3]

- Low-Reynolds Incompressible NS, staggered or not

Fully analogous to Stokes solvers: just replace Δ in L by $Q = -R^{-1}\Delta + \underline{u} \cdot \underline{\nabla}$

TME demonstrated 1978 [BD], [Dinar]

- High-Reynolds Incompressible NS, staggered or not

Fully analogous to Incompressible Euler (outside boundary layers: see discussion on such layers below): just replace $\underline{u} \cdot \underline{\nabla}$ everywhere with Q

TME demonstrated for first-order discretization on staggered ([BD], [Dinar] and non-staggered grids [G84, §19.5], and for second-order staggered discretization [BY2]

Difficulty

- *Compressible Euler*, non-conservative, on staggered grid:
The subprincipal operator on $(u_1, u_2, u_3, \rho, \varepsilon, p)$ is

$$L = \begin{pmatrix} \rho \underline{u} \cdot \nabla & 0 & 0 & 0 & 0 & \partial_1 \\ 0 & \rho \underline{u} \cdot \nabla & 0 & 0 & 0 & \partial_2 \\ 0 & 0 & \rho \underline{u} \cdot \nabla & 0 & 0 & \partial_3 \\ \rho^2 \partial_1 & \rho^2 \partial_2 & \rho^2 \partial_3 & \rho \underline{u} \cdot \nabla & 0 & 0 \\ p \partial_1 & p \partial_2 & p \partial_3 & 0 & \rho \underline{u} \cdot \nabla & 0 \\ 0 & 0 & 0 & -\partial p / \partial \rho & -\partial p / \partial \varepsilon & 1 \end{pmatrix}$$

$$\det L = \rho^5 (\underline{u} \cdot \nabla)^3 ((\underline{u} \cdot \nabla)^2 - a^2 \Delta)$$

$$a^2 = \frac{\partial p}{\partial \rho} + \frac{p}{\rho^2} \frac{\partial p}{\partial \varepsilon}, \quad M_0 = |\underline{u}|/a$$

ρ, ε, p defined at cell centers,

u_i – at center of cell faces perpendicular to the i -th coordinate

- 2D Compressible Euler, nonconservative and conservative, staggered grid, using canonical variables (u, v, S, H) . Structured and unstructured grids
- 2D/3D incompressible and compressible Euler: Canonical variables in which velocities are replaced by vector potential representation. Nonstaggered structured and unstructured grid

Possible Solutions

$$M = \begin{pmatrix} 1 & 0 & 0 & 0 & 0 & -\rho(\underline{u} \cdot \nabla) \partial_1 \\ 0 & 1 & 0 & 0 & 0 & -\rho(\underline{u} \cdot \nabla) \partial_2 \\ 0 & 0 & 1 & 0 & 0 & -\rho(\underline{u} \cdot \nabla) \partial_3 \\ 0 & 0 & 0 & 1 & 0 & -\rho^2 \Delta \\ 0 & 0 & 0 & 0 & 1 & -p \Delta \\ 0 & 0 & 0 & 0 & 0 & \rho^2 (\underline{u} \cdot \nabla)^2 \end{pmatrix}$$

The advection and full-potential operators are each relaxed by one of the approaches described for them below. (The *semi* coarsening described there would then be used as an *inner* multigrid cycle for *relaxing* one factor of the determinant, to be distinguished from the *outer* multigrid cycle, which can use *full* coarsening.)

Use (u, v) at cell edges, H at middle of cell, S at vertices. Upwind only S at momentum equations. Relax S, H by marching. (u, v) by a weighting relaxation. Crocco's form is used here to define relaxation

All variables at cell nodes. Relax hyperbolic quantities using marching. Relax vector potential using point Gauss-Seidel

Status

Not tried

TME in [T2–T5]

TME achieved (unpublished) for interior and exterior flows in 2D, interior in 3D

Difficulty

- *Compressible Navier-Stokes*, non-conservative.

The subprincipal operator on $(u_1, u_2, u_3, \rho, \varepsilon, p)$ is

$$L_s = \begin{pmatrix} Q_\mu - \bar{\lambda}\partial_{11} & -\bar{\lambda}\partial_{12} & -\bar{\lambda}\partial_{13} & 0 & 0 & \partial_1 \\ -\bar{\lambda}\partial_{21} & Q_\mu - \bar{\lambda}\partial_{22} & -\bar{\lambda}\partial_{23} & 0 & 0 & \partial_2 \\ -\bar{\lambda}\partial_{31} & -\bar{\lambda}\partial_{32} & Q_\mu - \bar{\lambda}\partial_{33} & 0 & 0 & \partial_3 \\ \rho^2\partial_1 & \rho^2\partial_2 & \rho^2\partial_3 & Q_0 & 0 & 0 \\ p\partial_1 & p\partial_2 & p\partial_3 & 0 & Q_\kappa & 0 \\ 0 & 0 & 0 & -\partial p/\partial\rho & -\partial p/\partial\varepsilon & 1 \end{pmatrix}$$

where $Q_\alpha = -\alpha\Delta + \rho\underline{u} \cdot \nabla$, $\bar{\lambda} = \lambda + \mu$, $\lambda = \frac{2}{3}\mu$,
 $\kappa = k/c_v$ (coefficient of thermal conductivity divided
 by the specific heat at constant volume),

$\det L_s = Q_\mu^2 \det L_c$, where L_c is the “core operator”

$$L_c = \begin{pmatrix} Q_0 & 0 & -\rho^2\Delta \\ 0 & Q_\kappa & -p\Delta \\ -\partial p/\partial\rho & -\partial p/\partial\varepsilon & Q_{\mu+\bar{\lambda}} \end{pmatrix}$$

At standard conditions of laminar air flow the
 Prandtl number $\gamma\mu/\kappa \approx 0.72$; for turbulence $\gamma\mu/\kappa \approx 0.9$,
 with $\gamma = c_p/c_v = 1.4$

Possible Solutions

Status

- (1) Where $\bar{\lambda}, \mu, \kappa \ll \rho h|\underline{u}|$ relax as in Euler above Not tried
- (2) Otherwise use

$$M = \begin{pmatrix} 1 & 0 & 0 & 0 & 0 & -\partial_1 \\ 0 & 1 & 0 & 0 & 0 & -\partial_2 \\ 0 & 0 & 1 & 0 & 0 & -\partial_3 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ \bar{\lambda}\partial_1 & \bar{\lambda}\partial_2 & \bar{\lambda}\partial_3 & 0 & 0 & Q_{\mu+\bar{\lambda}} \end{pmatrix}$$

relaxing each Q_μ by one of the approaches
 described for the advection-diffusion below,
 and L_c by procedures discussed for it below
 (in the chapter on non-elliptic operators)

<i>Difficulty</i>	<i>Possible Solutions</i>	<i>Status</i>
<ul style="list-style-type: none"> • Non-conservative <i>not staggered</i> Euler and NS 	<ul style="list-style-type: none"> (1) Probably similar to the staggered (cf. transition from staggered to non-staggered in Stokes) (2) In the 2D incompressible case: Premultiply L by a projection operator P, obtaining a Poisson equation for the pressure. Solve pressure equation with multigrid and the advection equation by marching downstream. 	<p>TME demonstrated for 2D incompressible Euler [RSS] in the cases of channel (with bump) and airfoil flows</p>
<ul style="list-style-type: none"> • <i>Conservative</i> discretization of any of the above systems 	<p>Apply a prefactor P such that PL has principally the above non-conservative form. See, however, the difficulty associated with FDA <i>decomposability</i> (discussed in the chapter on non-elliptic operators), which may arise with such PL operators</p>	<p>Mentioned in [G, §3.4], but not tested</p>

Difficulty

Possible Solutions

Status

⊙ **Non-elliptic operators**, or more precisely: small ellipticity measures at some (e.g., large) scales. The main operators of interest here are

- (1) The advection operator (or, similarly, the convection-diffusion operator at large Reynolds numbers).
- (2) The near-sonic full-potential operator or more generally the core operator L_c .

(See below a separate discussion of anisotropies caused by the discretization)

- Grid *aligned* with the characteristics

Block (e.g., line or plane) or ILU relaxation schemes and/or semi-coarsening, possibly in alternating directions, guided by mode analyses [B77], [Stages]

TME demonstrated in many cases

- Distinguishing different regimes (open vs. closed characteristics)

Running separately the relaxation subroutine of a given non-elliptic factor can

- (1) Separately check its convergence properties
- (2) Produce a scalar $\sigma \approx 1$ at regions of open characteristics and $\sigma \ll 1$ on closed characteristics (such as separated flow zones)

Difficulty

- *Non-aligned* grids, with *open* characteristics (e.g., entering flow): The main difficulty is the shorter distance (along the characteristics) for which a coarser grid still approximates some *smooth* solution components (characteristic components with intermediate cross-characteristic smoothness) [NESP], [BY1]

Possible Solutions

Three possible approaches, all guided by *half-space* two-level FMG mode analysis, using for simplicity the first Differential Approximation (FDA) to the discrete operator [NESP], [G, §7.5]:

- (1) Downstream-ordered relaxation marching [R88, §2.3]. (Suitable only for the advection factor, sometimes still requires W cycles, and not very good for massively parallel processing). In the case of an $O(h^p)$ discretization which is not purely upstreamed, relaxation should involve a predictor-corrector downstream marching. If the predictor order is q , the corrector should be applied at least p/q times.
- (2) Semi-coarsening (especially for the near-sonic full-potential operator). Better suits massive parallel processing
- (3) Cycle index = $2^{p/m}$, where p is the order of discretization and m is the order of the differential factor. (Suitable actually only for the advection operator, for which $m = 1$; especially attractive $p = 2$ in 3D; not requiring ordered relaxation, but still disadvantageous for massively parallel processing because of the high cycle index)

Status

- (1) TME demonstrated in [BY2], and in Ruge's recent calculations, both for the advection operator by itself and as part of the incompressible Euler system
- (2) TME has been shown for the sonic full-potential operator [sonic]
- (3) For $p = 1$, TME has been shown on various occasions. For $p = 2$, should be tried

Difficulty

Possible Solutions

Status

- The mixed *convection-diffusion* operator with order p approximation, having natural viscosity ν and artificial viscosity αh^p

Treatment as elliptic operator on levels where $\nu \gtrsim (2^p \cdot 4 - 5)\alpha h^p$ and as the non-elliptic advection operator otherwise

Not precisely tried

- *Closed* characteristics (recirculating flows). Here *uniformity* of viscosity (including numerical viscosity) is important for accuracy. The *size* of viscosity is less important here (except at resolved boundary layers, discussed below). In fact, a uniform $O(h)$ artificial viscosity can yield higher order approximations. Full convergence may also be less important here (steady state may take exceedingly long to be attained in reality, if at all)

Using the above-mentioned scalar σ , form a σ -dependent convergence test, to tell between slowness of open and closed characteristics (and possibly ignore the latter). Also based on σ , at recirculation regions use uniform (explicit) $O(h)$ numerical viscosity, with continuation from large to small viscosity integrated into the FMG algorithm. The cycles can employ one of the following 3 options.

TME cycles by methods (1) and (2) were shown in [BY3] and [YVB] respectively. Method (3), which should be best for massive parallelization, has not been implemented

- (1) DCW method (using Defect Corrections within W cycles), with suitable over-weighting of residuals [BY3]. Suitable only for $O(h)$ discretizations.
- (2) Effectively downstream relaxation ordering (using alternate-direction sweeps) and doubling of transferred residuals (for $O(h)$ discretization) [YVB].
- (3) Semicoarsening, generally similar to [sonic]

- Full-potential operator $(\underline{u} \cdot \underline{\nabla})^2 - a^2 \Delta$, $M_0 = |\underline{u}|/a \lesssim .7$ (uniformly elliptic)

Any classical algorithm is suitable, but the algorithm of the next case is also adequate

TME well established

<i>Difficulty</i>	<i>Possible Solutions</i>	<i>Status</i>
<ul style="list-style-type: none"> • Full potential $.7 \lesssim M_0 \lesssim 1.4$ 	Relaxation marching downstream (for transition to the supersonic case below) together with semicoarsening in the characteristic (cross-stream) direction	TME shown for the case $M = 1$ [Sonic]. Other cases have not yet been implemented
<ul style="list-style-type: none"> • Full potential $1.4 \lesssim M_0$ (uniformly hyperbolic, with the stream as the time-like direction, and with $O(1)$ "Courant number".) 	Marching in the stream direction, possibly with a predictor-corrector procedure. For full massive parallelization, however, wave methods (extending standing wave methods [Ira]) should be used	Not yet tried?

Difficulty

- The “core operator”

$$L_c = \begin{bmatrix} Q_0 & 0 & -\rho^2 \Delta \\ 0 & Q_\kappa & -p\Delta \\ -\partial p / \partial \rho & -\partial p / \partial \varepsilon & Q_{\mu+\bar{\lambda}} \end{bmatrix}$$

should be relaxed as part of relaxing the compressible NS system, in the case that $\rho|u|h \lesssim \max(\bar{\lambda}, \mu, \kappa)$.

In the case of alignment between the grid and the flow, with meshsize h_1 and h_2 in the stream and cross-stream directions, respectively, and $h_2 \leq h_1$ (e.g., in boundary layers), the case where L_c need be relaxed is when $\rho|u|h_2^2 \lesssim h_1 \max(\bar{\lambda}, \mu, \kappa)$.

In aerodynamics, $\bar{\lambda}$, μ and κ are comparable, so the case of interest is $|u|h_2^2 \leq \nu h_1$, where $\nu = \mu/\rho$

Possible Solutions

Best relaxation scheme depends on the flow parameters.

For example:

- (1) If $\kappa \ll \rho|u|h$, then $Q_\kappa \approx Q_0$ (in principal terms) and one can use DGS with

$$M = \begin{pmatrix} 1 & 0 & \rho^2 \Delta \\ 0 & 1 & p\Delta \\ 0 & 0 & Q_0 \end{pmatrix}$$

resulting in the need to relax the first two equations each on an advection operator (see methods above), and the third equation on the operator $Q_0 Q_{\mu+\bar{\lambda}} - \rho^2 a^2 \Delta$.

In the case of interest the principal part of the latter is $[(\mu + \bar{\lambda})Q_0 + \rho^2 a^2] \Delta$, so it can be relaxed by the general method for relaxing a product operator (see $L = L_2 L_1$ above).

- (2) In the aerodynamics and aligned case of interest, the term $Q_{\mu+\bar{\lambda}}$ in L_c is not principal. Therefore relaxation can easily be conducted with the weighting (preconditioning) matrix

$$P = \begin{pmatrix} 1 & 0 & 0 \\ -p & \rho^2 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

and the distribution matrix

$$M = \begin{pmatrix} 0 & 1 & 0 \\ 0 & -p_\rho/p_\varepsilon & 1 \\ 1 & 0 & 0 \end{pmatrix}$$

yielding PLM whose principal part is its main diagonal, on which separately appear the Laplace operator Δ , the convection-diffusion operator $Q_{\bar{\kappa}}$ where $\bar{\kappa} = p_\rho \rho^2 / (2pp_\varepsilon) = 1.25\kappa$ (for air), and a free function

Status

Not tried

Not tried

Difficulty

- *FDA factorizability question:* The decomposition of a system relaxation into its scalar factors depends on the equality of the different occurrences of the advection-diffusion operator Q (or $Q_{\mu+\bar{\lambda}}$) appearing in PL, the prefactoring by P of a conservative discretization L . However, in relaxing a non-elliptic discrete operator, important is not only the differential operator it approximates, but also its First Differential Approximation (FDA) terms in non-characteristic directions; e.g., the cross-stream *numerical* viscosity of Q . This may not be the same in the different occurrences of Q , putting the factorization into question
- High order discretization (away from shocks)

Possible Solutions

- (1) Examining several examples of conservative discretization of transsonic flows, the FDA terms in various occurrences of $Q_{\mu+\bar{\lambda}}$ turn out sufficiently close to each other (e.g., only (4% discrepancy) to allow full efficiency of the proposed relaxation schemes.
 - (2) Conservative schemes may be designed so that the various FDAs of $Q_{\mu+\bar{\lambda}}$ are identical, or at least so that the scheme is still factorizable.
- (1) “Double discretization” schemes: Use high-order only in calculating residuals transferred to the coarse grid, *not* in relaxation (unless the high order scheme is preferable also for h-f modes).
 - (2) However, in relaxing *non-elliptic* factors (e.g., downstream relaxation-marching for convection operator) the high order must be used (e.g., by a predictor-corrector downstream relaxation)

Status

Further examination is needed

Some “genuinely multidimensional upwind” schemes turn out to yield factorizable schemes, e.g., in the subsonic case in the control-volume structured-grid context [DS2]. Further studies are in progress

Introduced 1978 [BD]. Successfully implemented in various *elliptic* cases (see description and refs in [G, §10.2]). Methods for non-elliptic have not been tested beyond second order.

Comment: High order approximations on unstructured grids are very expensive

(1) A set of N continuity equations,

volume is large compared with $\max(h^{-2}D_i, h^{-1}\rho_i|u|)$,

for a simple model

<i>Difficulty</i>	<i>Possible Solutions</i>	<i>Status</i>
⊙ Shocks		
• Shock displacements associated with corrections from a coarse grid that does not resolve the shock	Obtained by a conservative fine-to-coarse residual transfer plus local post-relaxation passes near the shock	Full efficiency shown [DS]
• Poor h -ellipticity of high-resolution schemes	Construction of new, genuinely multidimensional upwind schemes	Developed in the context of unstructured triangular grids [DS1]
• Relaxation near strong shocks	Switching to general robust schemes (e.g., box Kacmarz), adding extra local passes (c.f. relaxation near boundaries)	Not tried?

Difficulty

Possible Solutions

Status

- *Relaxation at and near Boundaries:*

Difficulties:

- (1) There is no smoothing analysis in case the boundaries are not aligned with the grid.
- (2) The fine-to-coarse residual weighting near boundaries is generally very imprecise, hence the residuals should be reduced there more than in the interior.
- (3) Larger residuals are created near polations.

A general-type robust relaxation scheme, e.g., *box Kacmarz*, throughout several-meshsize-wide zone near the boundary. Boxes size in each direction should be several meshsizes and the boxes should have substantial overlap. One can afford several passes of such a relaxation per each full interior sweep since the zone width is $O(h^{1-\epsilon})$, with $0 \leq \epsilon < 1$. In particular, add near-boundary relaxation passes after the FMG interpolation (allowing the latter to be of lower order near the boundary)

For uniformly elliptic equations it has been proved [RLMA], [RQMA] and demonstrated computationally (for cases of reentrant corners [Bai]) that the interior efficiency as predicted by mode analysis (implying TME) can always be obtained. TME demonstrated (by Ruge & Brandt) for incompressible Euler on staggered cartesian cartesian grids

- Boundary layers (in the case that they need be resolved). (See also grid adaptation below.)

Resolved by boundary-fitted local grid patches, with local semi refinements: finer levels, in narrower layers near the boundary, have smaller cross-layer meshsizes, allowing the physical cross-stream viscosity to dominate over the numerical one. Additional terms in the governing equations (NS instead of Euler, or turbulent modelling, etc.) may be used in these patches. Downstream marching relaxation and cross-stream semi coarsening in the multigrid cycles, employed in a “ λ -FMG” kind of algorithm [G, §9.6], so that coarse FMG stages already include local semi-refinements at the boundary, thus effectively incorporating continuation in R_e into the FMG stages

Description in [R88, §2.4]; not implemented. The local refinement techniques for Poisson equation, with TME, are demonstrated in [Bai]

Difficulty

Possible Solutions

Status

- *Far-field* artificial boundary conditions: requiring in some cases non-local *absorbing boundary conditions* (ABC) for some wave factor. [Has any MPer had experience with this difficulty?]

Increasingly coarser grids covering increasingly larger domains. The size of each domain is based on accuracy-to-work. Optimization criteria (similar to those in [B77, §8], [G, §9.5], implying also a natural criterion for the largest needed domain. On *interior* boundaries (boundaries of a grid residing in the interior of the next coarser grid) the solution is interpolated from the coarser grid. On such boundaries, if ABC is at all needed, only high-frequency components need be absorbed, for which the ABC are *local*, and can be enforced as part of the relaxation process (of the corresponding wave factor)

Details of the algorithm have been worked out, and TME (or its equivalent accuracy-to-work relation) has recently been demonstrated (by Brandt & Danowitz) for the 2D Poisson equation in the unbounded plane. Techniques for non-elliptic or indefinite cases have not been systematically studied.

19

- *Small-scale singularities* invisible on the next coarser grid, such as small “islands” or “holes” in the domain (e.g., an airplane smaller than the meshsize of some coarser grid) or small BC features (e.g., small regions of Neumann BC in otherwise Dirichlet BC)

Local relaxation passes around the singularities after return from the next coarser grid, together with either one of the following three devices:

- (a) Enlarging the singularity on the coarser grid.
- (b) Modifying the interior coarse-grid equation near the singularity.
- (c) If the coarse grid equations are not modified, convergence is slow, but slow to converge are just few very special components. Hence slowness can be eliminated by recombining iterants.

TME shown in elliptic cases [Rec]

Difficulty

Possible Solutions

Status

⊙ Grid-induced slow convergence

One can avoid many of the following maladies by using suitable multi-grid structures (described below under “grid adaptation”)

- Large aspect ratios

Either one of the following:

- (1) Block (part-line or part-plane) relaxation, analyzed by mode analysis [B77].
- (2) Semi coarsening [Arl], [Stages, §3.2] (often natural, since the large aspect ratio is in the first place created by semi refinements) with relaxation “semi smoothing” analysis [Stages, §2.1], [G, §3.3].
- (3) Combinations of block relaxation in some directions and semi coarsening in others

TME has been shown in a variety of elliptic cases

- Expanding grids

Relaxation marching in the direction of increasing meshsize; or distributive relaxation [Njm, §6]

<i>Difficulty</i>	<i>Possible Solutions</i>	<i>Status</i>
<ul style="list-style-type: none"> • Grid adaptation 	<p>Use local multigrid levels in creating any desired local refinement, aspect ratio, boundary fitting or even flow fitting (see [R88, §2.7]). Base refinement criteria on the fine-to-coarse multigrid correction (τ). Adaptation can be integrated into the λ-FMG algorithm together with proper (e.g., Reynolds-number) continuations</p>	<p>Introduced in [B77] and [G], but tried only for Poisson equation near singularities [Bai]</p>
<ul style="list-style-type: none"> ⊙ Stagnation point (causing an instability in the coarse-grid corrections) 	<p>Coarse-grid numerical viscosity depending on the <i>average</i> (e.g., “full-weighting”) of the fine-grid numerical viscosity (not on its injected value) [BY3, §4.5]</p>	<p>TME shown in an example [BY3]</p>

References

- [AJ] Jameson, A., Solution of the Euler equations for two dimensional transonic flow by a multigrid method, *Appl. Math. Comp.* **13** (1983) 327–356.
- [AMGT] Brandt, A., Algebraic multigrid theory: The symmetric case, in *Preliminary Proc. Int. Multigrid Conf.*, Copper Mountain, Colorado, April 6–8, 1983; *Appl. Math. Comp.* **19** (1986) 23–56.
- [Arl] Arlinger, B., Multigrid technique applied to lifting transonic flow using full potential equation, SAAB-SCANIA Rep. L-0-1 B439, 1978.
- [Bai] Bai, D. and Brandt, A., Local mesh refinement multilevel techniques, *SIAM J. Sci. Stat. Comp.* **8** (1987) 109–134.
- [BD] Brandt, A. and Dinar, N., Multi-grid solutions to elliptic flow problems, in *Numerical Methods for Partial Differential Equations* (Parter, S., ed.), Academic Press, New York, 1979, pp. 53–147.
- [BL] Baldwin, B. and Lomax, H., Thin-layer approximation and algebraic model for separated turbulent flows, AIAA Paper 78–257, Jan. 1978.
- [BM] Bussing, T.R.A. and Murman, E.M., Finite-volume method for the calculation of compressible chemically reacting flows, *AIAA J.* **26** (1988) 1070–1078.
- [BY1] Brandt, A. and Yavneh, I., Inadequacy of first-order upwind difference scheme for some recirculating flows, *J. Comp. Phys.* **93** (1991) 128–143.
- [BY2] Brandt, A. and Yavneh, I., On multigrid solution of high-Reynolds incompressible entering flows, *J. Comp. Phys.* **101** (1992) 151–164.
- [BY3] Brandt, A. and Yavneh, I., Accelerated multigrid convergence and high-Reynolds recirculating flows, *SIAM J. Sci. Comp.* **14** (1993) 607–626.
- [B73] Brandt, A., Multi-level adaptive technique (MLAT) for fast numerical solutions to boundary value problems, in *Proc. 3rd Int. Conf. on Numerical Methods in Fluid Mechanics* (Cabannes, H. and Temam, R., eds.), Lecture Notes in Physics 18, Springer-Verlag, 1973, pp. 82–89.
- [B77] Brandt, A., Multi-level adaptive solutions to boundary value problems, *Math. Comp.* **31** (1977) 333–390.
- [Dinar] Dinar, N., Fast Methods for the Numerical Solutions of Boundary Value Problems, Ph.D. Thesis, Weizmann Institute of Science, Rehovot, 1979.
- [DS] Sidilkover, D., Higher order accurate method for recovering shock location.
- [DS1] Sidilkover, D., A genuinely multidimensional upwind scheme and efficient multigrid solver for the compressible Euler equations, ICASE Report 97–84, 1994.

- [DS2] Sidilkover, D., Some approaches towards constructing optimally efficient multigrid solvers for the inviscid flow equations, ICASE Report 97-39. Submitted to *Computer and Fluids*.
- [G] Either [G82] or [G84].
- [G82] Brandt, A., Guide to multigrid development, in *Multigrid Methods* (Hackbusch, W. and Trottenberg, U., eds.), Springer-Verlag, 1982, pp. 220-312.
- [G84] Brandt, A., *Multigrid Techniques: 1984 Guide, with Applications to Fluid Dynamics*, 1984, 191 pages, ISBN-3-88457-081-1; GMD-Studien Nr. 85; Available from GMD-AIW, Postfach 1316, D-53731, St. Augustin 1, Germany, 1984.
- [Ira] Livshits, I., Multigrid Solvers for Wave Equations, Ph.D. Thesis, Bar-Ilan University, 1995.
- [NESP] Brandt, A., Multi-grid solvers for non-elliptic and singular-perturbation steady-state problems, Weizmann Institute of Science, Rehovot, December 1981.
- [Njm] Brandt, A., Multi-level adaptive techniques (MLAT) for singular perturbation problems, in *Numerical Analysis of Singular Perturbation Problems* (Hemker, P.W. and Miller, J.J.H., eds.), Academic Press, New York, 1979, 53-142.
- [Par] Brandt, A. and Greenwald, J., Parabolic multigrid revisited, in *Multigrid Methods, III* (Hackbusch, W. and Trottenberg, U., eds.), Birkhäuser Verlag, Basel, 1991, pp. 143-154.
- [Quasi] Brandt, A. and Ta'asan, S., Multigrid solutions to quasi-elliptic schemes, in *Progress and Supercomputing in Computational Fluid Dynamics* (Murman, E.M. and Abarbanel, S.S., eds.), Birkhäuser, Boston, 1985, pp. 235-255.
- [Rec] Brandt, A. and Mikulinsky, V., Recombining iterants in multigrid algorithms and problems with small islands, *SIAM J. Sci. Comp.* **16** (1995) 20-28.
- [RLMA] Brandt, A., Rigorous local mode analysis of multigrid, in *Preliminary Proc. 4th Copper Mountain Conf. on Multigrid Methods*, Copper Mountain, Colorado, April 1989.
- [RQMA] Brandt, A., Rigorous quantitative analysis of multigrid: I. Constant coefficients two level cycle with L_2 norm, *SIAM J. Num. Anal.* **31** (1994) 1695-1730.
- [RS] Ruge, U. and Stueben, K., Algebraic multigrid, in *Multigrid Methods* (McCormick, S.F., ed.), SIAM, 1987.
- [RSS] Roberts, T.W., Sidilkover, D. and Swanson, R.C., Textbook multigrid efficiency for the steady Euler equations, AIAA Paper 97-1949, in *13th Computational Fluid Dynamics Conf.*, June 1997.
- [R1] Rubbert, P.E., CFD and the changing world of airplane design, AIAA Wright Brothers Lecture, Anaheim, CA, 1994.
- [R2] Vatsa, V.N. and Wedan, B.W., Development of a flexible and efficient multigrid code for 3-D Navier-Stokes equations and its application to a grid-refinement study, *Computers and Fluids* **18**(4) (1990) 391-403.

- [R3] Garner, P., Meredith, P. and Stoner, R., Areas of future CFD development as illustrated by transport aircraft applications, AIAA Paper 91-1528, 1991.
- [R88] Brandt, A., The Weizmann Institute Research in Multilevel Computation: 1988 Report, in *Proc. 4th Copper Mountain Conf. on Multigrid Methods* (Mandel, J. et al, eds.), SIAM, 1989, pp. 13-53.
- [Sonic] Brandt, A. and Diskin, B., Multigrid solvers for the non-aligned sonic flow: the constant coefficient case. To appear in *Computer and Fluids*.
- [South] South, J.C. and Brandt, A., Application of a multi-level grid method to transonic flow calculations, in *Transonic Flow Problems in Turbo Machinery* (Adam, T.C. and Platzler, M.F., eds.), Hemisphere, Washington, 1977, pp. 180-207.
- [Stages] Brandt, A., Stages in developing multigrid solutions, in *Proc. 2nd Int. Congr. on Numerical Methods for Engineers* (Absi, E., Glowinski, R., Lascaux, P. and Veysseyre, H., eds.), Dunod, Paris, 1980, pp. 23-43.
- [T1] Ta'asan, S., Canonical forms of multidimensional steady state inviscid flows, ICASE Report 93-34, 1993.
- [T2] Ta'asan, S., Optimal multigrid method for inviscid flows, *Proc. European Multigrid Conf., EMG93*, Amsterdam, July 1993.
- [T3] Ta'asan, S., Canonical-variables multigrid method for steady-state Euler equations, *Proc. 14th Int. Conf. on Numerical Methods for Fluid Dynamics*, Bangalore, India, 1994.
- [T4] Ta'asan, S., Essentially optimal multigrid method for steady state Euler equations, *33rd Aerospace Sciences Meeting and Exhibit*, AIAA Report 95-0209, Reno, NV, January 1995.
- [T5] Ta'asan, S., Essentially optimal multigrid method for steady state Euler equations, *33rd Aerospace Sciences Meeting and Exhibit*, AIAA Report 95-0209, Reno, NV, January 1995.
- [T6] Ta'asan, S., Lectures on numerical solution of PDE (unpublished).
- [YVB] Yavneh, I., Venner, C.H. and Brandt, A., Fast multigrid solution of the advection problem with closed characteristics, *J. Comp. Phys.*, submitted.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 1998	3. REPORT TYPE AND DATES COVERED Contractor Report		
4. TITLE AND SUBTITLE Barriers to Achieving Textbook Multigrid Efficiency (TME) in CFD			5. FUNDING NUMBERS C NAS1-97046 C NAS1-19480 WU 505-90-52-01	
6. AUTHOR(S) Achi Brandt				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Institute for Computer Applications in Science and Engineering Mail Stop 403, NASA Langley Research Center Hampton, VA 23681-2199			8. PERFORMING ORGANIZATION REPORT NUMBER ICASE Interim Report No. 32	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-2199			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/CR-1998-207647 ICASE Interim Report No. 32	
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Dennis M. Bushnell Final Report				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 64 Distribution: Nonstandard Availability: NASA-CASI (301)621-0390			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) "Textbook multigrid efficiency" (TME) means solving a discrete PDE problem in a computational work which is only a small (less than 10) multiple of the operation count in the discretized system of equations itself. As a guide to attaining this optimal performance for general CFD problems, the table below lists every foreseen kind of computational difficulty for achieving that goal, together with the possible ways for resolving that difficulty, their current state of development, and references. Included in the table are staggered and nonstaggered, conservative and nonconservative discretizations of viscous and inviscid, incompressible and compressible flows at various Mach numbers, as well as a simple (algebraic) turbulence model and comments on chemically reacting flows. The listing of associated computational barriers involves: non-alignment of streamlines or sonic characteristics with the grids; recirculating flows; stagnation points; discretization and relaxation on and near shocks and boundaries; far-field artificial boundary conditions; small-scale singularities (meaning important features, such as the complete airplane, which are not visible on some of the coarse grids); large grid aspect ratios; boundary layer resolution; and grid adaption.				
14. SUBJECT TERMS cfd, multigrid, Euler equations, Navier-Stokes equations, incompressible flows, transonic flows, algebraic turbulence, reacting flows, non-alignment, recirculating flows, stagnation point, shocks, far-field boundary conditions, boundary layer, grid adaption			15. NUMBER OF PAGES 33	16. PRICE CODE A03
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	