

# Design Development Analyses in Support of a Heatpipe-Brayton Cycle Heat Exchanger

Brian Steeve<sup>1</sup>, Melissa Van Dyke<sup>1</sup>, Alok Majumdar<sup>1</sup>, Dalton Nguyen<sup>1</sup>,  
Melissa Corley<sup>3</sup>, Ray M. Guffee<sup>2</sup>, Richard J. Kapernick<sup>2</sup>

<sup>1</sup>NASA Marshall Space Flight Center, Huntsville, AL 35812

<sup>2</sup>Los Alamos National Laboratory, Los Alamos, NM 87545

<sup>3</sup>Mechanical Engineering, Stanford University, Stanford, CA 94309

**Abstract.** One of the power systems under consideration for nuclear electric propulsion or as a planetary surface power source is a heatpipe-cooled reactor coupled to a Brayton cycle. In this system, power is transferred from the heatpipes to the Brayton gas via a heat exchanger attached to the heatpipes. This paper discusses the fluid, thermal and structural analyses that were performed in support of the design of the heat exchanger to be tested in the SAFE-100 experimental program at Marshall Space Flight Center. A companion paper, "Mechanical Design and Fabrication of a SAFE-100 Heat Exchanger for use in NASA's Advanced Propulsion Thermal-hydraulic Simulator", presents the fabrication issues and prototyping studies that, together with these analyses, led to the development of this heat exchanger. An important consideration throughout the design development of the heat exchanger was its capability to be utilized for higher power and temperature applications. This paper also discusses this aspect of the design and presents designs for specific applications that are under consideration.

## Outline

- I. Introduction
- II. Design Summary
- III. Analysis
  - a. Conditions
    - i. Test
    - ii. Reactor
  - b. Fluid/Thermal
  - c. Structural
    - i. Method
      1. Modeling description
      2. Steady state conditions assumed worst case
      3. Twelve test and two reactor conditions analyzed
      4. Thermal solution
      5. Structural solution
    - ii. Criteria
      1. ASME BPVC used as a guideline
      2. Looked at pressure stress, and fatigue/creep damage
    - iii. Results
      1. Test
      2. Reactor
- IV. Conclusion