




# Lunar Module Wiring Design Considerations and Failure Modes



1. Describe the rationale for component type selection.
2. Describe the rationale for the chosen assembly processes.
3. Describe the redesign considerations and lessons learned.


## Choice of Conductors and Insulation

---




\*FEP - Fluorinated ethylene propylene


# Wire Splices - Crimp



# Wire Splices – Solder 1




# Wire Splices – Solder 2




# Wire Connectors

---



## Wire Connectors – Crimp Pins

---




## Wire Connectors

---



# Fabrication of Wire Harnesses

---



**Wires wrong length.**

Sharp edge damage.


Protective covers.

Support harnesses.

Inadequate training.

Locate termination points more accurately.

Tooling boards made to include extensive 3-D fixtures.



## Fabrication Problems

---

Wires wrong length.

**Sharp edge damage.**

Protective covers.

Support harnesses.

Inadequate training.

Tooling boards smoothed to avoid any sharp edges.



## Fabrication Problems

---

Wires wrong length.

Sharp edge damage.

**Protective covers.**

Support harnesses.

Inadequate training.

Temporary protective covers added for completed sub-assemblies.



## Fabrication Problems

---

Wires wrong length.


Sharp edge damage.

Protective covers.

**Support harnesses.**

Inadequate training.

Tooling aids improved to prevent damage during transport.



Wires wrong length.

Sharp edge damage.

Protective covers.

Support harnesses.

**Inadequate training.**

Training improved for technical details to create consistent quality fabrication.

Pride in work quality.


More frequent inspections.

Harnesses checked for electrical characteristics (continuity, conductor resistance, insulation resistance, dielectric strength)

Check before and after installation to locate errors and damage.

Check voltage not to exceed 75% of lowest-rated connector.

## Wire Harness Installation



## Wire Harness Installation

---

**Damage from:**


**Sharp edges.**

Work on adjacent harnesses.

Connector damage.

Breaking wires.

Chafe guards added to protect from sharp edges.



## Wire Harness Installation

---

**Damage from:**

Sharp edges.

**Work on adjacent harnesses.**

Connector damage.

Breaking wires.

Permanent harness tray covers and temporary harness covers.



## Wire Harness Installation

---

**Damage from:**

Sharp edges.

Work on adjacent harnesses.

**Connector damage.**

Breaking wires.

Connector protective covers.



### **Damage from:**

Sharp edges.

Work on adjacent harnesses.

Connector damage.

**Breaking wires.**

Increased training and emphasis on quality awareness. The space race was on and America's pride was on the line.

No in-flight anomaly was attributable to problems with Lunar Module wiring, despite there being 22,900 m (75,000 ft) of wire in 20,000 segments in a Lunar Module.

# **Apollo-Era Engineering Suggestions for Future Programs**

Use of plated conductors saves weight.

Use of plated conductors saves weight.

Small-gage wiring is weaker; so, alloys such as Cu-Cr-Cd should be considered for strength.

Use of plated conductors saves weight.

Small-gage wiring is weaker; so, alloys such as Cu-Cr-Cd should be considered for strength.

Silver gives lower resistance, but nickel withstands heat better.

Use of plated conductors saves weight.

Small-gage wiring is weaker; so, alloys such as Cu-Cr-Cd should be considered for strength.

Silver gives lower resistance, but nickel withstands heat better.

Aluminum should be considered for large electrical busses for weight savings.

Polymer tape-wrap wire insulation is very light weight and effective.

Polymer tape-wrap wire insulation is very light weight and effective.

Other types of modern insulation might be more cost-effective.

Crimp splices are superior to solder splices.

- Lighter weigh
- Greater reliability
- Temperature independence

Crimp splices are superior to solder splices.

Lighter weight

Greater reliability

Temperature independence

Modular plug-ins to join multiple wires to a common point are more reliable, but heavier than crimp splices.

A rear environmental seal that does not require additional potting is preferred.

A rear environmental seal that does not require additional potting is preferred.

Pins should be crimped or welded to the incoming wires and be removable from the rear of the connector.

1. Describe the rationale for component type selection.
2. Describe the rationale for the chosen assembly processes.
3. Describe the redesign considerations and lessons learned.

**Apollo Experience Report --  
Electrical Wiring Subsystem**

**Apollo Experience Report -- Lunar  
Module Electrical Power Subsystem**