

AUG 9 1 1951 REC'D

RM SE51H20

NACA RM SE51H20

Source of Acquisition  
CASI Acquired

~~CONFIDENTIAL~~  
**NACA**

~~CLASSIFICATION CANCELLED~~

# RESEARCH MEMORANDUM

for the

Air Materiel Command, U. S. Air Force

CONTROL PERFORMANCE OF GENERAL ELECTRIC FUEL AND TORQUE  
REGULATOR OPERATING ON T31-3 TURBINE-PROPELLER  
ENGINE IN SEA-LEVEL TEST STAND

By Frank L. Oppenheimer and James Lazar

Lewis Flight Propulsion Laboratory  
Cleveland, Ohio

~~CONFIDENTIAL~~  
~~CLASSIFICATION CANCELLED~~

*J. W. Crowley 1/14/55*

This document contains classified information affecting the National Defense of the United States within the meaning of the Espionage Act, USC 5031 and 32. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.  
Information disclosed herein is for the use only of the primary and casual services of the United States, appropriate civilian officers and employees of the Department who have a legitimate interest therein, and to United States citizens of known loyalty and whose interest of necessity must be informed thereof.

*Status*

*change # 2916*

**NATIONAL ADVISORY COMMITTEE  
FOR AERONAUTICS**

WASHINGTON

AUGUST 29 1951

**FILE COPY**

To be returned to  
the files of the National  
Advisory Committee  
for Aeronautics  
Washington, D. C.

~~CONFIDENTIAL~~  
~~CLASSIFICATION CANCELLED~~

CONFIDENTIAL  
CLASSIFICATION CANCELLED

## NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

for the

Air Materiel Command, U. S. Air Force

CONTROL PERFORMANCE OF GENERAL ELECTRIC FUEL AND TORQUE

REGULATOR OPERATING ON T31-3 TURBINE-PROPELLER

ENGINE IN SEA-LEVEL TEST STAND

By Frank L. Oppenheimer and James Lazar

## SUMMARY

A General Electric fuel and torque regulator was tested in conjunction with a T31-3 turbine-propeller engine in the sea-level static test stand at the NACA Lewis laboratory. The engine and control were operated over the entire speed range: 11,000 rpm, nominal flight idle, to 13,000 rpm, full power. Steady-state and transient data were recorded and are presented with a description of the four control loops being used in the system.

Results of this investigation indicated that single-lever control operation was satisfactory under conditions of test. Transient data presented showed that turbine-outlet temperature did overshoot maximum operating value on acceleration but that the time duration of overshoot did not exceed approximately 1 second. This temperature limiting resulted from a control on fuel flow as a function of engine speed. Speed and torque first reached their desired values 0.4 second from the time of change in power-setting lever position. Maximum speed overshoot was 3 percent.

## INTRODUCTION

At the request of the Air Materiel Command, U. S. Air Force, a general program was established at the NACA Lewis laboratory to study several controls operating on a turbine-propeller engine. The present report concerns that part of the program wherein a General Electric fuel and torque regulator, serial No. 1021, was investigated in conjunction with a T31-3 turbine-propeller engine at sea-level static conditions. Representative data for operation of the controlled engine were recorded. These data indicate transient characteristics of the

CONFIDENTIAL  
CLASSIFICATION CANCELLED

controlled engine for operation in the cruising speed range. This report describes the control, method, and procedure of test, and presents some representative data. The theory of control operation presented in this report is based on literature obtained from the manufacturer, on visual inspection of the control components, and on data obtained from operation of the controlled engine.

## DESCRIPTION OF CONTROL

### Combined System

The fuel and torque regulator is made up of five components used to control the fuel supply, propeller blade angle, and speed of a gas turbine. These components are:

- (1) Torque control loop
- (2) Speed governing loop
- (3) Manual pressure control system
- (4) Altitude compensation loop
- (5) Thermal loop (inoperative in the control)

A block diagram of the fuel and torque regulator is shown in figure 1(a). In order to establish operation of the engine at preselected values of controlled variables for a desired power level, a pilot's power-setting lever is incorporated in the regulator. This lever preselects torque  $Q_s$  and speed  $N_s$ , and puts a safe limit on fuel flow  $W_{f,s}$  for a desired condition of engine operation. In this regulator, corrections to engine speed are accomplished primarily by changing fuel flow and corrections to engine torque are accomplished by changing blade angle. Propeller blade angle and fuel valve position are affected by any of the following:

- (1) Pilot's power-setting lever
- (2) Airframe flight velocity
- (3) Governor speed setting
- (4) Altitude

The regulator is a hydraulic system, and measurements of all controlled engine variables are converted to hydraulic pressures. The following discussions will deal with each individual loop of the system.

## Torque Control Loop

In the torque control loop the propeller blade angle is varied to control the torque absorbed by the propeller. Figure 1(b) is a block diagram of the torque control loop only. The torque error is the absorbed torque of the propeller  $Q$  subtracted from a preselected value of torque  $Q_s$  set by the power-setting lever  $HP_s$ . This error  $Q_s - Q$  causes an unbalance of pressures in the control loop and is eliminated by the repositioning of the blade-angle input lever  $\beta_a$  with an integral torque error correction represented by the function  $K_1/p$ . The positioning of the blade-angle input lever  $\beta_a$  linearly schedules blade angle  $\beta$  by means of a hydraulic blade-angle-change mechanism represented by the function  $\frac{K_2}{1 + \tau_{sp}}$ . With fuel flow held constant, changes in propeller blade angle result in a torque change  $\left(\frac{\Delta Q}{\Delta \beta}\right)_{W_f}$  and also cause a speed change  $\left(\frac{\Delta N}{\Delta \beta}\right)_{W_f}$ .

## Speed Control Loop

In the speed control loop fuel flow is primarily varied to control speed. A block diagram of the speed control loop is shown in figure 1(c). Engine turbine speed  $N$  is sensed by a governor. The speed error is the actual engine operating speed subtracted from a preselected value of engine speed  $N_s$  set by the power-setting lever. If speed increases beyond the desired value, the error  $N_s - N$  is eliminated by reduction of variable-control oil pressure (VCO) with a speed error correction represented by the function  $F_1(p)$ . A reduction in variable-control oil pressure causes the fuel pump to reduce fuel flow  $W_f$  in a manner represented by the function  $F_2(p)$ . A reduction in fuel flow with blade angle held constant causes speed to reduce as given by the response  $\left(\frac{\Delta N}{\Delta W_f}\right)_\beta$ . Torque also changes with a change in fuel flow  $\left(\frac{\Delta Q}{\Delta W_f}\right)_\beta$  if blade angle is held constant. Fuel flow is limited to approximately 10 percent over that required for the preselected speed. This means of restricting fuel flow is indicated in figure 1(a) as the fuel-flow limiter.

If engine speed drops below the limiting value of speed reset, a torque reset lever is actuated to reduce blade angle, thereby reducing torque and increasing speed to a value such that the speed error is small enough to be corrected by fuel flow.

### Manual Pressure Control System

The manual pressure control operates in the starting regime only. The airframe cannot be controlled in flight with this system. The manual control varies fuel flow with blade angle held constant from ground idle operation at 8000 rpm to flight idle engine speed of 11,000 rpm. The automatic control loops function when the engine is operating in the cruising speed range 11,000 to 13,000 rpm. In the manual pressure control system variable-control oil pressure is preselected for a desired turbine speed. A block diagram of the manual pressure control system is shown in figure 1(d).

A change in position of the power-setting lever  $HP_s$  manually changes variable-control oil pressure VCO. An increase or decrease in variable-control oil pressure increases or decreases fuel flow  $W_f$  in a manner represented by the function  $F_2(p)$ . Thus, speed increases with fuel flow and, with blade angle held constant, torque is changed when fuel flow is varied, as given by the response  $\left(\frac{\Delta Q}{\Delta W_f}\right)_\beta$ .

### Altitude Compensation Loop

Altitude compensation is utilized to maintain the turbine at a safe operating temperature. When operating at altitude, the fuel flow required is less than at sea level because the mass flow of air is reduced. In the altitude compensation loop a variable ratio device is used to reduce available fuel flow to the combustor with altitude and to decrease the amount of governor overspeed correction. Figure 1(e) is a block diagram of the altitude compensation loop. The system consists of two bellows opposing each other, one actuated by compressor inlet pressure CIP, and the other sealed at atmospheric pressure. The action of these bellows changes variable-control oil pressure to speed error gain in order to meet altitude requirements. This action is represented by the function  $K_3$ . In this control loop variable-control oil pressure changes with respect to speed error in a manner represented by the function  $F_1(p)$  modified by the function  $K_3$ . Fuel flow changes with a change in variable-control oil pressure as represented by the function  $F_2(p)$ .

### APPARATUS

#### Engine Installation

Engine. - T31-3 turbine-propeller engine, serial No. GE-021-014

Propeller. - Aeroproducts, A542-F-17

Control. - General Electric fuel and torque regulator, serial No. 1021, compensated for altitude

Test facilities. - NACA Lewis laboratory sea-level static test stand

#### Instrumentation

Recorder. - Transient responses of engine parameters were recorded on a multiple channel, galvanometer type, photorecording oscillograph with 40-cycles-per-second natural-frequency galvanometer elements damped at 0.8 damping ratio. A time scale was recorded on the lower edge of the oscillograph chart, one pip for each tenth of a second.

Parameters recorded. - Table I lists the measured quantity, steady-state instrumentation, and transient instrumentation for the following parameters:

Engine speed

Power-setting lever position

Fuel flow, proportional to static pressure

Torque

Turbine-outlet temperature

Blade-angle input

Blade angle

In the basic fuel loop, the variable-control oil pressure was recorded only under steady-state conditions.

#### PROCEDURE

Transient operation of the controlled engine was obtained by manually advancing or cutting back the power-setting lever in a step-wise manner. Engine parameters were measured continuously on a photo-recording oscillograph. Before and after each transient, photographs of steady-state values indicated on panel meters were taken to calibrate the individual oscillograph traces.

Decreasing and increasing step changes in the power-setting lever position were made according to the following speed and power settings at sea-level, static conditions:

Maximum power - 11,000 rpm  
13,000 - 11,000 rpm  
12,500 - 11,000 rpm  
12,000 - 11,000 rpm  
11,500 - 11,000 rpm

Maximum power - 12,000 rpm  
13,000 - 12,000 rpm  
12,500 - 12,000 rpm

Maximum power - 12,500 rpm  
13,000 - 12,500 rpm

Maximum power - 13,000 rpm

Steady-state readings were taken of speed, fuel flow, torque, and temperature in order to obtain a schedule of these parameters at various power-setting lever positions from idle at 22° to maximum power at 65°.

#### SCHEDULING OF PARAMETERS

The control regulates fuel flow to the engine by means of a variable displacement fuel pump (reference 1). The displacement, and thus the output, of the pump is determined by a pilot valve actuated by variable-control oil pressure supplied by the torque regulator. Figure 2(a) is a curve of fuel flow variation with variable-control oil pressure, as determined from steady-state operation of the torque regulator at various power lever settings. In steady-state operation fuel flow varies linearly with variable-control oil pressure. Under transient conditions the fuel pump approximates a first-order lag system (reference 1).

The magnitudes of speed, fuel flow, torque, and temperature during engine operation are determined by efficiency, safety, and time response. By means of scheduling the aforementioned parameters for each power-setting lever position, efficient matching of torque and speed, safe temperature limits, and sufficiently large gains for rapid response can be established. Figure 2(b) is the schedule of steady-state variation of speed, fuel flow, blade angle, torque, and temperature with power-setting lever position for the fuel and torque regulator.

## EVALUATION OF CONTROL BEHAVIOR

## Control Fulfillment of Accepted Criteria

Four general turbine-propeller engine control requirements are as follows:

- (1) Adaptability to a large number of different turbine-propeller engines
- (2) Ability to prevent the engine from being damaged
- (3) Operation without attention from the pilot except to change called-for thrust
- (4) Response of the engine in the length of time and manner desired

From the transient data presented in figure 3 and indexed in table II, this fuel and torque regulator control can be said to meet several of the aforementioned requirements. It can be utilized to control turbine-propeller engines where torque can be directly measured and where propeller blade angle is a linear function of the input to the blade angle controller.

The control is designed to correct blade angle in order to eliminate any torque error. Therefore, (1) torque has to be known at any instant, and (2) blade angle has to respond in a linear fashion to any blade-angle input called for in order to enable the engine to correct quickly and consistently to the conditions called for.

The control has incorporated within it a limit to prevent fuel flow from exceeding by more than approximately 10 percent the amount required for the preselected engine speed. This provision serves to prevent the engine from exceeding a maximum safe turbine-outlet operating temperature of 1265° F for more than approximately 1 second at any level of engine operation, as indicated by all data obtained in this investigation. Extended operation above the aforementioned temperature could cause severe damage to the engine turbine. These data also indicate that for the conditions existing during this investigation temperature is a function of fuel flow and is kept at a safe level by the limiting of fuel flow as a function of speed.

This control requires no attention from the pilot except to change the power setting.

For an increase in power from any value of speed above 11,500 rpm to maximum speed and power, the control is able to correct engine parameters without speed, blade-angle, or engine-torque dips at the start

of the called-for change in these parameters, as indicated by the data. If increases in power are called for from values of speed below 11,500 rpm, blade-angle dips do occur at the start of the called-for change in parameters, either for a small incremental change in power or for a burst to full power, as shown in figures 3(a) concluded, 3(b) concluded, 3(c) concluded, and 3(e) concluded. Although a direct measurement of engine thrust was not obtained in this investigation, the aforementioned dips in blade angle possibly could have produced a dip in propeller torque great enough to more than offset the effect of increasing speed, thus causing a resultant thrust dip.

From compilation of all data obtained in this investigation, the maximum rise time for first reaching the desired value in speed and torque is 0.4 second from the time of change in power-setting lever position. This time response is quite satisfactory, considering the fact that the response time of an airframe is many times the aforementioned rise time.

#### Specific Control Characteristics

For a decreasing power change, the controlled engine parameters tend to oscillate two or three times after the desired value has been reached. When an increase in power is called for, the parameters oscillate once or twice before steadying out. For a given increment in the power range of the engine, the amplitudes of oscillation of parameters are larger for a decrease in power than for an increase in power. Although blade angle changes are never abrupt, fuel flow tends to overshoot when a decrease in power is called for, whereas for an increase in power the fuel-flow limiter attenuates the amplitude of oscillation considerably. This tendency towards greater instability for decreases in power holds throughout the engine cruising speed range, regardless of the size of the incremental power change, as indicated by the data.

In general, torque approaches its final value with one fairly large overshoot and has one or more small oscillations following the initial rise. Speed has a moderate overshoot, dip, and then it settles out. From compilation of data obtained in this investigation, the maximum speed overshoot of its rated value is 3 percent. Temperature overshoots and oscillates at large amplitudes for decreases in power. It overshoots and oscillates more moderately for increases in power. Thus the large overshoot of fuel flow for decreases in power causes similar behavior in temperature. Therefore, after consideration of the behavior of all the engine parameters, an improvement in response to decreasing power commands might be had by adding a variable minimum fuel-flow limiter. This addition could establish more stable performance by reducing the amplitude of oscillations due to fuel flow variation.

From a review of the control system, an increase in speed above the desired value is corrected by a decrease in fuel flow. Therefore, engine speed can be reduced if a failure of the hydraulic propeller mechanism causes the propeller to go to flat pitch; however, no provision has been made to reduce fuel flow in case the propeller fails and goes to full pitch. There is an indication that the addition of an interconnection between torque and fuel flow could provide safe control of the engine if the hydraulic propeller mechanism fails and the propeller goes to full pitch.

#### SUMMARY OF RESULTS

The following results were obtained from a sea-level static investigation of a General Electric fuel and torque regulator on a T31-3 turbine-propeller engine at the NACA Lewis laboratory:

1. Single-lever operation with this control was satisfactory.
2. Duration of temperature overshoot beyond the safe turbine-outlet operating temperature of 1265° F did not exceed approximately 1 second at any level of engine operation.
3. Temperature limiting resulted from a control on fuel flow as a function of engine speed.
4. The maximum rise time for first reaching the desired value in speed and torque was 0.4 second from the time of change in power-setting lever position.
5. Maximum speed overshoot was 3 percent.

Possibly the addition of a variable minimum fuel-flow limiter for decreasing power commands could establish more stable performance by reducing the amplitudes of oscillations due to fuel flow variation.

There is an indication that the addition of an interconnection between torque and fuel flow could provide safe control of the engine if the hydraulic propeller mechanism fails and the propeller goes to full pitch.

Lewis Flight Propulsion Laboratory  
National Advisory Committee for Aeronautics  
Cleveland, Ohio, July 12, 1951

## APPENDIX - SYMBOLS

The following symbols are used in this report:

CIP	compressor-inlet pressure
$F_1(p)$	function representing speed error correction
$F_2(p)$	function representing fuel pump operation
HP <sub>s</sub>	power-setting lever
K <sub>1</sub>	torque error correction gain
K <sub>2</sub>	blade angle to input gain
K <sub>3</sub>	variable-control oil pressure to speed error gain
N	turbine operating speed, rpm
N <sub>s</sub>	preselected turbine operating speed, rpm
p	differential operator, $\frac{d}{dt}$
Q	absorbed torque of the propeller
Q <sub>s</sub>	preselected propeller torque
S	power-setting lever position
T	temperature
VCO	variable-control oil pressure
W <sub>f</sub>	fuel flow
W <sub>f,s</sub>	preselected fuel flow
$\beta$	blade angle, deg
$\beta_a$	blade-angle input lever
$\Delta$	incremental change
$\tau_s$	hydraulic blade-angle-change mechanism time constant

## Subscripts:

i        initial

f        final

## REFERENCE

1. Shames, Harold, Himmel, Seymour C., and Blivas, Darnold: Frequency Response of Positive-Displacement Variable-Stroke Fuel Pump. NACA TN 2109, 1950.


TABLE I - INSTRUMENTATION

Measured quantity	Steady-state instrumentation	Transient instrumentation	
		Sensor	Frequency response range (cps)
Engine speed	Three-phase tachometer generator	Direct-current generator	Limited by filter circuit 0-2.65
Power lever position	Wire-wound potentiometer connected to give position indication on microammeter	Wire-wound potentiometer connected to give position indication on oscillograph	40 cps natural frequency, 0.8 damping ratio
Fuel flow, proportional to static pressure	Rotameter	Aneroid-type pressure sensor with strain-gage element	40 cps natural frequency, 0.8 damping ratio
Torque	Bourdon-type gage	Aneroid-type pressure sensor with strain-gage element	40 cps natural frequency, 0.8 damping ratio
Turbine-outlet temperature	One-chromel-alumel thermocouple connected to Brown recorder	Three 24-gage chromel constantan thermocouples in series	0-1
Blade angle input	Wire-wound potentiometer connected to give position indication on microammeter	Wire-wound potentiometer connected to give position indication on oscillograph	40 cps natural frequency, 0.8 damping ratio
Blade angle	Wire-wound potentiometer connected to give position indication on microammeter	Wire-wound potentiometer connected to give position indication on oscillograph	40 cps natural frequency, 0.8 damping ratio
Variable-control oil pressure	Bourdon-type gage		


TABLE II - INDEX TO TRANSIENT RUNS

Figure	Throttle position, (deg)	
	Initial	Final
3(a)	64.5	41.0
3(a) concluded	41.5	64.5
3(b)	53.3	41.0
3(b) concluded	41.0	53.3
3(c)	46.8	41.0
3(c) concluded	41.0	46.8
3(d)	44.5	40.5
3(d) concluded	41.0	44.5
3(e)	42.7	41.0
3(e) concluded	41.0	42.7
3(f)	63.8	44.5
3(f) concluded	44.5	63.5
3(g)	53.3	44.5
3(g) concluded	44.5	53.8
3(h)	47.0	44.5
3(h) concluded	44.5	47.0
3(i)	64.5	47.0
3(i) concluded	47.0	64.2
3(j)	53.3	47.0
3(j) concluded	47.0	53.0
3(k)	65.0	53.3
3(k) concluded	53.3	64.5






(a) Combined system.




(b) Torque control loop.




Figure 1. - Block diagram of fuel and torque regulator.



(c) Speed control loop.




(d) Manual pressure control system.



(e) Altitude compensation loop.


Figure 1. - Concluded. Block diagram of fuel and torque regulator.





(a) Variation of fuel flow with variable-control oil pressure; steady state.


Figure 2. - Parameter schedules.



(b) Steady-state variation of speed, fuel flow, torque, and temperature with power-setting lever position.


Figure 2. - Concluded. Parameter schedules.

**Page intentionally left blank**



$N_1$ , 13,372 rpm	$N_f$ , 11,470 rpm
$S_1$ , 64.5°	$S_f$ , 41.0°
$W_{f,1}$ , 1497 lb/hr	$W_{f,f}$ , 678.1 lb/hr
$Q_1$ , 571.7 ft-lb	$Q_f$ , 114.5 ft-lb
$T_1$ , 1247° F	$T_f$ , 779.5° F
$\beta_{a,1}$ , 52 $\mu$ a	$\beta_{a,f}$ , 23 $\mu$ a
$\beta_1$ , 28.6°	$\beta_f$ , 15.0°

(a) Throttle position, 64.5° to 41.0°.




$N_1$ , 11,481 rpm	$N_f$ , 13,382 rpm
$S_1$ , 41.5°	$S_f$ , 64.5°
$W_{f,1}$ , 687.5 lb/hr	$W_{f,f}$ , 1493 lb/hr
$Q_1$ , 98.74 ft-lb	$Q_f$ , 568.7 ft-lb
$T_1$ , 756.0° F	$T_f$ , 1211° F
$\beta_{a,1}$ , 24 $\mu$ a	$\beta_{a,f}$ , 52 $\mu$ a
$\beta_1$ , 15.0°	$\beta_f$ , 28.6°

(a) Concluded. Throttle position, 41.5° to 64.5°.

Figure 3. - Transient operation of automatically controlled engine




**Page intentionally left blank**



$N_1$ , 13,496 rpm	$N_f$ , 11,367 rpm
$S_1$ , 53.3°	$S_f$ , 41.0°
$W_{f,1}$ , 1182 lb/hr	$W_{f,f}$ , 664.6 lb/hr
$Q_1$ , 355.5 ft-lb	$Q_f$ , 110.6 ft-lb
$T_1$ , 899.1° F	$T_f$ , 753.9° F
$\beta_{a,1}$ , 41 $\mu$ a	$\beta_{a,f}$ , 24 $\mu$ a
$\beta_1$ , 23.4°	$\beta_f$ , 14.8°

(b) Throttle position, 53.3° to 41.0°.




$N_1$ , 11,393 rpm	$N_f$ , 13,496 rpm
$S_1$ , 41.0°	$S_f$ , 53.3°
$W_{f,1}$ , 664.6 lb/hr	$W_{f,f}$ , 1190 lb/hr
$Q_1$ , 94.79 ft-lb	$Q_f$ , 339.7 ft-lb
$T_1$ , 744.3° F	$T_f$ , 899.1° F
$\beta_{a,1}$ , 24 $\mu$ a	$\beta_{a,f}$ , 42 $\mu$ a
$\beta_1$ , 14.8°	$\beta_f$ , 23.6°




(b) Concluded. Throttle position, 41.0° to 53.3°.

Figure 3. - Continued. Transient operation of automatically controll engine.

**Page intentionally left blank**



$N_i$ , 12,891 rpm	$N_f$ , 11,357 rpm
$S_i$ , 46.8°	$S_f$ , 41.0°
$W_{f,i}$ , 951.1 lb/hr	$W_{f,f}$ , 664.6 lb/hr
$Q_i$ , 216.2 ft-lb	$Q_f$ , 111.6 ft-lb
$T_i$ , 820.1° F	$T_f$ , 752.8° F
$\beta_{a,i}$ , 34 $\mu$ a	$\beta_{a,f}$ , 24 $\mu$ a
$\beta_i$ , 20.0°	$\beta_f$ , 15.0°




$N_i$ , 11,341 rpm	$N_f$ , 12,907 rpm
$S_i$ , 41.0°	$S_f$ , 46.8°
$W_{f,i}$ , 664.6 lb/hr	$W_{f,f}$ , 958.4 lb/hr
$Q_i$ , 96.76 ft-lb	$Q_f$ , 193.5 ft-lb
$T_i$ , 742.1° F	$T_f$ , 816.9° F
$\beta_{a,i}$ , 24 $\mu$ a	$\beta_{a,f}$ , 34 $\mu$ a
$\beta_i$ , 15.0°	$\beta_f$ , 20.0°




Figure 3. - Continued. Transient operation of automatically controllengine.

**Page intentionally left blank**



$N_i$ , 12,390 rpm	$N_f$ , 11,315 rpm
$S_i$ , 44.5°	$S_f$ , 40.5°
$W_{f,i}$ , 845.9 lb/hr	$W_{f,f}$ , 662.5 lb/hr
$Q_i$ , 163.9 ft-lb	$Q_f$ , 106.6 ft-lb
$T_i$ , 791.2° F	$T_f$ , 751.7° F
$\beta_{a,i}$ , 30 $\mu$ a	$\beta_{a,f}$ , 24 $\mu$ a
$\beta_i$ , 18.4°	$\beta_f$ , 15.15°




$N_i$ , 11,357 rpm	$N_f$ , 12,390 rpm
$S_i$ , 41.0°	$S_f$ , 44.5°
$W_{f,i}$ , 664.6 lb/hr	$W_{f,f}$ , 842.7 lb/hr
$Q_i$ , 95.78 ft-lb	$Q_f$ , 156.0 ft-lb
$T_i$ , 744.3° F	$T_f$ , 784.8° F
$\beta_{a,i}$ , 24 $\mu$ a	$\beta_{a,f}$ , 30 $\mu$ a
$\beta_i$ , 15.25°	$\beta_f$ , 18.2°



Figure 3. - Continued. Transient operation of automatically controlled engine.


**Page intentionally left blank**

2281



(e) Throttle position, 42.7° to 41.0°

$N_i$ , 11,873 rpm	$N_f$ , 11,470 rpm
$S_i$ , 42.7°	$S_f$ , 41.0°
$W_{f,i}$ , 746.9 lb/hr	$W_{f,f}$ , 690.6 lb/hr
$Q_i$ , 123.4 ft-lb	$Q_f$ , 110.6 ft-lb
$T_i$ , 763.5° F	$T_f$ , 753.9° F
$\beta_{a,i}$ , 26 $\mu$ a	$\beta_{a,f}$ , 26 $\mu$ a
$\beta_i$ , 16.6°	$\beta_f$ , 16.05°



(e) Concluded. Throttle position, 41.0° to 2.7°.

Figure 3. - Continued. Transient operation of automatical controlled engine.

$N_i$ , 11,357 rpm	$N_f$ , 11,894 rpm
$S_i$ , 41.0°	$S_f$ , 42.7°
$W_{f,i}$ , 669.8 lb/hr	$W_{f,f}$ , 753.1 lb/hr
$Q_i$ , 98.74 ft-lb	$Q_f$ , 122.4 ft-lb
$T_i$ , 747.5° F	$T_f$ , 766.7° F
$\beta_{a,i}$ , 25 $\mu$ a	$\beta_{a,f}$ , 26 $\mu$ a
$\beta_i$ , 15.6°	$\beta_f$ , 16.85°



**Page intentionally left blank**

2281






Figure 3. - Continued. Transient operation of automatically controlled engine.




**Page intentionally left blank**

2281



$N_i$ , 13,382 rpm	$N_f$ , 12,321 rpm
$S_i$ , 53.3°	$S_f$ , 44.5°
$W_{f,i}$ , 1168 lb/hr	$W_{f,f}$ , 846.4 lb/hr
$Q_i$ , 348.9 ft-lb	$Q_f$ , 176.4 ft-lb
$T_i$ , 913.7° F	$T_f$ , 811.8° F
$\beta_{a,i}$ , 41 $\mu$ a	$\beta_{a,f}$ , 30 $\mu$ a
$\beta_i$ , 23.6°	$\beta_f$ , 18.65°

(g) Throttle position, 53.3° to 44.5°.



$N_i$ , 12,321 rpm	$N_f$ , 13,382 rpm
$S_i$ , 44.5°	$S_f$ , 53.8°
$W_{f,i}$ , 846.4 lb/hr	$W_{f,f}$ , 1177 lb/hr
$Q_i$ , 171.5 ft-lb	$Q_f$ , 337.0 ft-lb
$T_i$ , 803.4° F	$T_f$ , 909.5° F
$\beta_{a,i}$ , 30 $\mu$ a	$\beta_{a,f}$ , 40 $\mu$ a
$\beta_i$ , 18.65°	$\beta_f$ , 23.6°


(g) Concluded. Throttle position, 44.5° to 53.8°.

Figure 3. - Continued. Transient operation of automatically controlled engine.




**Page intentionally left blank**

2281



$N_i$ , 12,877 rpm	$N_f$ , 12,336 rpm
$S_i$ , 47.0°	$S_f$ , 44.5°
$W_{f,i}$ , 959.0 lb/hr	$W_{f,f}$ , 849.5 lb/hr
$Q_i$ , 220.0 ft-lb	$Q_f$ , 178.4 ft-lb
$T_i$ , 833.1° F	$T_f$ , 808.7° F
$\beta_{a,i}$ , 33 $\mu$ a	$\beta_{a,f}$ , 30 $\mu$ a
$\beta_i$ , 20.2°	$\beta_f$ , 18.9°

(h) Throttle position, 47.0° to 44.5°.




$N_i$ , 12,336 rpm	$N_f$ , 12,867 rpm
$S_i$ , 44.5°	$S_f$ , 47.0°
$W_{f,i}$ , 849.5 lb/hr	$W_{f,f}$ , 955.9 lb/hr
$Q_i$ , 174.4 ft-lb	$Q_f$ , 217.0 ft-lb
$T_i$ , 805.5° F	$T_f$ , 832.0° F
$\beta_{a,i}$ , 30 $\mu$ a	$\beta_{a,f}$ , 32 $\mu$ a
$\beta_i$ , 18.9°	$\beta_f$ , 20.2°

(h) Concluded. Throttle position, 44.5° to 4.0°.

Figure 3. - Continued. Transient operation of automatically controlled engine.




**Page intentionally left blank**



$N_i$ , 13,264 rpm	$N_f$ , 12,851 rpm
$S_i$ , 64.5°	$S_f$ , 47.0°
$W_{f,i}$ , 1469 lb/hr	$W_{f,f}$ , 965.2 lb/hr
$Q_i$ , 561.0 ft-lb	$Q_f$ , 228.0 ft-lb
$T_i$ , 1263° F	$T_f$ , 860.7° F
$\beta_{a,i}$ , 53 $\mu$ a	$\beta_{a,f}$ , 33 $\mu$ a
$\beta_i$ , 28.6°	$\beta_f$ , 20.45°

(1) Throttle position, 84.5° to 47.0°.




$N_i$ , 12,851 rpm	$N_f$ , 13,264 rpm
$S_i$ , 47.0°	$S_f$ , 64.2°
$W_{f,i}$ , 965.2 lb/hr	$W_{f,f}$ , 1465 lb/hr
$Q_i$ , 225.0 ft-lb	$Q_f$ , 561.9 ft-lb
$T_i$ , 844.7° F	$T_f$ , 1260° F
$\beta_{a,i}$ , 34 $\mu$ a	$\beta_{a,f}$ , 52 $\mu$ a
$\beta_i$ , 20.45°	$\beta_f$ , 28.6°

(1) Concluded. Throttle position, 47.0° to 64.2°.

Figure 3. - Continued. Transient operation of automatically controlled engine.




**Page intentionally left blank**



(j) Throttle position, 53.3° to 47.0°.

$N_i$ , 13,382 rpm	$N_f$ , 12,836 rpm
$S_i$ , 53.3°	$S_f$ , 47.0°
$W_{f,i}$ , 1149 lb/hr	$W_{f,f}$ , 961.1 lb/hr
$Q_i$ , 335.0 ft-lb	$Q_f$ , 228.0 ft-lb
$T_i$ , 909.5° F	$T_f$ , 843.7° F
$\beta_{a,i}$ , 40 $\mu$ a	$\beta_{a,f}$ , 34 $\mu$ a
$\beta_i$ , 23.15°	$\beta_f$ , 20.45°




$N_i$ , 12,836 rpm	$N_f$ , 13,382 rpm
$S_i$ , 47.0°	$S_f$ , 53.0°
$W_{f,i}$ , 961.1 lb/hr	$W_{f,f}$ , 1155 lb/hr
$Q_i$ , 226.0 ft-lb	$Q_f$ , 335.0 ft-lb
$T_i$ , 838.4° F	$T_f$ , 907.4° F
$\beta_{a,i}$ , 34 $\mu$ a	$\beta_{a,f}$ , 40 $\mu$ a
$\beta_i$ , 20.45°	$\beta_f$ , 23.15°



(j) Concluded. Throttle position, 47.0° to 53.0°.


Figure 3. - Continued. Transient operation of automatically controlled engine.

**Page intentionally left blank**



(k) Throttle position, 65.0° to 53.3°.

$N_i$ , 13,238 rpm	$N_f$ , 13,315 rpm
$S_i$ , 65.0°	$S_f$ , 53.3°
$W_{f,i}$ , 1475 lb/hr	$W_{f,f}$ , 1177 lb/hr
$Q_i$ , 577.8 ft-lb	$Q_f$ , 349.9 ft-lb
$T_i$ , 1321° F	$T_f$ , 944.5° F
$\beta_{a,i}$ , 54 $\mu$ a	$\beta_{a,f}$ , 41 $\mu$ a
$\beta_i$ , 29.05°	$\beta_f$ , 23.6°



$N_i$ , 13,315 rpm	$N_f$ , 13,238 rpm
$S_i$ , 53.3°	$S_f$ , 64.5°
$W_{f,i}$ , 1183 lb/hr	$W_{f,f}$ , 1475 lb/hr
$Q_i$ , 356.8 ft-lb	$Q_f$ , 568.9 ft-lb
$T_i$ , 939.2° F	$T_f$ , 1302° F
$\beta_{a,i}$ , 42 $\mu$ a	$\beta_{a,f}$ , 53 $\mu$ a
$\beta_i$ , 23.8°	$\beta_f$ , 28.8°



(k) Concluded. Throttle position, 53.3° to 64.5°.

Figure 3. - Concluded. Transient operation of automatically controll engine.

CONTROL PERFORMANCE OF GENERAL ELECTRIC FUEL AND TORQUE  
REGULATOR OPERATING ON T31-3 TURBINE-PROPELLER  
ENGINE IN SEA-LEVEL TEST STAND

*Frank L. Oppenheimer*

Frank L. Oppenheimer  
Aeronautical Research Scientist  
Propulsion Systems

James Lazar  
Aeronautical Research Scientist

Approved:

*John C. Sanders*

John C. Sanders  
Aeronautical Research Scientist  
Propulsion Systems

*Eugene W. Wasielewski*

Eugene W. Wasielewski  
Chief, Engine Research Division