


# NASA Tech Briefs

A blue robotic hand, labeled 'SALISBURY ROBOTICS', is shown holding a blue printed circuit board (PCB) with various electronic components. The hand is positioned in the center-right of the frame, with its fingers gripping the board. The background is a light-colored wall with a power outlet visible on the left. The overall image is a cover for a technical publication.

Official Publication of  
National Aeronautics and  
Space Administration  
Volume 15 Number 2

Transferring Technology  
to Industry and  
Government  
February 1991

**Dexterous  
Robots  
Lend Hand  
To Industry**

## Science Teacher Fred Holtzclaw Has Successfully Created Energy In A Classroom.

In the nearly 20 years that Mr. Holtzclaw has been teaching high school science in Tennessee, he's learned a lot about energy. How to impart enthusiasm, for instance. The hard work needed to overcome inertia. And most difficult of all, what to do about burn-out.

He's not alone. Every day, teachers all over the country face the same challenges.

That's why Martin Marietta is helping to underwrite a new regional Academy for Teachers of Science and Math at the University of Tennessee. It's an intensive program of study and discussion for Martin Marietta Fellows; outstanding educators in all grade levels. Through the Academy, the private sector, government and academia are all joining together to support a critical educational initiative by President Bush.


It's important to help keep things moving in the classroom, and teachers like Fred Holtzclaw are the right place to start. If we want to fire-up the masterminds of tomorrow, the best thing we can do is keep our outstanding teachers energized today.


**MARTIN MARIETTA**

6801 ROCKLEDGE DRIVE, BETHESDA, MARYLAND 20817

**MASTERMINDING TOMORROW'S TECHNOLOGIES**







**MORE CHROMATOGRAPHIC FITTINGS THAN ANYWHERE ELSE IN THE WORLD.** Circle Reader Action No. 498


**VICI**

Valco Instruments Co. Inc.  
P.O. Box 55603, Houston, TX 77255 USA  
Telephone (713) 688-9345  
Telefax (713) 688-8106 Telex 79-0033 VALCO HOU


**VICI** AG

Valco Europe  
Untertannberg 7 CH-6214 Schenkon, Switzerland  
Telephone (045) 21 68 68  
Telefax (045) 21 30 20 Telex 868342 VICI CH


# Cut MCAE Costs Without Cutting Capabilities or Performance




3-D Fluid Flow




Shaded Plot



Electromagnetic Analysis



Temperature Distribution in Cryogenic Turboexpander Housing\*



Interactive CAD-like Color Pre- and Postprocessor

## **COSMOS/M™**

### Modeling and FEA on your PC, Mac II or Workstation

#### ANALYSIS:

- STATICS: *Linear and Nonlinear*
- DYNAMICS: *Linear and Nonlinear*
- HEAT TRANSFER
- FLUID FLOW: *3D, Turbulent, Compressible*
- ELECTROMAGNETICS
- FATIGUE
- CRASH DYNAMICS
- NONLINEAR: *Plasticity, Large Strain, etc.*
- KINEMATICS

#### FEATURES:

- H/P METHOD
- AUTOMATIC ADAPTIVE MESHING
- 15,000 NODES 60,000 D.O.F.
- SUBSTRUCTURING
- COMPOSITE/SANDWICH
- CAD INTERFACES  
*IGES and DXF® Input*
- ANSYS®, NASTRAN® and  
PATRAN® TRANSLATORS

**Free Offer:**

**213-452-2158**

For a limited time, SRAC will send you a FREE 100 node working version of COSMOS/M which will enable you to run your own statics, dynamics and heat transfer problems. Introductory user guide plus shipping and handling fee \$30.00.

**Dealer Inquiries Welcome**

**FEA SYSTEM FROM \$995**

ANSYS is the registered trademark of Swanson Analysis Systems Incorporated. DXF is a registered trademark of Autodesk, Inc. NASTRAN is the registered trademark of NASA. Patran is the registered trademark of PDA Engineering. \*Courtesy of ACD, Inc.

*Structural Research*

**AND ANALYSIS CORPORATION**

1661 Lincoln Blvd./Ste. 200/Santa Monica, CA 90404 USA  
TEL: (213) 452-2158/TLX: 705578/FAX: (213) 399-6421

**Circle Reader Action No. 676**



*Car owners!  
Here's how to*

# BABY YOUR CAR'S ENGINE

"TUFOIL®  
SLIPPERIER  
THAN  
TEFLON®"

"INVENTOR OF THE YEAR" AWARD  
AND INDUCTION INTO  
"N.J. INVENTORS HALL OF FAME"  
GOES TO INVENTOR OF TUFOIL

New cars are expensive ... so is gas!  
Let Tufoil® be your key to survival!

## WHY BUY A NEW CAR?

A new car is one of life's biggest investments. Why not put off such a big expense as long as possible and at the same time, spend less to run the car you now own? The money you save is money in your pocket.

Tens of thousands of drivers are already using Tufoil to "beat the system". Here's how it's done ... it's simple!

## ENGINES LAST & LAST

The normal life of an engine is usually about 100,000 miles, give or take a few miles either way. This is no longer the case. By adding 4 ounces of Tufoil with each oil change, together with an effective maintenance program, 200,000 miles and more are not uncommon. But that's not all!

Together with this extended engine life are numerous benefits. For instance, quick acceleration. One user writes that his car "Takes off like a scared rabbit!"

## SILKY SMOOTH OPERATION

That's just the beginning! Easy starts and better gas mileage are soon apparent due to the reduction in friction. Your engine is now free to run smooooothly.



One of our customers put it nicely when he said, "You can hear it, you can feel it," with Tufoil in the engine.

## PROVEN EFFECTIVE

Our files bulge with testimonials. Customers not only call, but write to us about their fantastic results! They're telling friends and relatives. As a matter of fact they're spreading

the news about Tufoil all over the world.

It stands to reason, though. Tufoil is so unique that even the United States and Canadian governments have confirmed its effectiveness. One report shows that Tufoil is actually slipperier than Teflon™!

## NO TIME LIKE THE PRESENT

There's never been a better time to try Tufoil and prove to yourself and your car that what everyone's been saying is really true! We think you'll find it's one of the smartest decisions you've made. In fact we're so sure, we guarantee it'll work. If you don't agree, we'll gladly refund your \$14.25, the cost of your initial 8 ounce treatment.

So why wait any longer? The sooner you start, the better! If your car has over 5-10,000 miles on it, now's the time to start! Use the order form below to baby your car (and your checkbook). You'll be glad you did!

## ORDER TODAY

1-800-922-0075 

*The Alternative to expensive driving!*

FREE ... Products based on TUFOIL technology. Check one with each order of 2 bottles or a quart. Check 2 for each gallon order. Values range from \$3.98 to \$9.95.

- TUFOIL Gun-Coat — Super rust inhibited, smooth action
- TUFOIL Compu-Lube — Low viscosity for computer mechanisms
- TUFOIL Lightning Grease — Easily sheared grease for instruments
- TUFOIL Lubit-8 — General purpose, household use lubricant

FREE brochures ...

- 30 Questions/Answers about TUFOIL

FLUON® is reg. T.M. of ICI Americas Inc.  
TEFLON® is reg. T.M. of DuPont®  
TUFOIL® is reg. T.M. of Fluoramics  
U.S. Patent No. 4,284,518  
U.S. Patent No. 4,224,173  
U.S. Patent No. 3,933,656  
Other U.S. Patents issued and pending.

When  
POPULAR MECHANICS  
tested TUFOIL, it reported  
"TUFOIL is absolutely  
spectacular!"

**YES**

**rush my TUFOIL order:**

- ONE 8 oz. bottle ... treat one car for \$14.25 (plus \$3.50 shipping and handling). See money back guarantee.
- TWO 8 oz. bottles ... treat two cars for \$25.00 (plus \$4.00 shipping and handling) **SAVE \$6.00**
- ONE Quart bottle ... treat 4 cars for \$34.95 (plus \$4.00 shipping and handling)
- ONE GALLON ... treat 16 cars for \$125.00 (plus \$6.00 shipping and handling.)

We ship within days!

MONEY BACK GUARANTEE ON 8-OZ.

**Fluoramics, Inc.** NTB291  
18 Industrial Avenue  
Mahwah, NJ 07430

My check or money order for \$ \_\_\_\_\_ is enclosed.

Charge my credit card:

Am. Express  Master Card  Visa  
Card No. \_\_\_\_\_

Exp. Date \_\_\_\_\_

Phone No. \_\_\_\_\_

Name \_\_\_\_\_

Address UPS Shipping Address \_\_\_\_\_

City \_\_\_\_\_

State \_\_\_\_\_ Zip \_\_\_\_\_

(N.J. residents please add 7% sales tax).

Canadian Distributor: 1-800-363-7753




Photo courtesy Ames Research Center

*This computer-generated image shows the fluid flow over an F-18 fighter jet. For more on the computer simulation of physical phenomena, turn to page 32.*

## SPECIAL FEATURES

Space-Based Image Processing Aids Medicine .....	10
NASA Patents .....	82

## TECHNICAL SECTION

 New Product Ideas .....	12
 NASA TU Services .....	14
 Electronic Components and Circuits .....	16
 Electronic Systems .....	22
 Physical Sciences .....	34
 Materials .....	42
 Computer Programs .....	46
 Mechanics .....	52
 Machinery .....	59
 Fabrication Technology .....	60
 Mathematics and Information Sciences .....	66
 Life Sciences .....	69
 Subject Index .....	76

## DEPARTMENTS

*On The Cover: A dexterous mechanical hand is used as a testbed for a knowledge-based robotic system, developed at Sandia National Laboratories, which generates and executes grasps of objects (such as the gear shown) without need of a database of object models. A NASA-owned invention, the three-fingered hand can move objects about, twist them, and otherwise manipulate them by finger motion alone, and can be adapted to different arms. See page 82.*

(Photo courtesy Sandia National Laboratories)

New on the Market.....	72
New Literature.....	74
Advertisers Index.....	80

### New This Month

*This issue we introduce two new features to NASA Tech Briefs:*

**NASA's Innovators**—A bimonthly series focusing on NASA engineers and scientists who define the cutting edge in their respective fields (page 10);

**NASA Patents**—A quarterly column describing recently patented NASA inventions available for license by industry (page 82).

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither Associated Business Publications Co., Ltd. nor anyone acting on behalf of Associated Business Publications Co., Ltd. nor the United States Government nor any person acting on behalf of the United States Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights. The U.S. Government does not endorse any commercial product, process, or activity identified in this publication.

Permissions: Authorization to photocopy items for internal or personal use, or the internal or personal use of specific clients, is granted by Associated Business Publications, provided that the flat fee of \$3.00 per copy is paid directly to the Copyright Clearance Center (21 Congress St., Salem, MA 01970). For those organizations that have been granted a photocopy license by CCC, a separate system of payment has been arranged. The fee code for users of the Transactional Reporting Service is: ISSN 0145-319X/90 \$3.00+.00

NASA Tech Briefs, ISSN 0145-319X, USPS 750-070, copyright © 1991 in U.S., is published monthly by Associated Business Publications Co., Ltd., 41 E. 42nd St., New York, NY 10017-5391. The copyrighted information does not include the individual tech briefs which are supplied by NASA. Editorial, sales, production and circulation offices at 41 East 42nd Street, New York, NY 10017-5391. Subscription for non-qualified subscribers in the U.S., Panama Canal Zone, and Puerto Rico, \$75.00 for 1 year; \$125.00 for 2 years; \$200.00 for 3 years. Single copies \$10.00. Foreign subscriptions one-year U.S. Funds \$150.00. Remit by check, draft, postal, express orders or VISA, MasterCard, and American Express. Other remittances at sender's risk. Address all communications for subscriptions or circulation to NASA Tech Briefs, 41 East 42nd Street, New York, NY 10017-5391. Second-class postage paid at New York, NY and additional mailing offices.

**POSTMASTER: please send address changes to NASA Tech Briefs, 41 E. 42nd Street, Suite 921, New York, NY 10017-5391.**

Also available in  
2 and 4 channel versions.

 **GOULD**  
Electronics

# Gould recorders show up in the most convenient places.

## Introducing the first family of digital recording oscilloscopes.


Now you can get the power of a digital  
storage oscilloscope with the built-in con-  
venience of traditional recording.

Gould recognizes that physical testing is  
extremely demanding. That's why we've  
designed a family of Digital Recording  
Oscilloscopes (DROs™) with features  
that let you:

- Capture and record up to eight  
channels simultaneously
- Record off-ground measurements  
with isolated or differential inputs
- Capture and record single shot  
events with 50 nanosecond  
resolution
- Use the built-in thermal array  
recorder for:
  - continuous trend recording
  - screen dump of selected data
  - output of a segment of memory  
or the complete memory

All this in a single, portable package.

For more information and a free Gould Guide to  
DSO/DROs diskette, call (216) 328-7000 or use the  
coupon below. Because if you think the Gould DRO  
sounds good, you ought to see it on paper.



**Yes!**

I want a free Gould Guide to DSO/DROs diskette.  
(please print)


NTB 2/91

NAME: \_\_\_\_\_  
TITLE: \_\_\_\_\_  
COMPANY: \_\_\_\_\_  
STREET: \_\_\_\_\_  
CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_  
TELEPHONE: \_\_\_\_\_

Send to: Gould, Inc., Test and Measurement Group, 8333 Rockside Rd.,  
Valley View, Ohio, 44125 or call (216) 328-7000, FAX: (216) 328-7400.

Circle Reader Action No. 483

# Real Time Television On Workstations



## The RGB/View System for Multimedia Effects

The RGB/View™ displays live TV or other full motion video on workstations and high resolution personal computers. The RGB/View accepts video signals (NTSC or PAL) from a built-in TV tuner, camera, tape recorder or videodisc.

FLIR input is also available. True color video is displayed full screen or as a window on the monitor.

- Works with any computer to 1280 x 1024 pixels
- Image capture
- Text and graphics overlays on the video
- Scale, reposition, freeze
- X-Windows support
- Cable ready tuner
- Stereo audio
- Standalone and board level models available
- Priced from \$7500.00

Applications include interactive video disk training, video teleconferencing, process control, surveillance, simulation, C<sup>3</sup>I and robotics.

*The RGB/View may be retrofitted to existing display systems.*



**SPECTRUM**

2550 Ninth Street Berkeley, CA 94710  
TEL: (415) 848-0180 FAX: (415) 848-0971

# NASA Tech Briefs

Official Publication of  
National Aeronautics and  
Space Administration



## NASA Tech Briefs:

Published by .....	Associated Business Publications
Editor-in-Chief/Publisher .....	Bill Schnirring
Associate Publisher .....	Frank Nothhaft
Editor .....	Joseph T. Pramberger
Managing Editor .....	R.J. Laer
Assistant Editor .....	Kathleen Carrea
Assistant Editor .....	Justina Cardillo
Assistant Editor .....	Patrick Corbett
Technical Advisor .....	Dr. Robert E. Waterman
Production Manager .....	Rita Nothhaft
Traffic Manager .....	James E. Cobb
Art Director .....	Pierre Granier
Circulation Manager .....	Cheryl Cohen
Advertising Coordinator .....	Daniel Murphy
Telecommunications Specialist .....	Evelyn Mars
Reader Service Manager .....	Sylvia Valentin

### Briefs & Supporting Literature:

Provided to National Aeronautics and Space Administration by  
**International Computers & Telecommunications, Inc.**,  
NY, NY with assistance from **Logical Technical Services, NY, NY**

Technical/Managing Editor.....	Ted Selinsky
Art Director .....	Luis Martinez
Administrator .....	Elizabeth Texeira
Chief Copy Editor .....	Lorne Bullen
Staff Writers/Editors.....	Dr. James Boyd, Dr. Larry Grunberger, Dr. Theron Cole, Jordan Randjelovich, George Watson, Oden Browne
Graphics.....	Vernald Gillman, Pamela Baynham, Charles Sammartano
Editorial & Production.....	Bill Little, Ivonne Valdes, Susan Kyu OH, Frank Ponce

### NASA:

NASA Tech Briefs are provided by the National Aeronautics and Space Administration, Technology Utilization Division, Washington, DC:  
Administrator.....Richard H. Truly  
Assistant Administrator for Commercial Programs.....James T. Rose  
Deputy Assistant Administrator(Programs).....Frank E. Penaranda  
Deputy Director TU Division(Publications Manager).....Leonard A. Ault  
Manager, Technology Utilization Office, NASA Scientific and Technical Information Facility.....Walter M. Heiland

### Associated Business Publications

41 East 42nd Street, Suite 921, New York, NY 10017-5391  
(212) 490-3999 FAX (212) 986-7864

President .....	Bill Schnirring
Executive Vice President .....	Frank Nothhaft
Vice President .....	Domenic A. Mucchetti
Operations Manager .....	Rita Nothhaft
Controller .....	Felecia Lahey
Systems Analyst .....	Patrick Wolfert

### Advertising:

New York Office:(212) 490-3999 FAX (212) 986-7864

Director of Advertising Sales.....	Domenic A. Mucchetti
Account Executive (NY,NJ).....	Brian Clerkin at (201) 366-2751
Account Executive (VA,DC,MD,DE,WV).....	John D. Floyd, CBC at (215) 399-3265
Account Executive.....	Debby Crane at (201) 967-9838
Account Executive (Midwest).....	Paul Leshar, CBC at (708) 501-4140
Account Executive (Northwest).....	Bill Hague at (206) 858-7575
Regional Sales Manager (South).....	Douglas Shaller at (212) 490-3999
Account Executives (Eastern MA,NH,ME,RI).....	Paul Gillespie at (508) 429-8907; Bill Doucette at (508) 429-9861
Account Executives (Western MA,CT,VT) .....	George Watts or David Haggelt at (413) 253-9881
Account Executives (Calif.,AZ,NV,NM) for Area Codes 818/213/805 Robert D'Alexander for Area Codes 408/415/916/209/707) Elizabeth Cooper	



### NTBM-Research Center

Account Supervisor.....Lourdes Del Valle




# GRAFTOOL™

“...in a class by itself...delivers on all accounts...  
easy to use...the ultimate graphics package, fulfilling  
everybody's needs.”


Reprinted with permission from PC Magazine, March 14th, 1989, Copyright ©1989 Ziff Communications Co. and PC Magazine, November 13th, 1990 © Ziff Communications Co.



Easily create complex curves & surfaces with the graphical Formula-Solver™



Automate customized graph creation with pre-recorded macro & batch files.



Integrate 2-D and 3-D data on a single graph to add meaning and impact.

## Presentation graphics and analysis for scientific users.

Your technical data requires more muscle and sophistication than basic business graphics and plotting packages can provide. It's simply a matter of using the right tool for the job. In addition to publication-quality graphics, you need powerful analysis tools and capabilities such as Graftool's ■ Intelligent Data Cursor™ to read out data points on curves & surfaces ■ Linear & non-linear curve-fitting ■ Unlimited zoom & rotation ■ Multiple axes in linear, log, or probability scales ■ Advanced data handling, allowing over 268,000,000 data points ■ Powerful scientific spreadsheet which can directly read your Lotus or ASCII files

- Unrestricted placement of graphs & text
- Direct compatibility with Microsoft Word & WordPerfect.

With Graftool, all this power and flexibility purr quietly under the hood, while pop-up menus and push-buttons bring an ease of use previously unheard of in scientific software. Just "point & process" with increased productivity and greater understanding.

GRAFTOOL — the right tool for your technical solutions.

GRAFTOOL \$495.

- Interactive demo available
- Academic discounts.



3-D VISIONS

412 S. Pacific Coast Highway, Second Floor  
Redondo Beach, CA 90277  
Call: 1 (800) 729-4723, 1 (213) 540-8818  
FAX: 1 (213) 540-3492  
Circle Reader Action No. 669

# Space-Based Image Processing Aids Medicine

NASA's

I  
N  
N  
O  
V  
A  
T  
O  
R  
S




Photo courtesy NASA

**Robert Selzer, supervisor of the Biomedical Image Processing Laboratory, and staff member Anne Shircore process angiograms as part of an ongoing study to determine whether lowering serum cholesterol has a beneficial effect on atherosclerosis.**

A team of scientists at NASA's Jet Propulsion Laboratory is creating computerized images of the human body to help researchers solve medical mysteries. Using image processing techniques first developed to visualize data captured by spacecraft, they are enabling researchers to quickly "see" how new drugs fight disease, and to better understand changes in the body over time.

Conventional methods of drug testing in clinical trials often involve thousands of subjects and many years of study, and can cost upward of \$50 million. Computer analysis techniques accelerate the testing process, reduce costs, and allow more precise evaluations of test data, according to **Robert Selzer**, supervisor of JPL's five-member Biomedical Image Processing Laboratory. Funded by NASA's Life Sciences Division and the National Institutes of Health, the laboratory's projects range from visualiz-

ing atherosclerosis in heart patients to testing muscle loss during prolonged inactivity.

## Images Of The Heart

Since the mid-1970s, the laboratory has been a national leader in the processing of coronary angiograms, designed to help surgeons pinpoint the location of atherosclerotic lesions in order to determine the best way to treat coronary disease. Called angiography, the process is also used for intervention studies: Selzer's group, in conjunction with the University of Southern California Medical School, is investigating whether the lowering of blood cholesterol has a positive effect on coronary disease. The project involves the testing of 260 men who have had bypass surgery. Half of the subjects received the cholesterol-lowering drug Lovastatin, the others a placebo. Angiograms of their coronary arteries were made three times: at the beginning of the

study, after two years, and after four years.

X-ray images captured at 60 frames per second on 35 mm film were used to track the flow of an iodine compound into the subjects' arteries. Selzer's group is processing the film on two projectors, each equipped with a 1000-line video camera. The camera's output goes to a frame grabber that digitizes the image and transmits it to a MicroVax II for display on a computer screen.

The next step involves measurement of the arterial walls by tracking the inner edges of the artery. The computer searches in a direction perpendicular to the vessel for the point of maximum density gradient—where the image intensity changes the quickest. Once the edges are detected, the computer estimates the location of the prediseased arterial wall and measures the percentage of narrowing.

"We are comparing identical measurements of the vessels over



Photo courtesy NASA

### Computer-generated image of lower leg muscles, part of a study of muscle atrophy.

time in order to detect changes," Selzer, 58, explained. The advantage of using a computer, he said, is it can detect much smaller changes than possible through visual analysis. "This saves time and drastically reduces the number of test subjects needed."

Selzer's team is exploring other technologies that are less invasive or dangerous to the patient, such as ultrasound imaging. While too low in resolution to view coronary arteries, ultrasound imaging is useful for locating blockages in the carotid artery, which transports blood to the brain. Sound waves are employed to trace the artery's walls and determine their thickness. A computer then processes the data and generates a three-dimensional picture of the vessel, which helps the researchers to precisely match the location of measurements during repeated tests.

### Studying Muscle Loss

Another noninvasive tool for looking inside the body is magnetic resonance imaging (MRI). The Biomed-

ical Image Processing Laboratory is using MRI to study the muscle atrophy that afflicts astronauts in space and hospital patients bedridden for long periods. MRI data is collected by measuring the energy the muscle's protons release after the temporary imposition of a high-strength electromagnetic field. With the aid of a MicroVax computer, the researchers create pictures of muscle cross sections. By combining the cross-sectional images into a composite 3D image, they can determine the total volume of each muscle and, with repeated measurements, the rate of atrophy.

As part of a month-long bed-rest study managed by NASA's Ames Research Center, Selzer's group applied MRI technology to visualize the muscle loss in the lower legs of 19 test subjects. Images taken at the end of the study showed, on average, a seven percent loss in the subjects' muscle mass. Such data could prove useful in developing special exercises and other measures to counter atrophy, said Selzer, who holds a masters degree in physics.

### Valuable Solutions

The laboratory has launched a new project with Beth Israel Medical Hospital in Boston using imaging technology to detect changes in skin lesions over time. Such changes can signal the onset of melanoma, a type of cancer that is difficult to treat if not detected early. Some patients have large numbers of lesions, which makes it difficult for the dermatologist to ac-

curately detect all changes. Image processing techniques will be used to match photographs of the skin taken over time and to document changes.

"The nice thing about what we're doing in this laboratory," commented Selzer, "is that there's no ambiguity about the value of the solutions to the problems. It's clear that this work is important to people's health." □

*For further information about the technologies described in this article, contact:*

*Arif Husain  
Jet Propulsion Laboratory  
NASA Resident Office  
Mail Stop 180-801  
4800 Oak Grove Drive  
Pasadena, CA 91109*




Photo courtesy NASA

**Selzer's team is using imaging techniques to detect changes in skin lesions over time.**



## New Product Ideas

New Product Ideas are just a few of the many innovations described in this issue of *NASA Tech Briefs* and having promising commercial applications. Each is discussed further on the referenced page in the appropri-

ate sections in this issue. If you are interested in developing a product from these or other NASA innovations, you can receive further technical information by requesting the TSP referenced at the end of the full-

length article or by writing the Technology Utilization Office of the sponsoring NASA center (see page 14). NASA's patent-licensing program to encourage commercial development is described on page 14.

### Rotationally Actuated Prosthetic Hand

A prosthetic hand includes two pincerlike fingers that are actuated by rotation of the

forearm. The device features simpler design and operation, less weight, and takes up less space than conventional mechanisms of this type. (See page 69)

### Long-Lifetime Laser Materials for Effective Diode Pumping

While Nd lasers have proved to be quite useful, they would be even more so if they could be pumped by laser diodes. Because the cost of the diodes outweighs the cost of the laser material by perhaps two orders of magnitude, the cost would be reduced significantly. (See page 42)

### Semiconductor Laser With Multilayer Dielectric Reflector

A multilayer dielectric reflector would be included in a proposed surface-emitting, distributed-feedback, grating semiconductor laser (e.g., a GaAlAs device). The reflector would contribute to the efficiency and output power of the laser. (See page 18)

### Modified Furnace Makes More Silicon Ribbon


The rate of growth of silicon ribbon by the dendritic-web process is increased by a modification in the lid of the growth crucible. The modified furnace produces silicon ribbon at the rate of 8.9 cm<sup>2</sup>/min — 44 percent higher than the previous rate. (See page 64)

### Low-Wear Ball-Bearing Separator

A proposed ball-bearing separator for use in a cryogenic pump would be stronger and more resistant to wear than present separators made of polytetrafluoroethylene reinforced with glass fibers. The new separator would consist of a molded plastic-and-metal composite ring imbued with solid lubricant and containing an embedded metal ring. (See page 56)

### Self-Testing Static Random-Access Memory

A proposed static random-access memory for a computer would feature improved error-detecting and -correcting capabilities. The new self-testing scheme would provide for the detection and correction of errors at any time during normal operation — even while data are being written into the memory. (See page 30)



## Only Specmaster gives you full-text Mil-Specs, NAS, SAE and ASTM standards plus vendor catalogs on CD-ROM.

- Now you can search, retrieve, review and print government and industry standards and vendor catalogs with computer speed and ease.
- DOD-listed file is **UPDATED WEEKLY!** (50,000 military and federal specifications, standards, QPLs, DIDs, handbooks, etc.)
- Specmaster can be **NETWORKED** on a NETBIOS-compatible PC-LAN.
- Call **800-638-8094** for a demonstration or additional information. In MD 301-590-2300.

**National Standards Association**

1200 Quince Orchard Blvd., Gaithersburg, MD 20878

Circle Reader Action No. 415



# ENCORE

COMPUTER CORPORATION

**When first impressions  
must count, count on  
Encore Computer Corporation first**

## **Mission accomplished**

For thirty years, Encore computer systems have been vital to NASA's triumphs, helping transform inconceivable missions into indelible footprints on man's history.

Today, Encore is the dominant force in deterministic, real-time computing. And, as the innovator of parallelism, Encore is a step ahead with UNIX®-based, symmetric, multiprocessing technologies.

Gathering, distributing and interpreting data at lightning speeds, across the earth and beyond, Encore computer systems ensure exacting solutions to the complex demands of aerospace and defense applications.

## **All systems go**

Developed to meet the demands of time-critical, real-time environments, the CONCEPT/32® family — with a global installed base of over 8,000 systems — is the established leader in real-time performance and cost effectiveness.

Compatible with existing CONCEPT/32 applications and retaining its uncompromised real-time performance characteristics, the new Encore 90™ family delivers access to industry standards. Its breakthrough guest operating system architecture allows multiple real-time and UNIX operating systems to work together in one multiprocessing environment, and provides powerful support for open-architecture environments.

## **Countdown to liftoff**

Into the next millenium, Encore will continue to pursue the bold, system-based solutions and revolutionary technologies which have made it NASA's partner in progress for the past three decades.

So before you take a giant leap, take one small step. Call Encore at 800-933-6267 from the U.S.A. or Canada; 305-797-5742 in the U.S.A. from anywhere else in the galaxy, or write Encore Computer Corporation, MS 704, 6901 West Sunrise Boulevard, Fort Lauderdale, Florida 33313-4499, U.S.A. It will make a world of difference.

Photo courtesy of NASA



**Encore computer  
systems continue to  
provide solutions  
for many NASA  
applications.**

**Circle Reader Action No. 353**



## HOW YOU CAN BENEFIT FROM NASA'S TECHNOLOGY UTILIZATION SERVICES

If you're a regular reader of TECH BRIEFS, then you're already making use of one of the low-and-no-cost services provided by NASA's Technology Utilization (TU) Network. But a TECH BRIEFS subscription represents only a fraction of the technical information and applications/engineering services offered by the TU Network as a whole. In fact, when all of the components of NASA's Technology Utilization Network are considered, TECH BRIEFS represents the proverbial tip of the iceberg.

We've outlined below NASA's TU Network—named the participants, described their services, and listed the individuals you can contact for more information relating to your specific needs. We encourage you to make use of the information, access, and applications services offered by NASA's Technology Utilization Network.

### How You Can Utilize NASA's Industrial Applications Centers—A nationwide network offering a broad range of technical services, including computerized access to over 100 million documents worldwide.

You can contact NASA's network of Industrial Applications Centers (IACs) for assistance in solving a specific technical problem or meeting your information needs. The "user friendly" IACs are staffed by technology transfer experts who provide computerized information retrieval from one of the world's largest banks of technical data. Nearly 500 computerized data bases, ranging from NASA's own data base to Chemical Abstracts and INSPEC, are accessible through the ten IACs located throughout the nation. The IACs also offer technical consultation services and/or linkage with other experts in the field. You can obtain more information about these services by calling or writing the nearest IAC. User fees are charged for IAC information services.

#### **Aerospace Research Center (ARAC)** Indianapolis Center for Advanced Research

611 N. Capitol Avenue  
Indianapolis, IN 46204  
Dr. F. Timothy Janis, Director  
(317) 262-5036

#### **Central Industrial Applications Center/NASA (CIAC)**

**Rural Enterprises, Inc.**  
Post Office Box 1335  
Durant, OK 74702  
Dr. Dickie Deel, Director  
(405) 924-5094  
(800) 658-2823 (toll-free U.S.)

#### **Science and Technology Research Center (STRC)** Post Office Box 12235

Research Triangle Park,  
NC 27709-2235  
H.L. (Lynn) Reese, Director  
(919) 549-0671

#### **NASA Industrial Applications Ctr.** 823 William Pitt Union University of Pittsburgh Pittsburgh, PA 15260

Lani Hummel  
Executive Director  
(412) 648-7000

#### **Southern Technology Applications Center (STAC)** Post Office Box 24 Progress Ctr., One Progress Blvd Alachua, FL 32615

J. Ronald Thornton, Director  
(904) 462-3913  
(800) 354-4832 (FL only)  
(800) 225-0308 (toll-free US)

#### **NASA/UK Technology Applications Center** University of Kentucky

109 Kinkead Hall  
Lexington, KY 40506-0057  
William R. Strong, Director  
(606) 257-6322

#### **NERAC, Inc.** One Technology Drive Tolland, CT 06084 Dr. Daniel U. Wilde, President (203) 872-7000

#### **Technology Application Center (TAC)** University of New Mexico Albuquerque, NM 87131 Dr. Stanley A. Morain, Director (505) 277-3622

#### **NASA Industrial Applications Center** University of Southern California

Research Annex  
3716 South Hope Street  
Los Angeles, CA 90007-4344  
Robert Stark, Director  
(213) 743-6132

(800) 642-2872 (CA only)  
(800) 872-7477 (toll-free US)

#### **NASA/SU Industrial Applications Center**

Southern University Department of Computer Science  
Post Office Box 9737  
Baton Rouge, LA 70813-9737  
Dr. John Hubbell, Director  
(504) 771-6272  
(504) 771-4950

If you represent a public sector organization with a particular need, you can contact NASA's Application Team for technology matching and problem solving assistance. Staffed by professional engineers from a variety of disciplines, the Application Team works with public sector organizations to identify and solve critical problems with existing NASA technology. **Technology Application Team, Research Triangle Institute, P.O. Box 12194, Research Triangle Park, NC 27709; Dr. Doris Rouse, Director, (919) 541-6980**

### How You Can Access Technology Transfer Services At NASA Field Centers: **Technology Utilization Officers & Patent Counsels**—Each NASA Field Center has a Technology Utilization Officer (TUO) and a Patent Counsel to facilitate technology transfer between NASA and the private sector.

If you need further information about new technologies presented in NASA Tech Briefs, request the Technical Support Package (TSP). If a TSP is not available, you can contact the Technology Utilization Officer at the NASA Field Center that sponsored the research. He can arrange for assistance in applying the technology by putting you in touch with the people who developed it. If you want information about the patent status of a technology or are interested in licensing a NASA invention, contact the Patent Counsel at the NASA Field Center that sponsored the research. Refer to the NASA reference number at the end of the Tech Brief.

#### **Ames Research Ctr.** Technology Utilization

Officer: Geoffrey S. Lee  
Mail Code 223-3  
Moffett Field, CA 94035  
(415) 604-4044  
Patent Counsel:  
Darrell G. Brekke  
Mail Code 200-11  
Moffett Field, CA 94035  
(415) 604-5104

#### **Lewis Research Center**

Technology Utilization  
Officer: Anthony F.  
Ratajczak  
Mail Stop 7-3  
21000 Brookpark Road  
Cleveland, OH 44135  
(216) 433-2225  
Patent Counsel:  
Gene E. Shook  
Mail Code LE-LAW  
21000 Brookpark Road  
Cleveland, OH 44135  
(216) 433-5753

#### **John C. Stennis Space Center**

Technology Utilization  
Officer: Richard A.  
Galle (acting)  
Code HA-32  
Stennis Space Center,  
MS 39529  
(601) 688-1929

#### **John F. Kennedy Space Center**

Technology Utilization  
Officer: Thomas M.  
Hammond  
Mail Stop PT-PMO-A  
Kennedy Space  
Center, FL 32899  
(407) 867-3017  
Patent Counsel:  
James D. Harrell  
Mail Code PT-PAT  
Kennedy Space  
Center, FL 32899  
(407) 867-2544

#### **Langley Research Ctr.**

Technology Utilization  
Officer: Joseph J. Mathis Jr.  
Deputy Head, TU Office  
Mail Stop 139A  
Hampton, VA 23665  
(804) 864-2484  
Patent Counsel:  
George F. Helfrich  
Mail Code 279  
Hampton, VA 23665  
(804) 864-3523

#### **Goddard Space Flight Center**

Technology Utilization  
Officer: Donald S.  
Friedman  
Mail Code 702.1  
Greenbelt, MD 20771  
(301) 286-6242  
Patent Counsel:  
R. Dennis Marchant  
Mail Code 204  
Greenbelt, MD 20771  
(301) 286-7351

#### **Jet Propulsion Lab.**

NASA Resident Office  
Technology Utilization  
Officer: Arif Husain  
Mail Stop 180-801  
4800 Oak Grove Drive  
Pasadena, CA 91109  
(818) 354-4862  
Patent Counsel:  
Thomas H. Jones  
Mail Code 180-801  
4800 Oak Grove Drive  
Pasadena, CA 91109  
(818) 354-5179  
Technology Utilization  
Mgr. for JPL: Dr. Norman L. Chaffin  
Mail Stop 156-211  
4800 Oak Grove Drive  
Pasadena, CA 91109  
(818) 354-2240

#### **George C. Marshall Space Flight Center**

Technology Utilization  
Officer: Ismail Akbay  
Code AT01  
Marshall Space Flight  
Center,  
AL 35812  
(205) 544-2223  
Fax (205) 544-3151  
Patent Counsel:  
Bill Sheehan  
Mail Code CC01  
Marshall Space Flight  
Center,  
AL 35812  
(205) 544-0021


#### **Lyndon B. Johnson Space Center**

Technology Utilization  
Officer: Dean C. Glenn  
Mail Code IC-4  
Houston, TX 77058  
(713) 483-3809  
Patent Counsel:  
Edward K. Fein  
Mail Code AL3  
Houston, TX 77058  
(713) 483-4871  
**NASA Headquarters**  
Technology Utilization  
Officer: Leonard A. Ault  
Code CU  
Washington, DC 20546  
(202) 557-5598  
Assistant General  
Counsel for Patent  
Matters: Robert F.  
Kempf, Code GP  
Washington, DC 20546  
(703) 557-5598

**A Shortcut To Software: COSMIC**—For software developed with NASA funding, contact COSMIC, NASA's Computer Software Management and Information Center. New and updated programs are announced in the Computer Programs section. COSMIC publishes an annual software catalog. For more information call or write: **COSMIC**, 382 East Broad Street, Athens, GA 30602 *John A. Gibson, Dir., (404) 542-3265.*

**If You Have a Question..NASA Scientific & Technical Information Facility** can answer questions about NASA's Technology Utilization Network and its services and documents. The STI staff supplies documents and provides referrals. Call, write or use the feedback card in this issue to contact: **NASA Scientific and Technical Information Facility**, Technology Utilization Office, P.O. Box 8757, Baltimore, MD 21240-0757. *Walter M. Heiland, Manager, (301) 859-5300, Ext. 245.*

# In college, you would have killed for MathCAD. So why aren't you calculating with it now?



100,000 engineers and scientists already let MathCAD do their calculations for them.

Now that college is far behind you, perhaps it's time you graduated from spreadsheets, calculators and programming.

Because in today's working world of engineering and science, there's no time for anything less than MathCAD. The software that lets you perform engineering and scientific calculations in a way that's faster, more natural, and less error-prone than any calculator, spreadsheet, or program you could

write yourself.

Thanks to MathCAD's live document interface,<sup>™</sup> you can enter equations anywhere on the screen, add text to support your work, and graph the results.



March 14, 1989 issue. Best of '88 Best of '87

It also comes complete with over 120 commonly used functions built right in. Perfect for creating complex equations and

formulas, as well as exponentials, differentials, cubic splines, FFTs and matrices.

You get three-dimensional plotting, vivid graphing, and the ability to import HPGL files from most popular CAD programs, including AutoCAD.<sup>®</sup>

Done calculating? MathCAD prints *all* your analyses in presentation-quality documents, even on PostScript<sup>®</sup> compatible printers.

All of which has made MathCAD far and away the best-selling math software in the world. In fact, it's used by over 100,000 engineers and scientists — just like you.

There's MathCAD for the PC. MathCAD for the Mac, written to

take full advantage of the Macintosh<sup>®</sup> interface. And a Unix<sup>®</sup> version that utilizes the speed and unlimited memory of your Unix workstation.

We also have Applications Packs for Advanced Math, Statistics, Mechanical, Chemical, and Electrical Engineering. Each is a collection of adaptable mathematical models, designed to let you start solving your real world problems right away.




For a free MathCAD demo disk, or upgrade information, dial 1-800-MATHCAD (in MA, 617-577-1017). Or see your software dealer.

Available for IBM<sup>®</sup> compatibles, Macintosh computers, and Unix workstations. TM and ® signify manufacturer's trademark or registered trademark, respectively.


1-800-MATHCAD

# MathCAD<sup>®</sup>

MathSoft, Inc., 201 Broadway, Cambridge, MA 02139



MathCAD 2.5 includes 3-D plotting, HPGL sketch import, and PostScript output.



# Electronic Components and Circuits

## Hardware, Techniques, and Processes

- 16 V-Grooved GaAs Solar Cell
- 18 Semiconductor Laser With Multilayer Dielectric Reflector
- 20 Optical Backplane Interconnection

### V-Grooved GaAs Solar Cell

Greater optical coupling provides more conversion of light to electricity.

Lewis Research Center, Cleveland, Ohio

V-grooved GaAs solar photovoltaic cells promise increased optical coupling and, consequently, greater conversion of light into electricity, in comparison with planar GaAs cells. The V-groove geometry (see Figure 1) increases both the trapping of incident light and the lengths of optical paths in the cell material. The net effect is an increase in total absorptivity, tolerance to damage by energetic particles, and short-circuit current. These improvements are expected to follow from similar improvements obtained in silicon solar cells during recent years.

The fabrication of a typical experimental cell of the new type began with the selection of a (100) n<sup>+</sup>-type wafer of GaAs with a carrier concentration of  $2.8 \times 10^{18} \text{ cm}^{-3}$ . The wafer was baked in a horizontal, cold-wall, sub-atmospheric-pressure metal-organic chemical-vapor-deposition (MOCVD) reactor in an atmosphere of H<sub>2</sub> and AsH<sub>3</sub>. A thin buffer layer followed by a 4.5- $\mu\text{m}$ -thick epitaxial base layer with n doping of  $2.1 \times 10^{17} \text{ cm}^{-3}$  was then grown. The growth temperature was 620 °C, the

ratio of the number density of atoms of arsenic to that of gallium was 46, the dopant was a mixture of 500 parts per million of hydrogen sulfide in ultra-high-purity hydrogen, and the pressure in the chamber was 100 torr (133 kPa).

The V-groove pattern was established on the n base epilayer by masking the surface with a photoresist pattern of parallel lines 4  $\mu\text{m}$  wide and spaces 3  $\mu\text{m}$  wide, aligned along the (01 $\bar{1}$ ) axis. The grooves were then formed by anisotropic etching for 150 s at 24 °C in a solution of H<sub>2</sub>SO<sub>4</sub>:H<sub>2</sub>O<sub>2</sub>:H<sub>2</sub>O in the ratio of 5:1:1.

The grooved wafer was again baked in an atmosphere of H<sub>2</sub> and AsH<sub>3</sub>. The V-grooves were oriented parallel to the flow of gas, and the atmosphere and temperature for growth were resumed except that the dopant was changed to diethyl zinc. Under these conditions, the 0.1- $\mu\text{m}$ -thick p emitter layer with carrier concentration of  $4.2 \times 10^{18} \text{ cm}^{-3}$  was grown on the V-grooves. Au/Zn contacts were electron-beam-evaporated onto the p emitter, and Au/Ge/Ni contacts were deposited

similarly on the back of the substrate. An antireflection coat of Ta<sub>2</sub>O<sub>5</sub> was then applied to the grooves.

Although the thickness of the antireflection coat was not optimized in the experimental grooved cells, the short-circuit current density was 13 percent above that of comparable planar cells. The quantum efficiency of the new cells was also greater (see Figure 2).

This work was done by S. G. Bailey, G. R. Landis, D. M. Wilt, R. D. Thomas, and A. Arrison of Lewis Research Center and N. S. Fatemi of Sverdrup Technology, Inc. Further information may be found in NASA TM-101970 [N89-22177], "A V-Grooved GaAs Solar Cell."

Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. LEW-14954




Figure 1. The Grooved Photovoltaic Cell converts more of the incoming light into electricity than does a comparable planar photovoltaic cell. The increase in energy-conversion efficiency is the result of longer optical paths and greater trapping of light.




Figure 2. The Quantum Efficiencies of V-grooved and planar GaAs cells are compared.

# CUSTOMIZING YOUR WAVEFORM ANALYSIS DOESN'T TAKE A PC.

## IT JUST TAKES A LITTLE TACT.™


The company that gave you the first digital oscilloscope, the longest memory, best resolution and greatest storage capacity has gone a giant step further toward the perfect scope. All you need is a Nicolet 400 Series DSO - and TACT.™

TACT software elevates Nicolet's 400 Series DSO into the first application-specific oscilloscope. It gives you the power to say and do the right thing at the right time - to enhance the productivity of your test capabilities.

### No computer needed.

Other scopes give you waveforms. Nicolet gives you answers. Forget the PC. You don't need one. Program directly on the scope using a built-in, full-screen editor and 101-key PC-type keyboard. Creating your own custom

programs, calculations and plots has never been this fast...this simple. Time savings are dramatic as TACT's LEARN mode writes and remembers most of your programs for you. Automatically.



Perform complex data reductions. Print a complete analysis. Plot trends from previous tests. And automate pass/fail decisions. They're no problem. You just need TACT.

### BASIC language - SUPERIOR performance.

A built-in BASIC language with easy access to on-screen prompts and menus puts even more power in your hands. All scope functions, conditional testing, variable storage, custom print and plotter output capabilities are just a touch away. With TACT put waveforms in; get reliable answers out.

To simplify your testing you need two things. Nicolet...and a little TACT. Call Nicolet toll free 1-800-356-3090 for further information.

# Semiconductor Laser With Multilayer Dielectric Reflector

The reflector would increase output by reducing absorption in the substrate.

NASA's Jet Propulsion Laboratory, Pasadena, California

A multilayer dielectric reflector would be included in a proposed surface-emitting, distributed-feedback, grating semiconductor laser (e.g., a GaAlAs device). The reflector would contribute to the efficiency and output power of the laser by reducing the amount of light that enters the substrate, where it is wasted by absorption.

A device of this type includes a double-heterostructure laser bounded at both ends by passive waveguides. The passive waveguides contain grooves perpendicular to the axis of propagation. These grooves have a spatial period equal to the wavelength of the laser light and act as diffraction gratings (see Figure 1). The second-order component of diffracted light in each grating is reflected back toward the laser, thus providing feedback for the laser resonator. Two first-order components of refracted light travel perpendicularly to the grating surfaces: one outward, the other inward, toward the substrate. In prior de-

VICES of this type, most of the light in the inward-diffracted component is absorbed in the substrate, with a consequent loss of some output and efficiency.


In the proposed device, the multilayer dielectric reflector would be interposed between the substrate and the active and waveguide layers. It would reverse the propagation of light entering the substrate, returning it to the feedback and output beams. This layer would consist of 10 or more pairs of quarter-wavelength-thick sublayers of alternating higher and lower index of refraction. The reflector would be grown on the substrate before depositing the lower-cladding, active, and waveguide layers. The reflector sublayers would be made of the same materials as those of the cladding layers to preserve the epitaxial nature of subsequent growth, and would be deposited by such high-quality material-growing processes as molecular-beam epitaxy or metal/organic chemical-vapor

deposition. Other than the deposition of the reflector sublayers, no additional processing would be required beyond that required to fabricate a surface-emitting laser without the reflector. The reflector could be integrated with grating structures of several different types; for example, the gratings could be formed on the outside or the inside of the cladding layers and/or made of such other materials as InGaAsP.


Two major issues govern the selection of the indexes of refraction. One is that the reflectivity of the reflector layer increases with both the number of sublayers and the difference between the two indexes of refraction in them. Therefore, in designing a device, one can trade off the number of sublayers against the index difference while maintaining the desired reflectivity. The other is that to confine the laser electromagnetic mode to the waveguide, it is necessary to make the effective index of refraction (a function of both the index of refraction and the width) of the waveguide greater than the index of refraction of any of the reflector sublayers; this imposes an upper limit on the difference between the two indexes in the sublayers.

This work was done by Robert J. Lang of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 39 on the TSP Request Card.

This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial development should be addressed to the Patent Counsel, NASA Resident Office-JPL [see page 14]. Refer to NPO-17763.



PRIOR DESIGN (WITHOUT MULTILAYER DIELECTRIC REFLECTOR)



PROPOSED DESIGN (WITH MULTILAYER DIELECTRIC REFLECTOR)

Figure 1. The **Multilayer Dielectric Reflector** added to a surface-emitting, distributed-feedback, grating semiconductor laser would reflect light away from the substrate, thereby increasing the output.





Figure 2. The **Index of Refraction** in the reflector sublayers would alternate between a higher and a lower value. The higher value would be less than the effective index of refraction of the waveguide layer.



## NOW TEAC'S XR SERIES IS 28-CHANNELS WIDE.

Introducing the world's first 28-channel VHS data recorder. The TEAC XR-9000. Now the performance and capacity of the larger open-reel decks are available with the convenience, economy and ease of operation of VHS cassettes. All within a lightweight, minimum foot print unit.

The XR-9000 offers TEAC's exclusive menu-driven on-screen display plus numerous auto-functions to provide a simple step-by-step setup procedure. You can use your computer to remotely control the XR-9000. And recorded data from the XR-9000 can be fed directly into a computer.

It's been over a decade since TEAC introduced

the world's first VHS cassette data recorder. Since then, we've helped develop every major improvement in VHS data recording technology. Today we're building VHS data recorders from 7- to 28-channels with models available in Wide Band Groups I and II, plus interchangeable FM, Super FM DR, and PCM modules. And in an industry with little tolerance for error, TEAC's enviable record of performance and reliability is unsurpassed.

So, if you're looking for greater capacity, with the most variety of options and models, at the most efficient cost-per-channel, TEAC XR series data recorders is the only place you'll find it.

# TEAC®

Information Products Division.

©1990 TEAC AMERICA, INC. 7733 TELEGRAPH RD., MONTEBELLO, CA 90640 WEST (213) 726-0303 EAST (508) 683-8322

Circle Reader Action No. 344


# Optical Backplane Interconnection

Output and input devices would be switched by changing wavelengths.

Langley Research Center, Hampton, Virginia

The optical backplane interconnection (OBIT) is a method of optically interconnecting many parallel outputs from a data processor to many parallel inputs of other data processors by optically changing the wavelength of the output optical beam. Heretofore, most interconnections in the backplanes of data processors have been made

by electronic switch connections, and both a command and an electrical or optical connection have been required for each switch connection. For example, an optical matrix-vector switch, in which a column of optical emitters can communicate with a row of optical detectors by use of a liquid-crystal light valve placed between the emit-



A Change in Wavelength in light emitted by a laser in array 1 would cause a change in the angle of the laser beam, causing the beam to strike a different detector in array 2.

ters and detectors, requires a column and row address for each switch connection. More than one connection can be made, but each connection requires a column and a row switch address. The OBIT requires only one command: the exact wavelength necessary to make the connection between the two desired processors.

The OBIT is envisioned to have an array of outputs and inputs, such as those shown in the figure. The selection of which output is to be connected to which input would be made by use of a wavelength that undergoes a particular angle of deflection. The method and means for generating and selecting a given wavelength is provided by an opto-electronic integrated circuit (not shown) that is part of the overall design. The array control would basically select the wavelengths by which the processors could communicate. In addition, it could be possible, depending upon the design configuration, to have one laser/detector array emit more than one wavelength and communicate with an adjacent array in more than one location simultaneously.

The limits to the numbers of rows and columns of the arrays would depend on the limits on the change in the angle of deflection caused by a change in wavelength when the emitting beam is passed through a diffraction-grating or other optical deflector. The limits would be a function of the properties of the gratings and the ability to shift wavelengths in the lasers or other sources of light. The numbers of parallel interconnections that could be made would be limited by the loss mechanisms in the coupling scheme and the availability of optical amplification.

One of the materials from groups III and V of the periodic table of the elements, probably GaAs/AlGaAs or InP/InGaAs/InGaAsP, would be the medium for fabrication of the integrated optical structure. An approximate physical model of the device was implemented with fiber-optic couplers, lasers of different wavelengths, and a diffraction grating. Many features, including smallness, would make it advantageous to incorporate an OBIT (as opposed to an electrical or matrix-vector optical switching device) into an integrated optical device. The OBIT technique would simplify or eliminate wiring and would speed the transfer of data over existing electrical or optical interconnections. Computer hookups and fiber-optical communication networks would benefit from this concept.

This work was done by Herbert D. Hendricks of Langley Research Center. For further information, Circle 50 on the TSP Request Card. LAR-14052


## Off-The-Shelf. And Right On The Money.

When you need precision solutions to tough design problems, you can get them right away from Parker Metal Bellows. And you don't have to break the bank to do it.


Parker off-the-shelf welded diaphragm metal bellows, flexible shaft couplings, compressors and vacuum pumps have proven themselves time and time again.

And because dozens of these precision-crafted products are available off-the-shelf and in a wide variety of sizes, configurations and capacities, they are as cost-effective as they are convenient.

Get the precision solutions you need right now, and at the right price. Call, write or fax today for the FREE Parker Metal Bellows Off-The-Shelf Product Catalog and Specification Guide.



Parker Metal Bellows  
Sharon Division, Parker Berteau Aerospace  
1075 Providence Highway, Sharon, MA 02067  
Phone (617) 784-1400. Fax (617) 784-1405.



# The programmable display system:

The computer interface with the pushbutton feel.

Vivisun Series 2000, now the leading programmable display pushbutton system, interfaces the operator with the host computer. The user-friendly LED dot-matrix displays can display any graphics or alpha-numeric and are available in green, red or amber. They can efficiently guide the operator through any complex sequence with no errors and no wasted time.

They also simplify operator training as well as control panel design. One Vivisun Series 2000

programmable display system can do the work of 50 or more dedicated switches. In short, Vivisun Series 2000 gives the design engineer more control over the design.


Contact us today.



## AEROSPACE OPTICS INC.

3201 Sandy Lane, Fort Worth, Texas 76112  
(817) 451-1141 • Telex 75-8461 • Fax (817) 654-3405

*Vivisun Series 2000  
programmable displays. The intelligent  
communications system.*



SERIES

# VIVISUN 2000™

Circle Reader Action No. 309



## Electronic Systems

### Hardware, Techniques, and Processes

- 22 Algorithmically Specialized Parallel Architecture for Robotics
- 24 Neural Networks of VLSI Components

- 26 Simplified Learning Scheme for Analog Neural Network
- 28 Quad-Port Transceivers for a Dual-CRR LAN
- 30 Self-Testing Static Random-Access Memory

### Books and Reports

- 31 Experiments in Multi-variable Adaptive Control of a Flexible Structure
- 32 Displaying Computer Simulations of Physical Phenomena

## Algorithmically Specialized Parallel Architecture for Robotics

The system is an MIMD-SIMD parallel architecture capable of exploiting parallelism in different forms and at several computational levels.

*NASA's Jet Propulsion Laboratory, Pasadena, California*

A computing system called the Robot Mathematics Processor (RMP) contains a large number of processor elements (PE's) connected in various parallel and serial combinations that are reconfigurable via software. The RMP is a special-purpose architecture designed for solving diverse computational problems in robot control, simulation, trajectory generation, workspace analysis, and the like. It is an algorithmically specialized parallel architecture capable of exploiting the common properties of the parallel algorithms developed for this class of problems. It can exploit parallelism in different forms and at several computational levels in these computation-intensive applications.

From the perspective of interaction with other computing equipment, the system can be regarded as a processor that can be attached to the bus of the external host as a part of bus memory. The system interacts with the external host processor(s) controlled by the user(s). The external host processor can be any stand-alone computer or a bus-oriented multiprocessor system. The data and instructions from the external host to the RMP and the results from the RMP to the external host are communicated through a dual-access shared memory that is part of the bus memory. The RMP is activated by a procedure call from the external host, which is executed via a "write" operation in a designated address and is interpreted as an "interrupt" by the RMP. This memory mapping scheme provides maximum flexibility and speed inasmuch as the data-transfer rate is limited by the read/write cycle of the external host. A bus adaptor provides the required interface for different buses.


The system (see figure) contains a general-purpose processor, which is called the internal host, and  $n$  single-instruction multiple-data (SIMD) parallel processors, which are called "cells." The host processor is the control unit of the system: it handles the interface with the external host, controls the activities of the cells, and performs the required input/output operations. It also handles the serial and data-

dependent computation. The ensemble of cells performs parallel computation. By using two synchronization mechanisms, the ensemble can perform parallel computation in different combinations of multiple-instruction multiple-data (MIMD) and SIMD modes. The first mechanism is a global clock-based one similar to systolic arrays. The cells are driven by a common clock that allows the ensemble to perform parallel computation in a two-level SIMD/SIMD mode. The second mechanism is a local data-driven one similar to wave front arrays that allows each cell to operate asynchronously and the ensemble to perform parallel computation in a two-level MIMD/SIMD mode.

The major advantage of the system lies in the design of the cells, which provides flexibility and reconfigurability superior to those of previous SIMD processors. Each cell contains six processor elements (PE's), which are simple floating-point processors capable of performing such primitive operations as multiplication, addition, and the like. Each PE has a three-bus architecture

with an internal data path that enables such accumulative operations as sum-of-product and Newton-Raphson iterations for performing division. Two table lookup units (TLU's) provide the seed values for initiating the division operations by Newton-Raphson method. They are also used for trigonometric-functions evaluation.

Basically, the PE's are organized in two groups, each containing three PE's. In solving problems for robot control and simulation, the two groups can perform two basic (matrix-vector) operations in parallel, while each group can exploit parallelism in the operation. Also, each group can be considered as an independent SIMD subsystem or a pipeline stage, making it possible to decompose the whole system into two independent MIMD-SIMD parallel architectures or two  $n$ -stage pipes. The cell control mechanism is designed to provide such flexibility and reconfigurability while also minimizing the instruction length and complexity. Each cell has three control units: one master control unit (or microcontroller) and two slave control units (or nanocontrollers). The master control unit controls the overall activities of the cell and provides the instruc-



The ARASH-URCH is a flexible parallel processing system that is reconfigurable via software. It is designed to exploit parallelism to a high degree to speed computations in robotic and image-processing applications.

# Open World, Open Database

*McDonnell Douglas selects truly open database to support NASA Space Station effort.*



In a NASA support environment, you have to be flexible enough to work on many types of computer systems. These include VAX, IBM and UNIX-based systems.

That's one reason why McDonnell Douglas Space Systems Company chose ORACLE as its Space Station database solution.

No database provides more choices and is more open. It runs on virtually every PC, mini and mainframe, regardless of operating system, software or network.

Because the Space Station program is truly an integrated, long-term, nationwide effort, it is information intensive. McDonnell Douglas uses ORACLE to capture, store, organize and share approximately a gigabyte of vital Space Station design information.

ORACLE's ability to handle massive amounts of data is unmatched. Flexible sorts and selection of specific data groups become easy. And straightforward command procedures accelerate data comparison and manipulation.

Equally important, a wide variety of Oracle software tools can be mixed and matched as needed without compatibility problems.

Oracle Corporation is proud to play an important role in the structural development of the Space Station. A truly open database is helping to open a universe of possibilities.

To find out more about Oracle, call 1-800-633-0584, ext. 6727. Authorized ADP Schedule Price List Contract No. GS00K 88 AGS 5937.

And begin your immediate ascent to new technological heights.

**ORACLE®**  
FEDERAL DIVISION

Compatibility • Portability • Connectability

tions to be executed by all the PE's. Each slave control unit performs the read/write operations for one group of PE's. The slave control units are run by a clock twice faster than that of the master control unit. This allows a complete overlapping of the read/write and arithmetic operations. In addition, data can be fed to the PE's with adequate speed while also reducing the memory architecture complexity.

The direct path among the PE's of each

group enables a linear interconnection among them. A multiplexer is used to provide other topologies among the PE's of each cell. Under the control of the master control unit, the multiplexer can establish a ring topology for each group, or a ring topology among all PE's of the cell, or a linear topology among all PE's of the cell. The latter case is used to transform the whole system into a uniform "pipe."

This work was done by Amir Fijany and

Antal K. Bejczy of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 13 on the TSP Request Card.

This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial development should be addressed to the Patent Counsel, NASA Resident Office — JPL [see page 14]. Refer to NPO-17632.

## Neural Networks of VLSI Components

"Building-block" electronic circuits would be assembled into analog/digital parallel-processing networks.

NASA's Jet Propulsion Laboratory, Pasadena, California

A concept for the design of an electronic neural network calls for the assembly of very-large-scale integrated (VLSI) circuits of a few standard types. Each VLSI chip, which would contain both analog and digital circuitry, would be used in modular or "building-block" fashion by interconnecting it in any of a variety of ways with other chips. Depending on the specific modular components and connection pattern selected to represent the input, output, and hidden (intermediate between input and output) layers of neurons, the assembly could be made to perform a specified feed-forward and/or feedback neural-network function in which the neurons in each layer would process data signals concurrently (in parallel).

Figure 1 illustrates a generic feedforward neural network operating under the control of a host digital computer. A small-computer-system-interface (SCSI) bus would be used to transfer all network weight (that is, synaptic-connection-strength), input, and output values between the host computer and the neural network. In addition, inputs to and outputs from the network could be switched directly to signal lines associated with an application.

Digital weight and input values from the host computer would be converted to analog signals that would be stored in capacitors on the VLSI circuit chips. Because an analog-to-digital converter typically requires much space on a VLSI chip, space would be saved by the use of only one off-chip, a highly precise analog-to-digital converter multiplexed in time to serially refresh all the capacitor charges on one chip. A disadvantage of this approach — that the analog weight signals would be quantized by the lengths of the digital words and the precision of the analog-to-digital converter — would be more than compensated by the ease with which the weights could be manipulated by the host computer.

A neural network for a typical application might contain as many as 1,000 neurons in the input layer and smaller num-

bers of neurons in the hidden and output layers. Such a network might be used to process images, for example. The network illustrated in Figure 2 would contain custom-designed complementary metal oxide/semiconductor mixed analog/digital circuits of three types. Input signals would be fed to the network via multiplexing input neuron chips that would store and buffer the input voltages. Hidden- and output-layer neurons would be implemented by variable-gain neuron chips that would apply variable-slope sigmoidal activation functions to the sums of signals coming

from the previous synaptic layer. Each connection (synapse) chip would have 32 summed outputs that would be fully connected to 32 inputs, for a total of 1,024 on-chip synapse cells. Inputs and outputs could be directly connected to other synapse chips to obtain larger synaptic layers. Downloading interface circuits would store weights and input values in digital form and would periodically update the charges on the appropriate storage capacitors.

This work was done by Silvio P. Eberhardt of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 129 on the TSP Request Card. NPO-17833




Figure 1. A Feedforward Neural Network in a typical situation would operate under the control of a host computer and would receive inputs from, and send outputs to, other equipment.





Figure 2. Modular VLSI "Building-Block" circuits would be assembled into a neural network.

THE MATHWORKS INTRODUCES

# SIMULAB™

## Block Diagram Software for Nonlinear Simulation of Dynamic Systems



(Top) Use the Scope block to see the "real-time" response of this F-14 model during the simulation; (Center) Specify simulation parameters via dialog boxes or the MATLAB command line; (Bottom) SIMULAB takes full advantage of the X/Motif and Macintosh windowing systems.

The  
**MATH  
WORKS**  
Inc.

Cochituate Place  
24 Prime Park Way, Natick, MA 01760  
Tel: (508) 653-1415  
Fax: (508) 653-2997  
Telex: 910-240-5521  
Email: info@mathworks.com

**I**ntroducing SIMULAB, the next generation software for modelling, analyzing, and simulating nonlinear systems. SIMULAB delivers a combination of flexibility, ease of use, and speed in a single package.

- A complete set of tools for constructing and analyzing models of dynamic systems, including linear, nonlinear, discrete, continuous, and hybrid systems.
- The ability to describe models either in Block Diagram form or as sets of differential equations.
- A design, analysis, and simulation environment that is seamlessly integrated with MATLAB™ and the MATLAB Toolboxes.
- An intuitive graphical user interface based on the industry-standard X Window/Motif and Macintosh windowing systems.

Circle Reader Action No. 503

SIMULAB provides you with the tools for constructing and analyzing block diagram models interactively using a mouse and pull-down menus. You can explore the behavior of systems during a simulation and interactively see how the model's behavior changes as you change its parameters.

SIMULAB includes a comprehensive set of built-in blocks for creating models. In addition, SIMULAB lets you extend its functionality by creating your own tools. Customize built-in SIMULAB blocks or create your own as C, Fortran, or MATLAB code. SIMULAB delivers the flexibility to meet your needs.

SIMULAB is available for a wide range of computers, including UNIX workstations and the Apple Macintosh. For more information on how SIMULAB can address your applications, contact The MathWorks today for a free information packet.

# Simplified Learning Scheme for Analog Neural Network

Synaptic connections are adjusted one at a time in small increments.

NASA's Jet Propulsion Laboratory, Pasadena, California

A simplified gradient-descent learning scheme for an electronic neural-network processor is less efficient than the better-known back-propagation scheme is, but offers two advantages: (1) it is easily implemented in circuitry because the data-access circuitry is separated from the learning circuitry; (2) the independence of the data-access circuitry makes it possible to implement feedforward as well as feedback networks, including those of the multiple-attractor type. [The output vector of a multiple-attractor network tends to remain at one of a multiplicity of equilibrium points (the attractors) until the input changes enough to push the output to another equilibrium point.] Multiple-attractor networks are important in such applications as the recognition of patterns.

Figure 1 illustrates a simple neural network that includes an input layer, an output layer, and a middle (hidden) layer of neurons. Each neuron is represented as an analog amplifier circuit, the output of which is a non-linear function (called the "activation function") of its input. The input and output terminals of all the neurons are connected to each other by a matrix of resistors that represent synapses. The matrix includes both feedforward and feedback synapses. The strength of each synaptic connection is adjusted by varying its conductance; where no connection is desired (e.g., no feedforward or feedback along a specific path), the conductance is set to zero.

To initiate the learning process, an input vector of stimuli is fed to the input neurons, and the resulting vector,  $\mathbf{o}$ , of responses of output neurons is measured and compared with the desired response or target vector,  $\mathbf{t}$ . The conductance of one of the synaptic connections is then changed temporarily by a small amount, and the effect on  $\mathbf{o}$  is observed. Thus, the gradient is directly and experimentally determined. If the change causes  $\mathbf{o}$  to move toward (or away from)  $\mathbf{t}$ , then the conductance of that connection is changed in the same (or the opposite, respectively) direction as that of the temporary change, by a small amount related to the error between  $\mathbf{o}$  and  $\mathbf{t}$ . If the temporary change causes no change in the output, then the connection is allowed to remain at its original strength. This procedure is repeated, one synapse at a time, until the entire synaptic matrix has been updated. The procedure for the entire matrix may have to be repeated many times for each stimulus/response pair until the network has learned the entire set of correct responses.

Figure 2 is a simplified schematic diagram of the learning circuitry of a synaptic matrix. Each synapse includes a third terminal for the modification of its connection

Figure 1. This **Simple Neural Network** includes a synaptic matrix of resistors that are to be updated in a learning process.





Figure 2. This **Learning Subsystem** semipermanently adjusts the resistances of a synaptic matrix like that of Figure 1, in response to changes in the output error of the neural network that occur when those resistances are temporarily changed by small amounts.



strength. An electronic programming switch can be closed to connect each synapse to the update line. The learning controller consists of circuitry that updates each synapse in turn by closing its programming switch (via the row- and column-selecting lines), changes the conductance of the synapse slightly, and evaluates the effect of the change.

This work was done by Silvio P. Eberhardt of Caltech for NASA's Jet Propulsion Lab-

oratory. For further information, Circle 154 on the TSP Request Card.

This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial development should be addressed to the Patent Counsel, NASA Resident Office-JPL [see page 14]. Refer to NPO-17664.

# SUPER CIRCUIT BOARDS FROM HITACHI CHEMICAL, OF COURSE.

## INSULATED WIRES

Insulated 0.1mm (4 mil) diameter copper wires are routinely used for high wiring densities.

## OVERLAY

A cover layer of epoxy glass cloth is used to encapsulate the board and to securely affix the wires in place.

## ADHESIVE + UNDERLAY


The wires are securely bonded to an adhesive material, and additionally insulated from the format board with underlay pre-preg material.

## THROUGH HOLE PLATING

Copper plated through holes interconnect each wire both mechanically as well as electrically to inner layer power and ground planes.

## INNER LAYER FORMAT BOARD

Multilayer format board can be used for power and ground sources.



## PADS

Electroplated pad configurations are used for surface mount technology.

## WIRE CROSSOVER

Polyimide insulated wires having a dielectric break down voltage greater than 500VDC permit crossover wiring.

## BASIC GRID 2.54 mm (0.1 inch)

Basic grid is standard at 2.54 mm (0.100 inch), however, 1.91 mm (0.075 inch) and 1.27 mm (0.050 inch) are also possible.

## 3 WIRES BETWEEN IC PINS & DIAGONAL WIRING

Concurrent wire routing can easily accommodate 3 wires between IC pins plus diagonal wiring to minimize crosstalk.

## GLASS EPOXY BASE MATERIAL

Base material is an epoxy glass cloth FR-4 material. Plating catalysts are impregnated within the material to insure good platability.

Smaller Denser Faster. This is Super Circuit sophistication at its finest, and is a prime reason you should consider SMT combined with Multiwire® Interconnection Technology. In this day of higher density silicon chip integration and higher speeds, circuit boards need to become an active extension of the component. Multiwire Boards (MWB®) are the next logical step. Using uniform 0.1mm diameter insulated copper wire for signal interconnection, MWB can routinely accommodate super high wiring densities and high signal speeds. This allows transmission line performance characteristics while offering critical wire length and precisely controlled impedance levels. Concurrent Routing, a uniquely developed wiring technique, permits a high degree of design flexibility while achieving enhanced electrical performance, especially where high signal speeds and crosstalk management are critical.

At Hitachi Chemical we offer total, one vendor responsibility to the circuit board industry, and we manufacture 100% of all materials used in our highly complex products. We are the *only* circuit board manufacturer providing 21st century products as well as producing the specialized materials to achieve these designs. Our space age interconnection technology provides clear epoxy films for improved insulation resistance, polyimide laminate boards for high heat characteristics, low dielectric laminate materials to facilitate high speed signal transfer, flexible and rigid-flex MWB, printed circuit boards, ceramic boards and multilayer boards.

So if you need super technology for your applications, turn to Hitachi Chemical, the pioneer of Super Circuit Boards and all of the materials that make them so super!



# HITACHI

Hitachi Chemical Co., Ltd.



## Hitachi Chemical Electro-Products, Inc.

Sales Offices: 3469 Lawrenceville Hwy. Suite 205 Tucker, GA 30085 (404) 938-9388  
 1800 West Park Drive Suite 305 Westborough, MA 01581 (508) 366-4092  
 4141 Blue Lake Cir. Suite 217 Dallas, TX 75234 (214) 960-9675  
 34500 Grand River Ave. Farmington Hills, MI 48024 (313) 477-2290  
 1333 Lawrence Expwy. Suite 212 Santa Clara, CA 95051 (408) 244-2570  
 2102 Business Center Dr. Suite 130 Irvine, CA 92715 (714) 253-5790

# Quad-Port Transceivers for a Dual-CRR LAN

Redundancy protects against failures.

NASA's Jet Propulsion Laboratory, Pasadena, California

Quad-port fiber-optic transceivers have been demonstrated successfully as the physical-layer interface units in the WhisperNet — a local-area network (LAN) of computers and other devices in communication with each other. The WhisperNet is arranged in a fully redundant configuration in which each quad-port transceiver communicates over four pairs of optical fibers with signals flowing as though in two sets of counterrotating rings (CRR's) (see Figure 1). The WhisperNet meets the interface specifications of the Institute of Electrical and Electronics Engineers (IEEE) Standard 802.3 and Ethernet Version 2.0.

The WhisperNet concept eliminates the need for repeaters (other than the quad-port transceivers), star couplers, and a wiring center. One WhisperNet ring is more versatile than is one segment of Ethernet coaxial cable, to which it corresponds. The quad-port transceiver performs the function of the physical layer according to the Ethernet specification, but by use of optical fiber instead of coaxial cable.

Once a terminal, computer, printer, or other device is connected to the WhisperNet, it can gain access to many other devices on the network at a speed of 10 Mb/s via virtual connections. As used here, "virtual connection" denotes a connection between two devices via the network, in which the network becomes imperceptible in that it functions as a wire between the two devices and in which different speeds, parities, flow controls, and other characteristics of ports are resolved automatically within the network.

Each quad-port transceiver contains two independent dual-port transceivers (see Figure 2), each of which serves one of the CRR's. The quad-port transceivers implement the special dual-CRR features that provide the redundancy that enables the network to tolerate multiple failures. These features are the following:

- Normally, the Ethernet message is transmitted on two CRR's (four fiber-optic rings).
- The network can survive a break in a cable (that is, an optical fiber) in one of the rings without degradation of performance.
- A single failed-node bypass does not isolate the node from the network.
- The network automatically reconfigures itself after breaks in cables on both rings, interconnecting the operating sections of both rings into a larger C-shaped ring.
- A node can be added to, or moved within, the network without causing the network to fail.

Because of its high reliability and availability and its "fail-soft" nature, the network is

well suited to military and critical commercial applications.

This work was done by Joseph A. Wiencko, Jr., and Gary R. Mangus of Fiber-Com, Inc., for NASA's Jet Propulsion Laboratory. For further information, Circle 146 on the TSP Request Card. NPO-17541

Figure 1. Each Node of the Dual-CRR LAN contains a quad-port transceiver that serves four pairs of optical fibers.







Figure 2. A Quad-Port Transceiver consists of two dual-port transceivers and ancillary equipment in a compact package. This transceiver serves as the interface between the optical fibers and the external computing devices.



**ANOTHER ASTRO-MED FIRST  
IN 8-CHANNEL RECORDERS**

# LASER PRINTER RESOLUTION!



- Laser Quality Writing—300 dpi
- 20 kHz Frequency Response
- Automatic Self-Calibration—Traceable to NBS
- Expandable to 16 Channels
- Data Capture with 200 kHz Sample Rate Per Channel
- Built-In Programmable Signal Conditioners

From its laser-sharp charts to its unparalleled frequency response, this remarkable new 8-channel recorder brings you the technology of the Twenty-First Century today! It outperforms even Astro-Med's MT-9500, which in 1987 was heralded as the first breakthrough in 8-channel recorders in 20 years. It has 50% more reso-

lution, 4 times higher frequency response, and 8 times more memory than the MT-9500. With automatic self-calibration traceable to NBS, expandability to 16 channels, and a host of other important features. We call it the MT-95000, a product so unique that it is protected by U.S. Patent No. 4,739,344.

Phone, Fax or Write for details!

**AT** **Astro-Med, Inc.**

Astro-Med Industrial Park, West Warwick Rhode Island 02893  
Telephone (401) 828-4000 • Toll Free 800-343-4039  
Telex No. 710-382-6409 • Fax (401) 822-2430

# Self-Testing Static Random-Access Memory

Errors could be detected and corrected during operation.

NASA's Jet Propulsion Laboratory, Pasadena, California


A proposed static random-access memory for a computer would feature improved error-detecting and -correcting capabilities. Unlike schemes that involve the use of Hamming codes to detect and correct errors after data have been read out of a memory, the new self-testing scheme would provide for the detection and correction of errors at any time during normal operation — even while data are being

written into the memory. Unlike in prior error-detection and -correction schemes, faults in the equipment (e.g., memory cells stuck at "one" or "zero") that may cause errors in the output data (depending on the input data) could be detected by repeatedly testing every memory cell to determine whether it can still store both "one" and "zero," without destroying the data stored in the memory.

Each cell of the memory would include a static subcell and a dynamic subcell, which would be part of a built-in comparator (see figure). Pass transistors G and G would store the true and complement values of a datum in the static subcell as charge on gates A and B of the comparator. When a datum was written into the cell, it would be stored in both subcells; then the pass transistors would be turned off so that both subcells would be isolated. The static and dynamic subcells would be continuously compared to each other by the built-in comparator. The output of the comparator would be connected to transistor H, which would normally be turned on. The output of transistor H would be connected to a signal line called the "column error signal" (CES) line shared by all memory cells in the same column. A transient fault that flipped either subcell of a memory cell in a column would thus be indicated immediately by a CES.

The memory could be made to recover from transient errors by combining the use of a parity bit with a binary search procedure. In this procedure, the H transistors in progressively narrowing groups of rows would be alternately turned on and off until a row giving rise to CES's in each column was identified. A parity check would then be performed on the faulty row to determine whether the error was caused

## BUILD TO SUIT.



### Announcing Flow Charting™ 3

Now, you can create, update and print presentation-perfect flowcharts to your specifications — in no time!

Quick to master and a snap to use, Patton & Patton's flowcharting software is the standard of both large and small businesses around the world — and is available through all major software dealers.

See your dealer today! Or, for a "live," interactive demo disk, call: **800-525-0082, ext. 2802.** International: 408-778-6557, ext. 2802.



Works on IBM & 100% compatible PC's, supports CGA/EGA/VGA and over 150 dot matrix and laser printers, with multiple print densities and 10 font sizes. **Creates multi-page charts, portrait or landscape, on most standard paper sizes.** Mouse or keyboard controlled.

IBM is a registered trademark of International Business Machines Corporation.



**PATTON & PATTON**  
Software Corporation

*Excellence in charting the flow of ideas!*



The Self-Testing Static Random-Access Memory would detect and correct both "hard" and "soft" errors at any time during normal operation—even while data are being written in or read out.

by the identified static or dynamic subcell. An error could be corrected by either reversing the datum in the faulty static subcell in the case of a parity error or by refreshing the datum in the faulty dynamic subcell where there was no parity error. The binary search would then be backtracked to detect and correct single bit errors in other rows.

This technique could correct single bit errors in any number of words in memory. In the worst case, the time needed to identify a faulty row would be proportional to  $\log_2(2N)$ , where N is the number of rows. However, backtracking would cause the average identification time to decrease with an increase in the number of faulty rows.

The search of faulty rows could be done during normal memory read/write operations because the CES lines would be independent of the data lines. When a faulty row was isolated, it would be read out, and the faulty bit indicated by the CES would be reversed immediately. This concept also provides for delayed commitment in writing a datum into a cell by temporarily separating the two inverters in the static subcell. The new datum could be loaded dynamically into only one inverter while retaining the previous datum dynamically in the other inverter. If the new datum were to prove faulty, the lower inverter could be used to restore the previous datum.

*This work was done by Savio Chau and David Rennels of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 140 on the TSP Request Card.*

## Books and Reports


These reports, studies, handbooks are available from NASA as Technical Support Packages (TSP's) when a Request Card number is cited; otherwise they are available from the National Technical Information Service.

## Experiments in Multivariable Adaptive Control of a Flexible Structure

A six-input, six-output adaptive control system is successfully demonstrated.

A report describes experiments in the use of a six-input/six-output multivariable adaptive control system to suppress vibrations in a complicated flexible structure. This represents the first time a multivariable adaptive control system of this size has ever been demonstrated experimentally on a physical structure. The structure, 18.5 ft (5.6

# FOR A TOUGH CASE GET HARDIGG



### Rotational molding.

Corners and edges are 10% to 20% thicker than flat walls, providing strength where you need it most. One piece stress-free molded lid and base.

### Molded-in tongue-in-groove gasketed parting line.

Resilient polyethylene shell returns to original configuration after impact.

### Low-profile cam-action wing-turn catches attached to molded-in metal inserts.

High strength, lightweight hardware. Replacement will not penetrate container shell.

### Recessed hardware.

Fully protected from damage.

### Positive anti-shear locks.

Prevents lid separation from base on impact. Minimizes stress on hardware.

Lightweight, MIL-SPEC off-the-shelf protection against shock, vibration, moisture, temperature extremes.



**HARDIGG INDUSTRIES, INC.**  
HARDIGG CONTAINERS

393 No. Main Street, P.O. Box 201, South Deerfield, MA 01373 (413) 665-2163 FAX: (413) 665-8061

Circle Reader Action No. 492

*This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial develop-*

*ment should be addressed to the Patent Counsel, NASA Resident Office-JPL [see page 14]. Refer to NPO-17939.*

m) in diameter, resembles both an antenna and a large spider web. It includes a circular central hub connected to 12 radial ribs, and a large flexible boom that hangs below the hub. The ribs are connected together by two concentric rings of pretensioned wires that couple the circumferential motions of the ribs. This structure is intended to exhibit low modal frequencies and complicated dynamics like those of large structures in outer space. However, the conclusions drawn from this general line of research are also relevant to such applications as the active suppression of wind and earthquake vibrations in tall buildings and other large terrestrial structures.

Collocated sensor-and-actuator pairs were placed at two stations on the hub and near the inner end of each of the ribs 1, 4, 7, and 10. The hub actuators were linear force actuators that applied torque to the hub by pushing on its circumference. The hub sensors were rotary variable-differential transformers that measured the rotary vibrations of the hub. The rib actuators were solenoid-based actuators that provided torque by reacting against mounts on the

hub. The rib sensors were linear variable-differential transformers that measured circumferential displacements of the ribs.

In a previous series of experiments on the same structure, only two collocated sensor-and-actuator pairs were installed — both on the hub. In that two-input/two-output system, the dynamics of the system were thus intentionally limited to the "boom-dish" vibrational modes that could be observed and controlled from the hub. In the experiments described in this report, the six-input/six-output system added the pure "dish" vibrational modes to those that are both observable and controllable, thereby enriching the dynamics of the system and extending control authority over a larger domain of the structure.

The adaptive-control algorithm was developed to control the first 4 boom-dish modes and the first 12 dish modes of the structure as defined by a finite-element model of its dynamics. In implementing the control scheme, the researchers encountered some practical difficulties stemming from the use of a Kalman filter to process angular-position measurements into

angular vibrational speeds and from associated problems of limited computational power and sampling rates. Manual adjustment of the filter bandwidths and gain weightings proved to be necessary to provide stable closed-loop adaptive control and to optimize the adaptive performance. Nevertheless, the researchers conclude that the six-input/six-output control system represents a significant upgrade relative to the two-input/two-output system, yielding a significant improvement in spatial controllability and effective damping of a largest set of modes.

*This work was done by Che-Hang C. Ih, David S. Bayard, Asif Ahmed, and Shyh J. Wang of Caltech for NASA's Jet Propulsion Laboratory. To obtain a copy of the report, "Experiments in Multivariable Adaptive Control of a Large Flexible Structure," Circle 36 on the TSP Request Card. NPO-17846*

## Displaying Computer Simulations of Physical Phenomena

Visual, aural, tactile, and kinesthetic effects can be used to teach such physical sciences as the dynamics of fluids.

A paper discusses computer simulation as a means of experiencing and learning to understand physical phenomena. The paper covers both present simulation capabilities and the major advances expected in the near future.

Today, the flow of air about a complete aircraft can be simulated on a supercomputer, and this dynamic, three-dimensional simulation can be viewed interactively on advanced graphics workstations. The viewer can zoom into a region of the simulation or rotate the viewing position about the region to study the display in more detail. Examples in other fields can also be cited.

But although graphics workstations have improved the interface between the scientist and the computer, they have filled only a small portion of the total bandwidth available for a human to exchange information with the environment. The primary improvements have been in visualization — specifically in the quality of the picture and the speed with which it is rendered.

Research on simulated environments shows that immersion of the human in the simulation environment is much more effective than is simply displaying a picture on the video screen of a workstation. In one series of experiments, the display of the simulated environment filled the subject's entire field of view, and six-degree-of-freedom controls and voice recognition were

used. It is now technically feasible to implement many features of this more complete simulated environment.

The paper describes an ideal simulated environment and compares the state of the art with respect to the following features:

- Controls for manipulation,
- Voice input,
- Sensory feedback from the environment (sound, motion, and position),
- Spatial and color resolution,
- Frame-repetition rate,
- Field of view,
- Accuracies of simulation models, and
- Ability to highlight important features and suppress less-important ones.

The paper recommends that classrooms in universities, government, and industry be linked to advanced computing centers so that computer simulations can be integrated into the education process. Large-bandwidth transmission facilities for computer, video, and audio information of the types that will make such links possible are now being installed.

*This work was done by Val Watson of Ames Research Center. To obtain a copy of the report, "A Breakthrough for Experiencing and Understanding Simulated Physics," Circle 68 on the TSP Request Card. ARC-12502*

## What is Desktop Signal Processing all About?

- 25 to 450 MFLOPs and Beyond
  - 1.6 G bytes/sec system bandwidth
  - 8, 12 & 16 bit Analog I/O
- 32 bit Digital I/O up to 100 Mbytes/sec
  - Macintosh®, IBM® & SUN® hosts
- Extensive Signal Processing Library

**It's About Time.**



**DOLPHIN  
SCIENTIFIC**

2698 Junipero Ave, Suite 104 Long Beach, CA 90806-2124  
voice (213)988-8930 fax (213)988-8935

©1990 Dolphin Scientific, Inc. All Rights Reserved.  
All other trademarks mentioned are held by their respective companies.

## TECHNOLOGY 2000 Proceedings

Complete proceedings of all technical sessions at the first national technology transfer conference, covering the latest innovations in:

- |  |                                      |
|--|--------------------------------------|
| • artificial intelligence                  | • materials science                  |
| • computer technology                      | • optics and communications          |
| • environmental science                    | • power and energy                   |
| • life sciences                            | • robotics                           |
| • information and data management          | • sensors and measurement technology |
| • manufacturing and fabrication technology | • superconductivity                  |

**More than 90 technical papers  
in a single, bound volume!**

**Only \$50 Postpaid**

Mail check or money order to:  
Technology Utilization Foundation  
41 East 42nd Street Suite 921  
New York, NY 10017

Or Call (212) 490-3999 for Visa and Mastercard orders

# NOW THAT 10GB FITS ON AN 8MM TAPE, WHAT ARE YOU WAITING FOR?



You don't need to wait hours to change tapes.

You don't need to wait months for other storage technologies to catch up.

One 8mm tape drive will already deliver more than they promise.

It's the digital CY-8200, now with optional data compression. And you can get it exclusively from Contemporary Cybernetics Group.

With data compression, the CY-8200 can quadruple the amount of data you can load on an 8mm cassette that fits neatly in your shirt pocket. Meaning the already tremendous savings in man hours, media costs, storage and shipping are multiplied by four.

Until now, the best 8mm drive on the market stored an impressive 2.5GB per tape at speeds up to 15 MB per minute.



## True "Plug-And-Play" Compatibility With:

Alliant	DEC 3100	IBM S/36	Pertec
Alpha Micro	DEC HSC	IBM AS/400	Plexus
Altos	DEC Q-Bus	Macintosh	Prime
Apollo	DEC TU/TA81	NCR	Pyramid
Arix	DEC Unibus	Novell	Sequent
AT&T	Gould	PC 386/ix	Sun
Convergent	HP	PC MS-DOS	Unisys
Data General	IBM RT	PC Xenix/Unix	Wang
		and more...	

Our data compression option allows you to write up to 10 GB per tape at up to 60 MB per minute. Completely unattended.


Of course, the data compression feature is switch-selectable, so you can turn off data compression to read and write standard 8mm tapes.

Plus it's a simple upgrade for the best tape drive built: our CY-8200. Offering a complete range of standard

interfaces, a 2-line, 40-column display option, and optional security card encryption. And assuring you of full support and a 12-month warranty from the leader in advanced 8mm helical scan technology.

The CY-8200 with data compression will remain the best value in data storage for a long time to come. So now you've got many good reasons for calling us today at (804) 873-0900 and no good reason for waiting.

CONTEMPORARY  
**CYBERNETICS**  
*Group*



## Physical Sciences

### Hardware, Techniques, and Processes

- 34 Oscillating Thermal Switch
- 34 Airborne Laser Polarization Sensor

- 36 Optical Isolators With Transverse Magnets
- 38 Low-Thermal-Conduction Links for Silicon Sensors
- 39 Two-Wavelength Interferometric Keratometer

- 40 Statistical Partial Calibration of Polarimetric SAR Imagery
- 40 Measuring Wildfires From Aircraft and Satellites
- 41 Testing Conductive Films for Continuity

## Oscillating Thermal Switch

The transferred heat would actuate a device with no moving parts.

NASA's Jet Propulsion Laboratory, Pasadena, California

A proposed heat switch would transfer heat from a source to a sink in regular cycles. The switch is intended for use in a gas-sorption refrigerator. This type of refrigerator produces heat loads that must be connected and disconnected in precisely timed periods. The proposed heat switch, unlike those now available, would be self-sustaining; it would be actuated by the transferred heat, contain no moving parts, and need no external heaters or electronic circuitry to synchronize heat-transfer periods or control heat-transfer rates.

The proposed heat switch would contain a variable-conductance heat pipe. The heat-pipe component of the switch would transfer heat from a heat source to a heat sink when its reservoir of noncondensable gas is cold. The heat pipe would not transfer heat (i.e., would turn off) when the reservoir is hot. The pipe would alternate between on and off at a rate determined by thermal resistance and capacitance elements attached to it, to the heat sink, and to the reservoir. The thermal lags caused by the thermal resistors and capacitors would keep the variations of temperature of the heat pipe out of phase with those of the reservoir, thereby sustaining the temperature oscillations and providing regular on/off thermal switching.

At the beginning of a cycle, a relatively large volume of the noncondensable gas would separate the liquid and vapor in the heat pipe from the heat sink, decoupling the pipe thermally from the sink (see figure). In this state, thermal capacitor 1 and the gas reservoir would be transiting from hot to cold. Then energy from the heat sink

would raise the temperature of the heat pipe. The vapor in the pipe would then move into the cold end, forcing the noncondensable gas into the reservoir. Upon making contact with the cold end, the vapor would transfer heat from the source to the sink.


At this time, the thermal path to thermal capacitor 1 would be exposed to the hot liquid and vapor. Heat would flow from the pipe through thermal resistor  $R_{t1}$  into thermal capacitor 1 ( $C_{t1}$ ), raising its temperature. Heat would flow from this thermal capacitor through thermal resistor  $R_{t3}$ , raising the temperature of the reservoir and its thermal capacitor  $C_{t2}$ .  $R_{t3}$  and  $C_{t2}$  would be chosen so that the reservoir would start to heat only when the temperature of capacitor 1 approached that of the pipe.

As the reservoir is heated up, it would drive gas into the heat pipe, forcing the gas

front away from the cold end. Eventually, the front would push the vapor away from the sink, and the pipe would turn off; that is, heat would no longer flow from the pipe to the sink or to capacitor 1. Capacitor 1 would start to cool down by transferring heat through  $R_{t2}$  to the heat sink. Again,  $R_{t3}$  and  $C_{t2}$  would be large enough so that the reservoir would start to cool only when the temperature of capacitor 1 approached that of the heat sink. The system would then be in the initial condition, and the cycle would repeat. A difference of 50 °C or more between the temperatures of the source and sink should be adequate to sustain the oscillations.

This work was done by S. Walter Petrick of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 31 on the TSP Request Card. NPO-17125

When the **Gas Front** is at its far left excursion, no heat would flow from the heat pipe in the heat sink; that is, the switch would be off. When the gas front recedes to the far right, heat would flow from the pipe to the heat sink; that is, the switch would be on. The thermal resistors and thermal capacitors would produce thermal lags in heating and cooling of the gas reservoir, thereby restarting a new on/off cycle as soon as one ends.



## Airborne Laser Polarization Sensor

This instrument measures polarization characteristics of the Earth at three wavelengths.

Goddard Space Flight Center, Greenbelt, Maryland

The Airborne Laser Polarization Sensor (ALPS) measures the optical polarization characteristics of the land surface. The ALPS is designed to be flown at altitudes of

≤ 300 m to minimize any polarizing or depolarizing effects of the intervening atmosphere and to look along the nadir to minimize any effects that depend on the look

angle. The data from the measurements are used in conjunction with data from ground surveys and aircraft-mounted video recorders to refine mathematical models

# Who Knows More About Cases and Containers?

THE PEOPLE WHO BUILT THIS ONE TO CARRY A SATELLITE?

OR

THE PEOPLE WHO OFFER PRE-ENGINEERED CASES IN WHATEVER SIZE YOU NEED?



## The answer is yes.

You may have known us as Metricase, the leader in welded, ruggedized cases. Or you may have known us as Applied Design, leaders in custom containers for everything from spacecraft to spare parts. Today we are one company, Erie Engineered Products, offering you the combined experience,

knowledge and production capabilities of these two great organizations.

If you are planning one challenging container, or would just like the best value on hundreds of pre-engineered cases, please take advantage of our unique dual experience.

For a copy of our new capabilities brochure and

catalog or to talk with a fellow engineer, call (716) 694-2020. Or write Erie Engineered Products, Inc., 908 Niagara Falls Blvd., North Tonawanda, New York 14120.



# ERIE

Custom & Pre-Engineered Cases & Containers

Circle Reader Action No. 536


used in the interpretation of higher-altitude polarimetric measurements of reflected sunlight.

The ALPS (see figure) includes a pulsed neodymium:yttrium aluminum garnet laser that emits simultaneously at the fundamental, second-harmonic, and third-harmonic wavelengths of 1,064, 532, and 355 nm, respectively, at rates up to 20 Hz. The output energies per pulse are 100, 300, and 100 mJ, respectively, at the three wavelengths. The laser beam is polarized and transmitted down to the ground.

The portion of laser light that returns from the ground is received by three sets of polarization-sensitive detectors. Each set contains four detectors to obtain data that can be used to calculate the four Stokes parameters for each wavelength. (The Stokes parameters specify the relationship between the polarizations of the incident and the reflected light.) Each detector includes a photomultiplier tube, a linear polarizer, lens, and a 10-nm-band-pass filter. For each wavelength, the polarizer in one detector is oriented at 0° with respect to the polarization of the incident beam, the polarizer in another detector is oriented at 90°, and those in the two other detectors are oriented at 45°. One of the 45° units also includes a quarter-wave plate.

By integrating each return pulse over a period long enough to average together the ground and tree-top returns, one can simulate the effects of a return signal more nearly like that received by a passive solar polarization sensor. To separate the polarization effects of the layers within a tree canopy, a future version of the ALPS will be made to function in a lidar (pulsed ranging) mode, processing the return signals through 200-

The **Airborne Laser Polarization Sensor** aims a polarized laser beam at the ground and measures the polarization of the reflected light. Although the simplified version shown here schematically contains only 4 detectors, the actual system contains 12 (4 for each of 3 wavelengths).



MHz waveform digitizers.

The signals from the detectors are fed simultaneously to a 12-channel, 12-bit, charge-integrating analog-to-digital converter mounted in a CAMAC crate (a mounting unit in a standard modular instrumentation-and-digital-interface system). The digitized signals are transferred through the CAMAC crate controller (a communication unit in the CAMAC crate) to a PC-type computer. A time code is superimposed on the "ground-

truth" videotape record to enable correlation of the polarization data with data on the type of surface in view. The acquisition and analysis of data are controlled via an easy-to-use menu-driven software system.

*This work was done by James Kalshoven, Jr., and Philip Dabney of Goddard Space Flight Center. For further information, Circle 1 on the TSP Request Card. GSC-13314*

## Optical Isolators With Transverse Magnets

Large apertures are obtained in compact isolators that include readily available permanent magnets.

*Langley Research Center, Hampton, Virginia*

Progress with laser systems has stimulated a demand for an optical isolator of high quality and compact size with a large aperture. An ideal optical isolator is a device that allows total transmission of a beam in the forward direction while totally blocking transmission of the beam in the backward direction, thus preventing backward reflections from disturbing the forward signal. In a high-power laser system, the use of an isolator between an oscillator and an amplifier can protect the oscillator optics from damage by amplified backward reflection.

The commonly used type of isolator consists of a Faraday rotator, a quarter-wave plate, and a pair of polarizers. The most popular Faraday-rotation materials of high optical quality available commercially in large sizes require relatively large mag-

netic fields. The required magnetic fields can be reduced by using such high-Verdet-constant materials as garnet crystals, which have limitations on transmission range, optical quality, and size, and are not readily available. In addition, electromagnets with water-cooled solenoids are used in typical isolators to produce the large longitudinal magnetic fields required for the proper rotation, making the isolators cumbersome and very expensive.

A new design for an isolator includes a zigzag, forward-and-backward-pass beam path and use of a transverse rather than longitudinal magnetic field (see figure). These design choices produce an isolator with as large an aperture as desired using low-Verdet-constant glass rather than the more expensive crystals. This design also uses commercially available permanent

magnets in the Faraday rotator rather than the more expensive and bulky electromagnets. Thus, this isolator is more compact and less expensive than was previously possible in a large-aperture design. This isolator can also be designed to transmit a rectangular beam. The square cross section of the beam can easily be extended to a rectangular shape by increasing one dimension of the glass without having to increase the magnetic field.

A demonstration isolator of the new type, though not of optimum design, was built from available equipment. The isolator had two internal reflections in the forward zigzag pass, two reflections in the backward zigzag pass, and two reflections for the end reflector. The transverse magnet had an average field of 7 kG. Nonoptimum design produced a high transmission loss of 74

# The Road To The Future



## TECHNOLOGY 2001

The Second National Technology Transfer  
Conference and Exposition

December 3-5, 1991  
San Jose Convention Center  
San Jose, CA


Circle Number 700 for Information on Attending.  
Circle Number 703 for Information on Exhibiting.

percent. The measured isolation was 36 percent, and the output beam had good quality.

These unique properties make this optical isolator potentially very useful in laser systems involving slab lasers and amplifiers. It could also have application to the study of very-high-power lasers for fusion research.

This work was done by Yuan X. Fan and Robert L. Byer of Stanford University for Langley Research Center. For further information, Circle 23 on the TSP Request Card. LAR-14092

The Zigzag Beam-Path Design results in a smaller, less-expensive optical isolator.



## Low-Thermal-Conduction Links for Silicon Sensors

Surface etching reduces conduction and allows sturdier links.

Goddard Space Flight Center,  
Greenbelt, Maryland


A simple method of texturing the surface of silicon reduces the thermal conductivities of links in silicon x-ray calorimeters and infrared bolometers. In monolithic design, the sensor devices, thermal links, electrical leads, and mechanical supports are all part of the same silicon structure. Until now, the thermal links to the cold bath have been made long and thin or else in complicated shapes to minimize heat transferred through them from the detector to the cold bath. Such links are fragile and have low vibrational frequencies.

Now, however, a textured surface gives the links a high density of phonon scattering sites that reduce the conduction of heat. Therefore, the links can be made shorter and more robust. For 10- $\mu\text{m}$ -thick textured thermal links we measure a thermal conductance of  $2 \times 10^{-11}$  W/K. To obtain this conductance without texturing, the thermal-link thickness must be reduced to 4  $\mu\text{m}$ .

A dilute solution of the anisotropic silicon etchant ethylene diamine pyrocatechol (EDP) is applied to the thermal links to produce small, dense, randomly positioned pyramids ranging in size from about 1 to 5  $\mu\text{m}$  (see figure). The pyramid texture scatters phonons effectively. The texturing process is independent of the design of the monolithic sensor structure.

The texturing technique has been used in making x-ray calorimeters and is expected to be used soon in making infrared bolometers. It should be applicable to any microelectronic device in which a high degree of thermal isolation is needed.

This work was done by D. Brent Mott of Goddard Space Flight Center. No further documentation is available. GSC-13321



**Irregular Pyramids** form a texture on the surface of silicon. These scanning electron micrographs show two such surfaces (at 0° and 45° incidence) that were exposed to a dilute solution of EDP for 5 min at 95 °C. Sizes can be estimated by use of the 5- and 10- $\mu\text{m}$  scale lines near the tops of the photographs.

# Two-Wavelength Interferometric Keratometer

Strongly aspherical surfaces could be measured precisely.

NASA's Jet Propulsion Laboratory, Pasadena, California

A proposed interferometric keratometer would measure the shapes of corneas without touching them. The keratometer might also be used to test strongly aspherical optics. The keratometer, which would resemble present commercial lens-testing interferometers, would generate interferograms representative of the deviation of the surfaces under test from sphericity. Such interferograms can be used to generate contour maps of the surfaces. While existing instruments typically cover corneal diameters no greater than 3 mm, the proposed keratometer would measure corneal topography to diameters as large as 12 mm.

The instrument would employ visible light at two wavelengths; for example, the 0.633- $\mu\text{m}$  red light from an He-Ne laser and the 0.613- $\mu\text{m}$  orange light from another He-Ne laser. The optical train would include three off-axis paraboloidal reflectors. The first reflector would serve as a collimator. The second would form a large-aperture ( $f/1.0$ ) wave front converging on the cornea and partially recollimate the wave front reflected from the surface of the cornea, preserving the optical-path differences. The third reflector would create a quasi-spherical wave front converging onto the obstruction in a Smartt point-diffraction interferometer. (Other interferometric configurations are possible.)

The fringe pattern at the exit pupil of the keratometer would contain the interferograms at each of the two wavelengths superimposed on each other. The superposition would give rise to a beat of spatial variation in the contrast in the fringes between the two interferograms. In effect, this pattern would constitute a third, long-wavelength interferogram of the surface under test. The effective wavelength  $\lambda_{\text{eff}}$  (twice the contour depth interval represented by one fringe space) of the third interferogram would be given by

$$\lambda_{\text{eff}} = \lambda_1 \lambda_2 / (\lambda_1 - \lambda_2)$$

where  $\lambda_1$  and  $\lambda_2$  are the wavelengths of the illumination. In the case of the He-Ne-laser light mentioned previously,  $\lambda_{\text{eff}}$  would be 19.4  $\mu\text{m}$ ; thus, one fringe space would represent a depth interval of  $19.4/2 = 9.7 \mu\text{m}$ .

At the price of reduced topographic sensitivity, two-wavelength interferometry enables the measurement of surfaces more aspherical or steeply sloped than could otherwise be measured. When the effective-long-wavelength interferometric information is used to remove the  $2\pi$  ambiguities in the phases in the shorter-wavelength interferograms, the advantages of both long- and short-wavelength interferometry can be combined to measure strongly aspherical

surfaces with high topographic sensitivity.

This work was done by Eric Hochberg and Norman Page of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 85 on the TSP Request Card.


In accordance with Public Law 96-517, the contractor has elected to retain title to this invention. Inquiries concerning rights for its commercial use should be ad-

ressed to

Edward Ansell  
Director of Patents and Licensing  
Mail Stop 305-6  
California Institute of Technology  
1201 East California Boulevard  
Pasadena, CA 91125

Refer to NPO-17537, volume and number of this NASA Tech Briefs issue, and the page number.

Send for your  
free copy



Your  
Best Source  
For:

## OPTICS

Lenses  
Mirrors  
Polarizers  
Etalons  
Filters  
Prisms  
Aspheres  
Beamsplitters  
Micro Optics  
Windows

## MECHANICAL COMPONENTS

Optical Tables  
Breadboards  
Positioners  
Mirror Mounts  
Posts & Rods  
Stages  
Bases  
Rails

## INSTRUMENTS

HeNe Lasers  
CO<sub>2</sub> Lasers  
Diode Lasers  
Detectors

10,000 Products...  
Over 600 New to this Catalog!  
Use our new toll-free number  
1-800-835-2626

# MELLES GRIOT

1770 Kettering St., Irvine, CA 92714 • (714) 261-5600 • Fax: (714) 261-7589


# Statistical Partial Calibration of Polarimetric SAR Imagery

Statistical properties of the backscatter can be used to compensate for cross-polarization in the antennas.

NASA's Jet Propulsion Laboratory, Pasadena, California

A mathematical technique for the partial calibration of quadpolarization synthetic-aperture-radar (SAR) image data makes it possible to remove partially those contaminating cross-polarization effects (crosstalk) that arise in the antenna(s) and/or other transmitting and receiving channels. [Quadpolarization data are complex-number representations of the amplitudes and phases of the horizontally and vertically polarized transmitted and received (backscattered) signals and the relationships (including cross-polarization effects) between them]. Therefore, the quadpolarization data processed with the help of this technique better approximate the backscattering properties of the target area. Furthermore, if corner reflectors or other known discrete radar targets are placed in the target area, all of the data channels can be calibrated both relatively to each other and absolutely.

The technique relies on the following two major simplifying assumptions about natural radar targets: (1) the cross-polarized returns from them are reciprocal (the matrices that describe their backscattering properties are symmetrical); (2) for a given polarization of the transmitted signal, the like- and cross-polarized components of the backscatter, integrated over the areas of extended, azimuthally symmetrical targets, are not correlated with each other. The technique also relies on some linearizing approximations that are based on the following additional assumptions: (1) the transmitting and receiving crosstalk parameters are all smaller than  $-10$  dB; (2) the cross-polarized target backscatter parameter is at least 5 dB below the like-polarized target backscatter parameters, but not below the noise level; (3) the cross-cor-



The **Polarization Signature of an Ideal Trihedral Corner Reflector** has a simple form, represented by the scattering matrix

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

that can be used in the calibration of a polarimetric SAR system.

relation between the like-polarized target backscatter parameters is at least 10 dB below the smaller of them.

The equations that result from these assumptions are combined into an iterative algorithm that processes the raw quadpolarization data into approximations of the transmitting and receiving cross-polarization matrices. These matrices can then be inverted to recover an approximation of the target scattering matrix from the crosstalk-contaminated quadpolarization data.

The backscatter from a trihedral corner reflector (see figure) is describable by known equations that can be used in conjunction

with the iterative algorithm to obtain a relative polarimetric calibration of the complete transmitting, receiving, and signal-processing system. This calibration is valid at the look angle of the reflector and is nearly complete except for an ambiguity in the relative sign of the like- and cross-polarized components. If, in addition, the cross section of the reflector is known, the calibration can be made absolute in magnitude.

*This work was done by Jeffrey D. Klein of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 30 on the TSP Request Card. NPO-17888*

## Measuring Wildfires From Aircraft and Satellites

Remote sensing systems yield a wealth of data.

Ames Research Center, Moffett Field, California

Data about wildfires, collected remotely from satellites and aircraft, provides valuable information both for the management of wildfires and for research on the causes and effects of fires. Aircraft and satellite systems yield wide-area views, providing total coverage of the affected areas. Moreover, they collect data at a variety of wavelengths in the electromagnetic spectrum. The digital transmission of the data makes it easy to enhance images so that the combustion characteristics of biomass can be

identified.

A system developed for use aboard the ER-2 aircraft (see figure) includes a digital scanner that records data in 12 channels at wavelengths from 0.42 to 12.5  $\mu\text{m}$ . The data from the system have been used to correlate the characteristics of fires and fuels with reflected and emitted energies. In addition, the system transmits data to a ground station for immediate use in fighting fires.

The advanced very-high-resolution radi-


ometer (AVHRR) on the TIROS polar-orbiting satellite provides images and radiance data at 1- and 4-km resolutions. It collects data in five channels at wavelengths from 0.58 to 12.5  $\mu\text{m}$ . It gives synoptic views for regional and global monitoring of fires and for extension of the knowledge of biotic and abiotic responses of ecosystems to larger scales.

The ability to collect digitally encoded information from a multispectral scanner enables researchers to estimate gaseous

and particulate emissions from the fires. The data provide information on the temperatures of flame fronts and soils, the intensities and rates of spread of fires, the characteristics of fuels and smoke plumes, energy-release rates, and concentrations and movements of trace gases. These data can be related to the heating and cooling of soils, the loss of nutrients, and the effects on atmospheric, terrestrial, and aquatic systems.

This work was done by J. A. Brass and J. C. Arvesen of Ames Research Center, V. G. Ambrosia of TGS Technology, Inc., P. J. Riggan of the U.S. Department of Agriculture Forest Service, and J. S. Meyers of ATAC, Inc. Further information may be found in AIAA paper 87-A24933, "Aircraft and Satellite Thermographic Systems for Wildfire Mapping and Assessment."

Copies may be purchased [prepayment required] from AIAA Technical Information Service Library, 555 West 57th Street, New York, New York 10019, Telephone No. (212) 247-6500. ARC-12132



The Airborne Imaging System records data in 12 wavelength channels and sends digitized data in 2 of these channels to a station on the ground for immediate use in monitoring fires.

## Testing Conductive Films for Continuity

A noncontacting, nondestructive apparatus detects discontinuities.

NASA's Jet Propulsion Laboratory, Pasadena, California

An apparatus tests thin conductive films for continuity without touching them. The apparatus thus avoids the damage to the film and the error from contact resistance that might result from touching the film with a conventional probe.


The apparatus was developed to determine the integrity of conductive coats applied to the surfaces of dielectric materials to inhibit the accumulation of electrostatic charges. During handling, a film can become cracked, and the cracks can reduce its conductance.

A 10-keV diverging electron gun nearly uniformly irradiates the specimen of conductive film on its substrate while the edge of the specimen is connected to ground. Then a scanning platform, on which the specimen is mounted, is moved horizontally to scan a noncontacting electrostatic probe across the surface of the film (see figure).

Where the film is locally in good electrical contact with ground, it readily drains away the incident electrons, and the probe senses ground potential on the film. Where the film is locally surrounded by cracks that disconnect it from ground or where the film contains holes that expose the dielectric, the electron charge builds up, and the probe can sense a potential as great as  $-8,000$  V. The probe can thus readily identify defects.

This work was done by Philip L. Leung of Caltech for NASA's Jet Propulsion Lab-

oratory. For further information, Circle 126 on the TSP Request Card. NPO-17938



The Specimen is Irradiated with 10-keV electrons; then the noncontacting electrostatic probe scans the specimen and measures the charge on the spot directly under it.

## CLONE ANY PART QUICKLY

**repro-rubber**

**Makes exact rubber-like replicas**

Supplied in soft-pliable or medium-hard.

■ Self curing—15-20 min.

■ Odorless, non-toxic metrology grade

■ Easy to use kits ■ Deadly accurate

■ Works w/o release agent

**facsimile**  
MEASURE-IMAGE

**Makes hard plastic replicas**

Strong, exact replicas of intricate shapes.

■ Self curing—6-8 min. ■ Easy to use kits

■ Easy transfer of threads: contoured forms, gears, etc.

■ Sets up hard, like metal—sharp edges.

Clones surface finish precisely—ideal for use with optical comparator.




**INDUSTRIAL USES:**  
Casting; metalworking; plastic fabricating; fasteners; aircraft and missiles; aerospace and nuclear; automotive; sheet metal stampings; composites; investment casting; glass and modelmaking.

**FLEXBAR**

Call or write for our 300 page free catalog!

**FLEXBAR MACHINE CORP.**

250 Gibbs Road, Central Islip, NY 11722  
1-800-879-7575 • FAX: (516) 582-8487



# Materials

## Hardware, Techniques and Processes

42 Long-Lifetime Laser Materials for Effective Diode Pumping


## Books and Reports

44 Phase Transformations in Mullite-Precursor Xerogels  
45 Open-Section Composite Structural Elements

## Long-Lifetime Laser Materials for Effective Diode Pumping

Long quantum lifetimes reduce the number of diodes required to pump.

*Langley Research Center, Hampton, Virginia*



**MICROWATCHER™**

MICROWATCHER can quickly identify and record flaws like the marginal soldering of this IC pin (magnified 50 times).  
Photo of actual MICROWATCHER monitor.

### Changing The Way You Look At Things.

MICROWATCHER is the portable video microscope of the 90's and beyond, bringing simplicity to non-destructive testing and inspection, from the laboratory . . . to the production floor.

- Eliminates eye strain
- Deep focus depth
- 10x to 1000x magnification
- High-resolution images
- Compatible with image processing, archiving, printing and measuring systems

Whether you are responsible for manufacturing, quality control or laboratory quantitative testing, MICROWATCHER will change the way you look at things. For more information, FAX or call Fred Soskel:

**PHOTOVOLT™**  
Division of Seradyn, Inc.  
A Subsidiary of  
Mitsubishi Kasei Corporation  
1200 Madison Avenue,  
Indianapolis, Indiana 46225

1-800-222-5711 (Outside Indiana)  
317-266-2969 (Call collect in Indiana)  
317-266-2991 (FAX)  
**See Us At Pittsburgh Conference**  
**Booths 2700-2706**

Copyright 1990—PHOTOVOLT, MICROWATCHER

While Nd lasers have proved to be quite useful, they would be even more so if they could be pumped by laser diodes. Pumping by laser diodes has been demonstrated with such common Nd laser materials as neodymium:yttrium aluminum garnet (Nd:YAG) and Nd:YLiF<sub>4</sub>, but such materials as Nd:LaF<sub>3</sub>, Nd:NaF•9YF<sub>3</sub>, and possibly Nd:YF<sub>3</sub> could be more useful because of the long lifetimes of their upper laser energy levels.

In the more common Nd:YAG, the lifetime of the upper laser energy level is relatively short. For a pulsed solid-state laser, the number of diodes required is approximately inversely proportional to the lifetime of the upper laser energy level. Thus, if a material with an upper-laser-level lifetime twice as long as that of Nd:YAG were used, about half the number of diodes would be required. For a continuous solid-state laser, the threshold is approximately inversely proportional to the lifetime of the upper laser level. Thus, such a laser could also be improved by the use of one of the proposed materials.

Cost effectiveness is the primary advantage of the solid-state laser materials that have longer upper-laser-level lifetimes. While the costs of the proposed laser materials may be somewhat higher than those of the more common ones, the number of diodes required for pumping may be reduced by factors that range from 2 to 4. Because the cost of the diodes outweighs the cost of the laser material by perhaps two orders of magnitude, the cost would be reduced significantly.

The proposed laser materials have been neglected until now, probably because of the relatively low value of the thermal-shock parameters associated with these fluoride materials. However, benefits of the use of these materials, with their long upper-laser-level lifetimes, may more than offset this disadvantage.

*This work was done by Norman P. Barnes of Langley Research Center. No further documentation is available.*

*This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial development should be addressed to the Patent Counsel, Langley Research Center [see page 14]. Refer to LAR-13807.*

# SHIN-ETSU LAUNCHES NEW PRODUCT TO MEET MIL A-46146 TYPE III

## New High Strength RTV Silicone Provides Key Properties for Aircraft/Aerospace Market

### DATA SHOWS NEW MATERIAL 'RIGHT ON SPECS'

LOS ANGELES—According to Mr. Shibata, President of Shin-Etsu Silicones of America, Inc., "When comparing our new KE 4899 RTV to Dow's 3145 RTV on a property-for-property basis, there is no clear winner. Both materials pass the Mil Spec requirements and both are of equal caliber."

The data shows Shin-Etsu's KE 4899 RTV to meet all of the requirements of MIL A-46146 TYPE III and to compare equally with Dow Corning's 3145 RTV. Both materials are non-corrosive, high strength, low odor, one part adhesives.

### THE MATCH-UP

PROPERTY	MIL A-46146 TYPE III	SHIN-ETSU KE 4899*	DOW RTV 3145**
HARDNESS (Shore A)	25 min.	33	33
TENSILE (psi)	500 min.	780	700
ELONGATION %:	500 min.	660	675
TEAR STRENGTH (ppi):	NR	150	125
SPECIFIC GRAVITY:	NR	1.08	1.12
CORROSION ON: Brass, steel, aluminum	None	Passes	Passes
COLORS:	NR	Grey/clear	Grey/clear

\*KE4899 data as tested.  
\*\*RTV 3145 data as reported — Dow Corning USA Form No. 10-024-82

### A COMMITMENT TO RESEARCH

Shin-Etsu Chemical Co., Ltd., founded in 1926, is a leading world class manufacturer of silicones, offering over 2,800 different products serving a broad spectrum of industrial markets, worldwide. Included in these product lines are many innovative one and two-component RTV silicones, gels, greases, fluoro and fluid silicones with their own revolutionary curing systems.

At the very core of these technological accomplishments is Shin-Etsu's commitment to research. Shin-Etsu's Technical Service Center, located in Torrance, California, provides standard elastomeric testing, including physical and chemical constituents. Its small batch production includes the synthesizing of polymers and compounding them in the latest state-of-the-art mixing equipment. The facility is dedicated to researching all aspects of silicones, including synthesis, property alteration, applications, forming and working, process improvement and complete product evaluation.

LOS ANGELES—Shin-Etsu Silicones of America released the above data today, showing the actual published data of both Dow's 3145 RTV and Shin-Etsu's new KE 4899 RTV.

Based upon the direct property-for-property comparison above, it has been determined that the Shin-Etsu material is a direct challenge to Dow's 3145 RTV and should prove an excellent first or second source material. According to Mr. Tomisato, RTV Marketing Manager, "We are accepting requests for samples now."

For more information on the Shin-Etsu Silicones of America KE 4899 RTV, or to receive a sample, contact Doug Bower or John Heitler at:

#### Shin-Etsu Silicones of America

431 Amapola Avenue  
Torrance, California, 90501  
(213) 533-1101

### Industry Thrilled with New Material for High Performance Bonding and Sealing on Corrosion-Sensitive Electrical/Electronic Parts

LOS ANGELES—According to Doug Bower of Shin-Etsu Silicones of America, Inc., "We've been working on coming up with this product for a very long time. We always knew that Dow's 3145 RTV was the one we had to meet or beat. We also knew that when we introduced this product it had to be right on the money. 'Close' or 'almost' was not about to cut it. As you can see by the comparative data, our RTV KE 4899 was worth the wait."

Mr. Shibata, President of Shin-Etsu Silicones of America, believes that the introduction of their new product will have a dramatic effect on the aircraft/aerospace industry. "Let's face it," said Mr. Shibata, "Dow has an excellent product that has not only been the industry standard for years, but a product without peers. Their 3145 RTV virtually had the market all to itself. As of today, all of that has changed. Now the aircraft/aerospace industry has a choice. Now there is a second one-component RTV silicone available that is every bit as good as Dow's 3145 (RTV) and meets MIL A-46146 Type III to the letter."

## Books and Reports

These reports, studies, handbooks are available from NASA as Technical Support Packages (TSP's) when a Request Card number is cited; otherwise they are available from the National Technical Information Service.

## Phase Transformations in Mullite-Precursor Xerogels

Monophasic and diphasic xerogels transform differently under thermal treatment.

A report describes an experimental study of the phase transformations that occur in monophasic and diphasic xerogels of overall stoichiometric mullite composition during thermal treatment. Mullite ( $3\text{Al}_2\text{O}_3 \cdot 2\text{SiO}_2$ ) is valued as a refractory material because it has relatively high mechanical strength, excellent resistance to thermal shock, high resistance to creep, low density, low thermal conductivity, and stability at high temperature. This study is part of a continuing effort to develop precursor materials that can be transformed into mullite and sintered at temperatures low enough to avoid degradation of non-

mullite reinforcing fibers in the manufacture of mullite/fiber composites.

By use of the sol-gel process, the monophasic xerogel was synthesized from tetraethyl orthosilicate, and the diphasic xerogel was synthesized from a colloidal suspension of silica and boehmite [ $\text{AlO}(\text{OH})$ ]. The xerogels were subjected to various thermal treatments. The chemical and structural changes that occurred during these treatments were characterized by subjecting specimens before and after to differential thermal analysis, thermogravimetric analysis, x-ray diffraction, scanning electron microscopy, and infrared spectroscopy. Preliminary experiments on sintering behavior were also performed.

The combined results of these experiments show a sequence for the formation of mullite from the two types of xerogel. The monophasic gel crystallizes from an amorphous structure to a silicon-substituted alumina spinel at about 980 °C. The spinel phase is metastable and becomes mullite when held isothermally near the crystallization temperature. The monophasic gel yields a well-crystallized mullite with some residual amorphous phase, the amount of which is reduced by further reaction at higher temperature. The mullite formed initially is deficient in alumina. The composition shifts towards stoichiometry at higher temperatures.

The diphasic material follows a different sequence. This xerogel is initially composed of boehmite and a distinct amorphous silica phase. The boehmite decomposes to a cubic alumina spinel structure at 490 °C. There is little or no reaction between the spinel and amorphous phases. Mullite is formed by solid-state reaction between  $\alpha\text{-Al}_2\text{O}_3$  and cristobalite, which form from the spinel and amorphous phases, respectively, at 1,360 °C. The mullite is not well-crystallized initially, and residual phases remain even after heating at 1,600 °C for 6 h. Initially, the mullite is also deficient in alumina, but the composition shifts towards stoichiometry at higher temperatures. The diphasic powder can be sintered to high densities, whereas the monophasic powder is much more difficult to densify in spite of its molecular-level homogeneity.

*This work was done by Mark J. Hyatt of Lewis Research Center and Narottam P. Bansal of Case Western Reserve University. Further information may be found in NASA TM-101349 [N89-11038], "Phase Transformations in Xerogels of Mullite Composition."*

*Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. LEW-14898*

# ACSL





## THE SIMULATION SOFTWARE STANDARD FOR MODELLING/ANALYZING REAL-WORLD SYSTEM DYNAMICS

- All the Power of FORTRAN
- 75% Less Programming
- Interactive, Friendly
- Full Color Graphics
- Variety of Well-Tested Algorithms
- 17 Platforms, Micro to Supercomputer

ACSL® (the Advanced Continuous Simulation Language) is used by thousands of scientists and engineers daily for studying the behavior of nonlinear systems. Evolving from roots in the aerospace community, simulation is rapidly expanding across a broad spectrum of government, education, and industry. Why? Because of the productivities gained by understanding systems behavior *prior* to making key decisions. Simulation makes sense, and ACSL is the tool of choice by serious professionals.

### FEATURES

- \* Fully Interactive
- \* Free Format
- \* Unlimited Model Size
- \* Eigenvalues, Eigenvectors, and Jacobians
- \* Symbolic Access to all Variables
- \* Bode, Nyquist, Nichols, and Root Locus Plots
- \* Discrete State Event Finder
- \* Numerous Algorithms, Including Fehlberg, Gear's Stiff, Runge-Kutta, Fixed/Variable Step
- \* Vector/Array Capabilities
- \* Powerful Macro Utility
- \* Links to Existing FORTRAN Routines/Libraries
- \* Interfaces to MATLAB™ and Other Popular Software Tools



## Mitchell & Gauthier Associates (MGA)

73 Junction Square Drive • Concord MA 01742-3096 USA  
TEL (508) 369-5115 • FAX (508) 369-0013

## Open-Section Composite Structural Elements

Superior mechanical properties of composites may overcome the inherent instabilities of open sections.

A report describes an investigation of the manufacture and the mechanical properties of graphite-fiber/aluminum-matrix open-section structural elements; e.g., channels and angle bars. The investigation was conducted with a view toward using such elements to build lightweight, thermally stable truss structures in outer space. The same characteristics that make them attractive for that application also make them attractive for such specialized terrestrial applications as transport to, and assembly at, remote or otherwise uninviting locations.

The advantages of open-section structural elements include shapes that permit high packing density during shipment; convenient paths for routing tubes, hoses, and cables; accessibility of both inner and outer surfaces for repair; and ease of attachment of additional hardware. In addition, in comparison with closed-section structural elements (e.g., box beams and tubes), open-section elements are easier and require less equipment to fabricate, and are more amenable to automated fabrication and assembly at the remote site. The primary disadvantage of open-section structural elements is that, in comparison with closed-section structural elements, they are not as resistant to some kinds of deformation under load. In particular, bending and torsional loads tend to change the shapes of the cross sections in such a way as to make open-section elements more vulnerable to buckling.

Accordingly, one of the objectives in this investigation was to exploit the tailorable anisotropy of the composite material to strengthen the open-section elements against buckling. The general approach involves (1) aligning most of the fibers along the longitudinal axis to increase the buckling strength by increasing the longitudinal modulus of elasticity and (2) aligning some of the fibers at off-axis angles to increase the transverse modulus of elasticity, thereby increasing the resistance to changes in the shape of the cross section and further decreasing the susceptibility to buckling.

Another objective was to exploit the tailorable thermal-expansion properties of the composite material to obtain overall thermal stability. High-modulus-of-elasticity, pitch-based graphite fibers have a negative coefficient of thermal expansion along their lengths, while aluminum has a positive coefficient. By combining the two materials

in suitable proportions and fiber orientations, one can obtain a composite that has low or zero thermal expansion, at least in some temperature range. Struts made of such a material would be particularly useful in frames that support precise optical instruments.

During the investigation, four structural elements in each of three different configurations were made from unidirectional P100 graphite fibers in a matrix of 6061 aluminum. The graphite occupied about half the volume of the composite. In addition, two truss structures were made of extruded struts of aluminum reinforced with boron carbide ( $B_4C$ ) particles. Several difficulties were encountered in the fabrication of the graphite/aluminum specimens. The major difficulty was the maintenance of the required uniformity of temperature in the region undergoing deformation. The structures made of the Al/ $B_4C$  composite were fabricated with little difficulty. This material is relatively inexpensive, and structures can be made from it by conventional manufacturing processes.

*This work was done by T. A. Loftin, C. A. Smith, S. J. Raheb, and A. M. Nowitzky of DWA Composite Specialties, Inc. for Marshall Space Flight Center. To obtain a copy of the report, "Composite Structural Elements With Integral End Fittings," Circle 3 on the TSP Request Card. MFS-26112*

## Silicon Diode Temperature Sensors

Lake Shore's DT-470 series silicon diodes provide accurate, repeatable performance over a wide cryogenic temperature range (1.4K to 475K). For your FREE copy of Lake Shore's 60 page Cryogenic Sensor Reference Guide, circle the reader response card in this magazine, or call 614-891-2243.



 **LakeShore**  
CRYOTRONICS, INC.

64 E. Walnut St.  
Westerville, OH 43081 USA  
Tel: 614-891-2243 Telex: 24-5415 CROTRON WTVL  
Fax: 614-891-1392

© Lake Shore Cryotronics, Inc. 1990

Circle Reader Action No. 578

## The TIODIZE PROCESS and Titanium

*"Created for Each Other"*



- STOP GALLING
- REDUCE FRICTION
- PREVENT CORROSION
- CORRECT EMISIVITY

The TIODIZE PROCESS is an electrolytic conversion coating that produces anti-galling, wear resistant properties in titanium and its alloys with no dimensional change.

The TIODIZE PROCESS can be combined with a multitude of coatings to help solve your problems.

Contact TIODIZE for more information.

# TIODIZE®



15701 INDUSTRY LANE • HUNTINGTON BEACH, CA 92649  
(714) 898-4377 • FAX: (714) 891-7467

Celebrating  
over  
**25**  
Years

# ROTOCON

## HIGH PERFORMANCE ROTARY CONTACTS

**THERMOCOUPLES,  
RTD's, LVDT's  
STRAIN GAUGES,  
1 to 100 contacts!**



Unlike conventional slipping designs, the unique ROTOCON Sealed Mercury Rotary Contacts are low noise, low resistance, zero maintenance links between stationary and rotating components.

- Zero Electrical Noise
- Low And Stable Resistance
- Compact Size
- Zero Maintenance
- Environmentally Sealed
- Rugged And Reliable
- Unaffected By Vibration
- Mount In Any Orientation

A variety of standard and custom ROTOCON models are available to fit your mounting configuration, rotation speed, and current requirements (up to 2000 Amps!).

**"Try Before You Buy"**

**Call:  
800-837-6010  
or 608-836-7571 (FAX 608-831-0300 TELEX 754381)**



**meridian laboratory**

2415 Evergreen Road, P.O. Box 156, Middleton, WI 53562-0156

Circle Reader Action No. 377

### SPACE-SAVER

# Vertical gyro



Model VG34-0301-2  
Size: 2.25" diameter x 4.75" long

## THE SMALLEST, LIGHTWEIGHT VG IN THE WORLD

Miniature gyro gives you precise vehicle control of pitch and roll. Fully qualified. 28 VDC power. Optional input ranges. Life tested to 1000 hours.

**Applications:** Guidance and control for helicopters, target drones, missiles, torpedoes and underwater vehicles.

**Write or call:**

Humphrey, Inc., 9212 Balboa Avenue, Dept. NTB291  
San Diego, CA 92123 • Telephone (619) 565-6631  
FAX (619) 565-6873



**Humphrey Inc.**

SAN DIEGO • WICHITA  
WORLDWIDE REPRESENTATION

Circle Reader Action No. 626



## Computer Programs

- 46 Computing the Dynamics of Helicopters
- 47 YAMM—Yet Another Menu Manager

- 48 Estimating the Cost of Developing Software
- 51 General-Purpose Ada Software Packages

**COSMIC: Transferring NASA Software**

COSMIC, NASA's Computer Software Management and Information Center, distributes software developed with NASA funding to industry, other government agencies and academia.

COSMIC's inventory is updated regularly; new programs are reported in Tech Briefs. For additional information on any of the programs described here, circle the appropriate TSP number.

If you don't find a program in this issue that meets your needs, call COSMIC directly for a free review of programs in your area of interest. You can also purchase the annual *COSMIC Software Catalog*, containing descriptions and ordering information for available software.

COSMIC is part of NASA's Technology Utilization Network.

**COSMIC@—** John A. Gibson, Director, (404) 542-3265  
The University of Georgia  
382 East Broad Street  
Athens, Georgia 30602

## Computer Programs

These programs may be obtained at a very reasonable cost from COSMIC, a facility sponsored by NASA to make computer programs available to the public. For information on program price, size, and availability, circle the reference number on the TSP and COSMIC Request Card in this issue.



## Machinery

### Computing the Dynamics of Helicopters

CAMRAD calculates the loads on, and the motions of, various rotorcraft.

The Comprehensive Analytical Model of Rotorcraft Aerodynamics (CAMRAD) computer program is designed to calculate the performance of, loads on, and noise generated by, a helicopter rotor; the vibration of the helicopter and its response to gusts; the dynamics and handling qualities of the helicopter in flight; and the aeroelastic stability of the helicopter as a system. The analysis is a consistent combination of structural, inertial, and aerodynamical mathematical models applicable to a wide range of problems and a wide class of vehicles.

The CAMRAD analysis can be applied to articulated, hingeless, gimbaled, and teetering rotors that have arbitrary numbers of blades. The degrees of freedom of a rotor blade included in CAMRAD are blade/flap bending, rigid pitch and elastic torsion, and, optionally, gimbal or teeter motion. General two-rotor aircraft can be modeled. Single-main-rotor, tandem-helicopter, and side-by-side-tilting-prop-rotor aircraft configurations can be considered. The case of a rotor or helicopter in a wind tunnel can also be modeled. The degrees of freedom of aircraft bodies included in CAMRAD are the six rigid-body motions, elastic airframe motions, and the rotor/engine speed perturbations.

CAMRAD calculates the loads on, and motions of, a heli-

copter or airframe in two stages. First, the trim solution is obtained; then the flutter, dynamics of flight, and/or transient behavior can be calculated. The trim operating conditions considered include level flight, steady climb or descent, and steady turns. The analysis of the rotor includes nonlinear inertial and aerodynamic models, applicable to large blade angles and a high inflow ratio. The mathematical model of the aerodynamics of the rotor is based on two-dimensional, steady-flow airfoil characteristics with corrections for the effects of three-dimensional and unsteady flow, including a model of dynamic stall.

In the analysis of flutter, the matrices that describe the linear differential equations of motion are constructed, and the equations are analyzed. In the analysis of the dynamics of flight, the stability derivatives are calculated and the matrices that describe the linear differential equations of motion are constructed. These equations are analyzed. In the analysis of transients, equations of motion of the rigid body are numerically integrated for prescribed transient gust or control input.

The CAMRAD program product is available by license for a period of 10 years to domestic U.S. licensees. The licensed program product includes the CAMRAD source code, command procedures, sample applications, and one set of supporting documentation. Copies of the documentation may be purchased separately. CAMRAD is written in FORTRAN 77 for the DEC VAX computer under VMS 4.6 with a recommended core memory of 4.04 megabytes. The DISSPLA package is necessary for graphical output. CAMRAD was developed in 1980.

*This program was written by Wayne Johnson of Ames Research Center. For further information, Circle 55 on the TSP Request Card. ARC-12337*



## Mathematics and Information Sciences


### YAMM—Yet Another Menu Manager

Alimentary connotations notwithstanding, this is about software for the management of software.

One of the most time-consuming, yet necessary, tasks of writing any piece of interactive software is the development of a software interface with the user. The Yet Another Menu Manager (YAMM) computer program is an application-independent menuing package of software designed to remove much of the difficulty and save much of the time inherent in the implementation of the front ends of large packages of software. Written in C for a UNIX-based operating system, YAMM provides a complete menuing front end for a wide variety of applications, with provisions for independence from specific types of terminals, configurations that meet the specific needs of users, and dynamic creation of menu trees.

An application program running under the menu package consists of two parts: a description of the menu configuration and the body of application code. The menu configuration is used at run time to define the menu structure and any nonstandard keyboard mappings and terminal capabilities. Menu definitions define specific menus within the menu tree. The names used in a definition may be either referenced to application functions or the names of other menus defined within the menu configuration. Application parameters are

NASA Tech Briefs, February 1991



when you  
really need  
to know \*  
call Zircar


the FULL LINE  
Fibrous Ceramic  
Products Company

\* About Precision Engineered,  
High Temperature Fibers,  
Papers, Textiles, Boards,  
Cylinders, Custom Shapes,  
Insulation Assemblies,  
Furnace Modules and  
Accessories



**Zircar**<sup>®</sup>  
FIBROUS CERAMICS

ZIRCAR Products Inc.  
110 N. Main St. PO Box 458, Florida, NY 10921  
TLX: 996608 FAX: (914) 651-3192 PH (914) 651-4481



...Recognized the world over in holding **COMPOSITE MATERIALS** for machining!



545 Blackhawk Park Avenue  
Rockford, Illinois 61104-5135  
Phone: (815) 962-8700  
Telex: 257312  
Fax: (815) 962-5568

**MAGNA-LOCK, U.S.A.**

- Manufacturers of **CUSTOM vacuum chucks**
- We're proud of our elite customer base in the **Aero-Space Industry**

**1-800-443-0760**

Circle Reader Action No. 419

entered by use of data-entry screens, which allow for required and optional parameters, tables, and lists of legal values. Both automatic and application-specific checking for errors are available. Help is available for both menu operation and specific applications.

The YAMM program was written in C for execution on a Sun Microsystems workstation running SunOS, based on the Berkeley (4.2bsd) version of UNIX. During development, YAMM has been used on both 68020 and SPARC architectures, running SunOS versions 3.5 and 4.0. YAMM should be portable to most other UNIX-based systems. It requires a control memory of approximately 232K bytes. YAMM was developed in 1988.

*This program was written by Alan S. Mazer and Richard J. Weidner of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 137 on the TSP Request Card.*  
NPO-17769

### Estimating the Cost of Developing Software

The SOFTCOST program combines diverse mathematical models that represent aspects of the development task.

The early estimation of required resources and of a schedule for the development and maintenance of software is usually the least precise aspect of the life cycle of software. However, it is desirable to make some sort of an orderly and rational attempt at estimation in order to plan and organize an implementation effort. The Software Cost Estimation Model program, SOFTCOST, was developed to provide a consistent automated resource-and-schedule mathematical model that is more formalized than the often-used guesswork model based on experience, intuition, and luck.

SOFTCOST was developed after the evaluation of a number of existing cost-estimation programs indicated that there was a need for a cost-estimation program that has a wide range of applicability and adaptability to diverse kinds of software. SOFTCOST combines several software-cost models found in the open literature into one comprehensive set of algorithms that compensate for nearly 50 implementation factors relative to size of the task, inherited baseline, organizational and system environment, and difficulty of the task.

SOFTCOST produces mean and variance estimates of software size, implementation productivity, recommended staff level, probable duration, amount of computer resources required, and amount and cost of software documentation. Since the confidence level for a project using mean estimates is small, the user is given the opportunity to enter risk-biased values for effort, duration, and staffing, to achieve higher confidence levels. SOFTCOST then produces a program evaluation and review technique/critical path method (PERT/CPM) file with subtask efforts, durations, and precedences defined so as to produce the work-breakdown structure (WBS) and schedule that are characterized by the requested overall effort and duration.


The SOFTCOST program operates in an interactive environment, prompting the user for all of the required input. The program builds the supporting PERT data base in a file for later generation or revision of reports. The PERT schedule and the WBS schedule can be printed and stored in a file for later use.

The SOFTCOST program is written in Microsoft BASIC for interactive execution and has been implemented on an IBM PC-XT/AT computer operating under MS-DOS 2.1 or higher with 256K bytes of memory. SOFTCOST was originally developed for the Zylog Z80 system running under CP/M in 1981. It was converted to run on the IBM PC-XT/AT in 1986.

*This program was written by Robert C. Tausworthe of NASA's Jet Propulsion Laboratory. For further information, Circle 22 on the TSP Request Card.*  
NPO-17936

## COMPOSITE BRAIDING


It's faster than filament winding, cheaper than pre-preg roving, and cleaner than in-line impreg.



Wardwell composite braiders produce rocket-motor exit cones and ignitors, rotor and propeller blades, thermoplastic airframe stiffeners, windmill spars, pressure vessels, skis, bicycle frames, tennis racquets, and more. Composite braiding deals more effectively with complex surfaces, offers superior parts versatility, tremendous hoop strength, and works with a wide variety of materials, including Kevlar, fiberglass, and carbon fibers. Find out how Wardwell's experience can help you bring life to your most challenging assignments.

**Our experience is the difference**

Call (401) 724-8800  
or write for our composite story.



**WARDWELL**  
WARDWELL BRAIDING MACHINE CO.  
1211 High Street, Central Falls, RI 02863 USA  
(401) 724-8800 Fax: (401) 723-2690 TWX: 710 384-1305

Circle Reader Action No. 396

## General-Purpose Ada Software Packages

A collection of subprograms brings to Ada many features from other programming languages.

The General-Purpose Ada Packages computer program contains 10 families of subprograms. The families bring to Ada many features from HAL/S, PL/I, FORTRAN, and other languages. These families are as follows: string subprograms (INDEX, TRIM, LOAD, etc.); scalar subprograms (MAX, MIN, REM, etc.); array subprograms (MAX, MIN, PROD, SUM, GET, and PUT); numerical subprograms (EXP, CUBIC, etc.); service subprograms (DATE\_TIME function, etc.); linear-algebra subprograms; Runge-Kutta integrators; and three text input/output families of software packages.

In two cases, a family consists of a single nongeneric package. In all other cases, a family comprises a generic package and its instances for a selected group of scalar types. All generic packages are designed to be easily instantiated for the types declared in the user's facility. Most packages have widespread applicability, although some are oriented for avionics applications. All are designed to facilitate writing new software in Ada.


Several of the packages use conventions introduced by other programming languages. A package of string subprograms is based on HAL/S (a language designed for the avionics software in the Space Shuttle) and PL/I. Packages of scalar and array subprograms are taken from HAL/S or generalized current Ada subprograms. A package of Runge-Kutta integrators is patterned after a built-in MAC (MIT Algebraic Compiler) integrator. Those packages modeled after HAL/S make it easy to translate existing HAL/S software to Ada.

The source code is available as ASCII text files on two 360K, 5.25-in. (13.3-cm) floppy disks written on an IBM/AT personal computer running under PC DOS, v. 3.1. The size of the largest file is 44,032 bytes. The software was developed by use of VAX Ada, v. 1.5 under DEC VMS, v. 4.5. It should be portable to any validated Ada compiler, and it should be executable either interactively or in batch. The software was developed in 1989.

*This program was written by Allan R. Klumpp of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 14 on the TSP Request Card.*  
NPO-17983

# World Class Infrared Thermometers

Every way you look at it—or look *into* it—no other infrared thermometer compares to microprocessor-based KT19. It makes highly repeatable measurements and is loaded with features, making it ideal for automated processes and R&D applications. Call today for more information: **(908) 603-5914**.  
Heimann Systems, A Div. of Siemens Components, Inc.



## HEIMANN

HMN-5004

Circle Reader Action No. 484



## Remote Viewing At it's finest

*The most advanced Remote Viewing Instruments for observing or inspecting into inaccessible areas or hostile environments.*

**BORESCOPIES** - More styles, sizes and operational features to satisfy all industrial applications.

**FIBERSCOPES** - Largest selection of standard instruments with brighter and sharper images.

**VIDEOSCOPIES** - Four different products for various industrial applications featuring ITI's proprietary Digital Image Enhancement.

**SYSTEMS** - Specialist in U.V., custom and turn key requirements.

Quality instruments designed for industrial applications. Made and serviced in the U.S.A.  
*Satisfaction guaranteed on all products.*

**ITI INSTRUMENT TECHNOLOGY, INC.**

P.O. Box 381, Westfield, MA 01086  
TEL: 413-562-3606 FAX: 413-568-9809



# Mechanics

Hardware, Techniques,  
and Processes

- 52 Faster Algorithm for Computation of Incompressible Flow
- 52 Semiautomatic Design of Zonal Computational Grids

- 54 O-Ring-Testing Fixture
- 56 Low-Wear Ball-Bearing Separator

## Books and Reports

- 57 High-Resolution Computations of Hypersonic Flows

- 57 Lubrication of Non-conformal Contacts
- 58 Simulation of Flow in a Turbine Cascade

## Faster Algorithm for Computation of Incompressible Flow


An artificial-compressibility method and an upwind-differencing scheme are combined.

Ames Research Center, Moffett Field, California

An improved algorithm yields faster numerical solutions of the Navier-Stokes equations of steady or unsteady three-dimensional flow of an incompressible fluid. Like some previous algorithms for incompressible flow, this one is based on the method of artificial compressibility. Unlike in a compressible flow, a disturbance at one point in an incompressible flow affects the flow at every other point simultaneously, making it necessary for any algorithm that simulates the flow to propagate information through the entire flow field during each time step. In the artificial-compressibility method, an unsteady flow is treated as incompressible in advancing from one time step to the next, but at each time step (or in the steady state), the fluid is treated as having a variable compressibility that enables the propagation of the flow field, and subiterations are performed in increments of pseudotime until the effects of compressibility subside. One principal computational advantage of artificial compressibility is that it directly couples the pressure and velocity fields at the same time step and converts the elliptic incompressible Navier-Stokes equations to a hyperbolic form that is more amenable to numerical integration.

The present algorithm incorporates a higher-order flux-difference-splitting numerical-integration scheme for the convective terms and a second-order central-difference numerical-integration scheme for the viscous terms. The use of upwind differencing makes the resulting system of equations diagonally dominant. The equations are solved with a line-relaxation scheme that allows the use of very large incre-

**Cross-Stream Velocity Vectors** computed for the square-cross-section duct show a pair of secondary vortices generated by large static pressure on the outside wall at the bend. The vortices move toward the inside wall between the 30° and 60° positions.



ments of pseudotime, leading to fast convergence, both for steady-state problems and for subiterations of time-dependent problems.

The algorithm has been tested by using it to compute steady flows in a duct that has a square cross section and a 90° bend (see figure) and in unsteady flow in an artificial heart.

The steady-state duct computations are in good agreement with experimental data. The artificial-heart computations yield particle traces that resemble those in photographs of the flow in a model of the artificial heart.

This work was done by S. E. Rogers and D. Kwak of **Ames Research Center** and C. Kiris of **Stanford University**. Further information may be found in **AIAA paper 89A-25378, "Numerical Solution of the Incompressible Navier-Stokes Equations for Steady-State and Time-Dependent Problems."**

Copies may be purchased [prepayment required] from **AIAA Technical Information Service Library, 555 West 57th Street, New York, New York 10019, Telephone No. (212) 247-6500. ARC-12370**

## Semiautomatic Design of Zonal Computational Grids

Knowledge-based software helps reduce the complexity of fluid-dynamical computations.


Ames Research Center, Moffett Field, California

EZGrid is a knowledge-based computer program that semiautomatically generates zonal computational grids for use in numerical simulations of two-dimensional flows. Zoning is necessary because of limitations imposed by the size of available computer memory and by the topological

complexity of a typical flow field. The complexity and amount of required memory can be reduced by dividing the flow field into zones, within each of which the computational grid is refined only to the extent necessary to resolve local high gradients. EZGrid was developed to speed and sys-

tematize zoning, which heretofore has been a tedious manual procedure with a high degree of subjectivity and consequent vulnerability to error.

Because there is usually no consensus among experts as to what constitutes the "ideal" or "correct" zoning of a specific



When you're done with the toys...

## Janus/Ada Professional Development Systems are ready.

### Janus/Ada 80386/80486 Unix


*POSIX compliant  
ACVC 1.11 Validated  
Full 32-bit compiler  
Extensive Runtime Libraries  
80386 Assembler and Disassembler  
Janus/Ada Debugger  
Interface to C  
JWindows  
Syntax Checker  
Program Profiler*

**ONLY \$900.00**

### Janus/Ada 80386 MS-DOS

*ACVC 1.11 Validated  
Hosted in 80386 protected mode  
Targeted to the standard DOS environment  
Extensive Runtime Libraries  
80X86 Assembler and Disassembler  
Janus/Ada Debugger including Periscope  
Janus/Ada Workstation Environment  
Interface to MASM  
JWindows  
Syntax Checker  
Program Profiler*


**ONLY \$500.00**



**RR** Software Inc.

P.O. Box 1512  
Madison, Wisconsin 53701  
U.S.A.


Telephone: 608-276-6022  
Facsimile: 608-276-6009  
Order line: 800-722-3248



THIS PRODUCT CONFORMS  
TO ANSI/MIL-STD-1815A AS  
DETERMINED BY THE AJPO  
UNDER ITS CURRENT  
TESTING PROCEDURES

flow field, EZGrid is not designed to eliminate subjectivity entirely. Instead, it codifies portions of zoning expertise on which there is or could be some consensus, thereby speeding the zoning process by narrowing the range of choices among possible zoning plans. One consequence of this approach is that EZGrid incorporates a way of entering qualitative information on the shapes and configurations of objects in a flow field at the beginning of a zoning procedure. The user still provides perceptual information on shapes and groupings of objects, but explicitly, in a consistent manner, only for the input geometry, and only during the setup phase at the beginning of an EZGrid run. For this purpose, EZGrid features interactive input via a language in which objects are regarded as being composed of primitive parts, and the shapes, sizes, orientations, and other attributes of objects are described in standardized terms. The user's choice in describing shapes can affect the zonal grid significantly (see figure).

Any attempt to define standard zoning practice must account for an individual user's bias, which involves such factors as flow-solver capabilities, user's experience, computational objectives, and aesthetics. In generating a flow-field zoning, EZGrid follows standard zoning guidelines, subject to a user's bias as reflected by a "user bias profile" which the user can "tune". This profile is the collection of parameters chosen to represent the factors described above, and it is tuned by the assignment of qualitative weights to each parameter, denoting the importance and/or acceptability of that parameter.



The User's Opinion Regarding the Shape of an Object in a flow field is entered via the choice of one of several prescribed names that describe various end/side shape combinations. EZGrid then fits, to the object, a zonal grid appropriate for that shape.

EZGrid constructs zoning plans by assembling predefined subplans. A subplan is a sequence of zoning actions applicable to a specific grouping of objects. The bulk of the zoning design knowledge is contained directly in the subplans. If there is more than one grouping, more than one subplan are selected and assembled together to produce a plan. The rules that determine the way in which the subplans

are combined contain the remainder of the zoning design knowledge. The assembly of plans from subplans increases efficiency, and a zoning-design problem is thus transformed into a simpler selection-and-assembly problem.

This work was done by Alison Andrews Vogel of Ames Research Center. For further information, Circle 86 on the TSP Request Card. ARC-12322

## O-Ring-Testing Fixture

Rings can be evaluated under conditions of storage and use. *Marshall Space Flight Center, Alabama*

A fixture tests O-rings for sealing ability under dynamic conditions after extended periods of compression. The fixture makes it possible to evaluate the effects of a variety of parameters, including temperature, pressure, rate of pressurization, rate and magnitude of radial gap movement, and pretest compression time.

The fixture moves the sealing surface radially away from the O-ring under test and slides the sealing surface axially across the ring. It also stores the O-ring under compression under any of various environmental conditions before it is tested.


A conical plug holds the O-ring under test in a groove in its tapered outer wall (see figure). The plug fits in a similar conical hole in a housing. A shim is placed in the housing so that it lies directly under the plug when the components are bolted together. The thickness of the shim determines the compression applied to the O-ring while it is stored.

When the time comes to test the O-ring

dynamically, the assembled plug and housing are placed in a test stand. An upper section is bolted to the plug with a torque wrench, and the bolts joining the plug to the housing are removed. This procedure ensures that the compression on the O-ring is not reduced during the preparation for the dynamic test. A hydraulic cylinder is then attached to the upper section.


Pressure is applied to the space below the O-ring through ports in the plug. (Auxiliary rings above and below the test ring enable pressurization and measurement of leakage.) The hydraulic cylinder is raised a preset distance at a preset rate, sliding the ring axially on the housing and creating a radial gap between the ring and the housing. Pressure sensors in the housing above and below the O-ring monitor leakage.

This work was done by James E. Turner and D. Scott McCluney of Marshall Space Flight Center. No further documentation is available. MFS-28414




The Hydraulic Cylinder Moves the Plug in the housing. The taper of 15° on the plug and the cavity of the housing ensures that a gap is created between the O-ring under test and the wall of the cavity. Secondary O-rings above and below the test ring maintain the pressure applied to the test ring.

# SPECIFY INCO SPECIALTY POWDERS FOR WIDE RANGE OF ELECTRONIC APPLICATIONS



*Inco Type T 287 Filamentary Powder, particle size (FSSS) 2.6-3.3 microns, apparent density 0.75-0.95 g/cc, relative surface resistivity 0.30 ohms per square ( $\square$ ).*



*Novamet HCA-1 Flake, screen mesh 98% minus 400, apparent density 0.90 g/cc, thickness 1.0-1.1 microns, surface resistivity 0.25  $\Omega/\square$ .*



*Novamet Silver Coated Nickel Spheres, 15% Ag, 2.5 g/cc apparent density, particle size 10 microns, screen mesh 99%-250, surface resistivity 0.03  $\Omega/\square$ .*



*Novamet Nickel Coated Graphite, 60% fully encapsulated Ni, apparent density 1.6 g/cc, particle size (FSSS) 100 microns, screen mesh 63% - 150/ + 250, surface resistivity 0.3  $\Omega/\square$ .*

Inco Specialty Powder Products now has a wide range of nickel and coated powders with exceptional conductive and magnetic properties. These properties make them ideal for a spectrum of electronic applications such as conducting film technology, coatings, adhesives, gaskets and EMI shielding.

## EXTENSIVE PRODUCT RANGE

The development of computer processed control coupled with the continuous powder production improvements enables us to meet your most stringent powder specifications for electronic applications.

In addition to the products pictured above, INCO SPP has available the following high performance powder products. Novamet Conductive Nickel Spheres, particle size (FSSS) 8-9 microns, apparent density 3.2-3.5 g/cc, surface resistivity 1.0 ohms per square. Novamet 525 Conductive Nickel Pigment, screen mesh 100% minus 400, particle size 3.2 microns, 0.65 BET surface area  $m^2/g$ , surface resistivity 0.35 ohms per square. Silver Coated Nickel Flake, 15% Ag, 2.6 g/cc apparent density, particle size (FSSS) 15 microns, screen mesh 99% minus 200, surface resistivity 0.04 ohms per square.

Magnetic ferrites and surge arrestor applications also

use our specialized range of nickel oxides. High Purity Black Nickel Oxide, 77.2% Ni, BET 75 ( $m^2/g$ ) particle size (FSSS) 5.2 microns, minus 325 mesh 99% plus. Green Nickel Oxide, 78.5% Ni, BET 3 ( $m^2/g$ ) particle size 1.6 microns, - 325 mesh 100%.

Inco Specialty Powder Products is your unique source for custom fitting high performance powders into electronic applications. Our customer focused, worldwide marketing service group is ready to help you with your current and future needs.

For more information write INCO Specialty Powder Products, Dept. 1-90, Park 80 West-Plaza Two, Saddle Brook, NJ 07662

## INCO SPP

Park 80 West-Plaza Two, Saddle Brook, NJ 07662  
Shin-Muromachi Building, 4-3 Nihonbashi-Muromachi 2-Chome,  
Chuo-ku, Tokyo 103 Japan  
1-3 Grosvenor Place, London SW1X7EA England  
15/FI Wilson House, 19-27 Wyndham Street Central, Hong Kong

Circle Reader Action No. 452

# Low-Wear Ball-Bearing Separator

A proposed component would be compatible with liquid oxygen or hydrogen.

Marshall Space Flight Center, Alabama


A proposed ball-bearing separator for use in a cryogenic pump would be stronger and more resistant to wear than is the present separator made of molded polytetrafluoroethylene (PTFE) reinforced with glass fibers. The fibers contribute to wear, and although these fibers strengthen the part, it is still prone to failure.

The proposed separator would consist of a molded plastic-and-metal composite ring imbued with solid lubricant and containing an embedded metal ring (see figure). The frame would provide strength and rigidity, and the molded wall — without glass fibers — would lubricate the balls.

The fabrication of the separator would begin with the insertion of the metal ring in the cavity of a compression mold. The tooling portion of the ring would be clamped between mating sections of the mold; tooling pins would extend between the sections of the mold through indexing holes in the tooling portion of the metal ring to lock it in position. The cavity would be filled with the molding material, and a compression ram would mold the plastic around the metal ring at a suitable pressure and temperature.

The molded separator would be removed

The **Metal Ring** would be embedded in the molded wall (top) to obtain a combination of strength and lubricity. Before molding and machining, the ring would include a tooling portion for handling and indexing.



## Research Engineers & Scientists

### Digital Signal Processing

The **Environmental Research Institute of Michigan (ERIM)**, a growing, leading-edge, research and development organization with headquarters in Ann Arbor, MI, has newly created opportunities for a select group of talented Research Engineers and Scientists for the following areas:

#### Systems:

- Digital signal processing
- Kalman filtering
- Motion compensation/navigation systems
- Documentation specialist
- Computer systems manager (networked SUN environment)

#### Software:

- Real time embedded systems
- Software systems engineering/simulation/modeling
- User interfaces
- Software testability
- Ada, CASE tools, UNIX, X11, MIL-STD-2167A environment

#### Hardware:

- RF and microwave design, high speed digital and analog circuit design, microprocessor and interface technology, digital signal processor design.

Previous experience with U.S. Government programs desirable, as is a BS, MS or PhD in Computer Science, Electrical Engineering or Mathematics.

You'll receive an excellent salary with outstanding benefits and growth potential. For prompt consideration, please forward your resume in strict confidence to either: **ERIM, Box 8618, Ann Arbor, MI 48107-8618; or ERIM, 5757 West Century Blvd., Suite 340, Los Angeles, CA 90045** — Attn: **Human Resources Manager-NT/190**. ERIM has recently implemented a Doctoral Fellowship Program to promote continued technology growth and development. The program, sponsored in conjunction with the University of Michigan's Department of Electrical Engineering and Computer Science (EECS), is now accepting inquiries at the above locations. An Equal Opportunity Employer. U.S. Citizenship Required.



At The Forefront Of Sensor Technology

Circle Reader Action No. 475

from the mold and placed on a lathe or milling machine (with the aid of the indexing holes in the tooling portion of the metal ring) for machining of the inside and outside wall surfaces and ball pockets. Finally the exposed tooling portion of the ring would be machined away.

The metal ring would be machined from forgings or plate stock of a material appropriate for the application. For example, Inconel\* I-718 alloy might be chosen for use in oxygen, while 440-C corrosion-resistant steel would be a good choice for use in hydrogen.

The molded composite would be a blend of PTFE and fluorinated ethylene/propylene (FEP) filled with brass and bronze powder and molybdenum disulfide powder. The FEP would provide bonding to the metal frame. The PTFE and molybdenum disulfide would give lubricity. The brass and bronze powders would impart mechanical stability and are known from previous experience to be compatible with oxygen.

\*"Inconel" is a registered trademark of the INCO family of companies.

This work was done by Elden L. Hawkinson of Rockwell International Corp. for **Marshall Space Flight Center**. For further information, Circle 109 on the TSP Request Card.

Inquiries concerning rights for the commercial use of this invention should be addressed to the Patent Counsel, Marshall Space Flight Center [see page 14]. Refer to MFS-29666.

## Books and Reports

These reports, studies, handbooks are available from NASA as Technical Support Packages (TSP's) when a Request Card number is cited; otherwise they are available from the National Technical Information Service.

### High-Resolution Computations of Hypersonic Flows

The enhancement of stability and the rate of convergence is discussed.

A report discusses the extension, to hypersonic flows, of a class of implicit, total-variation-diminishing (TVD) algorithms suitable for the numerical simulation of transonic and supersonic flows that obey the Euler and Navier-Stokes equations. The stabilities and the rates of convergence, relative to those of other algorithms, are discussed. The study is complemented by a variety of computations of steady and unsteady viscous and inviscid hypersonic flows about blunt bodies.

The improved algorithms implement conservative shock-capturing schemes that are accurate to second and third order in space and to first or second order in time. They are fully implicit. Particular emphasis is placed on high-resolution algorithms that are implicit and accurate to second order in time. The algorithms are formulated in finite-volume and pseudo-finite-volume forms, which, for certain physical problems and grid distributions, can enhance stability and the rate of convergence for highly clustered or skewed grids and require only a slight modification from the form in which they were originally presented for generalized geometries.

The report identifies some numerical aspects of TVD-type schemes that affect the rates of convergence for high mach numbers and flows of real gases, but have negligible effects on low-mach-number or perfect-gas flows. The performances of the various linearized implicit forms of the improved schemes similar to the forms of schemes used in some previous studies of transonic flows are re-examined for hypersonic flows.

The behaviors of the improved schemes with various forms of temporal differencing but similar forms of spatial discretization for inviscid and viscous flows is investigated. These studies indicate that the stabilities and rates of convergence of these schemes are different between viscous and inviscid flows. However, with the proper choice of the temporal discretization and suitable implicit linearization, these schemes are fairly efficient and accurate for very complex two-dimensional hyper-

sonic inviscid and viscous shock interactions.

The relative efficiency and accuracy of typical TVD-type schemes for shock-wave computations are examined. A comparative study of steady and unsteady flows reveals that the class of improved TVD-type schemes, in particular, for equilibrium real-gas and nonequilibrium flows produces shock resolutions just as accurate as those of most other TVD schemes and TVD flux-vector-splitting approaches, yet requires fewer operations. Even with the improvements, the rate of convergence is, in general, slower for real gases than for perfect gases. Also, the rate of convergence is, in general, slower for viscous flows than for inviscid, steady flows.

*This work was done by H. C. Yee of Ames Research Center, G. H. Klopfer of NEAR, Inc., and J.-L. Montagué of ONERA, France. Further information may be found in NASA TM-100097 [N88-22651], "High-Resolution Shock-Capturing Schemes for Inviscid and Viscous Hypersonic Flows."*

*Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. ARC-12254*

## Lubrication of Nonconformal Contacts

Regimes of minimum-film-thickness lubrication are analyzed.

A report discusses advances in the knowledge of the lubrication of nonconformal contacts in bearings and other machine elements. It reviews previous developments in the theory of lubrication, presents advances in the theory of lubrication to determine minimum film thickness, and describes experiments designed to investigate one of the regimes of lubrication for ball bearings.

The lubrication of nonconformal contacts is characterized by low contact area and high unit loading. The form of lubrication normally found in nonconformal contacts is elastohydrodynamic lubrication (EHL). Depending on the effects of the elastic deformation and the variation of the viscosity with pressure, four regimes of lubrication can be defined: isoviscous/rigid, isoviscous/elastic, piezoviscous/rigid, and piezoviscous/elastic.

The main technical discussion begins with the development of minimum-film-thickness results for the piezoviscous/rigid regime of a compressible Newtonian fluid with Roelands viscosity. These results pro-


## ALGOR FEA—Design and Stress Analysis \$889\*

For 286 or 386 desktop computers

- **Finite Elements:** truss, beam, 2-D solid, 3-D solid, membrane, plate/shell, pipe, boundary, rigid link, non-linear gap, thin and thick shell/plate composites.
- **Stress Analysis:** point load, pressure, temperature, accelerations, centrifugal loads, deflections.
- **Dynamic Analysis:** mode shapes, frequencies, time stress history, response spectrum, direct integration, random vibration.
- **Heat Transfer Analysis:** 2-D/3-D conduction, convection, radiation, heat source, temperature, steady state and transient.
- **Graphics:** 3-D models; hidden line removal; light source shading animation; stress, displacement, temperature and flux contours w/optional shading; deformations; pan; zoom; node/element numbers; color.
- **Modeling:** 2-D/3-D mesh, cylinders, extrusions profile-path, warped surfaces; boundaries, loads, materials. SUPERDRAW II and parametric model generation.
- \* **Full Capability, no size restrictions:** 3-D drawing, Computer Aided Design, solid modeling, design visualization, finite element stress analysis, and graphic post-processing.

GSA Contract #GS00K89AGS6270

Design the future with Algor.



Wire wheel model



Propeller hub/blades



Stress contour on clip



Temperature contour electronic part

Algor has the largest base of installed FEA software in the world!

TEL: (412) 967-2700 FAX: (412) 967-2781




Quality Engineering Software Since 1977

ALGOR INTERACTIVE SYSTEMS, INC.  
260 Alpha Drive, Pittsburgh, PA 15238

Circle Reader Action No. 361

# Tracking Block II Satellites Is No Problem!


The Latest In GPS Time and Frequency Technology for Clock Systems, Metrology, and Communications Systems



Antenna/Downconverter

- Special software – No Problem!
- Cable length – No Problem!
- Perfect frequency measurement capabilities
- NIST (NBS) data format
- Internal Disciplined Oscillator
- Displays 1 pps vs UTC/GPS to 0.1 ns resolution
- GSA approved

Specialized Antenna/Downconverter allows for maximum antenna-receiver separation



Model 2200



Model 2201

**FTS / AUSTRON**

P.O. Box 14766  
Austin, TX 78761-4766  
(512) 251-2313  
FAX (512) 251-9685  
Contact: Don Mitchell/GPS Specialist

Circle Reader Action No. 304

vide a basis for the analysis and design of a wide range of machine elements that operate in the piezoviscous/rigid regime.

The second major feature of this study is the development of a numerical method for the calculation of elastic deformations in contact stresses. A biquadratic polynomial is used to approximate the pressure distribution on the whole domain analyzed, and the deformation of every node is expressed as a linear combination of the nodal pressures, the coefficients of which can be combined into an influence-coefficient matrix. This approach has the advantages of higher numerical accuracy, less computing time, and a smaller storage-size requirement for the matrix.

The theory of ideal elastohydrodynamic lubrication is extended to real bearing systems to get a better understanding of failure mechanisms in machine elements. The improved elastic-deformation calculation is incorporated into the EHL numerical scheme. Using this revised numerical technique and the flow-factor model, the effects of surface roughness on the elastohydrodynamic lubrication of point contacts are studied. Conditions typical of an EHL contact in the piezoviscous/elastic regime entrained in pure rolling on rough bearings are investigated. Results are presented to demonstrate the effects of surface roughness on the shape of the film, the distribution of pressure, and rolling friction in a ball bearing.

Experiments to study the transient EHL effects in instrument ball bearings are reported. A parched subregime of elastohydrodynamic lubrication, lying between starved and mixed, is proposed to describe the behavior of instrument ball bearings. The parched regime is characterized by zero flow of lubricant outside the Hertz area, slow crossflow inside the Hertz area, and long-term transients in the thickness of the film. A parched bearing demands the least driving torque and has the best spin-axis definition of any lubrication regime.

This work was done by Yeau-Ren Jeng of Lewis Research Center. Further information may be found in NASA TM-87120 [N86-13679], "Lubrication of Nonconformal Contacts."

Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. LEW-14882

## Simulation of Flow in a Turbine Cascade

A lower-upper implicit scheme and interactive generation of grids are used.

A report discusses the application of a

lower-upper (LU) implicit numerical-integration scheme, together with an interactive grid-generation method, to the simulation of inviscid, compressible flow in a two-dimensional model of a turbine cascade. This study is part of the continuing effort to develop techniques for the computation of complicated three-dimensional flows in turbomachinery.

The Euler equations of two-dimensional flow are presented in conservation-law form, then transformed to curvilinear coordinates that conform to the flow boundaries. The LU implicit scheme is then introduced. This scheme, which was developed previously, is an approximate-factorization scheme that requires the inversion of only sparse lower and upper triangular matrices — a procedure that can be performed efficiently without extensive storage of data. As an implicit scheme, it allows the attainment of the steady state via a large time step.

The interactive computer program TURBO, still undergoing development, is used to generate computational grids. This program uses the control-point form of algebraic grid generation, in which the shapes and positions of coordinate curves are adjusted from control points distributed sparsely throughout the flow and the grid conforms precisely to the boundaries. As an algebraic method, the control-point form provides explicit control of the grid structure and requires relatively few computations. One distinct advantage of the TURBO program over other grid-generation programs is that it allows the local grid structure to be changed as necessary (e.g., refined in regions of high curvature or anticipated high gradients) for flows bounded by surfaces with complicated shapes.

The basic interactive process of TURBO is illustrated with examples of grids fitted to turbine stator vanes and cascades of such vanes. The LU implicit scheme is used to simulate the inviscid, compressible flow on one of the cascade grids. The predictions of the implicit scheme are shown to agree closely with laser-anemometer measurements of velocity and measurements of pressure on the surfaces of a vane in an experiment in a cascade that was annular but otherwise had similar geometry.

This work was done by Yung K. Choo of Lewis Research Center, Woo-Yung Soh of Sverdrup Technology, Inc., and Seokkwan Yoon of MCAT Institute for Ames Research Center. To obtain a copy of the report, "Application of a Lower-Upper Implicit Scheme and an Interactive Grid Generation for Turbomachinery Flow Field Simulations," Circle 119 on the TSP Request Card. ARC-12551



## Meissner-Effect Stepping Motor

Weight, cost, and maintenance would be reduced.

*Marshall Space Flight Center, Alabama*

A proposed stepping motor would derive torque from the diamagnetic repulsion produced by the Meissner effect — the exclusion of a magnetic field from the interior of a superconductor. The design of the motor would take advantage of silver-doped  $YB_2Cu_3O$  and other compounds that have recently been discovered to be superconductive at temperatures as high as that of liquid nitrogen.

The motor (see figure) would include a rotor and a stator in a nonmagnetic housing. The rotor would include a shaft mounted on bearings in the housing and restrained axially by retaining rings. The stator would include electromagnets spaced equally around the circumference and joined at the periphery by a magnetically soft cylinder that would conduct magnetic return flux between them. The rotor body, made of nonmagnetic material, would be mounted on the shaft and would include passages for liquid nitrogen, which would be used to cool it to the temperature required for superconductivity. The outer surface of the rotor body would be a cusped cylinder covered by a superconductive skin.

Figure 2 illustrates the principle of operation. In the top part of this figure, the peaks of the cusps (called "nodes") are positioned between electromagnets C and electromagnets A. Only electromagnets A are energized. Because of the Meissner effect, the magnetic flux of each energized electromagnet is confined to the right of the nearby node. The resulting gradient of magnetic pressure pushes the rotor toward the left.

In the middle part of the Figure 2, the rotor has moved so that the nodes now face the midpoints of unenergized electromagnets C. The fluxes from energized magnets A to unenergized magnets C now pass symmetrically through the bottoms of the valleys between the nodes, and consequently exert no net magnetic force to the right or left. However, because the fluxes from energized magnets A to unenergized magnets C are confined by the Meissner effect to the right of the nodes, there is still a net magnetic force on the rotor toward the left.

If electromagnets A were to remain energized, eventually the rotor would reach the position shown at the bottom of Figure 2. This is a magnetic-equilibrium position because the symmetry of the magnetic

fields on all cusps results in zero net magnetic force to the right or left. If it were desired to continue the movement to the left, then electromagnets C would have to be turned on, while electromagnets A would have to be turned off. Similarly, it would be necessary to turn on electromagnets B and turn off electromagnets C to produce motion past the next equilibrium position. Repetition of this cycle would result in continuous motion to the left. Of course, the sequence could be reversed to obtain motion to the right. Modern electronic rotor-position sensors and commutation circuitry

would be used to switch the electromagnets on and off at the required positions and times.

The stator of the proposed motor would weigh less and cost less than a conventional stepping motor does because it would not contain the usual heavy metallic, magnetic housing. The rotor would cost less, both to build and to maintain, because it would not contain an arcing commutator. The use of the Meissner effect to produce magnetic force and torque would promote high energy efficiency.

*This work was done by Glen A. Robertson of Marshall Space Flight Center. For further information, Circle 9 on the TSP Request Card. MFS-28409*




Figure 1. The **Skin of the Rotor** would be cooled below its superconducting-transition temperature by liquid nitrogen. O-Rings would prevent leaks of liquid nitrogen from the rotor.





Figure 2. This **Simplified, Flattened View** of the rotor illustrates the principle of operation. One out of every three adjacent magnets is switched on at a given time. The asymmetry of the magnetic field on the superconducting skin of the rotor results in a net magnetic force to the right or left.



## Fabrication Technology

### Hardware, Techniques, and Processes

60 Molecular-Beam Epitaxy of  $\text{IrSi}_3$   
60 Hot Oil Removes Wax

61 Fast, Nonspattering Inert-Gas Welding  
61 Making Large Suction Panels for Laminar-Flow Control

63 Electrical-Discharge Machining With Additional Axis  
64 Modified Furnace Makes More Silicon Ribbon

## Molecular-Beam Epitaxy of $\text{IrSi}_3$

In experiments,  $\text{IrSi}_3$  was formed at the lowest reported temperatures.


*NASA's Jet Propulsion Laboratory, Pasadena, California*

Molecular-beam epitaxy grows layers of iridium silicide ( $\text{IrSi}_3$ ) on silicon at temperatures of 630 to 800 °C. The formation of  $\text{IrSi}_3$  by prior techniques required annealing at 1,000 to 1,100 °C. The new, lower formation temperature is expected to enable the growth of arrays of  $\text{IrSi}_3/\text{Si}$  infrared detectors on Si wafers without thermally damaging image-processing circuitry integrated on the wafers.

$\text{IrSi}_3$  is particularly useful as a photodiode material because it forms Schottky diodes that have potential barriers of only 0.12 to 0.15 eV — the lowest of any metal on silicon. These photodiodes are sensitive to infrared radiation at wavelengths as large as 8 to 10  $\mu\text{m}$ .

Until now, an array of iridium/silicon photodiodes has typically been made by depositing a layer of pure iridium on a silicon substrate by evaporation, then annealing the structure to convert the layer to stable  $\text{IrSi}_3$ . Unfortunately, mixtures of Ir and  $\text{IrSi}$ ,  $\text{IrSi}$  and  $\text{IrSi}_{1.75}$ , and  $\text{IrSi}_{1.75}$  and  $\text{IrSi}_3$  also appear in the layer, producing a high series resistance and variations in the heights of the Schottky barriers. These unwanted materials are eliminated if the annealing temperature is greater than 1,000 °C, but the integrated circuitry in the silicon cannot survive such high temperatures.

With molecular-beam epitaxy, in contrast, iridium and silicon are deposited on the silicon wafer in the stoichiometric ratio of 1 to 3. Stable  $\text{IrSi}_3$  thus forms on the wafer surface, without unwanted metallic iridium or compounds. The process takes place in



These **Scanning Electron Micrographs** show the surfaces of films of  $\text{IrSi}_3$  deposited to a thickness of 77 Å on Si substrates. The temperatures are those of the substrates during deposition.

vacuum, and the silicon substrate can be cleaned in place, just before deposition starts, to ensure a good starting surface for the  $\text{IrSi}_3$  layer.

The deposited layers become epitaxial as the substrate temperature during deposition is raised above 630 °C. A smooth surface morphology of the layer is observed for the substrate temperature below 680 °C

(see figure). At higher temperatures, the quality of the surface deteriorates, and islands of  $\text{IrSi}_3$  form.

*This work was done by True-Lon Lin of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 78 on the TSP Request Card. NPO-17953*

## Hot Oil Removes Wax

A noncarcinogenic solvent replaces a carcinogenic one.

*Marshall Space Flight Center, Alabama*

Mineral oil heated to a temperature of 250 °F (121 °C) has been found effective in removing wax from workpieces after fabrication. (For example, one might have to remove wax from a combustion-chamber or heat-exchanger cavity that had been filled with wax in preparation for an electroforming or other fabrication process.) The heated mineral oil serves as a relative-

ly safe alternative to the carcinogenic and environmentally hazardous solvent perchloroethylene, which has commonly been used until now to remove wax.

Depending upon the size and shape of the part to be cleaned of wax, the part can be immersed in a tank of the hot oil, and/or the interior of the part can be flushed with the hot oil. A pump, fittings, and ancillary

tooling can be built easily for this purpose. After cleaning, the innocuous oil residue can be washed off the part by an alkaline aqueous degreasing process.

*This work was done by James J. Herzstock of Rockwell International Corp. for Marshall Space Flight Center. No further documentation is available.*

*Inquiries concerning rights for the commercial use of this invention should be addressed to the Patent Counsel, Marshall Space Flight Center [see page 14]. Refer to MFS-29713.*

## Fast, Nonspattering Inert-Gas Welding


A conceptual technique would combine the best features of three previous arc-welding methods.

*Marshall Space Flight Center, Alabama*

A proposed welding technique would combine the best features of metal (other than tungsten)/inert-gas welding, plasma arc welding, and tungsten/inert-gas welding. The technique would offer these advantages:

- Wire fed to the weld joint would be preheated; it could therefore be fed at high speed without spattering.
- High-frequency energy would not have to be supplied to the workpiece to initiate welding.
- The size of the arc gap would not be critical; a power-supply control circuit would adjust the voltage across the gap to compensate for changes.
- Only a low gas-flow rate would be needed.
- The welding electrode could be replaced easily as a prefabricated assembly.
- An external wire-feeding manipulator would not be needed.
- The welding process would be relatively forgiving of operator error.

The welding electrode would be a hollow tungsten rod containing a coaxial insulating tube (see figure). A mechanism would feed wire along the inside of the tube. The wire would emerge from the chamfered tip of the



**A Welding Wire Would Pass** along the hollow core of a welding-rod assembly. The gas surrounding the wire would become ionized at the tip of the rod. The rod would be about 3/8 in. (9.5 mm) in diameter.

rod and enter the weld puddle. An inert gas would enter the insulating tube via a porous sintered diffusing ring and flow along the tube to the welding tip. As it emerged from the tip, the gas would be ionized by a radio-frequency voltage applied across the gap between the wire and the hollow tungsten electrode. The plasma thus created would preheat the wire, provide an ionizing medium for initiation of the welding arc, and protect the wire and the hot welded metal from oxidation.

As in plasma welding, two power supplies

would be needed. One would furnish the welding power to the wire, and the other would energize the plasma. The welding power would be applied and the welding voltage sensed via a copper contact tube integrated into the electrode structure, as in metal/inert-gas welding.

*This work was done by Jeffrey L. Gilbert of Rockwell International Corp. for Marshall Space Flight Center. No further documentation is available.*  
MFS-29648

## Making Large Suction Panels for Laminar-Flow Control

Perforated titanium panels are used to identify and resolve issues related to manufacture.

*Langley Research Center, Hampton, Virginia*


The attainment of laminar flow on the wings of aircraft has significant potential for reducing drag and increasing fuel efficiency. One way to maintain a large chord-wise extent of laminar flow is to suck a small part of the boundary layer through the skin of a wing. This method, called laminar-flow control (LFC), can stabilize the boundary layer against small disturbances and delay the transition to turbulence. The basic theory is well established and has been verified in wind-tunnel tests and demonstrated in flight tests. Continuous suction through a porous surface is an effective means of delaying the boundary-layer transition. Until recently, however, it has been impractical to perforate airplane materials in production with holes of the small sizes required.

Recently, relatively large suction panels with aerodynamically satisfactory surface perforations and with the surface contours and smoothness characteristics necessary for LFC have been designed, fabricated, and tested. The requirements of production lines for commercial transport airplanes were carefully considered in the development of the panels. Much could be learned about the practicality of such panels for aircraft applications, inasmuch as the sizes of

the panels are representative of what could be used on the wing of a commercial transport airplane. Tests of the perforated panels in a transonic wind tunnel demonstrated aerodynamic stability at flight

mach numbers.

Three titanium suction panels were designed, developed, and manufactured for testing as the upper surface of a Langley 8-foot (2.4-m) Transonic Pressure Tunnel




**Large Titanium Suction Panels** were fabricated by use of an electron-beam perforation drilling process and sandwich construction.

# CAJON Products for Vacuum Service...

*IMMEDIATE delivery from local stocks*

## Flexible Tubing



*Offers rubber hose flexibility*

- 321 stainless steel construction
- Compressible by 20%, extendable by 50%
- Absorbs vibration, relieves thermal expansion, compensates for misalignment
- 1/4" to 1-1/2" tube O.D.
- Nominal lengths 1" to 36"

## Flexible Glass End Tubing



*Isolates vibration in glass systems*

- Relief for thermal expansion
- Compressible by 20%, extendable by 50%
- 1/4" to 1"
- Nominal lengths 2" & 3"
- 321SS fused to 7740 Pyrex glass
- Ultra-high vacuum to 25 PSI
- Single or double end glass

## Glass/Metal Transition Tube

*One step glass to metal transition eliminates graded seals*




- Converts a glass system to a metal system
- Smooth internal surface for high conductance
- Non porous transition area to prevent absorption & outgassing

- Metal, 304SS — Glass, 7740 Pyrex
- Temperature to 960°F (515°C)
- Ultra-high vacuum to 25 PSI
- 100% Helium leak tested
- 1/4", 3/8" & 1/2" sizes
- 6" lengths

## Hose Connectors


*Positive gripping—easy to install*



- Used on soft plastic or rubber tubing
- NPT & Tube Adapter ends
- Hose clamps for safety
- Reuseable
- 316SS and brass
- 1/8" to 3/4"

## Weld Fittings


*For automatic or manual welding*



- High conductance
- 316L & 316 stainless steel construction
- 1/4" to 1"
- Pressures to 5100 psi
- Thin wall design for cleaner, lower profile appearance

## Ultra-Torr® Fitting

*Provides vacuum-tight seal on glass, metal or plastic*



- Quick finger-tight assembly, reuseable
- Helium leak tested to  $4.0 \times 10^{-9}$  atm. cc/sec.
- 1/16" to 1-1/2"
- Use with undersize tubing
- Variety of configurations
- Brass & 316 stainless steel
- Temperatures to 450°F (232°C)

## Vac Goop®

*Anti-gall lubricant for use on threads, O-Rings, gaskets, glass seals and metal parts*

- Low vapor pressure minimizes outgassing problems
- Compatible with system materials
- Use on temperatures to 400°F (204°C)
- Impervious to moisture



LFC model. The suction panels represent one of the largest perforated LFC structures ever built, with a chord as large as that of the wing of a general-aviation airplane. The 7- by 7-ft (2.1- by 2.1-m) titanium panels have an 0.8-percent open-area porosity ratio. The perforations are 0.0025-in. (0.064-mm) holes at 0.025-in. (0.064-cm) spacings.

The perforation was done by an electron-beam drilling process that is capable of making 1,000 holes per second. Each panel has a sandwich construction (see figure) with the titanium skin bonded to a corrugated fiberglass core (forming flutes for the subsurface transfer of airflow) and has a graphite inner face sheet. Impervious bond areas divide the surface of the panel such that suction through perforated strips occurs at the surface. Metering holes located in the bottoms of the suction flutes transfer flow to aluminum ducts, from which the flow leaves the tunnel. Ducts are attached to a wing-box support mounted on a wall of the tunnel.

The distribution of pressure in the design of the airfoil incorporates the latest in the technology of supercritical flow and has a drag-divergence mach number comparable to those of modern turbulent airfoils. A significant region of supercritical flow exists on the upper surface. Features of the distribution of static pressure on the upper surface at the airfoil design point (mach number = 0.75, coefficient of lift = 0.55, Reynolds number = 20 million) include a short, steep favorable gradient near the leading edge, caused by the small nose radius, and a slightly adverse gradient over the majority of the chord, with the aft region exhibiting a Stratford-type recovery of pressure. Although the design Reynolds number for the perforated panels was 20 million, the design allows tests at Reynolds numbers as low as 8 million and as high as 40 million. Special development efforts were made to produce panels that meet LFC waviness criteria. The manufacturing tolerances of the test panels are considerably better than those attained in current production-line practice for turbulent aircraft. Critical issues related to the manufacture of large suction panels were identified and largely resolved. The techniques used to make the panels can be adapted to modern aircraft production lines.

*This work was done by Dal V. Maddaloni of Langley Research Center. Further information may be found in NASA TM-89011 [N86-29815], "Design and Fabrication of Large Suction Panels with Perforated Surfaces for Laminar Flow Control Testing in a Transonic Wind Tunnel."*

*Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. LAR-13844*

# Electrical-Discharge Machining With Additional Axis

Benefits include enhanced flexibility of operation and reduced cost of machining.

## Marshall Space Flight Center, Alabama


A proposed electrical-discharge-machining (EDM) apparatus would use a movable vertical wire as its electrode. The wire would be positionable horizontally along one axis as it slid vertically past the workpiece. The workpiece would be indexed in rotation about a horizontal axis.

The apparatus was proposed to make crenelated cylindrical parts, as shown in the figure. Because of the symmetry of the parts, the wire EDM process can be used to make two such parts at a time by defining the boundary between them. One advantage is that the cost of material is reduced because two such parts can be made from a forging only slightly larger than a forging used to make one such part by conventional machining with a cutting tool.

Another advantage is that wire EDM imparts less residual stress to the workpiece than conventional machining does. Yet another advantage is that less time is spent machining each part when the parts are produced in such symmetrical pairs.

*This work was done by Roger M.*

The **Upper End of the Electrical-Discharge Wire** is moved parallel to the y axis as it unrolls parallel to the z axis. Meanwhile, the workpiece is indexed in rotation about an axis parallel to the x axis and moved linearly back and forth in the x direction. The electrical discharge cuts the crenelated pattern in the workpiece.



Malinzak and Gary N. Booth of Rockwell International Corp. for Marshall Space

Flight Center. No further documentation is available. MFS-29630

# Elmo...cameras from day one!

In the 1940's and 50's, Japanese companies were well known for making toys, fabrics, table radios and light machinery. Elmo was making cameras.

**W**e made cameras for professionals who filmed everything from bathing beauties to brush-fire wars for newsreel watchers around the world.

More than half a century later, we still make cameras for professionals.

**Ultra-tech, super-sophisticated, rugged, miniaturized video cameras no larger than a man's thumb...the Elmo EM-102 and EC-202.**

These are color and black and white cameras with remote camera heads. Using 300,000 pixel CCD solid state pickups, they deliver picture quality equal to cameras many times their size and cost...with guaranteed picture quality up to 100 feet from the control unit.

Elmo micro cameras are now working in industry, robotics, aerospace, medicine, nuclear sciences,

non-destructive testing, surveillance and other applications where human eyes can't.

**Picture an industrial robot** in a toxic atmosphere. There's no danger to the human inspector in the adjacent room while an EM-102 or EC-202 with electronic shutter speeds of 1/60 to 1/1000 of a second keep a tight watch on the machine's actions.

**Varying light levels?** Our new sensor corrects white balance levels at the speed of light, and improved noise reduction circuitry assures consistent, high quality color and signal quality at all times.

You see, technology or not, it takes camera makers to know what a camera should be.

Find out more from Vince Giovinco, **1-800-654-7628**. He'll give you all the specs you want and all the technical support you'll need. By the way, our customers tell us we're the easiest company to deal with for personal service, technical assistance and delivery.

As small as your thumb  
Model EM-102

Compact  
C-mount  
(lens optional)  
Model EC-202

**ELMO**  
Mfg. Corp.

70 New Hyde Park Road, New Hyde Park, NY 11040  
21720 Nordhoff St., Chatsworth, CA 91311  
44 West Dr., Brampton, Ontario L6S 3T6, Canada

## Modified Furnace Makes More Silicon Ribbon

A simple change in the lid and heat shields makes faster growth rates possible.

NASA's Jet Propulsion Laboratory, Pasadena, California

The rate of growth of silicon ribbon by the dendritic-web process is increased by a modification in the lid of the growth crucible. The modified furnace produces silicon ribbon at the rate of  $8.9 \text{ cm}^2/\text{min}$  — 44 percent higher than the previous rate.

In the modified furnace, the slots in the shields that make up the lid grow progressively wider from the bottom to the top of the lid (see figure). This allows the ribbon to cool faster by radiation. As a result, the

crucible can be maintained at a higher temperature, the 5.8-cm-wide ribbon is thicker, and, therefore, the ribbon can be pulled faster.

The new lid has made it possible to attain a record high production rate of 54,000  $\text{cm}^2$  per week. It will be used in a pilot production line to demonstrate dendritic-web technology.

This work was done by Paul A. Piotrowski of Westinghouse Electric Corp.

for NASA's Jet Propulsion Laboratory. For further information, Circle 73 on the TSP Request Card.

In accordance with Public Law 96-517, the contractor has elected to retain title to this invention. Inquiries concerning rights for its commercial use should be addressed to

A. P. Iadicicco  
Intellectual Property Dept.  
Westinghouse Electric Corp.  
1310 Beulah Road-Churchill  
Pittsburgh, PA 15235

Refer to NPO-17350, volume and number of this NASA Tech Briefs issue, and the page number.



1.07" diameter  
optical encoder

## Small encoder, big performance!

Now you can choose the performance you need at a price you can afford . . . the Size 11 optical incremental encoder from Teledyne Gurley . . .

Model Number	8111	8211	8311
Maximum number of lines on the disc*	720	1,800	1,800
Maximum pulses per revolution with external electronics*	2,880	14,400	144,000
Nominal accuracy, in arc minutes	6.0	2.5	<1.0
Maximum frequency response with highest interpolation factor	400 kHz	600 kHz	4 MHz
Price Range**	\$128-\$261	\$146-\$379	\$214-\$581

\* Many other resolutions available.

\*\* Price range is for quantity 1-5 and does not include external electronics. Price depends on resolution and output option. Significant discounts are available for higher quantities.


**800-759-1844**

All 50 states and Canada.

**TELEDYNE GURLEY**

514 Fulton Street • P.O. Box 88 • Troy, NY 12181-0088 • (518) 272-6300 • TWX: (710) 443-8156 • FAX: (518) 274-0366

Circle Reader Action No. 620



The Stack of Heat Shields in the lid of the crucible has progressively wider slots. The setbacks allow the silicon ribbon to radiate heat faster as it emerges from the melt through the slots.



# Space Proven

**FEI SPACE QUALIFIED DC-DC CONVERTERS  
DELIVER HI-REL PERFORMANCE ON TIME AND ON BUDGET!**



Frequency Electronics ... specialists in high-performance, space proven products ... having supplied more than 3,000 units in over 90 satellite programs, continues in that 27-year tradition with Hi-Rel, Rad-Hard DC to DC converters.

These units can meet your most demanding specifications by tailoring our standard modular designs.

If you want out of this world performance, with down to earth delivery and pricing, call Frequency Electronics today.

## DC-DC CONVERTER FEATURES:

- Radiation hardened
- Power density to 0.16 W/gm (5W/oz)
- Inputs to 100 V DC
- Efficiency to 85%
- Outputs to 200 W
- Regulation to 0.1%
- Multiple outputs



## FREQUENCY ELECTRONICS, INC.

55 Charles Lindbergh Blvd., Mitchel Field, NY 11553  
516-794-4500 • FAX: 516-794-4340

Circle Reader Action No. 640



## Estimating the SNR of AVIRIS Data

Improved estimates of noise are better suited to the needs of investigators.

Ames Research Center, Moffett Field, California

A combination of established statistical and filtering techniques yields improved estimates of the signal-to-noise ratio (SNR) of multispectral imagery produced by the Airborne Visible/Infrared Imaging Spectrometer (AVIRIS). The three methods used heretofore to estimate the SNR have been inadequate: the "laboratory" method inflates the SNR, while the "dark-current" and "image" methods deflate the SNR. The new method yields a more accurate estimate of the random variability in AVIRIS imagery.

The new combination of techniques is called the "geostatistical" method. In the first step of this method, periodic noise is removed by notch filtering in the frequency domain. In the subsequent steps, sensor noise and variability within picture elements are isolated by use of the semivariance of picture elements. This function is defined as follows:

$$\gamma(h) = (\frac{1}{2})E[z(x_i) - z(x_i + h)]^2$$

where  $\gamma(h)$  denotes the semivariance for all pairs of picture elements in which the members of each pair are a distance  $h$  (called the "lag") apart,  $x_i$  is the applicable coordinate of the  $i$ th picture element,  $E$  denotes the expectation operator, and  $z$  denotes the signal at a picture element. The function  $\gamma(h)$  or the plot thereof is called the "semivariogram" (see figure).

An unbiased estimate of  $\gamma(h)$  is obtained from a transect of  $m$  pairs of picture elements separated by the same lag distance, as follows:


$$\bar{S}^2 = (\frac{1}{2}m) \sum_{i=1}^m [z(x_i) - z(x_i + h)]^2$$

This is a useful measure of the difference between the signals at spatially separate

picture elements. The larger  $\bar{S}^2$  and, therefore,  $\gamma(h)$  is, the less similar the picture elements are.

Three aspects of the semivariogram are of interest here: the sill, which is the asymptotic upper-bound value of  $\gamma(h)$ ; the nugget variance (so named because it is reminiscent of a statistical measure used in prospecting for gold)  $C_0$ , which is the limit of  $\gamma(h)$  when  $h$  approaches 0; and the spatially dependent structural variance,  $C$ , which is the sill minus the nugget variance. By definition  $\gamma(h)$  equals zero when  $h = 0$ . In practice, the limit of  $\gamma(h)$  when  $h$  approaches 0 has a positive value because the nugget variance represents variability at scales smaller than a picture element. This phenomenon is a characteristic of the "regularized" semivariogram calculated for plot rather than point data.

The key argument upon which the geostatistical method is based is that the nugget variance is a sound estimate of the spatially-independent noise variance relevant to the investigator. This argument is intuitively acceptable because at the limit of  $\gamma(h)$ , when  $h$  approaches 0, the nugget variance does not have a spatial component and is composed almost entirely of random sensor noise and variability within picture elements. The statistical justification for this argument requires consideration of a one-dimensional mathematical model in which  $x$  is a continuous parameter giving the location along a linear transect. The observed signal  $z(x)$ , comprises both radiance  $r(x)$  (assumed to be stationary) and noise  $n(x)$ , which is assumed to be stationary, uncorrelated with  $r(x)$ , and not autocorrelated. It can be shown that the square root of the nugget variance can



The **semivariogram** of an image gives a measure of the difference between the signals at spatially-separate picture elements.

be used to estimate the standard deviation of the random noise and the variability within picture elements and, thereby, the SNR of AVIRIS data, via the equation

$$SNR \approx \bar{z} / \sqrt{C_0}$$

where  $\bar{z}$  = the average of the  $z_i$ . Because  $\bar{z}$  and  $\sqrt{C_0}$  depend on wavelength, this calculation should be done for the data in each spectral band sensed by the AVIRIS.

This work was done by Paul J. Curran of Ames Research Center and Jennifer L. Dungan of TGS Technology, Inc. Further information may be found in NASA TM-101035 [N89-15443], "Estimating the Signal-to-Noise Ratio of AVIRIS Data."

Copies may be purchased [prepayment required] from the National Technical Information Service, Springfield, Virginia 22161, Telephone No. (703) 487-4650. Rush orders may be placed for an extra fee by calling (800) 336-4700. ARC-12361

## Algorithm for Solution of Subset-Regression Problems

Subsets can be selected directly from originally defined regression parameters.

Ames Research Center, Moffett Field, California

A reliable and flexible algorithm for the solution of the subset-regression problem performs a QR decomposition with a new column-pivoting strategy, which enables the selection of the subset directly from the originally defined regression parameters. This feature, in combination with a number

of extensions, makes the algorithm very flexible for use in the analysis of subset-regression problems in which the parameters have physical meanings.

The subset-regression problem is the least-squares problem

$$\min. \|Ax - b\|$$

x

where  $A$  is an  $m \times n$  ( $m \geq n$ ) system matrix that contains some columns that are nearly linearly dependent on an independent set of columns. As used here, "nearly" means that small perturbations of  $A$  that are of the order of the inaccuracies in the entries of  $A$  establish the linear dependen-


$$u(x) = x \int_0^x y u(y) dy + x$$

$$u(x) = x e^{\frac{x^3}{3}}$$

## Imagine having the power to experiment...

Imagine having more time to ponder the abstract, rather than having to derive the solution.

With MACSYMA® *symbolic math software* you can!

No other software today packs the computational power, versatility, and reliability of MACSYMA. MACSYMA can tackle any mathematical application you may have, whether in algebra, calculus, trigonometry, or practically any other branch of higher mathematics. It gives you problem-solving tools such as Laplace and Fourier transforms, Taylor and Poisson series, solution of first and second order differential equations, solutions to integrals, and more. It gives you sophisticated 2-D and 3-D graphics, and can convert your equations into Fortran or 'C' for optimal numeric performance, or T<sub>E</sub>X for inclusion in publications.

MACSYMA provides unequalled accuracy too,

with your choice of exact or arbitrary precision arithmetic, and gives you results at speeds from 10 to 100 times faster than traditional methods.

All this power is remarkably easy to use. With the help of the User's Guide, extensive on-line documentation, executable examples and demonstrations, and the Quick Reference Card, a beginning MACSYMA user can quickly become proficient, tackling problems that might otherwise have been too difficult or time-consuming.

Whatever your application — engineering, science, economics or pure math — your work is too important to trust to any other math software. You deserve MACSYMA.

More than just a system for doing mathematics by computer, it's the power tool for mathematics.

*symbolics*, Inc.

MACSYMA Division

8 New England Executive Park East, Burlington, MA 01803 USA • 1-800-622-7962 (in Massachusetts, 617-221-1250.)

MACSYMA is a registered trademark of Symbolics, Inc. T<sub>E</sub>X is a trademark of the American Mathematical Society.


Circle Reader Action No. 524

# TableCurve™

One step fits  
221 equations to  
your X-Y data.  
Automatically.  
In less than  
7 seconds.\*

With TableCurve™ finding the best formula to fit your data couldn't be simpler...or faster.

- **Flexible Data Input** – input from Lotus™, dBase™, ASCII and many other file formats, or manually from the keyboard.
- **Data Manipulation** – smooth data, weight data, or apply standard math calculations.
- **Curve Fitting** – 221 candidate equations including Gaussian, log-normal, sigmoidal, sine, and user-defined—ranked by best fit and interactively displayed.



- **Speed\*** – an 8MHz PC AT, with math coprocessor, will process 221 equations (50 data points) in 6.8 seconds. More powerful systems are much faster.
- **Output** – supports most dot-matrix and LaserJet™ printers. Output directly to SigmaPlot 4.0™, Lotus, ASCII, and other formats.
- **Quality Interface** – pull down menus, mouse support and more.

To find out more about TableCurve or other scientific and engineering software from Jandel, just give us a call.


Free brochure 800-874-1888  
In CA 415-924-8640  
FAX: 415-924-2850 / Telex: 4931977  
In Europe: R.J.A. Handels GmbH, Germany  
Ph: 2101/666268 FAX: 2101/64321

**Jandel** "Microcomputer Tools  
for the Scientist"  
SCIENTIFIC  
65 Koch Road ■ Corte Madera, CA 94925


Circle Reader Action No. 580

## Analog Designers... COMTRAN® Is Now On The 386™

Automatic optimization adjusts selected component values of your topology to make its response fit your arbitrary target curves in magnitude, phase,  $Z_{in}$ ,  $Z_{out}$  or any combination. Multiple passes allow standard value capacitors in precision filters or other networks.



- COMTRAN® is fast. Each plot here was generated on screen in 6 seconds. Optimization took less than 3 minutes using a 25 MHz 386/387 (or an HP 310).
- COMTRAN® is an interactive, intuitive AC circuit analysis program that handles component entry, editing, analysis, optimization, and user scaled Linear/Log graphics in one program.
- COMTRAN®'s tolerance mode graphically shows the effect of real world components. Impedance mode plots impedance at ANY node in your circuit.



Actual Plotted Output of COMTRAN (Reduced Size)

- COMTRAN® can create, capture and analyze time domain data, then use it to stimulate your circuit and plot the result in either time or frequency domain.
- COMTRAN® has over 10 years of field experience on HP computers. Now it runs on 386™ machines, too. And it still drives HPGL plotters.
- COMTRAN® is modular—buy only what you need today. Ready-to-use packages start at under \$1000.

### COMTRAN® Integrated Software

A Division of Jensen Transformers, Inc.  
10735 BURBANK BOULEVARD, N. HOLLYWOOD, CA 91601  
FAX (818) 763-4574 PHONE (213) 876-0059

COMTRAN is a registered trademark of Jensen Transformers, Inc. 386 is a trademark of Intel Corporation.

cy. The task is to find the minimal number,  $k$ , of columns that constitute the independent set.

One numerically reliable technique used thus far to detect near dependencies is that of singular-value decomposition (SVD), which determines a minimal set of columns. However, the columns selected by SVD are linear combinations of the original columns of  $A$ . This is a major disadvantage in such practical subset-regression problems as the identification of the parameters of an aerodynamic model.

The QR decomposition of  $A$  is denoted as

$$Q^T A = \begin{bmatrix} R \\ 0 \end{bmatrix}$$

where  $R$  is an  $n \times n$  upper triangular matrix and

$$Q_0^T Q_0 = I_m$$

In contrast with the SVD, this decomposition does not involve a right orthogonal transformation of  $A$  that would obscure the selection of  $k$  individual columns of  $A$ . The only right transformation of  $A$  allowed in this technique is a permutation of columns.

The idea of column pivoting is to exploit the freedom introduced by this column permutation to solve the rank-deficient least-squares problem. Furthermore, it is not necessary to compute the full SVD of  $A$  to determine  $k$  because accurate estimates of the singular values, which enable such a determination, are also obtained.

The algorithm rearranges the columns of  $A$  as  $[a_{c_1} \dots a_{c_k} a_{c_{k+1}} \dots a_{c_n}]$ , where the vectors  $[a_{c_1} \dots a_{c_k}]$  correspond to the so-called identifiable or independent components  $x_b$  of  $x$ , and  $[a_{c_{k+1}} \dots a_{c_n}]$  correspond to the dependent ones. When a component of  $x$  is deemed not identifiable, because its corresponding estimated variance becomes unacceptably large, then another procedure for determining the dependencies more precisely corresponds to determining whether an unacceptable increase in the variances of the components of  $x_b$  occurs.

In physical applications, information is often available about which components of  $x$  have to be in  $x_b$ , and a priori estimates of individual components of  $x$  with corresponding variances are available. This information, inserted after a modified QR decomposition, enables one to interchange columns of  $[a_{c_1} \dots a_{c_k}]$  with columns of  $[a_{c_{k+1}} \dots a_{c_n}]$ .

The algorithm can also be extended to enable the joint processing of columns that are contaminated by noise with those that are free of noise, without using scaling techniques. This involves a two- or three-stage procedure in which one investigates the dependencies after a modified QR decomposition in which  $A$  is partitioned into noisy and noise-free parts.

This work was done by Michel Verhaegen of Ames Research Center. For further information, Circle 8 on the TSP Request Card. ARC-12145



- 69 Prosthetic Hand Lifts Heavy Loads
- 69 Rotationally Actuated Prosthetic Hand
- 70 Treating Wastewater With Immobilized Enzymes
- 70 Optical Computation of Matrices From Vectors

## Prosthetic Hand Lifts Heavy Loads

Features include ruggedness, simplicity, and relatively low cost.

*Marshall Space Flight Center, Alabama*

A prosthetic hand is designed to enable an amputee to lift diverse heavy objects like rocks and logs. The device is both simple and rugged. In addition, it costs less than do many other prosthetic hands, which are often awkward, bulky, heavy, and otherwise not well suited to strenuous lifting.

The new prosthetic hand (see figure) has no moving parts other than flexible straps that hold it in place. It includes a simple L-shaped metal end effector that is serrated to help prevent the lifted object from slipping off. The end effector is bolted into the end of a reinforced fiberglass cuff, which is fitted onto the remaining part of the forearm. A sock of cotton or similar material is placed over the remaining part of the forearm before inserting it in the cuff.


Hook-and-pile straps hold a flexible band on the upper arm. An inner strap and an outer strap extend downward from this flexible band to hold the cuff on the forearm. A loop strap, a front shoulder strap, and a back strap

(hidden in the figure) keep the flexible band and, therefore, the prosthetic hand from being pulled off by heavy loads. The back strap and the front shoulder strap are anchored by a ring to a front strap, which anchors the system of straps under the shoulder opposite that of the amputated hand.

A steel strip on the side of the cuff that faces the body protects the cuff against damage by the lifted object. A rubber sheath could be placed over the cuff for additional protection.

*This work was done by James R. Carden, William Norton, and Jewell G. Belcher of Marshall Space Flight Center and Thomas W. Vest of Management Services, Inc. For further information, Circle 133 on the TSP Request Card.*

*Inquiries concerning rights for the commercial use of this invention should be addressed to the Patent Counsel, Marshall Space Flight Center [see page 14]. Refer to MFS-28465.*



## Rotationally Actuated Prosthetic Hand

A simple mechanism is powered by rotation of the forearm.

*Marshall Space Flight Center, Alabama*

A prosthetic hand includes two pincerlike fingers that are actuated by rotation of the forearm. In comparison with "bionic" devices and body-powered artificial limbs that include cable controls, the prosthetic hand is simpler in design, is simpler to operate, weighs less, and takes up less space.

The prosthetic hand (see figure) is attached to the affected arm of an amputee at two places: (1) a plastic cuff slips over the end of the remaining part of the forearm, and (2) a flexible band with hook-and-pile (Velcro™ or equivalent) straps is wrapped around the upper arm just above the elbow. A pair of braces jointed at the elbow restrain the main body of the hand against rotation about the axis of the forearm. However, the forearm is free to rotate about its own axis, and as it does so it rotates the cuff, which is mounted at one end of a shaft supported by roller bearings in the main body.

An oval cam is mounted at the other end of the shaft; it rotates with the cuff and shaft. Two fingers attached to the main body are pressed toward each other and onto the


cam by a rubber band. The cam pushes the fingers apart by an amount that depends on its rotational position. When the forearm and cuff are rotated to a position at which the long dimension of the oval lies along the gap between the fingers, the fingers are spread apart to the maximum extent; when the forearm and cuff are rotated 90° from the foregoing position, the ends of the fingers are pressed together. Intermediate separa-

tions are obtained at intermediate rotational positions.

*This work was done by William E. Norton, Jewell G. Belcher, Jr., and James R. Carden of Marshall Space Flight Center and Thomas W. Vest of Management Services, Inc. For further information, Circle 148 on the TSP Request Card.*

*Inquiries concerning rights for the commercial use of this invention should be addressed to the Patent Counsel, Marshall Space Flight Center [see page 14]. Refer to MFS-28426.*

The **Prosthetic Hand** is attached to the end of the remaining part of the forearm and to the upper arm just above the elbow. The pincerlike fingers are pushed apart to a degree that depends on the rotation of the forearm.




## Treating Wastewater With Immobilized Enzymes

Urea and other contaminants are removed.

Marshall Space Flight Center, Alabama

Experiments have shown that enzymes can be immobilized on supporting materials to make biocatalyst beds for the treatment of wastewater. With a suitable combination of enzymes, the concentrations of various inorganic and organic contaminants, including ammonia and urea, can be reduced significantly.

The enzyme urease can be used to catalyze the decomposition of urea according to



In an experiment, urease was immobilized on a 1,6-hexanediamine derivative of silica that had been activated by Ti(IV) ions. The immobilized-enzyme material was packed in a 7.1-cm<sup>3</sup> column. A solution of 30 mg/L urea was passed through the column at a flow of 2.5 cm<sup>3</sup>/min, yielding a contact time of 2.8 min. Analysis of the first 29 liters of effluent showed that the column had catalyzed the reaction of nearly all measurable urea to NH<sub>3</sub> and CO<sub>2</sub>.

The enzyme alcohol oxidase can be used to catalyze the decomposition of alcohols and formaldehyde. In an experiment, alcohol oxidase was immobilized on derivatized silica, and the immobilized-enzyme material was packed in a 35-cm<sup>3</sup> column. A solution of 50 mg/L methanol saturated with oxygen was pumped through the column at a flow of 5 cm<sup>3</sup>/min, yielding a contact time of 7.1 min. Initially, the column removed all measurable methanol; it then began to lose activity because of degradation by H<sub>2</sub>O<sub>2</sub>.


To protect the alcohol oxidase, it is necessary to add enzymes that catalyze the decomposition of H<sub>2</sub>O<sub>2</sub> in situ. One proposed way to do this is to coimmobilize the alcohol oxidase with catalase and superox-

ide dismutase on derivatized silica. When such a mixture was tested in a 30 cm<sup>3</sup> column at a flow of 3.4 cm<sup>3</sup>/min (contact time 5 min), it removed 24 mg/L of ethanol from 3.2 L of 80 mg/L ethanol solution.

In a third experiment, a bed of immobilized urease and a bed of mixed resins were used to post-treat shower water that contained 15 mg/L urea and had been treated conventionally by multifiltration. As the figure shows, multifiltration did not remove urea from the water, but treatment by the column reduced the concentration of urea to below measurable levels. After

further treatment by the bed of mixed resins, the concentrations of all of the carbon bound in inorganic compounds (principally CO<sub>2</sub>) and of the ammonia from the decomposition of the urea were reduced below measurable levels. The total concentration of carbon bound in organic compounds in the effluent was 3.3 mg/L.

This work was done by Clifford D. Jolly of Umpqua Research Co. for Marshall Space Flight Center. For further information, Circle 164 on the TSP Request Card. MFS-26090



The concentrations of Nitrogen Bound in Ammonia and of Urea are shown at various stages in the treatment of shower water. The limits of detection are 1.0 mg/L for urea and 0.1 mg/L for N in NH<sub>3</sub>.

## Optical Computation of Matrices From Vectors

Four-wave mixing yields a two-dimensional pattern of light and dark.

NASA's Jet Propulsion Laboratory, Pasadena, California

A proposed optical apparatus would generate a rectangular pattern of light and dark areas, the brightnesses of which would represent the elements of the matrix product of two vectors. Optical multipliers of this type might be used as real-time analog tensor generators, components of neural networks, and generators of patterns to steer electromagnetic beams by diffraction or to effect temporary interconnections in very-large-scale integrated circuits.

The apparatus (see figure) would, in ef-

fect, compute the tensor product  $\mathbf{xy}^T$  (where  $T$  denotes the matrix transpose) of the vectors  $\mathbf{x}$  and  $\mathbf{y}$ , which would be represented by linear arrays of small areas of various degrees of transparency. A laser beam would pass through the horizontal strip transparency representing vector  $\mathbf{x}$ . The beam would be expanded by horizontal cylindrical lens  $L_1$ , then collimated by horizontal cylindrical lens  $L_2$ , forming columns of uniformly collimated light representing the components of  $\mathbf{x}$ . In a similar manner, a second laser beam coherent

with the first would pass through the vertical strip transparency representing  $\mathbf{y}^T$ , then through vertical cylindrical lenses  $L_3$  and  $L_4$  to form rows of uniformly collimated light representing the components of  $\mathbf{y}^T$ .


The row and column patterns of laser light would be applied to opposite faces of a photorefractive crystal. A plane-wave pumping laser beam coherent with the first two beams would be applied to the photorefractive crystal (e.g., LiNbO<sub>3</sub>) from a third direction through a beam splitter. An output beam representing the matrix product

would be generated by four-wave mixing. The intensity in the output beam would be distributed spatially in proportion to the product of the three input waves. The output beam would propagate in the direction opposite that of the pumping beam, out through the beam splitter to the output plane, where it would be fed to sensors, a projection screen, or possibly another optical computing apparatus.

*This work was done by Hua-Kuang Liu of Caltech for NASA's Jet Propulsion Laboratory. For further information, Circle 114 on the TSP Request Card.*

*This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive*


The **Photorefractive Effect** would give rise to four-wave mixing, which would generate an output beam modulated spatially by the matrix product  $xy^T$ .



*license for its commercial development should be addressed to the Patent*

*Counsel, NASA Resident Office-JPL [see page 14]. Refer to NPO-17512*

## 101 ways to set this woman free.



Quick. Send for this book. After all, with Watlow flexible heater technology, almost anything's possible. Need a way to handle a heating problem more efficiently, more economically? It's in the book. Want to see actual case histories? This book's full of 'em. Want truly better solutions? Just circle the reader service number or call (314) 878-4600 now.

**WATLOW**  
12001 Lackland Road  
St. Louis, MO 63146




Circle Reader Action No. 416

## New on the Market



The **XS-420 thermal imaging camera** from Xedar Corp., Boulder, CO, features an image resolution of 270 x 270 elements and provides approximately 0.2° C thermal resolution. The battery-powered camera—including 50 mm f/7 Germanium optic and 1.5" viewfinder—weighs 8.5 lbs., and is TV-compatible.  
**Circle Reader Action Number 772.**

Adhesives Research Inc., Glen Rock, PA, has introduced a line of **electrically-conductive pressure-sensitive tapes**. The technology can be incorporated into a variety of adhesives and coated onto conductive or nonconductive materials such as copper foil and pressure-sensitive foam and film tapes. Applications include foils and tapes in EMI/RFI shielding, replacements for low-voltage wires, bonding layers, and anti-static uses in computers and integrated circuits.  
**Circle Reader Action Number 770.**



The **Spaceball™**, from Spatial Systems Inc., Billerica, MA, is a **force-sensing input control device** which enables a computer user to manipulate screen images using simple hand movements. Users can move from axis to axis instantly by changing the direction of the force applied to the ball. Spaceball is supported on major graphics platforms including Silicon Graphics, Apollo, Sun, Intergraph, and Hewlett-Packard.  
**Circle Reader Action Number 776.**

The Boardmaster **digital diagnostic system** from United Electronic Industries, Watertown, MA, tests digital devices with up to 40 pins, including surface mount packages. The stand-alone system can test digital ICs in- or out-of-circuit. TTL, CMOS, LSI, static and dynamic memory and interface devices are among the test programs included in the system library. All results and pin conditions are displayed on the unit's integral VDU.  
**Circle Reader Action Number 766.**



The ECR904 **ion beam source** from Microscience Inc., Norwell, MA, combines ECR plasma technology with ion beam extraction optics. As the ECR process does not require a filament, 904GR can work with reactive gases for extended periods of time. Applications include RIBE, CAIBE for GaAs technology, precision milling for semiconductor laser fabrication, and optical structures.  
**Circle Reader Action Number 768.**

A demonstration kit from EG&C Electro-Optics, Salem, MA, shows how **pulsed xenon lighting and silicon photodiodes** can be used as a UV-visible light system for analytical equipment. The kit includes a pulsed xenon lamp with LITE-PAC® power supply, focusing optics, an integrated reference and signal channel with cuvette, and a channel for direct viewing of the light pulse.  
**Circle Reader Action Number 774.**



The Model 891 ruggedized miniature **CCD video camera** from Videospection, Salt Lake City, UT, features a compact, lightweight aluminum modular housing. The CCD image sensor incorporates an X1000 anti-blooming capability, zero percent geometric distortion, over 70 dB dynamic range, and low image retention. The camera complies with Mil-E-5400 airborne electronic equipment requirements and is available in US RS-170 or European CCIR sync standards.  
**Circle Reader Action Number 792.**




CubiCalc™, from HyperLogic Corp., Escondido, CA, is a **fuzzy logic decision system shell** that allows users to design, prototype, and test a complete fuzzy system on a PC without external equipment or programming. The shell contains a text editor for entry of the English-like rules which form the basis of the decision procedure and another editor for entry of spreadsheet-like expressions used to define data pre-processing and post-processing steps. Available for \$495, CubiCalc is based on IBM AT computers running Microsoft Windows.  
**Circle Reader Action Number 798.**

Designed to report **real-time dimensional measurement and data accumulation** for instant inspection of machined parts, the Computer-Aided Gaging (CAG) system from Edmunds Gages, Farmington, CT, monitors complex gaging operations through full cycle. Using 16 to 32 multiple and expandable inputs, the microprocessor-based system can be linked in any combination to produce automatic mastering, user-programmable master size and part tolerances, and statistical, histogram, and XR displays.  
**Circle Reader Action Number 740.**



Cotronics Corp., Brooklyn, NY, has developed a **ceramic putty** with a melting point above 3200° F. Made from asbestos-free aluminum-oxide-based ceramics, THERMEEZ™ is resistant to oxidizing and reducing atmospheres, molten nonferrous metals, steam, and most chemicals and solvents. Applications include molded ceramic fiber components, high-temperature insulation, and liquid metal handling.  
**Circle Reader Action Number 794.**



The LRY-1000 **laser rangefinder** from the Electro-Optics Division of Holometrix, Cambridge, MA, measures distances up to 30 km to an accuracy of ±10 cm. The system features a 90 millijoule Nd:YAG laser transceiver operating at 20 pulses per second, a control console, and a laser power supply. Its adjustable laser beam width enables the LRY-1000 to be used in a variety of ranging, tracking, surveying, mapping, and photogrammetric applications.  
**Circle Reader Action Number 800.**

A new **digital audio multiplexer**, the NV2000 High-Definition Audio System from NVision, Nevada City, CA, supports and simplifies multi-channel audio interconnection requirements, including HDTV, D-1/D-2, and Type C videotape recorders. It provides 20 bit encoding and distribution capability for multiple channels of program audio with 100 dB S/N in a studio environment. Program audio channels and ancillary signals are multiplexed together into one data stream, allowing one deck of a video routing switch to carry all program audio, time code, and cue information.  
**Circle Reader Action Number 796.**

## New on the Market

RepliCAD, a computer-aided design system which automates the design and simulation of replacement parts, has been introduced by Honeywell Inc., Minneapolis, MN. The system can distribute Simulation Program for Integrated Circuit Emulation (SPICE) simulations across an Apollo computer network. Once the simulations have been defined using the "click and point" menu-driven software, the system task manager automatically distributes the SPICE simulations to idle Apollo nodes based on user selections.

Circle Reader Action Number 788.



The MDL series of miniature collimated diode lasers from LaserMax Inc., Rochester, NY, can be TTL-modulated up to 1 KHz or modulated at 10 Hz with a built-in flash circuit. The 11 mm diameter by 28 mm lasers function on unregulated DC power and are suitable for optical disc interferometry, holography, and alignment.

Circle Reader Action Number 786.



The D4C series fiber optic connector from OFTI, Billerica, MA, incorporates an internal spring-loaded ferrule designed to eliminate the risk of signal interruption when the cable is pulled. The one-piece connectors are available for single-mode fibers and both 125 and 140  $\mu$ m clad, multimode fibers. They perform over a temperature range from -40° to +80°C.

Circle Reader Action Number 778.

PSSI/BIMA ergonomic chairs from Plug-In Storage® Systems Inc., Orange, CT, are suitable for use in ESD and class 10 clean room environments. Static charges are dissipated through the chairs to a conductive floor. Electrically-conductive upholstery prevents static generation. Available in desk and bench heights, all models have been independently tested to below the class 10 limits of Federal Standard 209D, Table 1, for all particle sizes.

Circle Reader Action Number 790.



New miniature CCD cameras from PULNiX, Sunnyvale, CA, measure two inches square and operate without support electronics. The TM-7 cameras feature a high-resolution (768H x 493V) 1/2" format interline CCD. Any C-mount lens may be used with the TM-7.

Circle Reader Action Number 782.

Optical Coating Laboratory Inc., Santa Rosa, CA, has developed MetaMode™, a fully-automated, high-rate coating process which produces sputtered thin films. A relatively "cold" process, MetaMode allows flat or irregularly shaped substrates such as glass or plastic to be coated at or near room temperature, usually eliminating the need for heating or cooling cycles.

Circle Reader Action Number 780.

## NOISE PROBLEMS? WHERE FIRE IS A RISK, SOUNDFOAM HT KEEPS ITS COOL.



Soundcoat's exclusive SOUNDFOAM HT is an ultra-light sound absorption material made of low density, flame resistant polyimide foam. This makes it the ideal material for acoustic and thermal insulation where fire safety is a primary concern. The material can be custom cut and supplied with a high performance pressure sensitive adhesive for fast, permanent production line assembly or field retrofitting.

SOUNDFOAM HT from Soundcoat. Cuts noise and keeps its cool within a temperature range of -150°C (-238°F) to +260°C (+500°F).

The noise stops here.

**SOUNDCOAT®**

One Burt Drive, Deer Park, NY 11729 • 516-242-2200 Ext. 56 • FAX: 516-242-2246  
3002 Croddy Way, Santa Ana, CA 92704 • 714-979-9202 • FAX: 714-979-0834  
Send for your free noise control bulletin No. 725 today.

Circle Reader Action No. 438

## "WE DON'T JUST DELIVER"




PHONE:  
201-964-3828  
201-964-5746

- Weatherhead Brass Fittings
- Weatherhead Pressure Hose and Fittings
- Electrical Products by Thomas and Betts

Overnight delivery anywhere in US  
24 hour order line 1-800-235-0473  
Most items shipped same day

A COMPLETE SERVICE TO THE INDUSTRIAL AND TRUCKING INDUSTRY



Circle Reader Action No. 515

# Thermoplastic Quick Couplings for plastic tubing.



One hand connect disconnect

**Free guide** to fittings and quick couplings for plastic tubing. New! 36 page catalog of quality products for flexible and semi rigid plastic tubing, 1/16" to 3/8" ID.



**CPC™ COLDER PRODUCTS CO.**

1001 Westgate Drive • St. Paul, MN 55114 • Call 612-645-0091

Circle Reader Action No. 517

## SPECIAL OFFER:

### APOLLO COMMEMORATIVE POSTER

Actual size: 30" x 21"—in full color!



Relive mankind's greatest adventure with this official NASA commemorative poster. A gorgeous full-color rendition of the Apollo moon landing printed on high-quality poster stock and shipped in a protective tube. Special introductory price only \$8.95 each. **BONUS:** Order now and receive three prints for just \$23.95.

Rush me \_\_\_\_\_ Apollo commemorative poster(s). I have enclosed \$ \_\_\_\_\_ plus \$3.00 for postage. (NY residents add sales tax.) Total enclosed: \$ \_\_\_\_\_

Name \_\_\_\_\_

Company \_\_\_\_\_


Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Mail with payment to: NASA Tech Briefs, Dept. F,  
41 East 42nd St., New York, NY 10017

For credit card orders call: (212) 490-3999

## New Literature



More than 1700 **controls and gages** are featured in a free catalog from Dwyer Instruments, Inc., Michigan City, IN. Included are pressure and differential pressure gages and switches, manometers, air filter gages, flowmeters, Pitot tubes, air velocity gages, and pressure transmitters for air and fluids. All provide 4-20 mA output signals for spans from 0-0.1" wc up to 0-2000 psi. **Circle Reader Action Number 720.**


A brochure describing **TEC PLOT™**, an **interactive plotting program** for visualizing engineering and scientific data, is available from Amtec Engineering Inc., Bellevue, WA. TEC PLOT integrates X-Y, 2D, and 3D plotting capabilities, and allows the display of multiple plots on the screen using windows. **Circle Reader Action Number 728.**



A four-color brochure from Technetics Corp., Deland, FL, describes **fiber metal products** including abrasible seals, acoustic products, and thermal barrier systems produced with and without plasma flame sprayed ceramic coatings. The brochure also covers the company's quality control procedures, engineering laboratory, and design and manufacturing capabilities. **Circle Reader Action Number 722.**

Kurta Corp., Phoenix, AZ, has produced a four-color brochure highlighting its line of **digitizers, pointing devices, and software solutions**. The centerfold spotlights the Kurta Studio, a Macintosh-based system for PageMaker, FreeHand, and Persuasion software which features a color-coordinated template. **Circle Reader Action Number 726.**

J.W. Lemmens Inc., St. Louis, MO, is offering two free technical papers on its equipment and procedure used in **nondestructive testing of refractory products**. The system measures a material's modulus of elasticity through impulse excitation and provides a reading of strength, porosity, wear rate, and thermal shock resistance. Because the system can be set up to test automatically, it makes total batch testing and grading practical. **Circle Reader Action Number 716.**



A free 216-page guide describes **motion control products** developed by Aerotech Inc., Pittsburgh, PA. The publication features motor-driven linear and rotary positioning stages, microstepping translators, stepping motors and drives, servo motors, amplifiers, and brushless drives. Also described is the UNIDEX™ motion controller line ranging from single-axis point-to-point microstepping controllers to the eight-axis UNIDEX 21 contouring motion controller. **Circle Reader Action Number 724.**



Penny & Giles Data Systems Inc., Rosewell, GA, has published an eight-page brochure on the **Multi-Band Data Recorder**, which features a wide range of direct, FM, and high-density digital recording (HDDR) formats, and track configurations up to 42 channels. The free brochure describes ECAL, a unique Electronic Channel Alignment that permits up to four user-programmable equalizer settings per channel for optimum performance in IRIG, non-IRIG, and HDDR operations. **Circle Reader Action Number 718.**

## New Literature


A *Practical Guide to Neural Nets*, from Addison-Wesley Publishing Co., Reading, MA, explores the state of the art in research, system development, and deployed applications. It explains how **neural networks** function and how to move from theory to application for development of a neural net to be embedded in an expert system. An IBM-compatible diskette is included which demonstrates a neural net in the process of learning.

Circle Reader Action Number 702.

A 38-page booklet from Anritsu America Inc., Oakland, NJ, describes five **optics control techniques**: high-speed modulation of lightwaves, control of optical waves via nonlinear optical effects, development of a hyper-coherent optical sweep generator using semiconductor lasers, phase conjugate optics using dye-doped films, and semiconductor quantum effect devices. The booklet includes technical data and diagrams.

Circle Reader Action Number 710.

### CURRENT RESEARCH AND STUDIES ON OPTICS CONTROL




Anritsu

*Virtual Reality: The Next Revolution in Computer/Human Interface*, from Matrix Information Services, Lathrup Village, MI, reports on **virtual reality R&D efforts** worldwide, identifying key players and likely future competition. It previews commercial systems, discusses current and future legal issues, and includes a bibliography and conference schedule.

Circle Reader Action Number 704.

Lambda/Ten Optics, Westford, MA, has published a catalog featuring its **optical instruments** and components, including laser beam expanders, Newtonian collimators, parabolic mirrors off-axis, front surface flat mirrors, and coatings. It describes each product's function, applications, design benefits, specifications, and optional features.

Circle Reader Action Number 714.




Ramey Aerospace, Carmel Valley, CA, has published the *Space Shuttle Entry Handbook*, a comprehensive **course in deorbit and entry, guidance, navigation and control, and flight procedures**. Based on NASA astronaut training materials, the 300-page softcover book includes data on aerodynamics and thermodynamics.

Circle Reader Action Number 706.

**Vacuum pumps and accessories** are described in a 16-page catalog from Vaccon Co. Inc., Medfield, MA. The catalog includes performance data, physical dimensions, factors to consider when selecting a vacuum pump, and pricing information. A comparison chart of Vaccon J-Series air-powered vacuum pumps to equivalent electrical pumps is also provided.


Circle Reader Action Number 712.



A free catalog spotlights axial leaded conformal coated **monolithic ceramic capacitors** from Murata Erie, Smyrna, GA. It contains specifications such as temperature characteristics, capacitance tolerance, and mechanical and environmental details. Tape and reel dimensions are also included.

Circle Reader Action Number 708.

## TAKE A CLOSER LOOK . . . . .




AND SEE WHY  
**SOUTH CAROLINA**  
RANKS AS ONE OF THE  
NATION'S TOP TEN  
LOCATIONS FOR  
MANUFACTURING.

For a free Prospectus contact:

**Palmetto Economic Development Corporation**  
Representing Central Electric Cooperative and Santee Cooper  
1201 Main Street, Suite 1710 • Columbia, SC 29201-3213  
Phone: (803) 254-9211 • FAX: (803) 771-0233

Circle Reader Action No. 392

## Knock Out NOISE



**AZONIC** delivers the Knock Out punch to noise. **AZONIC**, the noise control experts offer . . .

**LOWER** prices,  
**FASTER** delivery,  
**FRIENDLIER** service,  
**BETTER** performance,  
**IMPROVED** designs.

We are the noise control champions. Let us help you fight your noise control problems.

**SATISFACTION GUARANTEED**

**1-800-842-9790**



send for FREE brochure and sample.

© 1990, Azonic, Inc.

**AZONIC**

1610 East Cliff Road  
Burnsville, MN 55337  
FAX 1-612-894-2748  
in Canada 1-403-266-3130

# Pure and Simple.

Introducing VAT's unique Mini Gate, an innovative new vacuum valve.



Starting at only \$695

## Pure

- ▼ Virtually particle-free with no closing shock
- ▼ Low degassing
- ▼ Fully bakeable to 200°C
- ▼ Vacuum to UHV

## Simple

- ▼ Patented sealing principle uses only one moving part
- ▼ Extremely compact and lightweight
- ▼ 1", 1 1/2", or 2" I.D.
- ▼ Visual indicator for open/closed position

See the Mini Gates and other innovative valves in our new 225 page catalog, 'Vacuum Valves 90'.



600 West Cummings Park  
Woburn, MA 01801  
Tel: (617) 935-1446  
(800) 828-5625

# Subject Index

## A

**ADA (PROGRAMMING LANGUAGE)**  
General-purpose Ada software packages  
page 51 NPO-17983

**ADAPTIVE CONTROL**  
Experiments in adaptive control of a flexible structure  
page 31 NPO-17846

**AERODYNAMICS**  
Computing the dynamics of helicopters  
page 46 ARC-12337

**AIRBORNE LASERS**  
Airborne laser polarization sensor  
page 34 GSC-13314

**ALGORITHMS**  
Algorithm for solution of subset-regression problems  
page 66 ARC-12145

**ALUMINUM GRAPHITE COMPOSITES**  
Open-section composite structural elements  
page 45 MFS-26112

**ARC WELDING**  
Fast, nonspattering inert-gas welding  
page 61 MFS-29648

**ARCHITECTURE (COMPUTERS)**  
Algorithmically specialized parallel architecture for robotics  
page 22 NPO-17632

## B

**BALL BEARINGS**  
Low-wear ball-bearing separator  
page 56 MFS-29666

**BEARINGS**  
Lubrication of nonconformal contacts  
page 57 LEW-14882

**BOUNDARY LAYER CONTROL**  
Making large suction panels for laminar-flow control  
page 61 LAR-13844

## C

**CALIBRATING**  
Statistical partial calibration of polarimetric SAR imagery  
page 40 NPO-17888

**COMMUNICATION NETWORKS**  
Quad-port transceivers for a dual-CRR LAN  
page 28 NPO-17541

**COMPOSITE STRUCTURES**  
Open-section composite structural elements  
page 45 MFS-26112

**COMPUTATIONAL FLUID DYNAMICS**  
Faster algorithm for computation of incompressible flow  
page 52 ARC-12370

Simulation of flow in a turbine cascade  
page 58 ARC-12551

**COMPUTATIONAL GRIDS**  
Semiautomatic design of zonal computational grids  
page 52 ARC-12322

**COMPUTER PROGRAMS**  
Estimating the cost of developing software  
page 48 NPO-17936

**COMPUTERIZED SIMULATION**  
Displaying computer simulations of physical phenomena  
page 32 ARC-12502

**CONDUCTORS**  
Testing conductive films for continuity  
page 41 NPO-17938

**CORNEA**  
Two-wavelength interferometric keratometer  
page 39 NPO-17537

**COST ESTIMATES**  
Estimating the cost of developing software  
page 48 NPO-17936

**CRYOGENIC EQUIPMENT**  
Low-wear ball-bearing separator  
page 56 MFS-29666

**CRYSTAL GROWTH**  
Modified furnace makes more silicon ribbon  
page 64 NPO-17350

## D

**DATA PROCESSING**  
Optical backplane interconnection  
page 20 LAR-14052

## E

**EARTH RESOURCES SURVEY AIRCRAFT**  
Measuring wildfires from aircraft and satellites  
page 40 ARC-12132

**EDUCATION**  
Displaying computer simulations of physical phenomena  
page 32 ARC-12502

**ELASTOHYDRODYNAMICS**  
Lubrication of nonconformal contacts  
page 57 LEW-14882

**ELECTRIC DISCHARGES**  
Electrical-discharge machining with additional axis  
page 63 MFS-29630

**ERROR CORRECTING DEVICES**  
Self-testing static random-access memory  
page 30 NPO-17939

**EYE (ANATOMY)**  
Two-wavelength interferometric keratometer  
page 39 NPO-17537

## F

**FARADAY EFFECT**  
Optical isolators with transverse magnet  
page 36 LAR-14092

**FIXTURES**  
O-ring-testing fixture  
page 54 MFS-28414

**FLEXIBLE BODIES**  
Experiments in adaptive control of a flexible structure  
page 31 NPO-17846

**FLIGHT CHARACTERISTICS**  
Computing the dynamics of helicopters  
page 46 ARC-12337

**FLUID DYNAMICS**  
Semiautomatic design of zonal computational grids  
page 52 ARC-12322

Simulation of flow in a turbine cascade  
page 58 ARC-12551

**FLUID FLOW**  
High-resolution computations of hypersonic flows  
page 57 ARC-12254

**FOREST FIRES**  
Measuring wildfires from aircraft and satellites  
page 40 ARC-12132

**FURNACES**  
Modified furnace makes more silicon ribbon  
page 64 NPO-17350

## G

**GALLIUM ARSENIDES**  
V-grooved GaAs solar cell  
page 16 LEW-14954

**GAS FLOW**  
High-resolution computations of hypersonic flows  
page 57 ARC-12254

**GAS TUNGSTEN ARC WELDING**  
Fast, nonspattering inert-gas welding  
page 61 MFS-29648

## H

**HAND (ANATOMY)**  
Prosthetic hand lifts heavy loads  
page 69 MFS-28465

Rotationally actuated prosthetic hand  
page 69 MFS-28426

**HEAT TRANSFER**  
Oscillating thermal switch  
page 34 NPO-17125

**HELICOPTER PERFORMANCE**  
Computing the dynamics of helicopters  
page 46 ARC-12337

**HIGH LEVEL LANGUAGES**  
General-purpose Ada software packages  
page 51 NPO-17983

# TECHNOLOGY TRANSFER AT IT'S BEST

NASA's annual report Spinoff informs the public about your new product incorporating space technology. Want to be included in the next issue? For details call 301-859-5300 Ext 242.

Circle Reader Action No. 366



## Quality Precision Assemblies & Components

**SINCE 1962 • Custom • Stock**  
At Sterling we're equipped to handle your entire assembly project starting with the creative engineering phase.  
**Call for FREE brochure.**

**S Sterling Instrument**  
2101 Jericho Turnpike,  
New Hyde Park, NY 11040  
Phone: (516) 328-3300  
Fax: (516) 326-8827



## PEM® SELF-CLINCHING & BROACHING FASTENERS

- strong, quality threads in metal and P.C. boards too thin to be tapped.
- variations include free-running, self-locking, floating and blind hole types meeting Unified, ISO and MIL standards.
- Available in steel, stainless steel and aluminum.




For your **FREE** condensed catalog, circle the number below. However, for a complete fastener specifications & design data catalog, call 1-800-237-4736. Or FAX us at 215-766-0143.



104


©1991

Circle Reader Action No. 339



Imagine a lightweight metal foil with a mesh-like, single-unit structure that eliminates the unraveling and contact resistance of woven mesh.

Imagine it with superior EMI/RFI/ESD shielding, electrical and heat transfer properties.



Imagine it wrapping, laminating, contracting, expanding.


Now imagine how you'd use it.

Call 203/481-4277 for a free sample of MicroGrid®.



Circle Reader Action No. 316

## Free Standing Wire Grid Polarizers For Spectroscopy at Millimeter and Sub-millimeter wavelength




### Applications

- FAR-IR Wavelength Polarization
  - Interferometer Beam Divider
  - Variable Reflector
  - Coupling Device for Long Wavelength Lasers
  - Suitable for High Vacuum and Cryogenic Conditions
- Custom design available

Another quality product from **SPECAC**

**SPECAC ANALYTICAL INC.**  
301 Commerce Drive Tel (203) 366-5112  
Fairfield, CT 06430 Fax (203) 384-1524  
A Cambridge Electronics Industries (CEI) Company  
Circle Reader Action No. 621



## SC/FOX™ Embedded-System Computers

**SC/FOX VME SBC (Single Board Computer)** 18 MIPS, 60 MIPS burst, general-purpose, slot-1 Master/Slave System Controller. Up to 640K bytes 0-ws memory, 1 SCSI, 1 ptr, 2 serial ports. Uses 16-bit Harris RTX 2000.

**SC/FOX PCS (Parallel Coprocessor System)** 15 MIPS, 50 MIPS burst, general purpose PC/AT/386 plug-in board, 32K to 1M byte 0-ws static memory, multiple PCS operation, SCSI option. Uses Harris RTX 2000.

**SC/FOX SBC (Single Board Computer)** 18 MIPS, 60 MIPS burst, Stand-alone operation, Eurocard size, 1 ptr, 1 serial port, up to 512K bytes 0-ws memory, 2 50-pin user connectors, SCSI option. Uses Harris RTX 2000.

**SC/FOX PCS32 (Parallel Coprocessor System 32)** 15 MIPS to 70 MIPS, general-purpose PC/AT/386 32-bit plug-in board with 64K to 1M byte 0-ws static memory. Uses 32-bit SC32 Forth microprocessor.

Ideal for embedded real-time control, data acquisition, or high-speed processing. Forth software included, C optional. OEM pricing.

**SILICON COMPOSERS INC (415) 322-8763**  
208 California Ave., Palo Alto, CA 94306  
Circle Reader Action No. 679

## More than 450 pages of tooling components!



This illustrated complete line catalog includes component parts for jigs and fixtures, chuck jaws, plug gauges, threaded inserts, stainless steel tooling components, toggle clamps, SWIFTSURE power workholding devices, drill jig bushings, locking pins, and modular fixturing. Completely illustrated. Send for your free copy.



Circle Reader Action No. 429

## RELIABILITY AND MAINTAINABILITY PREDICTION AND FMECA ANALYSIS SOFTWARE


Hundreds have used this leading computer-aided engineering software since 1982.

Powertronic Systems offers software to predict Reliability and Maintainability and for Failure Modes Effects and Criticality Analysis. Hundreds of users have selected from PSI's large, versatile and integrated software family for military and industrial equipment and for both electrical and mechanical systems. And, these programs are either interactive or can be input from batch modes from existing CAE or database programs.

Programs implement MIL-STD-1629; MIL-HDBK-217 including E Notice 1; and MIL-HDBK-472.

**PSI Powertronic Systems, Inc.**  
P.O. Box 29109 New Orleans 70189  
(504) 254-0383 FAX (504) 254-0393

Circle Reader Action No. 593



## FREE!

**CATALOG of REAL TIME DATA ACQUISITION PRODUCTS for the PC**

Filled with applications information, competitive comparisons, waveform analysis techniques, hardware and software specifications, and DEMO DISK!

We manufacture the industry's fastest data acquisition hardware and software designed for applications that demand a true real time display with simultaneous disk streaming. Call us at...

1-800-553-9006

**DATAQ INSTRUMENTS, INC**  
825 Sweitzer Avenue  
Akron, Ohio 44311  
Tel(216)434-4284 Fax(216) 434-5551

Circle Reader Action No. 505



## FREE! 130 Page Catalog


“Optics for Industry”

Free 130 page product catalog from Rolyn, world's largest supplier of "Off-the-Shelf" optics. 24-hour delivery of simple or compound lenses, filters, prisms, mirrors, beamsplitters, reticles, objectives, eyepieces plus thousands of other stock items. Rolyn also supplies custom products and coatings in prototype or production quantities. **ROLYN OPTICS Co.,** 706 Arrowgrand Circle, Covina, CA 91722-2199, (818)915- 5707, FAX (818)915-1379

Circle Reader Action No. 551

## IMAGE ANGSTROMS TO MICRONS Service Provided

ATOMIC FORCE MICROSCOPY  
SCANNING TUNNELING MICROSCOPY  
SCANNING TUNNELING SPECTROSCOPY



MICA ATOMS: Viewed with Atomic Force Microscope

Surface analysis and roughness done on ceramics, metals, polymers, semiconductors. Typical applications:

Sputtered and plated surfaces	Polished surfaces
CVD and ion implantation	Integrated circuits
Computer disks and tapes	Laser disk stamper
Nano machined surfaces	Diffraction gratings

Contact: Dr. Thomas L. Altshuler (508) 369-9033  
Advanced Materials Laboratory, Inc.  
242 Baker Avenue, Concord, MA 01742

Circle Reader Action No. 447

## VOLTAGE SELECTABLE INTERNATIONAL SYSTEM



Z-LINE TPC 884

The TPC, a voltage-selectable AC power distribution and control system, can have either 120 or 240 volt input and output. Designed with IEC-, UL-, CSA- and VDE- approved components, operating up to 16 amps in Europe and 20 amps in North America. Size: 19.0" x 1.75" x 7.0". EMI/RFI filtering, spike/surge suppression and overload circuit breaker protection are standard. Remote on/off is optional.

**Pulizzi Engineering, Inc.**  
3260 S. Susan St.,  
Santa Ana, CA 92714  
714/540-4229 FAX: 714/641-9062

Circle Reader Action No. 497



## Reel Moments: A History of Flight and Space

From Kitty Hawk to the Space Shuttle, this exciting videotape chronicles the successes and innovations, the heroes and inventors, in air and space travel. Includes vintage newsreel footage. (VHS, 40 minutes) \$19.95 each plus \$3.00 postage and handling.

Name \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Total Enclosed: \$ \_\_\_\_\_

Send check or money order to:  
**NASA Tech Briefs, Fulfillment Dept.**  
41 East 42nd Street, New York, NY 10017

## FREE PC Systems Handbook for Scientists & Engineers

Configure Your Own Data Acquisition Systems:  
Take Control while you Save Thousands of Dollars!!

Have you ever wanted to enjoy the many benefits of configuring your own PC-based Data Acquisition or Instrumentation system, but you didn't know where to begin? The PC Systems Handbook will lead you every step of the way, explaining all aspects of systems configuration with easy-to-understand text and clearly documented diagrams. A detailed glossary and two-dozen "Tech Notes" help you understand the terminology. Our new Spring 1991 Edition is expanded to 132 pages with a hard spine, making it suitable as a permanent addition to your bookshelf. And there is absolutely no charge for this invaluable reference.

### Topics Covered Include:

- Industrial Rack-Mount PC's — AT & 80386
- Real-Time Data Acquisition & Process Control Software
- PC Plug-in Boards for Analog/Digital, Digital/Analog, & Digital I/O
- Connect your PC to Test Instrumentation with IEEE-488, RS-232, RS-422
- Stepping and Servo Motor Control with your Personal Computer

Call 1 (800) 341-2525 or (203) 483-8815 (CT & Overseas)



Circle Reader Action No. 371



Climb aboard the world's best fighter aircraft—the F-16 Falcon, F-15 Eagle, and F-117—for high flying adventure! This action-packed VHS videotape features real combat footage. \$19.95 each plus \$3.00 postage. NY residents add sales tax.

Name \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_

State \_\_\_\_\_ Zip \_\_\_\_\_

Total enclosed: \_\_\_\_\_  
for \_\_\_\_\_ Jet videos.

Send check or money order to:  
**NASA Tech Briefs, Dept. F**  
41 East 42nd St.,  
New York, NY 10017

**HUMAN FACTORS ENGINEERING**  
YAMM — yet another menu manager  
page 47 NPO-17769

**HYPERSONIC FLOW**  
High-resolution computations of hypersonic flows  
page 57 ARC-12254

**INCOMPRESSIBLE FLOW**  
Faster algorithm for computation of incompressible flow  
page 52 ARC-12370

**INFRARED IMAGERY**  
Estimating the SNR of AVIRIS data  
page 66 ARC-12361

**INTERFEROMETRY**  
Two-wavelength interferometric keratometer  
page 39 NPO-17537

**IRIDIUM**  
Molecular-beam epitaxy of IrSi<sub>3</sub>  
page 60 NPO-17953

**LAMINAR FLOW**  
Making large suction panels for laminar-flow control  
page 61 LAR-13844

**LASER MATERIALS**  
Long-lifetime laser materials for effective diode pumping  
page 42 LAR-13807

**LASERS**  
Semiconductor laser with multilayer dielectric reflector  
page 18 NPO-17763

**LEARNING MACHINES**  
Simplified learning scheme for analog neural network  
page 26 NPO-17664

**LINKAGES**  
Low-thermal-conduction links for silicon sensors  
page 38 GSC-13321

**LOCAL AREA NETWORKS**  
Quad-port transceivers for a dual-CRR LAN  
page 28 NPO-17541

**LOGIC CIRCUITS**  
Simplified learning scheme for analog neural network  
page 26 NPO-17664

**LUBRICATION**  
Lubrication of nonconformal contacts  
page 57 LEW-14882

**MACHINING**  
Electrical-discharge machining with additional axis  
page 63 MFS-29630

**MAGNETO-OPTICS**  
Optical isolators with transverse magnet  
page 36 LAR-14092

**MAN-COMPUTER INTERFACE**  
YAMM — yet another menu manager  
page 47 NPO-17769

**MATRICES (MATHEMATICS)**  
Optical computation of matrices from vectors  
page 70 NPO-17512

**MEDICAL EQUIPMENT**  
Prosthetic hand lifts heavy loads  
page 69 MFS-28465  
Rotationally actuated prosthetic hand  
page 69 MFS-28426

**MEISSNER EFFECT**  
Meissner-effect stepping motor  
page 59 MFS-28409

**MINERAL OILS**  
Hot oil removes wax  
page 60 MFS-29713

**MOLECULAR BEAM EPITAXY**  
Molecular-beam epitaxy of IrSi<sub>3</sub>  
page 60 NPO-17953

**MOTORS**  
Meissner-effect stepping motor  
page 59 MFS-28409

**MULLITES**  
Phase transformations in multite-precursor xerogels  
page 44 LEW-14898

**NAVIER-STOKES EQUATION**  
Faster algorithm for computation of incompressible flow  
page 52 ARC-12370

**NEODYMIUM LASERS**  
Long-lifetime laser materials for effective diode pumping  
page 42 LAR-13807

**NEURAL NETWORKS**  
Neural networks of VLSI components  
page 24 NPO-17833

**NONDESTRUCTIVE TESTS**  
Testing conductive films for continuity  
page 41 NPO-17938

**O RING SEALS**  
O-ring-testing fixture  
page 54 MFS-28414

**OPTICAL COMMUNICATION**  
Optical backplane interconnection  
page 20 LAR-14052

**OPTICAL COMPUTERS**  
Optical computation of matrices from vectors  
page 70 NPO-17512

**OPTICAL EQUIPMENT**  
Optical isolators with transverse magnet  
page 36 LAR-14092

**PARALLEL PROCESSING (COMPUTERS)**  
Algorithmically specialized parallel architecture for robotics  
page 22 NPO-17632  
Neural networks of VLSI components  
page 24 NPO-17833

Optical backplane  
interconnection  
page 20 LAR-14052

**PHASE TRANSFORMATIONS**  
Phase transformations in  
multilayer-precursor xerogels  
page 44 LEW-14898

**PHOTOVOLTAIC CELLS**  
V-grooved GaAs solar  
cell  
page 16 LEW-14954

**PHYSICAL SCIENCES**  
Displaying computer  
simulations of physical  
phenomena  
page 32 ARC-12502

**PLASMA ARC WELDING**  
Fast, nonspattering inert-  
gas welding  
page 61 MFS-29648

**POLARIMETRY**  
Statistical partial calibra-  
tion of polarimetric SAR  
imagery  
page 40 NPO-17888

**POLARIZED LIGHT**  
Airborne laser polariza-  
tion sensor  
page 34 GSC-13314

**PRODUCT DEVELOPMENT**  
Estimating the cost of  
developing software  
page 48 NPO-17936

**PROGRAMMING LANGUAGES**  
General-purpose Ada  
software packages  
page 51 NPO-17983

**PROSTHETIC DEVICES**  
Prosthetic hand lifts  
heavy loads  
page 69 MFS-28465  
Rotationally actuated pro-  
sthetic hand  
page 69 MFS-28426

## R

**RANDOM ACCESS MEMORY**  
Self-testing static  
random-access memory  
page 30 NPO-17939

**REFLECTORS**  
Semiconductor laser with  
multilayer dielectric  
reflector  
page 18 NPO-17763

**REFRIGERATORS**  
Oscillating thermal switch  
page 34 NPO-17125

**REGRESSION ANALYSIS**  
Algorithm for solution of  
subset-regression  
problems  
page 66 ARC-12145

**REMOTE SENSING**  
Measuring wildfires from  
aircraft and satellites  
page 40 ARC-12132

Estimating the SNR of  
AVIRIS data  
page 66 ARC-12361

**REMOTE SENSORS**  
Airborne laser polariza-  
tion sensor  
page 34 GSC-13314

**ROBOTICS**  
Algorithmically special-  
ized parallel architecture  
for robotics  
page 22 NPO-17632

## S

**SEALS (STOPPERS)**  
O-ring-testing fixture  
page 54 MFS-28414

**SELF TESTS**  
Self-testing static  
random-access memory  
page 30 NPO-17939

**SEMICONDUCTOR DEVICES**  
Molecular-beam epitaxy  
of IrSi<sub>2</sub>  
page 60 NPO-17953

**SEMICONDUCTOR DIODES**  
Long-lifetime laser  
materials for effective  
diode pumping  
page 42 LAR-13807

**SEMICONDUCTOR LASERS**  
Semiconductor laser with  
multilayer dielectric  
reflector  
page 18 NPO-17763

**SET THEORY**  
Algorithm for solution of  
subset-regression  
problems  
page 66 ARC-12145

**SIGNAL TO NOISE RATIOS**  
Estimating the SNR of  
AVIRIS data  
page 66 ARC-12361

**SILICIDES**  
Molecular-beam epitaxy  
of IrSi<sub>2</sub>  
page 60 NPO-17953

**SILICON**  
Modified furnace makes  
more silicon ribbon  
page 64 NPO-17350

**SILICON RADIATION DETECTORS**  
Low-thermal-conduction  
links for silicon sensors  
page 38 GSC-13321

**SIMULATION**  
Displaying computer  
simulations of physical  
phenomena  
page 32 ARC-12502

**SLURRIES**  
Phase transformations in  
multilayer-precursor xerogels  
page 44 LEW-14898

**SOFTWARE TOOLS**  
YAMM — yet another  
menu manager  
page 47 NPO-17769

**SOLAR CELLS**  
V-grooved GaAs solar  
cell  
page 16 LEW-14954

**SOLID LUBRICANTS**  
Low-wear ball-bearing  
separator  
page 56 MFS-29666

**SOLVENTS**  
Hot oil removes wax  
page 60 MFS-29713

**SPARK MACHINING**  
Electrical-discharge  
machining with additional  
axis  
page 63 MFS-29630

**STEPPING MOTORS**  
Meissner-effect stepping  
motor  
page 59 MFS-28409

**STRUCTURAL MEMBERS**  
Open-section composite  
structural elements  
page 45 MFS-26112

**SWITCHES**  
Oscillating thermal switch  
page 34 NPO-17125

**SYNTHETIC APERTURE RADAR**  
Statistical partial calibra-  
tion of polarimetric SAR  
imagery  
page 40 NPO-17888

# Does It Move?

If your product or system involves motion, and you need accurate loads, displacements, velocities, accelerations, forces or motion path information...you need ADAMS®.

*The World's First Choice for Multibody System Analysis*

## ADAMS

Mechanical Dynamics, Inc. ▲ 2301 Commonwealth ▲ Ann Arbor, MI 48105 ▲ 313-994-3800

Circle Reader Action No. 548



## OUTER SPACE ADVENTURE

Experience the thunderous power of Space Shuttle launches, bouncing moon walks, and weightless space ballet — all in the action-packed VHS videotape SPACE SCAPES, featuring rare footage gleaned from NASA's film archives. This visual treat is set to the award-winning music of Jan Hammer. (Color, 30 minutes) Only \$19.95 each plus \$3.00 postage and handling.

Name \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_  
State \_\_\_\_\_ Zip \_\_\_\_\_  
Total Enclosed: \$ \_\_\_\_\_  
for \_\_\_\_\_ (quantity) Space  
Scapes videotapes.  
Send check or money order to:  
**NASA Tech Briefs, Dept. F**  
41 East 42nd St.  
New York, NY 10017



## Special Offer: Official NASA Caps

Black or white cap with gold leaves and official NASA insignia. A great gift item. Only \$8.95 each!

Rush me: \_\_\_\_\_ black \_\_\_\_\_ white  
NASA cap(s).  
Add \$2.50 for postage. NY residents add  
sales tax.  
Total Enclosed: \$ \_\_\_\_\_  
Name \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_  
State \_\_\_\_\_ Zip \_\_\_\_\_  
Mail payment to:  
**NASA Tech Briefs,**  
41 East 42nd St.,  
New York, NY 10017

**T**

**THERMAL INSULATION**  
Low-thermal-conduction links for silicon sensors  
page 38 GSC-13321

**THIN FILMS**  
Testing conductive films for continuity  
page 41 NPO-17938

**TRANSMITTER RECEIVERS**  
Quad-port transceivers for a dual-CRR LAN  
page 28 NPO-17541

**TURBINES**  
Simulation of flow in a turbine cascade  
page 58 ARC-12551

**TWO DIMENSIONAL FLOW**  
Semiautomatic design of zonal computational grids  
page 52 ARC-12322

**U**

**UREAS**  
Treating wastewater with immobilized enzymes  
page 70 MFS-26090

**USER REQUIREMENTS**  
YAMM — yet another menu manager  
page 47 NPO-17769

**V**

**VECTORS (MATHEMATICS)**  
Optical computation of matrices from vectors  
page 70 NPO-17512

**VERY LARGE SCALE INTEGRATION**  
Neural networks of VLSI components  
page 24 NPO-17833

**VIBRATION DAMPING**  
Experiments in adaptive control of a flexible structure  
page 31 NPO-17846

**W**

**WASTE WATER**  
Treating wastewater with immobilized enzymes  
page 70 MFS-26090

**WATER TREATMENT**  
Treating wastewater with immobilized enzymes  
page 70 MFS-26090

**WAXES**  
Hot oil removes wax  
page 60 MFS-29713

**WINGS**  
Making large suction panels for laminar-flow control  
page 61 LAR-13844

# Advertisers Index

3-D Visions ..... (RAC 669) ..... 9  
Advanced Materials  
Laboratory ..... (RAC 447) ..... 78  
AEROCON 91 ..... (RAC 488) ..... 80  
Aerospace Optics, Inc. .... (RAC 309) ..... 21  
Algor Interactive Systems, Inc. (RAC 361) ..... 57  
AMP ..... (RAC 657) .. COV III  
ANA Brass ..... (RAC 515) ..... 73  
Anritsu America, Inc. .... (RAC 507) .. COV IV  
Apollo Commemorative Poster ..... 74  
Astro-Med, Inc. .... (RAC 405) ..... 29  
Astron ..... (RAC 304) ..... 5  
Azonic, Inc. .... (RAC 478) ..... 75  
CAJON Company ..... (RAC 380) ..... 62  
Carr Lane Manufacturing Co. (RAC 429) ..... 77  
Colder Products Company .... (RAC 517) ..... 74  
Comtran Integrated Software .. (RAC 480) ..... 68  
Contemporary Cybernetics  
Group ..... (RAC 411) ..... 33  
Cyber Research, Inc. .... (RAC 371) ..... 78  
Dataq Instruments, Inc. .... (RAC 505) ..... 77  
Delkor Corporation ..... (RAC 316) ..... 77  
Dolphin Scientific ..... (RAC 510) ..... 32  
Elmo Manufacturing Corp. .... (RAC 509) ..... 63  
Encore Computer Corp. .... (RAC 353) ..... 13  
Erie Engineered Products, Inc. (RAC 536) ..... 35

ERIM ..... (RAC 475) ..... 56  
Flexbar Machine Corporation (RAC 534) ..... 41  
Fluoramics, Inc. .... (RAC 364) ..... 5  
Frequency Electronics, Inc. .. (RAC 640) ..... 65  
Gould Recording Systems .... (RAC 483) ..... 7  
Hardigg Industries, Inc. .... (RAC 492) ..... 31  
Heimann Systems ..... (RAC 484) ..... 51  
Hitachi Chemical Co., Ltd. .... (RAC 460) ..... 27  
Humphrey, Inc. .... (RAC 626) ..... 46  
INCO Specialty  
Powder Products ..... (RAC 452) ..... 55  
Inframetrics ..... (RAC 370) ..... 4  
Instrument Technology, Inc. .. (RAC 554) ..... 51  
Jandel Scientific ..... (RAC 580) ..... 68  
MACSYMA/SYMBOLICS ..... (RAC 524) ..... 67  
Magna-Lock, U.S.A. .... (RAC 419) ..... 48  
Martin Marietta ..... COV II-1  
MathSoft, Inc. .... (RAC 682) ..... 15  
Mechanical Dynamics ..... (RAC 548) ..... 79  
Melles Griot ..... (RAC 417) ..... 39  
Meridian Laboratory ..... (RAC 377) ..... 46  
Mitchell & Gauthier Associates (RAC 527) ..... 44  
National Design Engineering  
Show & Conference ..... (RAC 588) ..... 81  
National Instruments ..... (RAC 681) ..... 82  
National Standards Assoc. .... (RAC 415) ..... 12  
Nicolet Instruments ..... (RAC 696) ..... 17  
Oracle Corporation ..... (RAC 494) ..... 23  
Palmetto Economic  
Development Corp. .... (RAC 392) ..... 75  
Parker Metal Bellows ..... (RAC 519) ..... 20  
Patton & Patton  
Software Corporation ..... (RAC 499) ..... 30  
Penn Engineering &  
Manufacturing Corp. .... (RAC 339) ..... 77  
Photovolt ..... (RAC 562) ..... 42  
Powertronic Systems, Inc. .... (RAC 593) ..... 77  
Pulizzi Engineering, Inc. .... (RAC 497) ..... 78  
RGB Spectrum ..... (RAC 467) ..... 8  
Rolyon Optics Co. .... (RAC 551) ..... 7  
RR Software, Inc. .... (RAC 564) ..... 53  
Shin-Etsu Silicones of America (RAC 617) ..... 43  
Silicon Composers, Inc. .... (RAC 679) ..... 77  
Specac Analytical, Inc. .... (RAC 621) ..... 77  
Sterling Instruments ..... (RAC 391,556) .. 77  
Structural Research and  
Analysis Corporation ..... (RAC 676) ..... 3  
TEAC America, Inc. .... (RAC 344) ..... 19  
Technology 2000 Proceedings ..... 32  
Technology 2001 ..... (RAC 700,701) .. 37  
Teledyne Gurley ..... (RAC 620) ..... 64  
The MathWorks, Inc. .... (RAC 503) ..... 25  
The Soundcoat  
Company, Inc. .... (RAC 438) ..... 73  
Tiodize ..... (RAC 422) ..... 45  
Valco Instruments Co. Inc. .... (RAC 498) ..... 2  
VAT Incorporated ..... (RAC 518) ..... 76  
Videotapes ..... 78  
Wardwell Braiding  
Machine Co. .... (RAC 396) ..... 48  
Watlow ..... (RAC 416) ..... 71  
Zircar Products, Inc. .... (RAC 595) ..... 47

\*RAC stands for Reader Action Card. For future information on these advertisers, please circle the RAC number on the Reader Action Card in this issue. This index has been compiled as a service to our readers and advertisers. Every precaution is taken to insure its accuracy, but the publisher assumes no liability for errors or omissions.

## The Only Outsourcing Show for the Aerospace Industry

**AEROCON**  
AEROSPACE CONTRACT MANUFACTURERS



*This is the show where you can meet hundreds of aerospace-qualified job shops. It's AEROCON 91, April 9-11 at the Anaheim Convention Center.*

*You'll find companies with expert capabilities in metalworking, plastics and rubber. They produce custom parts and components and manufacturing services.*

*Exhibitors will be both domestic and foreign, ranging in size from small to large, plus disadvantaged.*

*AEROCON 91 — Linking buyers and sellers industry-wide and worldwide.*

*Ask about the CME Seminar Series offered by: SME & NAPM - LA & Orange County*

*For registration, seminar or exhibit information, call 1-800-635-9885.*

*Contract Manufacturers Expo West, Ltd., 3270 W. Big Beaver Road, Suite 123, Troy, Michigan 48084 313/643-6807 or FAX 313/643-0856.*

**AMERICA'S OUTSOURCING EXPOSITION FOR THE AEROSPACE INDUSTRY**  
April 9, 10 & 11, 1991 Anaheim Convention Center, Anaheim, California.

**Circle Reader Action No. 488**

FINAL  
★★★★

# GLOBAL DAILY

Monday, April 9, 1991

50 CENTS

Forecast  
Bright and sunny for  
pleasantly warm

## WHITE SOX WIN SERIES! Beat Cubs 3-2 for Third Consecutive World Championship

### U.S. EXPORTS REACH RECORD HIGH

WASHINGTON, D.C. — Federal Commerce Department figures show that U.S. exports reached a record high of \$175.4 billion in the first three months of 1991, up from \$170.4 billion in the same period last year. The Commerce Dept. said that the increase was due to a combination of factors, including a strong performance in the automotive and machinery sectors. U.S. exports to Japan were up 12.5% from the same period last year, while exports to Europe were up 10.5%. The Commerce Dept. also reported that U.S. imports fell to a record low of \$150.4 billion in the first three months of 1991, down from \$155.4 billion in the same period last year. The Commerce Dept. said that the decrease was due to a combination of factors, including a strong performance in the automotive and machinery sectors. U.S. imports from Japan were down 12.5% from the same period last year, while imports from Europe were down 10.5%.

### White Sox Win 3rd Straight

**GLOBE IN BRIEF**  
• New Report Shows 4 of 5 Best-Selling Cars Now Made in Detroit  
• Joint U.S.-Soviet Manned Mission to Mars on Schedule  
• Airfares Drop Airfares—Fuel Savings From New Engines Cited as Reason  
• Business Briefs (See Section B)  
• U.S. Firms Take Top Awards For Industrial Design  
• OEM Earnings Up 12.5%  
• Former Defense Suppliers From Now Earning Profits From Consumer Market  
• House Votes to Increase NASA Research Spending, Technology Transfer Issues Provide Incentive Passage

### Japan Seeks U.S. Video Technology to Increase Domestic HDTV Market Share

SAN FRANCISCO — Japanese electronics giant Sharp Corp. is seeking U.S. video technology to increase its share of the domestic HDTV market. Sharp officials said that the company is currently in negotiations with several U.S. manufacturers to license their HDTV technology. Sharp is currently producing HDTVs in Japan and is looking to expand its production capabilities in the U.S. market. The company is particularly interested in U.S. technology for HDTV receivers and tuners. Sharp officials said that the company is currently in negotiations with several U.S. manufacturers to license their HDTV technology. Sharp is currently producing HDTVs in Japan and is looking to expand its production capabilities in the U.S. market. The company is particularly interested in U.S. technology for HDTV receivers and tuners.

### EPA Reports 70% Fewer Landfills Needed in Next Decade

WASHINGTON, D.C. — The Environmental Protection Agency (EPA) reports that it will need 70% fewer landfills in the next decade. The EPA said that this is due to a combination of factors, including a strong performance in the automotive and machinery sectors. U.S. exports reached a record high of \$175.4 billion in the first three months of 1991, up from \$170.4 billion in the same period last year. The EPA also reported that U.S. imports fell to a record low of \$150.4 billion in the first three months of 1991, down from \$155.4 billion in the same period last year.

### Nation's Engineers Meet for 48th Annual Design Show Starting Today.

CHICAGO, Ill. — The National Design Engineering Show & Conference is starting today in Chicago. The show is a major event for the engineering industry and is expected to attract thousands of attendees. The show will feature a wide range of exhibits, including the latest in engineering technology and products. The show is a major event for the engineering industry and is expected to attract thousands of attendees. The show will feature a wide range of exhibits, including the latest in engineering technology and products.

### RETAIL GIANT POSTS RECORD EARNINGS

Sales of Recyclable Appliances Key to 1st Quarter Profits

# Future shock?

Shocking news? We don't think so. All right, maybe the White Sox won't win the World Series. But U.S. industry can maintain its world leadership.

As engineers, we design the future. And just one idea from the National Design Engineering Show & Conference can provide the spark for the innovations we'll need to keep us moving ahead.

National Design is the show for innovation. Engineers will find over 925 world-leading suppliers of advanced materials, electronics, fluid technologies, controls, mechanical components and more. Everything you need to start and finish your bill of materials.

Management can compare the value of automated design systems from the leading CAD/CAM/CAE hardware and software suppliers. And learn more about document imaging systems that will increase productivity.

Marketing can see what's new in industrial design and how to make products more marketable.

Your entire engineering team can learn about proactive design strategies that will help meet the demands of today's environmental mandates and quality-conscious consumers. You'll find over 50 sessions and short courses sponsored by the ASME at the National Design Conference, for knowledge you can use immediately at the office.

Take the first step towards a better engineered future. Mail the coupon below now for your free National Design Show Preview and Conference Program. It's your time to be a world champion.

For more information, call Customer Service (203) 964-8287. Ask for ext. 7550.



## National Design Engineering Show & Conference™

April 8-11, 1991  
McCormick Place  
Chicago, Illinois

We help designs make it in the real world.

**BONUS with your National Design admission!**  
Free crossover admission to these seven shows as part of National Manufacturing Week:

National Plant Engineering	National Electrical Equipment
Environmental Technology	National Electronic Manufacturing and Design
Computers & Software for Manufacturing	Computer Electronic Publishing
Facilities and Security	

**Mail today for more information.**

I want to attend National Design. Please send me a Show Preview and Conference Program.

I'm interested in exhibiting. Please call with information.

Name \_\_\_\_\_ Title \_\_\_\_\_

Company \_\_\_\_\_

Division/Mail Stop \_\_\_\_\_

Address \_\_\_\_\_

City/State/Zip \_\_\_\_\_

Phone \_\_\_\_\_ Fax \_\_\_\_\_

Mail to: Attendee Fulfillment, National Design, P.O. Box 3833, 999 Summer Street, Stamford, CT 06905-0833

XY1

# IEEE-488.2

The Most Choices  
for your PC



...and the Best Technology

## Hardware

- NAT4882 IEEE-488.2 Controller chip
  - Optimized GPIB functionality
- Turbo488 performance chip
  - 1 Mbytes/sec reads and writes
- SCSI, serial, parallel Converters
- Full-function Analyzer
- Data Buffer for plotters
- Extenders for distance
- Expanders for more devices
- FCC certified

## Software

- High-speed IEEE-488.2 routines  
`FindLstn(0, addrlist, fndlist, 5);`
- Industry-standard NI-488<sup>®</sup> functions  
`ibwrt(scope, "curve?", 6);`
- HP-style commands  
`PRINT #1, "OUTPUT 1;F1S2"`
- Windows 3.0 support
- Interactive development and configuration utilities

Call for FREE Catalog

(512) 794-0100

(800) IEEE-488 (U.S. and Canada)



JAPAN (03) 3788 1921 • UNITED KINGDOM (06) 35 523 545  
FRANCE (1) 48 65 33 70 • GERMANY (089) 436 1447  
ITALY (2) 4830 1892 • SWITZERLAND (056) 45 58 80

# PATENTS

NASA

Over the past three decades, NASA has granted more than 1000 patent licenses in virtually every area of technology. Sales of licensed inventions exceed \$10 million, and royalties paid to NASA approach \$1 million. The Space Agency has a portfolio of 3000 domestic and foreign patents and pending applications available now for license by small and large businesses, and by individuals. Recently patented inventions include:

### Carbide/Fluoride/Silver Self-Lubricating Composite

(U.S. Patent No. 4,728,448)

Inventor: **Harold E. Sliney**

Mr. Sliney, NASA's 1989 Inventor of the Year, has created a self-lubricating, friction- and wear-reducing composite material for use over a wide temperature spectrum from cryogenic to about 900°C in a chemically-reactive environment comprising silver, barium fluoride/calcium fluoride eutectic, and metal-bonded chromium carbide.

### Polyimides Containing Carbonyl and Ether Connecting Groups

(U.S. Patent No. 4,820,791)

Inventors: **Paul M. Hergenrother**  
and **Stephen J. Havens**

This invention relates to structural resins and, in particular, to new polyimides formed from the reaction of aromatic dianhydrides with novel aromatic diamines containing carbonyl and ether connecting groups between the aromatic rings, whereby processible, solvent-chemical-, and impact-resistant polyimides are obtained.

### Human Serum Albumin Crystals and Method of Preparation

(U.S. Patent No. 4,833,233)

Inventor: **Daniel C. Carter**

NASA's 1990 Inventor of the Year, Carter has developed a methodology for preparing crystals of human serum albumin in a form suitable for x-ray analysis of crystal structure. The size and quality of the resulting crystals enable drug binding and genetic engineering studies.

### Airplane Takeoff and Landing Performance Monitoring System

(U.S. Patent No. 4,843,554)

Inventors: **David B. Middleton, Raghava-**  
**chari Srivatsan, and Lee H. Person**

This invention provides the pilot with graphic and metric information to assist in decisions related to achieving rotation speed within the safe zone of the runway or stopping the aircraft on the runway after landing or takeoff abort. The real-time monitoring system displays the aircraft's position on the runway, summarizes the critical information into a situation advisory flag, flags engine failures and off-nominal acceleration performance, and indicates where on the runway events such as decision speed and expected stop points will occur based on actual or predicted performance.

### Methods of Using Fluoroepoxy Compounds as Adhesives for Fluoroplastic Adherends and Products Made Therefrom

(U.S. Patent No. 4,902,574)

Inventor: **Sheng Y. Lee**

Fluoroepoxy compounds are made by reacting a fluoroepoxy resin with an effective curing agent such as an adduct amine. While the compound is sufficiently liquid to wet a fluoroplastic surface, it can be applied to a fluoroplastic adherend such as Teflon and employed as an adhesive to form various fluoroplastic products, without requiring any surface treatment of the adherend. The compounds are formulated with high fluorine contents, normally above 46 percent by weight, preferably for bonding fluoroplastics with a high F-content, above 55 percent by weight.

### Multi-Fingered Robotic Hand

(U.S. Patent No. 4,921,293)

Inventors: **Carl F. Ruoff** and  
**J. Kenneth Salisbury, Jr.**

The invention is a robotic hand having a plurality of fingers, each with multiple joints pivotally connected to one another, with actuators attached at one end to an actuating and control mechanism mounted remotely from the hand and at the other end to the joints of the fingers for manipulating the digits and passing the robot arm in between the hand and the actuating and control mechanism. Pulleys route the actuators within the fingers.

To obtain a license for these or any other NASA-owned patents, a potential licensee must prepare a detailed plan which describes how the invention will be developed and marketed. This plan should delineate the nature and amount of anticipated investment of capital and other resources the applicant believes will be required to bring the invention to practical application. It should also contain a statement of the applicant's capability and intention to fulfill the plan, including information on manufacturing, marketing, financial, and technical resources. The plan is important because it forms the basis upon which the decision to grant a license is made, and is also used in formulating the terms of the license.

NASA patent licenses usually contain requirements for periodic reporting and marketing the licensed invention, restrictions on the fields of use in which the invention may be practiced, and a requirement that the invention be available for sale within a specified time period. Additionally, all licenses NASA grants contain royalty terms. NASA requires an initial royalty payment, a running royalty based on measures such as net sales, and yearly minimum royalties.

For further information on licensing the inventions described in this article, or for general information on NASA patent licensing, write to: NASA, Code GP, Washington, DC, 20546, or call (202) 453-2430. □



# Lightning response.

MIL-C-38999s, MIL-C-24308s.  
<5ns EMP clamping response,  
plus line-by-line filtering.  
Max protection in zero space.

Now: meet MIL-Std-461C and TEMPEST requirements without redesigning or kludging. Meet our tiny EMP killers — substrate mounted uni-polar or back-to-back zeners that tackle voltage surges inside the receptacle housing, at the pin. In under five nanoseconds.

And: beat noise problems in the same space, with our broad range of filters. Clamping followed by filtering helps reduce resonance and high-frequency spiking below the clamping threshold.

Lightning-fast EMP protection is available in the configurations you need, including 38999s, 24308s, and


ARINC types. All with the rugged engineering and attention to detail you can always expect from AMP.

Let us show you our lightning response. For technical information or literature, call us at 1-800-522-6752. AMP Aerospace & Government Systems Sector, Harrisburg, PA 17105-3608.

## THIS IS AMP TODAY. **AMP**

Circle Reader Action No. 657

# TOUCH AND GO...



## The Optical Spectrum Analyzer That Puts More Power At Your Fingertip!

- Broad Bandwidth (0.35 to 1.75  $\mu\text{m}$ )
- Broad Dynamic Range (up to > 80 dB)
- High Sensitivity (-80 dBm)
- Low Polarization Dependency ( $< \pm 0.5$  dB)
- High Level Accuracy ( $< \pm 1.5$  dB)

The advanced series of MV02 Optical Spectrum Analyzers provides a new dynamic user interface that simplifies operation with a touch EL panel and a high resolution

color display. The display section can be interfaced with up to three optical units that can be selected depending on measurement application. Color analysis can be measured directly and polarization modes can be viewed simultaneously. Direct spatial coupling is used for the double monochromator optical unit.

For literature or a demo, contact Anritsu America, Inc. 15 Thornton Road, Oakland, NJ 07436. Call 800-255-7234 or (in NJ) 201-337-1111. FAX 201-337-1033.



# Anritsu

Circle Reader Action No. 507

ANRITSU CORP., JAPAN