

## Estimating Basic Preliminary Design Performances of Aerospace Vehicles

Aerodynamics and Performance Estimation Toolset is a collection of four software programs for rapidly estimating the preliminary design performance of aerospace vehicles represented by doing simplified calculations based on ballistic trajectories, the ideal rocket equation, and supersonic wedges through standard atmosphere. The program consists of a set of Microsoft Excel worksheet subprograms. The input and output data are presented in a user-friendly format, and calculations are performed rapidly enough that the user can iterate among different trajectories and/or shapes to perform “what-if” studies. Estimates that can be computed by these programs include:

1. Ballistic trajectories as a function of departure angles, initial velocities, initial positions, and target altitudes; assuming point masses and no atmosphere. The program plots the trajectory in two-dimensions and outputs the position, pitch, and velocity along the trajectory.
2. The “Rocket Equation” program calculates and plots the trade space for a vehicle’s propellant mass fraction over a range of specific impulse and mission velocity values, propellant mass fractions as functions of specific impulses and velocities.
3. “Standard Atmosphere” will estimate the temperature, speed of sound, pressure, and air density as a function of altitude in a standard atmosphere, properties of a standard atmosphere as functions of altitude.
4. “Supersonic Wedges” will calculate the free-stream, normal-shock, oblique-shock, and isentropic flow properties for a wedge-shaped body flying supersonically through a standard atmosphere. It will also calculate the maximum angle for which a shock remains attached, and the minimum Mach number for which a shock becomes attached, all as functions of the wedge angle, altitude, and Mach number.

*This work was done by Paul L. Luz and Reginald Alexander of Marshall Space Flight Center. For further information, contact Caroline Wang, MSFC Software Release Authority, at (256) 544-3887 or Caroline.K.Wang@nasa.gov. Refer to MFS-31795.*

## Framework for Development of Object-Oriented Software

The Real-Time Control (RTC) Application Framework is a high-level software framework written in C++ that supports the rapid design and implementation of object-oriented application programs. This framework provides built-in functionality that solves common software development problems within distributed client-server, multi-threaded, and embedded programming environments. When using the RTC Framework to develop software for a specific domain, designers and implementers can focus entirely on the details of the domain-specific software rather than on creating custom solutions, utilities, and frameworks for the complexities of the programming environment. The RTC Framework was originally developed as part of a Space Shuttle Launch Processing System (LPS) replacement project called Checkout and Launch Control System (CLCS). As a result of the framework’s development, CLCS software development time was reduced by 66 percent. The framework is generic enough for developing applications outside of the launch-processing system domain. Other applicable high-level domains include command and control systems and simulation/training systems.

*This software was written by Gus Perez-Poveda of 360 Software Corporation, Tony Ciavarella of United Space Alliance, and Dan Nieten of Kennedy Space Center. For further information, access <http://www.360SoftwareCorp.com>.*

*In accordance with Public Law 96-517, the contractor has elected to retain title to this invention. Inquiries concerning rights for its commercial use should be addressed to:*

*360 Software Corporation  
12472 Lake Underhill Rd. #174  
Orlando, FL 32828  
Phone: (407) 694-2227*

*Refer to KSC-12499, volume and number of this NASA Tech Briefs issue, and the page number.*

## Analyzing Spacecraft Telecommunication Systems

Multi-Mission Telecom Analysis Tool (MMTAT) is a C-language computer program for analyzing proposed spacecraft telecommunication systems. MMTAT uti-

lizes parameterized input and computational models that can be run on standard desktop computers to perform fast and accurate analyses of telecommunication links. MMTAT is easy to use and can easily be integrated with other software applications and run as part of almost any computational simulation. It is distributed as either a stand-alone application program with a graphical user interface or a linkable library with a well-defined set of application programming interface (API) calls. As a stand-alone program, MMTAT provides both textual and graphical output. The graphs make it possible to understand, quickly and easily, how telecommunication performance varies with variations in input parameters. A delimited text file that can be read by any spreadsheet program is generated at the end of each run. The API in the linkable-library form of MMTAT enables the user to control simulation software and to change parameters during a simulation run. Results can be retrieved either at the end of a run or by use of a function call at any time step.

*This program was written by Mark Kordon, David Hanks, Roy Gladden, and Eric Wood of Caltech for NASA’s Jet Propulsion Laboratory. Further information is contained in a TSP (see page 1).*

*This software is available for commercial licensing. Please contact Don Hart of the California Institute of Technology at (818) 393-3425. Refer to NPO-40298.*

## Collaborative Planning of Robotic Exploration

The Science Activity Planner (SAP) software system includes an uplink-planning component, which enables collaborative planning of activities to be undertaken by an exploratory robot on a remote planet or on Earth. Included in the uplink-planning component is the SAP-Uplink Browser, which enables users to load multiple spacecraft activity plans into a single window, compare them, and merge them. The uplink-planning component includes a subcomponent that implements the Rover Markup Language Activity Planning format (RML-AP), based on the Extensible Markup Language (XML) format that enables the representation, within a single document, of planned spacecraft and robotic activities together with the scientific rea-