

5...4...3...2...1...

# SPACE LAUNCH SYSTEM


## SLS at Critical Design Review

**Chris Crumbly**

*Manager,  
Spacecraft/Payload Integration & Evolution*



# SLS Evolution Overview



# Building Today



**Interim Cryogenic Propulsion Stage:** Test article currently in production; flight article began July 2015.



**Stage Adapters:** First flight hardware launched on Exploration Flight Test-1 in Dec. 2014.

**Avionics:** Software Integration Test Facility preparing for qualification in second quarter 2016.



**Core Stage:** Production is underway on hardware for both test articles and EM-1 vehicle.




**Boosters:** Qualification Motor-1 test completed in March 2015.



**Engines:** RS-25 testing has begun at Stennis Space Center; renovations underway to B-2 stand.

# SLS MILESTONES SCHEDULE



# Payload Accommodation Concepts Under Study

## Mission concepts with Universal Stage Adaptor

## Mission concepts with 8m and 10m fairings




Orion with short-duration hab module




5m fairing w/robotic lunar lander & short-duration hab module



Science Missions



ARM Mission



8m fairing with large aperture telescope



10m fairing w/notional Mars payload

total mission volume = ~ 400m<sup>3</sup>

600m<sup>3</sup>


400m<sup>3</sup>

400m<sup>3</sup>

1200m<sup>3</sup>


1800m<sup>3</sup>

# Selective Laser Melting Road to Flight



# Advancing the State of the Art

## Friction Stir Weld (FSW) Performance Improvement: Sam Russell



**Objective:** Measure stress concentration effect in FSW welds and develop improved phased array ultrasound testing technique. Fit FSW tool with end mill for shaving post-weld.

### Accomplishments:

- Welded two sets of panels using FSW
- Prepared first set for inspection in usual manner and shaved second set by milling
- Used panels to estimate phased array testing detectability of defects in the surface
- Cut samples from panels and pulled in a tensile test machine to measure the strength of the shaved and unshaved panels

## Additive Manufacturing (AM) Infrared Inspection: Darrell Gaddy



**Objective:** Develop real-time inspection technique using infrared camera imaging and processing. Provide inspection of internal geometry that is not currently possible. Reduce time and cost for producing AM parts by eliminating post-production inspections.

### Accomplishments:

- Proved the feasibility of infrared hardware detecting AM process
- Developed custom software which created 3D geometry files of the additively manufactured part

## Cryoinsulation Development: Alison Protz



**Objective:** Investigate low-Global Warming Potential (GWP) cryoinsulation foams as a proactive risk mitigation for SLS Core Stage. Perform a market survey and begin bench scale lab testing of low-GWP cryoinsulation foams.

### Accomplishments:

- Completed market survey for low-GWP cryoinsulation foams
- Determined that primary vendors are focused on blowing agents requiring further development
- Smaller vendors have alternative low-GWP blowing agent possibilities

## Chromium VI Free Primer Development: Michael Alldredge



**Objective:** Evaluate corrosion protection capability of multiple commercially-available hexavalent chromium-free non-hazardous primers for cryogenic applications

### Accomplishments:

- Evaluated 4 primer candidates, which were selected in phase 1 of project
- Determined that Desoprime CF/CA 7502 has potential for further screening based on physical tests and cryogenic performance

## Low-Profile Diffuser (LPD): Mike Martin



**Objective:** Develop a diffuser concept to replace existing types with a high performing, low profile design to enable more propellant capacity and increase SLS performance

### Accomplishments:

- Completed flow testing of prototype diffuser to validate CFD models
- Analyzed test results to determine that good agreement exists between CFD and test data



[www.nasa.gov](http://www.nasa.gov)



[@NASA\\_SLS](https://twitter.com/NASA_SLS)



[NASASLS](https://www.facebook.com/NASASLS)



[google.com/+nasa](https://google.com/+nasa)



[youtube.com/nasa](https://youtube.com/nasa)



[@explorenasa](https://www.instagram.com/explorenasa)

#JOURNEYTOMARS



# Advancing the State of the Art

## Testing of SLM Turbomachinery: Jason Turpin



**Objective:** Design, fabricate, and spin test to failure, a Ti6-4 hydrogen turbopump impeller that was built using the Selective Laser Melting (SLM) fabrication process. Perform material testing on coupons.

### Accomplishments:

- Completed design of the impeller
- Fabricated SLM impeller and material coupons
- Completed structured light scanning and inspection
- Completed spin burst testing, material strength data development, and data analysis

## Material Properties Development: Ken Cooper




**Objective:** Develop and characterize Selective Laser Melting (SLM) parameters for additive manufacturing of Inconel 625 and Ti64. Generate reduced design allowables database of expected SLM properties.

### Accomplishments:

- Evaluated 100 samples to determine effects of changes in global energy input on hardness of coupons
- Built a sample set of 50 coupons to test resulting tensile strength at room temperature

## Solid State Ultracapacitor: Terry Rolin




**Objective:** Develop a solid-state ultracapacitor to replace batteries. Focus on internal barrier layer capacitor structures composed of coated barium titanate (BT). Fabricate/test single layer ultra-capacitor.

### Accomplishments:

- Fabricated ultracaps from coated BT powders using spark plasma sintering; measured permittivity values at MSFC
- Evaluated composite polyimide/BT dielectric materials, and developed new 3D printing processes and materials
- Evaluated many variations of single layer ultracap cell

## LB Method for Zero-g Propellant Dynamics: Joey Powers



**Objective:** Develop a new capability to predict propellant sloshing effects on spacecraft vehicle dynamics in low-g environments

### Accomplishments:

- Investigated Lattice Boltzmann method (LBM) for propellant dynamics in micro-g
- Developed modular two-dimensional flow solver
- Demonstrated stable two-phase flow with accurate steady-state density for a cryogen in a closed domain

## Performance of Composite Structure: Alan Nettles



**Objective:** Present information on composite materials properties of relevance to facilitate use for shroud and interstage structures on SLS vehicle. Seek to reduce cost, improve reliability and performance of composite dry structures.

### Accomplishments:

- Presented five topics to SLS Advanced Development community to date
- Topics included motivation for use of composites, roles of testing and design