

National Aeronautics and
Space Administration



Modular Tool Concept Eighth International TWI EWI Seminar 2016





Justin Littell
NASA/Marshall Space Flight Center
September 28, 2016

E-mail Address: Justin.A.Littell@NASA.gov
Work Phone Number: (256) 961-2335



MARSHALL
SPACE FLIGHT CENTER


Traditional Tooling



Traditional Tooling is complex, bulky, expensive and configuration specific.
Requires long durations to design, fabricate and assemble.

SLS Components


SLS 70-metric-ton
Initial Configuration



- Tooling used to manufacture the various components of the SLS rocket.


Different components with unique geometries require one-off traditional tools

MSA & LVSA



Products manufactured at NASA's Marshall Space Flight Center

SLS: MSA weld fixture




- Conical Shape
- Top 5.5 Meter diameter
- Bottom 5 Meter diameter

- Used Traditional Tooling approach but with minimal budget and schedule.
- Still exceeded budget
- Still required excessive schedule



SLS: MPCV Simulator



MSA
Conical

MPCV-S
Cylindrical

A simple change in component geometry requires a completely new traditional tooling

Modular Concept

◆ “Tombstone”




- Slides along the Turn Table’s slots to provide the backbone support at a specific radius

◆ “Shelves”

- Provides a stiff circumferential platform at a specific elevation


◆ “Shoes”

- Pads used for rounding the article driven by threaded rods within the “Shelves”




◆ “Knuckles”

- Clevis devices used for pinning Turn Buckles, capable of pivoting 45 or 90 degrees





◆ “Turn Buckle”

- Compression member used to provide additional support




SLS: Core Stage Simulator Fixture





- ◆ Cylindrical
- ◆ Diameter 8.4 meters
- ◆ Height: 4 meters

Modular model concept





Modular Tooling can adjust to various configurations
Offering multiple solutions to fixture issues

SLS: LVSA Fixture Configuration 1




- ◆ Conical
- ◆ Diameter: 8.4 to 7 meters
- ◆ Height: 4.5 meters

SLS: LVSA Fixture Configuration 2




- ◆ Conical
- ◆ Diameter: 8.4 to 5.5 meters
- ◆ Height: 9.1 meters


Expanded Capabilities





Caps & Y-ring
to Domes




Segmented
ring





Cone to cone
segments



Gore to gore
segments



Flange to
cylinder



Cone barrel to
barrel

Modular tooling can accommodate multitude platforms (longitudinal, circumferential, complex curve, and circular)

Summary

1st Time Use

| Fixture Method | Cost (Unit) | Time (Months) | | |
|-------------------|-------------|---------------|-------------|----------|
| | | Design | Fabrication | Assembly |
| Traditional | 10x | 3 | 3 | 3 |
| Modular Fixturing | 1x | 1 | 1 | 0.25 |

2nd Time Use

(different configuration)

| Fixture Method | Cost (Unit) | Time (Months) | | |
|-------------------|-------------|---------------|-------------|----------|
| | | Design | Fabrication | Assembly |
| Traditional | 10x | 3 | 3 | 3 |
| Modular Fixturing | 0.05x | 0.25 | 0.50 | 0.25 |

Modular Tooling saves time and money
 Summary table reflects actual costs and schedules observed during SLS manufacturing



The journey to Mars
begins with...

MARSHALL
SPACE FLIGHT CENTER